Explicit nonlinear model predictive control for vehicle stability control

Dipl.-Ing. Mathias Metzler, Dr. Davide Tavernini, Prof. Dr. Aldo Sorniotti,
Dr. Patrick Gruber

Centre for Automotive Engineering, University of Surrey, UK

Abstract

Nonlinear model predictive control is proposed in multiple academic studies as an advanced control system technology for vehicle operation at the limits of handling, allowing high tracking performance and formal consideration of system constraints. However, the implementation of implicit nonlinear model predictive control (NMPC), in which the control problem is solved on-line, poses significant challenges in terms of computational load. This issue can be overcome through explicit NMPC, in which the optimization problem is solved off-line, and the resulting explicit solution, with guaranteed level of sub-optimality, is evaluated on-line. Due to the simplicity of the explicit solution, the real-time execution of the controller is possible even on automotive control hardware platforms with low specifications. The explicit nature of the control law facilitates feasibility checks and functional safety validation. This study presents a yaw and lateral stability controller based on explicit NMPC, actuated through the electro-hydraulically controlled friction brakes of the vehicle. The controller performance is demonstrated during sine-with-dwell tests simulated with a high-fidelity model. The analysis includes a comparison of implicit and explicit implementations of the control system.

1 Introduction

The limit behavior of a vehicle is determined by tire nonlinearities. Therefore, model predictive control (MPC) implementations for vehicle stability control benefit from the inclusion of nonlinear system dynamics in the prediction model [1]. However, the resulting nonlinear optimization problem poses a major challenge for the real-time operation of the controllers, as demonstrated in [1] for an active steering system. Various alternatives to NMPC have been proposed in the literature, e.g., linear-time varying MPC [2], hybrid and switched MPC [3], or approximate NMPC [4]. [2] and [3] are based on the on-line solution of the MPC optimization problem.

In this study an explicit NMPC approach is used to solve the optimization problem off-line, given the relatively limited number of parameters of the specific formulation. The obtained explicit solution is a sub-optimal multi-variable feedback law, which can be easily evaluated in real-time.

With respect to the published explicit NMPC work, such as [5], the contribution of this study is in the nonlinear vehicle model for control system design, which considers: i) the interaction of the longitudinal and lateral tire forces; and ii) the effect of the load transfers in cornering. i) and ii) are crucial to the exploitation of the benefits of NMPC for vehicle control at the limits of handling.

Moreover, the flexibility of the NMPC cost function formulation adopted in this study will allow ease of implementation of the controller on real vehicles, with different and usually rather complex performance requirements for the stability control function.

2 Prediction model

2.1 Lateral force and yaw moment balance equations

A double track vehicle model (Figure 1), with the yaw rate, $\dot{\psi}$, and vehicle sideslip angle, β , as state variables, is used as prediction model for the formulation of the optimal control problem. The longitudinal dynamics are neglected, as a constant speed, v , is assumed over the prediction horizon.

Figure 1 Notations and sign conventions of the proposed vehicle model formulation.

The Newton-Euler lateral force and yaw moment balance equations of the vehicle rigid body are:

$$\dot{\beta} = \frac{1}{mv} [(F_{l_{FL}} + F_{l_{FR}}) \sin(\delta - \beta) + (F_{s_{FL}} + F_{s_{FR}}) \cos(\delta - \beta) - (F_{l_{RL}} + F_{l_{RR}}) \sin \beta + (F_{s_{RL}} + F_{s_{RR}}) \cos \beta] - \dot{\psi} \quad (1)$$

$$\begin{aligned} \ddot{\psi} = \frac{1}{I_z} \{ & [(F_{l_{FL}} + F_{l_{FR}}) \sin \delta + (F_{s_{FL}} + F_{s_{FR}}) \cos \delta] l_F - (F_{s_{RL}} + F_{s_{RR}}) l_R \\ & + (F_{l_{FR}} \cos \delta - F_{s_{FR}} \sin \delta + F_{l_{RR}}) \frac{d}{2} \\ & - (F_{l_{FL}} \cos \delta - F_{s_{FL}} \sin \delta + F_{l_{RL}}) \frac{d}{2} \} \end{aligned} \quad (2)$$

where m is the vehicle mass; I_z is the yaw mass moment of inertia; l_F and l_R are the front and rear semi-wheelbases; d is the track width; δ is the steering angle, which is assumed to be equal on the left and right front wheels; $F_{l_{ij}}$ and $F_{s_{ij}}$ are the longitudinal and lateral tire forces, respectively, with the subscripts $i = F, R$ referring to the front

and rear axles, and $j = L, R$ to the left and right sides.

As the vehicle stability controller ensures small sideslip angle values in any condition, and the relevant maneuvers imply rather limited values of steering angle, (1) and (2) are linearized with respect to the arguments β and $\delta - \beta$.

2.2 Vertical tire forces

The estimation of the vertical tire forces, $F_{z_{ij}}$, considers the load transfer associated with the lateral acceleration. The calculations are based on the constants defined in equations (3) and (4).

$$c_{Y_F} = \left(\frac{l_R}{l_F + l_R} \frac{h_F}{d} + \frac{K_F}{K_F + K_R} \frac{h'}{d} \right) m \quad (3)$$

$$c_{Y_R} = \left(\frac{l_F}{l_F + l_R} \frac{h_R}{d} + \frac{K_R}{K_F + K_R} \frac{h'}{d} \right) m \quad (4)$$

where h_F and h_R are the roll center heights of the front and rear suspensions; h' is the distance between the roll axis and the vehicle center of gravity; and K_F and K_R are the roll stiffness values of the front and rear suspensions.

From (3) and (4) the varying vertical tire loads are estimated as:

$$F_{z_{FL}} = F_{z_{FL},stat} - c_{Y_F} v \dot{\psi} \quad (5)$$

$$F_{z_{FR}} = F_{z_{FR},stat} + c_{Y_F} v \dot{\psi} \quad (6)$$

$$F_{z_{RL}} = F_{z_{RL},stat} - c_{Y_R} v \dot{\psi} \quad (7)$$

$$F_{z_{RR}} = F_{z_{RR},stat} + c_{Y_R} v \dot{\psi} \quad (8)$$

where $F_{z_{ij},stat}$ is the static vertical load on the individual tire. (5) – (8) neglect the effect of the sideslip angle rate contribution, $\dot{\beta}$. Future developments of this research will include consideration of the load transfers induced by the vehicle longitudinal dynamics.

2.3 Tire force model

The nonlinear behavior of the lateral tire forces is modeled with a simplified Pacejka Magic Formula [6]. The lateral forces in pure lateral slip conditions, $F_{s0_{ij}}$, are defined with nonlinear functions of the tire slip angles, α_{ij} .

$$F_{s0_{ij}} = D_{s_{ij}} \sin \left(C_{s_{ij}} \tan^{-1} \left(B_{s_{ij}} \alpha_{ij} \right) \right) \quad (9)$$

The coefficients in (9) are the lateral peak factor, D_{sij} ; the lateral shape factor, C_{sij} ; and the lateral stiffness factor, B_{sij} . D_{sij} depends on F_{zij} , while C_{sij} and B_{sij} are constant.

The interaction between longitudinal and lateral tire forces in combined slip conditions is considered with a linear approximation of the tire friction envelope:

$$F_{sij} = F_{s0ij} \left(1 + C_{lsij} \frac{F_{lij}}{D_{lij}} \right) \quad (10)$$

This means that each lateral tire force in combined slip, F_{sij} , is reduced by a factor, which depends on the current estimated longitudinal tire force, F_{lij} (≤ 0 in braking), divided by its maximum value, D_{lij} , in pure longitudinal slip conditions. D_{lij} is based on the estimated longitudinal tire-road friction coefficient, $\mu_{lp_{ij}}$, and the estimated vertical tire load:

$$D_{lij} = \mu_{lp_{ij}} F_{z_{ij}} \quad (11)$$

The constant C_{lsij} in (10) is used as a tuning parameter.

The computation of the slip angle values, α_{ij} , neglects the track width of the vehicle and assumes small vehicle sideslip angles:

$$\alpha_{FL} = \alpha_{FR} = \delta - \beta - \frac{\psi l_F}{v} \quad (12)$$

$$\alpha_{RL} = \alpha_{RR} = -\beta + \frac{\psi l_R}{v} \quad (13)$$

2.4 Model parameters

Table 1 includes a selection of the prediction model parameters, representative of a Sport Utility Vehicle (SUV).

Table 1 Main parameters of the prediction model.

Symbol	Description	Quantity
m	Vehicle mass	1962 kg
I_z	Vehicle yaw mass moment of inertia	3382 kgm ²
l_F	Front semi-wheelbase	1.10 m
l_R	Rear semi-wheelbase	1.57 m
d	Front and rear track width	1.62 m
K_F	Front suspension roll stiffness	60000 Nm/rad
K_R	Rear suspension roll stiffness	50000 Nm/rad

3 Vehicle stability controller

The formulation of the NMPC vehicle stability controller is based on an optimal control problem defined by a cost function and constraints, in addition to the vehicle model equations in Section 2.

3.1 Optimal control problem

3.1.1 Cost function

The cost function, V , of the optimal control problem is defined as the integral of optimality criteria over the prediction horizon. More specifically, the longitudinal tire force distribution imposed by the stability controller minimizes the weighted deviation from reference targets for: i) the overall vehicle traction or braking force, which tracks $F_{x,ref}$; ii) the overall vehicle direct yaw moment, which tracks $M_{z,ref}$, i.e., the reference yaw moment to be generated by the longitudinal tire force difference between the left and right sides of the vehicle; iii) the braking ratio, which tracks b_{ref} , i.e., the desired ratio between the front and total longitudinal tire forces within the considered vehicle side; and iv) the yaw rate error, $e_{\dot{\psi}}$, and rear axle slip angle, α_R , bounded through the respective slack variables, $N_{e_{\dot{\psi}}}$ and N_{α_R} , discussed in detail in Section 3.1.3.

The prediction horizon is the interval between the current time, t_k , and the time at the end of the horizon, $t_f = t_k + t_s N_p$, defined by the number of prediction steps, N_p , and the discrete sampling time, t_s . The longitudinal tire forces are the control inputs to the prediction model. They can vary N_c times over the prediction horizon, where N_c is the number of control steps, and then they are kept constant from $t_k + t_s(N_c - 1)$ until t_f .

$$\begin{aligned}
 V(t_k) = \int_{t_k}^{t_f} & \left[\frac{r_{u,F_x}}{U_{sc,F_x}^2} \left(F_{x,ref} - (F_{l_{FL}} + F_{l_{FR}} + F_{l_{RL}} + F_{l_{RR}}) \right)^2 \right. \\
 & + \frac{r_{u,M_z}}{U_{sc,M_z}^2} \left(M_{z,ref} - \frac{d}{2} (F_{l_{FR}} + F_{l_{RR}} - F_{l_{FL}} - F_{l_{RL}}) \right)^2 \\
 & + \frac{r_{u,b}}{U_{sc,b}^2} \left((1 - b_{ref}) F_{l_{FL}} - b_{ref} F_{l_{RL}} \right)^2 \\
 & + \frac{r_{u,b}}{U_{sc,b}^2} \left((1 - b_{ref}) F_{l_{FR}} - b_{ref} F_{l_{RR}} \right)^2 \\
 & \left. + \frac{q_{v,e_{\dot{\psi}}}}{N_{sc,e_{\dot{\psi}}}^2} N_{e_{\dot{\psi}}}^2 + \frac{q_{v,\alpha_R}}{N_{sc,\alpha_R}^2} N_{\alpha_R}^2 \right] dt
 \end{aligned} \tag{14}$$

The contribution of the different terms of $V(t_k)$ are weighted with the coefficients r_{u,F_x} , r_{u,M_z} , $r_{u,b}$, q_{v,e_ψ} , and q_{v,α_R} . Appropriate scaling factors, i.e., U_{sc,F_x} , U_{sc,M_z} , $U_{sc,b}$, N_{sc,e_ψ} , and N_{sc,α_R} , allow equivalent influences of the weights. The cost function formulation in (14) permits very different operating principles of the stability controller determined by the tuning choices, e.g., focused on both yaw rate and slip angle constraints, or the yaw rate tracking only, or the control allocation of the individual braking forces. The flexibility of this novel cost function formulation meets the diversified performance requirements of real vehicle implementations.

3.1.2 Reference generation

$F_{x,ref}$ is obtained from the demanded deceleration of the vehicle, $a_{x,ref}$. This is calculated from the driver input on the accelerator and brake pedals, and the condition of motion of the vehicle, e.g., in terms of yaw rate error and rear axle slip angle.

$$F_{x,ref} = m a_{x,ref} \quad (15)$$

For simplicity, in the preliminary implementation of this paper, focused on the sine-with-dwell test, $a_{x,ref}$ is set to 0, and will be considered as an additional parameter in the future.

The reference yaw moment, $M_{z,ref}$, is calculated based on the violation of the bounds on the yaw rate error and rear slip angle at t_k , with gains K_{e_ψ} and K_{α_R} , i.e., through proportional contributions. For appropriate signs, the terms relating the yaw rate error and rear slip angle to their bounds, $e_{\psi,max}$ and $\alpha_{R,max}$, are included.

$$M_{z,ref} = K_{e_\psi} U_{sc,M_z} \frac{N_{e_\psi}(t_k) \psi_{ref}(t_k) - \dot{\psi}(t_k)}{N_{sc,e_\psi} e_{\psi,max}} - K_{\alpha_R} U_{sc,M_z} \frac{N_{\alpha_R}(t_k) \alpha_R(t_k)}{N_{sc,\alpha_R} \alpha_{R,max}} \quad (16)$$

The ratio b_{ref} is considered constant in the current preliminary implementation of the controller.

For the desired handling of the controlled vehicle, a linear understeer characteristic with gradient K_{us} related to gravity g is considered, leading to the expression for the linear yaw rate reference, $\dot{\psi}_{lin}$, in (17). Both vehicle speed and steering angle are assumed constant over the prediction horizon.

$$\dot{\psi}_{lin} = \frac{v(t_k)}{l_F + l_R + \frac{K_{us}}{g} v(t_k)^2} \delta(t_k) \quad (17)$$

Taking into account the physical limitations of the vehicle, the maximum achievable yaw rate, $\dot{\psi}_{max}$, can be approximated in steady-state, based on the maximum lateral acceleration, $a_{y,max}$, in nominal friction conditions.

$$\dot{\psi}_{max} = \frac{a_{y,max}}{v(t_k)} \quad (18)$$

For smooth transition between the linear and maximum yaw rate, the use of a sigmoid function, with tuning parameters C_m and C_k , leads to a reference yaw rate, $\dot{\psi}_{ref}$, similar to the yaw rate associated with the understeer characteristic of the passive vehicle in nominal conditions.

$$\dot{\psi}_{ref} = C_m \dot{\psi}_{max} \frac{2}{\pi} \tan^{-1} \left(C_k \frac{\dot{\psi}_{lin}}{\dot{\psi}_{max}} \frac{\pi}{2} \right) \quad (19)$$

3.1.3 Constraint formulation

Soft constraints are used on the yaw rate error, $e_{\dot{\psi}} = \dot{\psi}_{ref} - \dot{\psi}$, with maximum and minimum bounds, $\pm e_{\dot{\psi},max}$:

$$-e_{\dot{\psi},max} - N_{e_{\dot{\psi}}}(t) \leq \dot{\psi}_{ref} - \dot{\psi} \leq e_{\dot{\psi},max} + N_{e_{\dot{\psi}}}(t) \quad (20)$$

As a consequence, the controller generates a direct yaw moment only when the yaw rate error exceeds the threshold indicated by positive values of the slack variable, $N_{e_{\dot{\psi}}}$.

Additional constraints are beneficial to vehicle stability for a wide range of driving conditions. For example, soft constraints are adopted on the rear slip angle, with maximum and minimum bounds, $\pm \alpha_{R,max}$:

$$-\alpha_{R,max} - N_{\alpha_R}(t) \leq \alpha_R \leq \alpha_{R,max} + N_{\alpha_R}(t) \quad (21)$$

The slack variables N_s , with $s = e_{\dot{\psi}}, \alpha_R$, represent the violation of the respective bounds, and are constrained to be positive:

$$N_{e_{\dot{\psi}}}(t) \geq 0 \quad (22)$$

$$N_{\alpha_R}(t) \geq 0 \quad (23)$$

Additionally, the longitudinal tire forces are constrained to be negative, since only braking torques can be applied by the friction brakes.

3.1.4 State transformation

The optimization problem, consisting of the cost function and the equality and inequality constraints, has the longitudinal tire forces, $F_{l_{ij}}(t)$, and slack variables, $N_{e_{\dot{\psi}}}(t)$ and $N_{\alpha_R}(t)$, as optimization variables in its continuous formulation. The sideslip angle, β , and yaw rate, $\dot{\psi}$, at the current time t_k , are required as initial conditions for the dynamic equality constraints. The vehicle speed, $v(t_k)$, and steering angle, $\delta(t_k)$, are considered as slowly varying parameters.

In the optimal control problem, the yaw rate error, $e_{\dot{\psi}} = \dot{\psi}_{ref} - \dot{\psi}$, and rear slip angle, α_R , are constrained. Therefore, a formulation of the optimization problem with the yaw rate error, $e_{\dot{\psi}}(t)$, and rear slip angle, $\alpha_R(t)$, instead of the sideslip angle, $\beta(t)$, and yaw rate, $\dot{\psi}(t)$, turned out to be beneficial. This is due to the fact that the state space exploration and splitting strategy of the explicit NMPC algorithm is based on orthogonal partitions. With the description using the new variables, the constrained variables are aligned with the coordinate axes of the orthogonal exploration space.

3.1.5 Settings

Table 2 reports the main settings for the optimal control problem of this study.

Table 2 Main settings of the optimal control problem.

Symbol	Description	Quantity
t_s	Sampling time	20 ms
N_p	Prediction steps	3
N_c	Control steps	1
$e_{\dot{\psi},max}$	Bound on yaw rate error	6 deg/s
$\alpha_{R,max}$	Bound on rear slip angle	4.5 deg

3.2 Multi-parametric nonlinear problem

The general optimal control formulation of Section 3.1 is reformulated into a form suitable for the numerical solution using the so-called direct methods.

According to the simultaneous approach, the ordinary differential equation constraints (1) – (2) are parameterized and discretized in time. The resulting algebraic equations are treated as additional nonlinear equality constraints. The forward Euler method, i.e., an explicit first order Runge-Kutta method with one stage, is applied as numerical integration scheme. The trajectories of control inputs and slack variables are parameterized by the vectors $U = [F_{l_{ij}}(t_k), \dots, F_{l_{ij}}(t_{k+N_c-1})]$ and $N = [N_s(t_k), \dots, N_s(t_{k+N_p})]$, respectively, which are considered as unknown variables. In addition, the parameters of the state trajectory, described by $x(t) = [\beta(t), \dot{\psi}(t)]$, are summarized in the vector $X = [x(t_{k+1}), \dots, x(t_{k+N_p})]$, representing the intermediate states, and treated as additional unknown variables. The integral in the cost function (14) is approximated by a finite sum by applying a numerical integration method. The continuous inequality constraints are parameterized and relaxed to hold only at some discrete time instants, $\{t_k, \dots, t_{k+N_p}\} \subset [t_k, t_f]$, leading to a finite number of discrete and parameterized constraint functions.

By implementing the finite parameterization and discretization on the continuous cost function and constraint functions, and by applying the integration scheme to the ordinary differential equations (ODEs), the following optimization problem, defined by the parameterized and discretized cost function V and constraint functions G , is obtained:

$$V^*(x_p(t_k)) = \min_z V(z, x_p(t_k)) \quad (24)$$

subject to:

$$G(z, x_p(t_k)) \leq 0 \quad (25)$$

The vector of parameters, $x_p(t_k)$, combines the initial states of the prediction model, $x(t_k)$, and slowly varying parameters, $p(t_k)$. The transformation, discussed in Section 3.1.4, leads to $x_p(t_k) = [e_\psi(t_k), \alpha_R(t_k), v(t_k), \delta(t_k)]$ as vector of parameters. Similarly, the vector of optimization variables, z , combines the vector of input trajectory parameters, U , the slack variable trajectory parameters, N , and the state trajectory parameters, X , leading to $z = [U, N, X]$.

Assuming that it exists, the optimal solution of the receding horizon MPC strategy at t_k , denoted as z^* , represents the optimal open-loop trajectory over the prediction horizon. The longitudinal tire forces, $F_{lij}(t_k)$, are converted into reference hydraulic pressures for the electro-hydraulic braking system. At the next time instant, the optimization problem is solved with the updated parameter vector, making the MPC strategy a closed-loop approach.

The general formulation (24) – (25) is considered as a multi-parametric nonlinear problem with $x_p(t_k)$ as parameter, i.e., for which the optimal solution z^* has to be found over a range of values of x_p .

4 Explicit NMPC

Since the online solution of (24) – (25) poses significant challenges for the real-time implementation due to the involved nonlinearities, this study investigates an explicit solution of the multi-parametric problem. However, for multi-parametric nonlinear programming (mp-NLP) problems it is in general not possible to derive an explicit solution in an exact form. Therefore, an explicit NMPC algorithm, using multi-parametric quadratic programming (mp-QP) approximations of the mp-NLP, is developed to derive a sub-optimal solution with guaranteed levels of sub-optimality.

4.1 Algorithm using mp-QP approximations

The algorithm is a combination of the approximate mp-NLP algorithm incorporating global optimization tools, as proposed in [7] and [8], and the multi-parametric quadratic approximation (mp-QA) algorithm, as proposed in [9] and [8], and revisited in [10].

The multi-parametric nonlinear program is locally approximated with a multi-parametric quadratic program, leading to an approximate solution of the mp-NLP, consisting of the solution of local mp-QP sub-problems on orthogonal partitions. The accuracy of the approximation is controlled via iterative and recursive partitioning of the parameter space. The partitions are refined based on heuristic splitting rules in parts of the parameter space, to improve accuracy of the local mp-QP approximation, and meet the tolerances and accuracy specifications in terms of sub-optimality bounds on the cost, solution, and maximum constraint violation.

The local approximation of the mp-NLP with an mp-QP problem is derived from second order Taylor series expansion of the cost function, V , in (24), and first-order Taylor series expansion of the constraint function, G , in (25) about the linearization point $(z_0, x_{p,0})$, with z_0 corresponding to the optimal solution, $z_0 = z^*(x_{p,0})$.

The algorithm can be summarized as follows:

- Initialize the orthogonal partition, Π , to the hyper-rectangle in the parameter space, $\mathbb{X}$, to be explored, i.e., $\Pi := \mathbb{X}$, and mark the hyper-rectangle, $\mathbb{X}$, as unexplored.
- While there are unexplored partitions, select any unexplored hyper-rectangle $X_0 \subseteq \Pi$, compute the volume and center point, $x_{p,0}$, and search for an optimal solution, $z_0 = z^*(x_{p,0})$, to the problem (24) – (25) for x_p fixed to $x_{p,0}$ by solving an NLP.
- If a feasible solution for (24) – (25) was found at point $x_{p,0}$, search for an optimal solution for (24) – (25) for x_p fixed to some test points $x_{p,i}$ by solving an NLP; otherwise mark X_0 to be split.
- If the problem (24) – (25) has a feasible solution at all points $x_{p,i}$, compute the local mp-QP problem, derived by Taylor series expansion at $(z_0, x_{p,0})$; otherwise mark X_0 to be split.
- If a feasible explicit solution, $\hat{z}(x_p)$, is found for the local mp-QP problem, compute an estimation, $\hat{\varepsilon}$, of the cost error bound, ε , an estimation, $\hat{\rho}$, of the solution error bound, ρ , and an estimation, $\hat{\gamma}$, of the maximum constraint violation, γ , in X_0 ; otherwise mark X_0 to be split.
- If the estimates of the bounds, $\hat{\varepsilon}$, $\hat{\rho}$, and $\hat{\gamma}$, are bigger than user-defined tolerances, $\bar{\varepsilon}$, $\bar{\rho}$, and $\bar{\gamma}$, mark X_0 to be split; otherwise mark X_0 as feasible and explored.

- While there are hyper-rectangles in Π that are marked to be split, select any hyper-rectangle $X_0 \subseteq \Pi$ marked to be split and split X_0 into new hyper-rectangles, $X_0, \dots, X_N$, by applying a heuristic splitting rule and mark the new hyper-rectangles, $X_0, \dots, X_N$, as unexplored.

In the implementation of the routine, the primal-dual interior-point algorithm with a filter line-search method IPOPT [11] is used to solve the nonlinear programming problems. For the solution of the mp-QP problems, the MPT 3.0 toolbox [12], an open source toolbox for parametric optimization, is embedded in the suggested algorithm.

The execution of the algorithm leads to an explicit approximate solution of the mp-NLP (24) – (25), including the solution of the mp-QP sub-problems over each orthogonal partition and consisting of piecewise affine solution functions and corresponding polyhedral critical regions. Therefore, the main computational effort is carried out off-line. The on-line computation reduces to the identification of the polyhedral region for a given parameter vector, x_p , and the evaluation of the associated multi-variable affine feedback law.

4.2 Post-processing and on-line evaluation

Appropriate post-processing generates and exports real-time executable code for the on-line evaluation of the explicit NMPC. The actual evaluation is a three-stage process:

- For a given parameter, $x_p(t_k)$, the first layer identifies the corresponding orthogonal partition and the associated local mp-QP sub-problem by traversing a memory-optimized binary search tree, generated based on [13] and implemented in the MPT 3.0 toolbox [12].
- Having determined the orthogonal partition, the second layer identifies the corresponding polyhedral critical region of the affine state-feedback law, by traversing a binary search tree or alternatively a sequential search data structure. It evaluates the feedback law, and returns the value.
- In the last layer, the feasibility of evaluation is reviewed and, in case of infeasibility, the control action applied at the previous time step is provided as reasonable alternative.

Since the dynamic system (1) – (2) is point symmetric with respect to the origin for a given speed, the exploration space can be reduced by bisection.

4.3 Implementation

The execution of the explicit NMPC algorithm, with suitable settings for the specific vehicle stability control application, leads to an explicit solution in the 4-dimensional

parameter space consisting of 165 orthogonal partitions including 4886 polyhedral regions in total. The considered range of the parameters was chosen to keep the complexity of the explicit controller moderate, and needs to be reviewed for the implementation of the controller on a vehicle demonstrator.

5 Simulation results

5.1 Sine-with-dwell test

The behavior of the vehicle with the explicit NMPC based stability controller is simulated along the sine-with-dwell test, as shown in Figure 2, to demonstrate the fulfilment of the performance requirements of the regulation UN/ECE-R13H [14].

Figure 2 Sine-with-dwell test; figure adapted from [15].

The test conditions are explained in [14] and can be summarized as follows:

- Vehicle coasting in high gear at 80 km/h.
- $A_{\delta_{sw}}$, defining the steering wheel amplitude, is the steering wheel angle, δ_{sw} , at the lateral acceleration $a_y = 0.3$ g, determined during a slowly increasing steering maneuver at 80 km/h.
- In each sine-with-dwell test run of the test series, the steering wheel amplitude is increased from run to run by $0.5 A_{\delta_{sw}}$, starting with $1.5 A_{\delta_{sw}}$ for the initial run.

The directional or yaw stability criteria to be fulfilled are:

- The yaw rate at time T_{0+1} , i.e., 1 s after T_0 , shall be $< 35\%$ of the yaw rate peak, $\dot{\psi}_{Peak}$.
- The yaw rate at time $T_{0+1.75}$, i.e., 1.75 s after T_0 , shall be $< 20\%$ of the yaw rate peak, $\dot{\psi}_{Peak}$.

$\dot{\psi}_{Peak}$ is defined as the first peak value of yaw rate, recorded after the steering wheel angle changes sign, and T_0 is defined as the time at the completion of the steering wheel input.

Moreover, the following responsiveness criterion must be met by vehicles with a mass ≤ 3500 kg, such as the one of this study:

- The lateral displacement of the vehicle center of gravity with respect to its initial straight path must be > 1.83 m.

The performance indices J_1 and J_2 are introduced to quantify the directional stability criteria:

$$J_1 = \frac{\dot{\psi}(T_{0+1})}{\dot{\psi}_{Peak}} 100 \quad (26)$$

$$J_2 = \frac{\dot{\psi}(T_{0+1.75})}{\dot{\psi}_{Peak}} 100 \quad (27)$$

5.2 Results

The results are based on an experimentally validated high-fidelity CarMaker simulation model of a case study SUV. The model includes consideration of the electro-hydraulic braking system pressure dynamics at the calipers, based on variable pure time delays and first order dynamics, parameterized through experimental tests on a real plant. The steering wheel amplitude, $A_{\delta_{sw}} = 25.8$ deg, was determined according to [14].

Figure 3 reports the response of the passive vehicle, i.e., the vehicle without the stability controller, during a sine-with-dwell test with a steering wheel amplitude $\delta_{sw} = 103.2$ deg, corresponding to test run 6 of the test series. The large values of rear axle slip angle and vehicle sideslip angle show that vehicle controllability is compromised. Similar behavior can be observed for the following test runs of the passive vehicle, with a maximum steering wheel amplitude $\delta_{sw} = 270.9$ deg for the final test run 19.

Figure 3 Passive vehicle.

Figure 4 shows the vehicle response of the controlled vehicle with the implicit NMPC based on the proposed formulation, and used as benchmark for the explicit NMPC. The plots are for test run 6, with the same steering wheel input as for the test with the passive vehicle reported in Figure 3. In contrast to the uncontrolled vehicle, the rear axle slip angle and vehicle sideslip angle have moderate values, which demonstrates the effectiveness of the proposed control system. The violation of the yaw rate error bound (indicated by the dash dotted lines in the relevant subplot of Figure 4) is significantly reduced by the control action, i.e., the yaw rate profile follows the steering wheel input profile. Moreover, the decrease of vehicle speed due to differential braking is at an acceptable level, and the final value of vehicle speed is higher than for the passive vehicle. The interdependence of the two main objectives, namely reducing the violation of the

bound on the yaw rate error and rear axle slip angle, can be influenced by the appropriate selection of the weights in the cost function (14). In this setting, priority is given to the rear slip angle contribution, with moderate weights on the yaw rate error contribution.

Figure 4 Vehicle with the implicit NMPC.

Figure 5 Vehicle with the explicit NMPC.

Figure 5 reports the vehicle response of the controlled vehicle with the explicit NMPC based stability controller. In comparison with the implicit NMPC in Figure 4, only a very marginal difference can be observed in the control action. More importantly, there is no observable difference in the vehicle response. The difference in results between implicit NMPC and explicit NMPC can be influenced by choosing the tolerances on the

respective error bounds of the explicit NMPC partitioning algorithm, to find a balance between reasonable levels of sub-optimality and moderate complexity of the explicit controller.

Figure 6 Directional stability criteria.

Figure 6 shows the performance indicators for the directional stability criteria, defined in equations (26) and (27), for the passive vehicle, without the stability controller, and the controlled vehicle, with the explicit NMPC stability controller active, simulated for the entire test series. The dash dotted lines in the figure represent the threshold values for J_1 and J_2 defined by the regulation [14]. A very significant reduction of the performance indicators is achieved by the proposed control system, for the entire set of steering wheel amplitude values. At the same time, the responsiveness criterion remains almost unchanged by the stability controller.

6 Conclusion

This study presented the design, implementation and performance assessment of an explicit NMPC for yaw and lateral stability control of a vehicle with an electro-hydraulic braking system. The preliminary simulations results demonstrate the effectiveness of the explicit NMPC approach, which does not imply any performance decay with respect to the corresponding implicit NMPC. Significant improvements of the vehicle response in sine-with-dwell tests are brought by the vehicle stability controller. The vehicle with

the controller remains within the specified thresholds of the stability criteria of the sine-with-dwell test.

Future steps will focus on:

- The detailed analysis of the performance benefits of the individual nonlinearities included in the prediction model.
- The comparison with stability control systems based on classical control structures.
- The revision and extension of the current explicit NMPC based stability controller, to meet the practical requirements for its implementation on a vehicle demonstrator.

Acknowledgements

The Authors would like to thank MTS Ltd for the financial support to the project.

References

- [1] P. Falcone, F. Borrelli, J. Asgari, H. E. Tseng, and D. Hrovat, “Predictive Active Steering Control for Autonomous Vehicle Systems,” *IEEE Trans. Control Syst. Technol.*, vol. 15, no. 3, pp. 566–580, 2007.
- [2] O. Barbarisi, G. Palmieri, S. Scala, and L. Glielmo, “LTV-MPC for Yaw Rate Control and Side Slip Control with Dynamically Constrained Differential Braking,” *Eur. J. Control*, vol. 15, no. 3–4, pp. 468–479, 2009.
- [3] S. Di Cairano, H. E. Tseng, D. Bernardini, and A. Bemporad, “Vehicle yaw stability control by coordinated active front steering and differential braking in the tire sideslip angles domain,” *IEEE Trans. Control Syst. Technol.*, vol. 21, no. 4, pp. 1236–1248, 2013.
- [4] M. Canale, L. Fagiano, and V. Razza, “Approximate NMPC for vehicle stability: Design, implementation and SIL testing,” *Control Eng. Pract.*, vol. 18, no. 6, pp. 630–639, 2010.
- [5] P. Tøndel and T. A. Johansen, “Lateral Vehicle Stabilization Using Constrained Nonlinear Control,” in *European Control Conference (ECC)*, pp. 1887–1892, 2003.
- [6] H. B. Pacejka, *Tire and Vehicle Dynamics*, 3rd ed. Oxford: Elsevier Ltd, 2012.
- [7] A. Grancharova, T. A. Johansen, and P. Tøndel, “Computational Aspects of Approximate Explicit Nonlinear Model Predictive Control,” in *Assessment and Future Directions of Nonlinear Model Predictive Control*, Berlin, Heidelberg:

- Springer, pp. 181–192, 2007.
- [8] A. Grancharova and T. A. Johansen, *Explicit Nonlinear Model Predictive Control, Theory and Applications*, vol. 429. Springer Science+Business Media, 2012.
 - [9] T. A. Johansen, “On multi-parametric nonlinear programming and explicit nonlinear model predictive control,” *Proc. 41st IEEE Conf. Decis. Control*, vol. 3, pp. 2768–2773, 2002.
 - [10] L. F. Domínguez and E. N. Pistikopoulos, “Recent Advances in Explicit Multiparametric Nonlinear Model Predictive Control,” *Ind. Eng. Chem. Res.*, vol. 50, no. 2, pp. 609–619, 2011.
 - [11] A. Wächter and L. T. Biegler, “On the implementation of an interior-point filter line-search algorithm for large-scale nonlinear programming,” *Math. Program.*, vol. 106, no. 1, pp. 25–57, 2006.
 - [12] M. Herceg, M. Kvasnica, C. N. Jones, and M. Morari, “Multi-Parametric Toolbox 3.0,” in *European Control Conference (ECC)*, pp. 502–510, 2013.
 - [13] P. Tøndel, T. A. Johansen, and A. Bemporad, “Evaluation of piecewise affine control via binary search tree,” *Automatica*, vol. 39, no. 5, pp. 945–950, 2003.
 - [14] UNECE, *Addendum 12-H: Regulation No. 13-H, Revision 2, Uniform provisions concerning the approval of passenger cars with regard to braking*. 2011.
 - [15] A. Lutz *et al.*, “Simulation methods supporting homologation of Electronic Stability Control in vehicle variants,” *Veh. Syst. Dyn.*, vol. 55, no. 10, pp. 1432–1497, 2017.