1167166 (5906716)

All rights reserved

INFORMATION TO ALL USERS

The quality of this reproduction is dependent upon the quality of the copy submitted.

In the unlikely event that the author did not send a complete manuscript and there are missing pages, these will be noted. Also, if material had to be removed, a note will indicate the deletion.

Published by ProQuest LLC (2017). Copyright of the Dissertation is held by the Author.

All rights reserved.

This work is protected against unauthorized copying under Title 17, United States Code
Microform Edition © ProQuest LLC.

ProQuest LLC.
789 East Eisenhower Parkway
P.O. Box 1346
Ann Arbor, MI 48106 – 1346

COMPARISON OF BEHAVIOUR
OF THREE TYPES OF
BRACED DOMES

BY
P D PAKANDAM

A THESIS PRESENTED FOR THE DEGREE OF
MASTER OF PHILOSOPHY

CIVIL ENGINEERING DEPARTMENT
UNIVERSITY OF SURREY

JUNE 1988

ABSTRACT

Domes provide an easy and economic method of covering large areas. The three types of braced domes, i.e. geodesic, Schwedler and three-way grid domes, composed of steel tubular members are investigated with a view to understand their behaviour.

The behaviour of these domes is studied under four load cases with two boundary conditions and two height to span ratios. Furthermore, a comparison is made of the behaviour of these domes. For this purpose, a well known computer package - LUSAS (based on finite element method of analysis) is used assuming pin-connected conditions. The data for the analysis are prepared with the help of an automatic data generation system using formex algebra. Computer program using the FORTRAN77 incorporating Gino routines were developed to present the results graphically. These results include member forces, nodal deflections and support reactions.

Each dome is optimized by choosing the required member sizes according to the magnitude of forces considering all four load cases. For convenience in construction, the number of different cross-sections for a dome is kept to four.

The study shows that member axial forces in the domes are almost uniform. This is true with the exception of members in the two outer rings of the domes, where both vertically and fully translational restraints are used as boundary conditions. Particularly, force concentrations are found in the members near the fully constrained supports.

The majority of members in the domes are carrying compressive forces and the extent of tensile forces is

limited to the members near the supports. Nevertheless, the maximum tensile force is not larger than 67% of the maximum compressive force in any dome for any load case. Particularly, the tensile forces are practically non-existent where all the boundary nodes of the domes are fully restrained.

ACKNOWLEDGEMENTS

My sincere gratitude is due to my supervisor, Prof. Z. S. Makowski, for his guidance through the development of my research work.

I would also like to express my gratitude to Dr. H. Nooshin, for his encouragement and advise throughout this work.

Special thanks go to my colleague Mr M. Ashraf, for his helpful comments throughout the period of my research. Thanks are also due to Mr D. I. Retief and Mr M. Khabbazan for their help.

To these and other friends and staff at the Space Structure Research Centre of the University of Surrey which made the period of my research a memorable one, I extend my sincere appreciation and thanks.

My special thanks go to my family for their support.

CONTENTS

	Page
ABSTRACT	1
ACKNOWLEDGEMENTS	3
 1 INTRODUCTION	 9
 2 BRACED DOMES	 13
2.1 Introduction	13
2.1 Types of braced domes	15
2.3 Optimization of braced domes	21
2.4 Formex Formulation of Braced Domes	22
2.5 Design Loading	24
2.6 Analysis	28
2.7 Design of Braced Domes	31
2.7.1 Support Conditions	32
2.7.2 The Roof Covering	33
2.7.3 Method of Fabrication, Method of Erection, Shape of Sections and Types of Joint	 33
2.8 Preliminary and Final Design of Domes	34
2.9 Outline of the Research Studies	36
2.9.1 Data Generation	37
2.9.2 Determination of Load Cases	37
2.9.3 Boundary Conditions	40
2.9.4 Analysis and Design	47
2.9.5 Check of Capacity	48
2.9.6 Comparison of Results	49
(A) Axial Forces	49
(B) Deflections	49
(C) Support Reactions	50
 3 GEODESIC DOMES	 51
3.1 Introduction	51

3.2	Regular Polyhedra	53
3.3	Data Generation for Geodesic Domes	55
3.3.1	The Basic Sub-structure	58
3.3.2	Geometric Particulars	59
3.4	Structural Analysis and Design	63
3.5	Configuration GD1	64
3.5.1	Specifications	64
3.5.2	Data Preparation	64
3.5.3	Load Cases	67
3.5.4	Boundary Conditions	67
3.5.5	Design	73
3.5.6	Capacity Check	73
3.6	Discussion of Results	78
3.6.1	The Study of Support Type S1	78
	(A) Axial Forces	78
	(B) Deflections	84
	(C) Support Reactions	89
3.6.2	The Study of Support Type S2	94
	(A) Axial Forces	94
	(B) Deflections	99
	(C) Support Reactions	104
3.7	Configuration GD2	109
3.7.1	Specifications	109
3.7.2	Data Preparation	109
3.7.3	Load Cases	112
3.7.4	Boundary Conditions	117
3.7.5	Design	117
3.7.6	Capacity Check	117
3.8	Discussion of Results	124
3.8.1	The Study of Support Type S1	124
	(A) Axial Forces	124
	(B) Deflections	129
	(C) Support Reactions	134
3.8.2	The Study of Support Type S2	139
	(A) Axial Forces	139

(B) Deflections	144
(C) Support Reactions	149
3.9 Concluding Discussion	154
3.10 Conclusions	167
4 SCHWEDLER DOMES	169
4.1 Introduction	169
4.2 Specifications of the Dome	171
4.3 Data Generation for Schwedler Domes	172
4.4 Structural Analysis and Design	174
4.5 Configuration SD1	175
4.5.1 Specifications	175
4.5.2 Data Preparation	175
4.5.3 Load Cases	179
4.5.4 Boundary Conditions	179
4.5.5 Design	179
4.5.6 Capacity Check	180
4.6 Discussion of Results	190
4.6.1 The Study of Support Type S1	190
(A) Axial Forces	190
(B) Deflections	196
(C) Support Reactions	201
4.6.2 The Study of Support Type S2	206
(A) Axial Forces	206
(B) Deflections	211
(C) Support Reactions	216
4.7 Configuration SD2	221
4.7.1 Specifications	221
4.7.2 Data Preparation	221
4.7.3 Load Cases	225
4.7.4 Boundary Conditions	225
4.7.5 Design	225
4.7.6 Capacity Check	226
4.8 Discussion of Results	236
4.8.1 The Study of Support Type S1	236

(A)	Axial Forces	236
(B)	Deflections	242
(C)	Support Reactions	247
4.8.2	The Study of Support Type S2	252
(A)	Axial Forces	252
(B)	Deflections	257
(C)	Support Reactions	262
4.9	Concluding Discussion	267
4.10	Conclusions	281
5	THREE-WAY GRID DOMES	283
5.1	Introduction	283
5.2	Discussion on the Three-way grid Method	285
5.3	Data Generation for Three-way grid Domes	286
5.3.1	Geometric Particulars	287
5.3.2	General Procedure	288
5.4	Structural Analysis and Design	292
5.5	Configuration TW1	293
5.5.1	Specifications	293
5.5.2	Data Preparation	293
5.5.3	Load Cases	296
5.5.4	Boundary Conditions	296
5.5.5	Design	302
5.5.6	Capacity Check	302
5.6	Discussion of Results	307
5.6.1	The Study of Support Type S1	307
(A)	Axial Forces	307
(B)	Deflections	313
(C)	Support Reactions	318
5.6.2	The Study of Support Type S2	323
(A)	Axial Forces	323
(B)	Deflections	328
(C)	Support Reactions	333
5.7	Configuration TW2	338
5.7.1	Specifications	338

5.7.2	Data Preparation	338
5.7.3	Load Cases	341
5.7.4	Boundary Conditions	341
5.7.5	Design	341
5.7.6	Capacity Check	342
5.8	Discussion of Results	352
5.8.1	The Study of Support Type S1	352
	(A) Axial Forces	352
	(B) Deflections	358
	(C) Support Reactions	363
5.8.2	The Study of Support Type S2	368
	(A) Axial Forces	368
	(B) Deflections	373
	(C) Support Reactions	378
5.9	Concluding Discussion	383
5.10	Conclusions	396
6	COMPARATIVE STUDIES	398
6.1	Introduction	398
6.2	Comparison of Geometric Properties	399
6.3	Design and Dead Weights	400
6.4	Dome Patterns	402
6.5	Axial Forces	403
6.6	Deflections	406
6.7	Support Reactions	408
6.8	Concluding Remarks	411
	REFERENCES	415

1

INTRODUCTION

DOMES : their form, function and architecture

Among the most astonishing creations of Nature, an egg is the master piece and the most shrewd use of structural material resulting in the greatest possible functional stability. The exceptional economy of material of doubly curved shell structures of revolution emphasizes the advantages of this particular form. Ovoidal shapes, however, are rarely used in civil engineering structures or architecture, and in practice the sphere becomes the optimal form of pure geometry, Ref 1.

Nature uses a profusion of various shell forms of single or double curvature, these natural structures provide the inspiration for architects and engineers in their search for novel solutions, Ref 1.

Domes are of special interest to engineers and architects as they enclose a maximum amount of space with a minimum surface and have proved to be very economic in the consumption of materials. Domes are also suitable for covering sports stadia, assembly halls, exhibition centres, swimming pools and industrial buildings in which large unobstructed areas are essential and where minimum

interference from internal supports is required. The provision of unobstructed sight-lines for large numbers of people is the primary requirement in sports halls and can easily be satisfied through the adoption of a domic shape, Ref 2.

A dome is a typical example of a synclastic surface in which the curvature at any point is of the same sign in all directions. Domic surfaces cannot be flattened into a plan without stretching or shrinking. This property is one of the reasons why, in practice, domes cannot be built from members of the same length; even geodesic domes require members of different lengths.

The dome was the natural development of the arch and has its own special problems largely due to a lack of appreciation of the forces involved. Many of the early domes were the main architectural features of their respective buildings and were high in relation to their base width.

The development of domes has been closely associated with the development of available materials. In antiquity, domes were built in stone, but brickwork gradually replaced the stone masonry. Timber was the principal roofing material used in the Middle Ages and some timber domes from this period still exist. Iron bars were used to take tension loads around the base, particularly where a dome was set on a rectangular building.

Most early buildings appear to have been built on a circular plan and domes proved to be an easy and convenient method of roofing them. However, though there is little doubt that the dome started only as a utilitarian form of roofing, the domic shape became a religious symbol associated in pagan, early Christian and Islamic periods with tombs, tabernacles,

baptisteries, churches, mosques and royal audience halls.

As a rule, earlier domes were hemielliptical or hemispherical in shape producing only vertical reactions on the supports. It has to be remembered that the design of these structures was based on the experience and the intuition of the designers.

Concrete was used extensively by the Romans for the building of domes, but plain concrete, although strong in compression, is very weak in tension, so un-reinforced concrete domes had to be made very thick. Adding steel reinforcement to the concrete in order to resist the tensile forces opened up an exiting new field of structural engineering. The first reinforced concrete "RC" shell dome, was built in early 20th century.

However, the initial great enthusiasm of designers for the use of RC shell started gradually to die out, once the drawbacks of this form of construction were realized-RC shells require elaborate and very expensive framework, are slow in construction and often not really economic in their final cost.

This was the time when the advantages of steel, aluminium alloys and also glass-fibre reinforced plastics were appreciated. The period of the last quarter of the last century has been specially marked all over the world through the bold and imaginative use of metal-braced domes.

New materials, aluminium alloys and specially steels are now the most commonly used materials for the construction of braced domes and are influencing their development and their use for covering large spans. Aluminium has permitted the realization of some of the most beautiful structures and its

use has been instrumental in the development of stressed-skin systems, in which the covering panels become an integral part of the structural framework, increasing at the same time the general stability.

In the present work a search has been carried out for a single-layer steel braced dome of minimum weight examining different types of bracing, different boundary conditions and varying height to span ratios.

An optimum design is obtained to satisfy four different load cases for each particular boundary condition and configuration. The results are presented in graphical form comparing member forces and nodal deflections.

2

BRACED DOMES

2.1 INTRODUCTION

The introduction of steel, with its greatly improved properties of high strength, proved to be a fundamental influence in the development of various type of braced dome and their use for large spans.

With the increased acceptance of structural steel, domes tended to get shallower in respect of their span and today domes which only have a slight rise become quite practical.

The dome is exceedingly economic in the use of material in terms of weight of steel per square metre covered and design has developed largely with the objective of reducing the number of different size members in the structure.

One of the most important problems facing designers is to find the grid configuration with the smallest number of different members and joints. Various types of jointing system have been proposed so far, though only some of them are now available in practice. This is mainly because often the most sophisticated ones are too complicated or cost too much to manufacture. From the viewpoint of cost and mass production, it is not favourable to use too many different

kinds of structural members or joints.

A dome is very difficult shape to clad and many methods have been used which usually require considerable tailoring. This makes cladding an expensive operation, which offset the good economics of the structure. Development work has been done on the problem and proposals for a good solution have now become available which enable standard steel profiled sheets to be used in a conventional manner, Ref 3.

The revival of the interest in braced domes and their further development took place after the Second World War. However, the main credit for recent structural development should go to several distinguished designers who are responsible for the further development of various types of braced dome and the construction of a large number of such structures in many parts of the world.

It is usual to subdivide braced domes into four main groups:

- (a) frame or skeleton-type single-layer domes;
- (b) truss-type domes and double-layer domes (suitable for covering very large spans);
- (c) stressed skin type (in which the covering is connected to the bracing members and form an integral part of the main load-carrying structural system);
- (d) formed surface type domes (in which thin steel, aluminium or GRP sheets are bent and interconnected along their edges to form the main skeleton system of the dome).

Most domes are examples of the first type. They are used for smaller spans, though there are few examples of single-layer domes reaching a clear span exceeding even 100 m, Ref 2.

The double-layer domes are exceptionally rigid and are used for very large span. At present the largest clear span in the world is covered by a double-layer dome of 213 m diameter, Ref 2.

2.2 TYPES OF BRACED DOMES

The survey of braced domes which have been built within the last 20 years shows that only four or five types proved to be frequently used in practice. Professor Makowski in his book, "Analysis, design and construction of braced domes" published in 1984, referred to the development of the most commonly used types of bracing for skeleton domes. They are

- (a) ribbed domes, which are now often used and are frequently constructed in prefabricated tubular arched rib units, Fig 2.2.1;
- (b) Schwedler domes, which were introduced in 1863 and still remain extremely popular especially in the USA, Fig 2.2.2;
- (c) braced domes, which in Europe are now mostly being built as three-way single-layer grids, Fig 2.2.3;
- (d) parallel-lamella domes, which continue to be used for very large spans in the USA, Fig 2.2.4;
- (e) geodesic domes, which are now well established and used in practice, but mainly in aluminium, Fig 2.2.5.

RIBBED DOMES

Fig 2.2.1

SCHWEDLER DOMES

Fig 2.2.2

THREE-WAY GRIDES DOMES

Fig 2.2.3

PARALLEL-LAMELLA DOMES

Fig 2.2.4

GEODESIC DOMES

Fig 2.2.5

2.3 OPTIMIZATION OF BRACED DOMES

Theoretical analyses on the economy of structures are most often based on the criterion of minimum volume of material. This approach does not necessarily lead to a correct answer, as any economic design is greatly influenced by practical aspects, which are based mainly on experience and ingenuity and therefore can never be fully included in theoretical analyses.

The search continues for a structure of minimum weight as a function of certain pre-assigned parameters, such as span, support conditions, external loading and structural topology.

To obtain an optimum braced dome in terms of minimum cost is much more difficult, because, in addition to the parameters mentioned above, the designer has to include in his optimization approach the influence of the cost of joints, type of roof covering, fabrication and erection techniques, which may have a profound influence on the final cost of the finished structure.

Before the introduction of electronic computers, only very rarely were comparisons of several alternative designs carried out, as each analysis was a tedious and time consuming operation. Nowadays, with the general availability of high-speed computers, the situation has changed drastically and the final designs of large-span important domes are the result of extensive feasibility studies of different types of dome, compared in order to assess the advantages and disadvantages of each solution.

As mentioned above, the dead weight of domes is a function of the structural material used. it depends mainly on the

span, rise-to-span ratio, type of bracing, boundary condition, intensity of external loading applied, the type of covering and the material in which the structure will be built.

The initial cost of the structure is frequently an important criterion in selecting a particular type of system. A responsible consulting engineer will, no doubt, remind his client that many factors have to be taken in to account, the availability of the material, the ease and speed of erection, the transportation cost and the maintenance cost, which unfortunately is only rarely taken in to account at the time of the final decision.

2.4 FORMEX FORMULATION OF BRACED DOMES

An excellent and elegant solution for automated data generation is provided by a general system of configuration processing which has formex algebra as its basis. The basic concepts of formex was originally conceived by H Nooshin in 1972-1973. The early ideas went through substantial transformation during the years that followed and an up to date account of the concept of formex algebra is given in the book written by Dr. Nooshin in "Formex Configuration Processing in structural Engineering" and published in 1984. Formex algebra is a mathematical system that consists of a set of abstract objects, a set of relations and a set of operations and functions. Formex algebra may be used in various ways to overcome the difficulties of data generation. It allows networks of all kinds to be formulated and is a valuable tool in dealing with complex configurations.

Formices may be used to represent the interconnection

pattern of a configuration. Geometric particulars may be related to the formex representation of a configuration through set of rules and conventions referred to as "retrobases". In order to represent a configuration through formices, it is convenient to adopt a set of rules known as "probasis" through which the correspondence or transformation may be specified.

Graphical representation and coordinate systems are common means to implement the mutual relation between configurations and formices and they normally constitute fundamental aspects of probases and retrobases. A graphical arrangement, for instance, may be interpreted either as an interconnection pattern or as a formex plot.

An interconnection pattern is considered to be free of any geometric definition. On the other hand, a graphical representation of the inter connection pattern or a formex plot is a geometric object. Thus, one may play with various graphical conventions and coordinate specifications either to ease the transformations or correspondence between configuration and formices or, moreover, to obtain configurations with little geometric similarity from the same interconnection pattern. For instance, configurations with rotation or cyclic symmetry, such as various types of domes, are conveniently specified in polar or spherical coordinate systems. On the other hand, formices may be plotted by using polar or spherical coordinate systems in order to obtain graphical and geometric configurations showing rotational and radial effects.

To generate the element topology and node coordinates required for the analysis computer program, in the present work, extensive use was made of formex algebra developed at the Space Structures Research Centre of the University of Surrey by H Nooshin.

2.5 DESIGN LOADING

An understanding of the flow of wind around any structure, leading to the accurate prediction of wind pressure and forces, is an essential requirement for modern structural design. This is especially important in view of the rapid developments in building design and construction techniques resulting in structures which are becoming far more susceptible to the effect of the wind. This is due in part, to the use of light-weight cladding materials, inevitably leading to reductions in strength and stiffness, and also to the application of sophisticated computer-assisted design methods. These methods have removed many of the elements of approximation from structural analysis and this, in turn, has led to structures whose performance can be more accurately predicted. For this reason, it is of fundamental importance that external loads, and in particular wind loads, are correctly estimated.

The determination of snow loading action on domes is extremely difficult and several known examples of collapse of domes show that the failure has been produced by the unsymmetric accumulation of snow.

The majority of codes are only able to provide data relating to the most of the common shapes of building, but as a rule do not provide for unusual or 'difficult' structures such as domes.

In the United Kingdom, there are no special considerations that are required by the codes of standards for the design of domes. The prime loading is obtained from BS 6399 : Part 1, code of basic data for the design of buildings, which gives the values for dead and superimposed loads, and CP3 : Chapter 5 : Part 2, gives information on the

determination of the design wind velocities in relation to the surrounding terrain and the height of the structure.

With a dome, however, due to its special structural characteristics, it is necessary to give consideration to particular loading situations. Nominally, the imposed loading due to snow should be considered with the possibility that it may be unsymmetrically positioned. This can quite easily be caused by the accumulation of snow in the valleys between domes in a multiple dome arrangement or simply due to the effects of wind where there is a single dome.

The possible values are difficult to ascertain as there is little information on this subject although the proposal given in ISO/DIS/4355, Basis for design of structures: determination of snow loads on roofs, 5.2.3, Simple curved roofs, will be of interest, although the actual values should be determined by the engineer in the light of the actual configuration and location of the structure. Section 5.2.3 is reproduced in Fig, 2.5.1.

In CP3 : Chapter 5 : Part 2, coefficients for domes are not given. An extract is given from the Recommendations for the calculation of wind effects on buildings and structures, issued by Technical Committee T.12 of the European Convention for constructional steelwork. This is shown in Fig, 2.5.2.

It may be concluded that, having regard to the reliability of the available information on domes, the codes of practice are only suitable for preliminary design purposes. It is therefore necessary to undertake further wind-tunnel tests in an attempt to establish more accurately the pressure distributions on domes.

Simple curved roofs

The following cases, 1 and 2, must be examined :

Restriction :

$$\mu_2 \leq 2,3$$

$$\mu = 0 \text{ if } \beta > 60^\circ$$

Intensity of nominal snowload on roof, $s = \mu s_c$, where s_c = characteristic intensity of snow load on ground.

Snow loads: Draft ISO/DIS 4355, Section 5.2.3 Simple curved roofs

Fig 2.5.1

C_{pe} is constant along the intersection between the dome and planes perpendicular to the wind : it can be determined as a first approximation by linear interpolation between the values at A, B and C. In the same way, values of C_{pe} at A if $0 < h/d < h$ and at B or C if $0 < h/d < 0,5$ can be obtained by linear interpolation.

External pressure coefficients C_{pe} :

Cylindrical structures supporting spheres
or portions of spheres

Wind loads: extract from *Recommendations for the calculation of wind effects on buildings and structures (ECCS)*

Fig 2.5.2

BRACED DOMES

The area of dome on sphere and plane for each node is required in order to estimate the value of dead, imposed, snow, and wind loads at each node by using corresponding surface area.

It is essential that specific consideration be given to each loading point and the possible combinations as these will have a considerable effect on the stability of the structure.

2.6 ANALYSIS

The exact analysis of braced domes remained, for many years, a very difficult task. However, the introduction of large-capacity electronic computers and the recent development in the algebraic processing of structures now enable designer to determine the stress distribution in braced domes with a very high degree of accuracy. So, many of the exciting possibilities offered by this form of construction can now be achieved readily and with confidence, Ref 10.

The object of analysis a structure is to predict its behaviour under prescribed external actions so that it may be designed to withstand these actions safely.

The internal forces and displacements of a structure under a given system of external actions satisfy the conditions of equilibrium and compatibility throughout the structure and any technique for analysis of structures consists of a systematic search to find a set of internal forces and displacements that satisfies these conditions simultaneously.

The stiffness method of analysis is a popular and widely used technique which is ideally suited to implementation on a digital computer.

In this method of analysis, equations of equilibrium are set up in terms of the nodal displacements as unknowns. These equations are solved to evaluate the nodal displacements and from the displacements member forces are calculated using the force-displacement relationships for each element.

The analysis requires a large amount of linear algebraic manipulation and the most suitable branch of mathematics for representing such manipulations is matrix algebra. In addition to being ideally suited to computer implementation, matrix algebra allows the basic concepts to stand out, allowing the fundamental principles to be easily and readily appreciated.

Linear structural analysis, as the name implies, deal with the analysis of structures which behave linearly. Virtually no structural systems behave in a truly linear fashion, but most practical systems behave almost linearly within the range of loading for which they are designed. In the analysis of a linear system, the equation of equilibrium are set up in terms of the undisplaced shape of the structure and solved to evaluate the displacements.

The first step in such an analysis is the determination of the relationship between forces and displacements affecting each part of the structure. These relationships are used in forming the primary stiffness matrix of the structure which relates the displacements of the joints of that structure to the components of the external load applied at the joints and the components of the reaction at the constrained joints. This relationship can be symbolized as

$$\overline{K} d = \overline{w},$$

where $\overline{K}$ is the primary stiffness matrix of the structure, d is the displacement vector of the structure and w is the appended load vector of the structure.

This relationship does not, however, take in to consideration the matter of support constraints. The aforementioned equation contains the equilibrium conditions throughout the structure but does not fully represent the compatibility requirements. The consistency of member-end displacements with the relevant joint displacements is insured, but the external compatibility conditions at the supports are not taken into account. Modifying the system $\overline{K} \cdot d = \overline{w}$ to take into account support conditions results in a system which is complete expression of all the conditions of equilibrium and compatibility throughout the structure. In symbolic notation, this relationship is

$$K d = w,$$

where K is the stiffness matrix of the structure, d is the displacement vector of the structure and w is the load vector of the structure.

Unlike $\overline{w}$, w does not include any information about the components of reaction. Which are of course, unknown at this stage. This system can now be solved to obtain values for the hitherto unknown nodal displacements, and from these displacements, again using the force-displacement relationships, member forces can be evaluated. From the member forces at a constrained joint, reactions can be evaluated simply by considering equilibrium.

2.7 DESIGN OF BRACED DOMES

Generally speaking, a larger number of different structural members and joints is needed in dome structures than in flat or cylindrical structures. Therefore, one of the most important problems facing a designer is to find the grid configuration with the smallest number of different members and joints.

A triangular spherical grid, because it provides greater rigidity than other grids, which is a governing factor in the lateral stability of domes, is the best arrangement of the grids.

The choice of the frequency has an important influence on the final cost. An excessive subdivision rapidly increases the number of joints in the structure and obviously has a direct bearing on the fabrication cost and the cutting of the members. If, on the other hand, the frequency is too low, the density of the resulting network will be reduced, causing at the same time an increase in the length of the component members. As they have to be designed to carry compressive forces, their increased length automatically leads to a higher slenderness ratio and requires a large cross-section to prevent elastic instability of the members. The increase in the weight of the structure obviously results in a higher cost.

The ratio of the height of the dome to its diameter, h/d , should not be too low, because of the possible danger of structural instability of the framework. The minimum h/d should be at least $1/5$.

Practical aspects always have decisive effects on the economic design of any structure. Unfortunately, they can

never be fully included in computer programs nor can be experience, intuition and ingenuity of designers ever be formulated in mathematical expressions. Another difficulty is that the practical aspects must be taken into account in the preliminary design before any theoretical analysis is started, otherwise it may not be possible to apply them. The most important practical aspects included in the discussion are

- (a) the support conditions;
- (b) the roof covering;
- (c) the method of fabrication, method of erection, shape of sections and type of joint.

2.7.1 Support Conditions

It may not be advisable to recommend any particular number of supports because it depends mainly on the architectural requirements and on the prevailing conditions. The most important factors affecting the economic design of domes are:

- (a) the number of supports;
- (b) the kind of supports;
- (c) the position of supports above the floor level.

Two effects of supports are known:

- (1) The greater the number of supports, the more uniform is the stress distribution in members, i.e. a more economic dome design can be achieved, but at the expense of the supports and foundations.
- (2) The more rigid the supports, the smaller are the

deflections of the joints or the greater is the lateral stability of the dome, but at the expense of the supports and foundations.

Therefore it is very difficult to make an exact assessment of the number and kind of supports in the preliminary design. The intuition, experience and ingenuity of designers will be perhaps the best advisers in the preliminary design of domes.

2.7.2 The Roof Covering

A vital part in the construction of any dome is the provision of a water-proof cladding system. A dome is an example of a synclastic surface in which the radius of curvature has the same sign in all directions. Such surfaces cannot be developed into a plane without shrinking or stretching.

Apart from difficulty of sealing such panels, which can create serious problems, most space frame structures consist of members which are designed to carry axial load only. Bending moment must therefore be avoided and in practice this means that cladding support points must be restricted to the node or joint positions. To achieve this it is necessary either to adopt a panel system which reflects the structural network or to provide an auxiliary system of purlins or supports bars.

2.7.3 Method of Fabrication, Method of Erection, Shape of Sections and Types of Joint

The practical aspects most predominantly affecting the

economy of design of any structure are: the method of fabrication, the method of erection, the shape of the sections and types of joint. Perhaps the best way is to consider all these aspects together.

It is not possible to make any definite recommendations concerning these aspects because the standard solutions are not necessarily the best and experience, intuition and ingenuity are necessary to envisage problems involved with the shape of section, method of fabrication, method of erection and type of joint.

2.8 PRELIMINARY AND FINAL DESIGN OF DOMES

The design of structures are usually carried out in two stages: preliminary and final.

The preliminary design is perhaps more important, as all the practical aspect should be envisaged at this stage. Some kind of feasibility study of the practical aspects could lead to a far greater economy than the most sophisticated theoretical analysis on the minimum volume of material. In other words, a theoretical analyst examining the economy of a structure should be familiar with the practical aspects and gifted with ingenuity.

The first step is to fix the span and rise of the dome, which are usually given by architects to suit the general requirements. The next step is to fix the number and kind of supports in conjunction with the architects. The next step in the preliminary design is the selection of the frequency of subdivision.

If a preliminary analysis is required, then some reasonable guess of the section properties and loading is necessary.

The members of domes are mainly subjected to axial forces combined with bending moments; torsional moments can usually be ignored. In order to simplify the preliminary analysis, pinned joints can be assumed and the members can be designed for axial forces only. Then, in the final analysis, with the joints assumed to be rigid, the axial forces would be reduced but some bending moments introduced.

For further simplification, only hollow circular sections are suggested.

The next simplification in the preliminary design refers to loading. Only one case of loading is suggested.

When the forces from the first approximate analysis are obtained and a preliminary design completed, then finally the second analysis with the assumption of fixed joints, corrected section properties and all required loading cases can be carried out easily.

2.9 OUTLINE OF THE RESEARCH STUDIES

The search has been carried out for a single-layer steel 50 m diameter braced dome of minimum weight.

The type of bracing has a fundamental influence upon the load carrying capacity of a dome and its deflection characteristics. Detail of optimization studies of some types of braced domes with special reference to their bracing arrangement, height to diameter* ratio, boundary conditions and load cases, involving the following

(A) Types of pattern:

- 1 Geodesic dome
- 2 Schwedler dome
- 3 Three-way grid dome

(B) Types of height to diameter ratios:

- 1 One third (Configuration 1)
- 2 One fifth (Configuration 2)

(C) Boundary conditions:

- 1 Support type S1
- 2 Support type S2

(D) Load cases:

1	Dead load and imposed load	LA
2	Dead load and unsymmetric snow load	LB
3	Dead load and wind load	LC
4	Dead load, snow load and wind load	LD

A total of 48 analyses are dealt with.

* The term 'diameter' in this contest is used to mean the diameter of the largest circle that passes through the supports of a dome in plan view.

2.9.1 Data Generation

Formex algebra and its interactive programming language, Formian, have been used to generate the element topology and nodal coordinates required for the analysis computer program.

2.9.2 Determination of Load Cases

The prime loading is obtained from BS 6399 : Part 1, which gives the value for dead and superimposed loads, and CP3 : Chapter 5 : Part 2, which provides information on the determination of the design wind velocities in relation to the surrounding terrain and the height of the structure.

The unsymmetric snow load is obtained from the proposal given in ISO/DIS/4355, Basis for design of structures : determination of snow load on roofs, 5.2.3, Simple curved roofs.

The coefficients of wind loads are determined from the Recommendations for the calculation of wind effects on buildings and structures, issued by Technical Committee T.12 of the European Convention for Constructional Steelwork.

The loads taken into account in order to verify the design for a dome 10 m high from the ground, were

- (a) the dead load (DL) amounting approximately to
$$DL = 0.40 \text{ kN/m}^2$$
- (b) the imposed load (IL) measured on plane
$$IL = 0.75 \text{ kN/m}^2$$
- (c) snow ordinarily considered as uniformly distributed in the horizontal projection, its intensity being

LOAD CASE LA

LA = 1.4 DL + 1.6 IL
DL = 0.40 kN/m² on sphere

IL = I_m · λ_{ep}
I_m = 0.75 kN/m²
λ_{ep} = Area on plan

IMPOSED LOAD

LOAD CASE LC

LC = 1.4 DL + 1.4 WL
DL = 0.40 kN/m² on sphere

WL = C_{pe} · q · λ_{es}
q = 0.537 kN/m²
λ_{es} = Area on sphere

WIND LOAD

LOAD CASE LB

LB = 1.4 DL + 1.6 SL
DL = 0.40 kN/m² on sphere

SL = U · S_e · λ_{ep}
S_e = 0.75 kN/m²
λ_{ep} = Area on plan

SNOW LOAD

LOAD CASE LD

LD = 1.2 DL + 1.2 SL + 1.2 WL
DL = 0.40 kN/m² on sphere

WL = C_{pe} · q · λ_{es}
q = 0.537 kN/m²
λ_{es} = Area on sphere

WIND LOAD

SL = U · S_e · λ_{ep}
S_e = 0.75 kN/m²
λ_{ep} = Area on plan

SNOW LOAD

LOAD CASES

Height to diameter ratio = 1/3

Fig 2.9.1

LOAD CASE LA

$$LA = 1.4 DL + 1.6 IL$$

$$DL = 0.40 \text{ kN/m}^2 \text{ on sphere}$$

$$IL = Im \cdot Aep$$

$$Im = 0.75 \text{ kN/m}^2$$

$$Aep = \text{Area on plan}$$

IMPOSED LOAD

$$WL = Cpe \cdot q \cdot Aes$$

$$q = 0.537 \text{ kN/m}^2$$

$$Aes = \text{Area on sphere}$$

$$\begin{matrix} A = -0.15 \\ B = -0.75 \\ C = -0.20 \end{matrix} \quad Cpe$$

WIND LOAD

LOAD CASE LD

$$LD = 1.2 DL + 1.2 SL + 1.2 WL$$

$$DL = 0.40 \text{ kN/m}^2 \text{ on sphere}$$

$$SL = U \cdot Se \cdot Aep$$

$$Se = 0.75 \text{ kN/m}^2$$

$$Aep = \text{Area on plan}$$

$$WL = Cpe \cdot q \cdot Aes$$

$$q = 0.537 \text{ kN/m}^2$$

$$Aes = \text{Area on sphere}$$

$$SL = U \cdot Se \cdot Aep$$

$$Se = 0.75 \text{ kN/m}^2$$

$$Aep = \text{Area on plan}$$

SNOW LOAD

WIND LOAD

SNOW LOAD

LOAD CASES

Height to diameter ratio = 1/5

Fig 2.9.2

BRACED DOMES

$$S_e = 0.75 \text{ kN/m}^2$$

(d) wind pressure is given by

$$q = 0.613 V_s^2$$

where q is in N/m^2 and V_s in m/s

$$V_s = V \cdot s_1 \cdot s_2 \cdot s_3$$

$$V = 40 \text{ m/s}$$

$$s_1 = 1$$

$$s_2 = 0.74$$

$$s_3 = 1$$

$$V_s = 29.6 \text{ m/s}$$

$$q = 0.613 \cdot 29.6 \cdot 29.6 \text{ N/m}^2$$

thus

$$q = 537 \text{ N/m}^2$$

The above load cases and coefficients of snow and wind loads for the two configurations are illustrated in Figs 2.9.1 and 2.9.2, respectively.

A computer based technique has been devised to find the accurate projected area for each node, and the values of dead, imposed, snow and wind loads at each node is determined by using the corresponding surface area.

2.9.3 Boundary Conditions

The following two types of boundary conditions were investigated for the detailed study of the domes:

type S1 All the boundary nodes of the dome are supported, five or six of them are restrained against complete translation movements and the remainder have vertical constraints only.

GEODESIC DOME

CONFIGURATION 6D1
Height to diameter ratio = 1/3.2

Support Type S1

Support Type S2

GEODESIC DOME
Configuration 6D1

LEGEND
Vertical Constraint
Complete Translational Constraint

Fig 2.9.3

GEODESIC DOME

CONFIGURATION GD2
Height to span ratio = 1/5

Support type S1

GEODESIC DOME

Configuration GD2

Support type S2

LEGEND
Vertical Constraint ○
Complete Translational Constraint ●

Fig 2.9.1

SCHWEDLER DOME

CONFIGURATION SD1
Height to diameter ratio = $1/3$

Support type S1

Support type S2

SCHWEDLER DOME

Configuration SD1

LEGEND
Vertical Constraint $\odot$
Complete Translational Constraint $\bullet$

Fig 2.9.5

SCHWEDLER DOME

CONFIGURATION SD2
Height to diameter ratio = 1/5

Support type S1

Support type S2

SCHWEDLER DOME
Configuration SD2

LEGEND
Vertical Constraint ⊙
Complete Translational Constraint ●

Fig 2.9.6

THREE-WAY GRID DOME

CONFIGURATION TW1
Height to diameter ratio = $1/3$

Support type S1

THREE-WAY GRID DOME
Configuration TW1

Support type S2

LEGEND
Vertical Constraint ⊙
Complete Translational Constraint ●

Fig 2.9.7

THREE-WAY GRID DOME

CONFIGURATION TW2
Height to diameter ratio = $1/5$

Support type S1

Support type S2

THREE-WAY GRID DOME
Configuration TW2

LEGEND
Vertical Constraint ⊙
Complete Translational Constraint ●

Fig 2.9.8

BRACED DOMES

type S2 All the boundary nodes of the dome are restrained against translational movements both in the horizontal and vertical planes of the structure.

All the support points are considered free to rotate in any direction.

The configuration of the domes and their support arrangements are shown in Figs 2.9.3 to 2.9.8.

2.9.4 Analysis and Design

In order to determine the nodal deflections and detailed stress distribution within the members, the structure was analysed using "LUSAS" system, which is based on the finite element displacement method of analysis, and contains a comprehensive range of elements and solution procedures for the analysis of most types of engineering structures.

All domes have been analysed under nodal concentrated loads, as given above. The domes are analysed by assuming pin-connected end conditions of the members, and subsequently the members are designed for axial forces only. The top covering of the domes have been considered to be connected on the nodes. The members are made by circular hollow section, obtained from BS 4848 : Part 2 : 1975.

The design of members have been based on BS 5950 : part 1 : 1985, which considers the limit state design. The design strength P_y is 275 N/mm² for steel of grade 43. The elements were assumed to be made from compact cross sections.

2.9.5 Check of Capacity

The tension capacity 'Pt' of the members have been taken from:

$$P_t = A_e \cdot P_y$$

where A_e is the effective area of the section.

The compression resistance 'Pc' of the members have been obtained from:

$$P_c = A_g \cdot p_c$$

where

A_g is the gross sectional area,

p_c is the compressive strength obtained from

BS 5950 : part 1 : 1985, table 27(b).

The member axial forces should be less than or equal to the corresponding capacities.

The type of joints considered facilitated to use gross sectional area A_g , even in the tension members design instead of the effective area A_e .

In order to determine the compressive strength p_c , the value of effective length L_e , has been taken as the length of the member, i.e. ($L_e = L$).

The ratio of the internal forces to the capacity of members are plotted in graphical forms. The dashed line indicate tensile forces. The value along the member describe the ratio of the internal force to the capacity of the member.

2.9.6 Comparison of Results

To simplify the comparison of member forces, nodal displacements and support reactions obtained from each analysis, the results are represented in the graphical form. The discussion of axial forces, deflections and support reactions is made below.

(A) AXIAL FORCES

The distribution of force is shown in the form of coefficients recorded along lengths of the corresponding members. The value of a member force can be obtained by multiplying the coefficient of a member with the given factor on each figure. Also, the thickness representing a member is proportional to the magnitude of the force in it.

The compressive axial force in a member can be identified by a negative sign preceeding its coefficient. In addition, the members with compressive force are represented by firm lines as against dotted lines for the plotting of the member with tensile axial forces.

The comparison of axial forces in the dome with the two types of supports, under influence of each load case, is represented on the same figure. In the figure, the axial forces obtained from the two support types are shown. A value is recorded along the member. This value can be used to obtain the axial force in member by multiplying it with the given factor.

(B) DEFLECTIONS

The deflections are represented by contours; in addition, they are also shown in the form of dots. The size of a dot

is related to the magnitude of the corresponding nodal deflection in the vertical direction. A value is also recorded along each dot, which can be used to determine the magnitude of the deflection by multiplying it with the given factor. A negative value indicates a downward deflection.

Furthermore, the deflections of certain nodes are compared, as illustrated with the help of curves, for the four load cases. These nodes lie on that particular dome diameter, which results in the load pattern being symmetric about that diameter. These curves are plotted for both the support types.

(C) SUPPORT REACTIONS

A vertical reaction is shown by a line directed from the support point to the centre of the plan view of the structure. The length of such line is proportional to the magnitude of reaction. The more magnitude of the reaction is, the longer this line will be. In addition, the value of each reaction is also given in such figures. Meantime, the distribution of vertical reactions is illustrated by means of dotted lines.

The resultant of horizontal reactions, if any, for each support point is given by a dashed line whose length is again proportional to its magnitudes.

3

GEODESIC DOMES

3.1 INTRODUCTION

Richard Buckminster Fuller, the inventor of geodesic domes, has made a phenomenal impact on architects since 1954. For many years, Buckminster Fuller has lectured, conducted seminars and inspired architectural students all over the world. He has been described by various people in various ways, as a philosopher, architect, engineer, scientist, mathematician and inventor, Ref 2.

Nature, "said Buckminster Fuller", always build the most economic structures. He claimed that geodesic domes based on mathematical principles embodying force distributions similar to those found in atoms, molecules and crystals will be the lightest, strongest and cheapest construction ever made.

The sphere encloses maximum space with minimum surface and the triangle is the basic undeformable rigid figure. The term 'geodesic' given by Buckminster Fuller is related to the division of the earth into great circles which are the geodesic lines of the sphere. Geodesic distance between two points on the earth are the shortest along these lines.

The original ideas of Buckminster Fuller (the father of geodesic domes) have been, of course, extended by many of his followers. The research investigations on geometrical configurations of geodesic structures, carried out at numerous institutes in various countries, and the phenomenal interest of architects in this form of construction illustrate the fact that the advantages of geodesic domes are now being appreciated by designers all over the world, Ref 15.

An ideal prefabricated system would be a structure consisting of identical elements jointed together by simple connectors, the same for all the joints. In such a case, the elements and connectors could be mass-produced with considerable economy. The geodesic domes developed by Buckminster Fuller are exceptionally good in this respect and allow full advantage to be taken of prefabrication, since the variation in length of their component members is quite small even for sizable spans and complicated types of bracing. This results in a regular network and leads to substantially uniform stressing of all members of the dome under the applied loading.

However, geodesic domes also have a disadvantage : in practice, the geodesic geometry near the base has to be modified if the structure has to rest on a horizontal base ring. If this happens, then the joints along the base ring have to be adjusted as well as the lengths of the infilling members in the lower part of the dome.

3.2 REGULAR POLYHEDRA

There are only five regular polyhedra, all of whose edges of the same length and all of whose faces are regular, identical polygons. They are

(a) Tetrahedron	This can be described as a solid having 4 triangular faces, 4 apexes, and 6 edges, or simply :
Faces 4-3, apexes 4 and edges 6.
(b) Cube	Faces 6-4, apexes 8 and edges 12.
(c) Octahedron	Faces 8-3, apexes 6 and edges 12.
(d) Dodecahedron	Faces 12-5, apexes 20 and edges 30.
(e) Icosahedron	Faces 20-3, apexes 12 and edges 30.

These five regular polyhedra are usually referred to as the "platonic solids" Fig 3.2.1.

TETRAHEDRON

CUBE

OCTAHEDRON

DODECAHEDRON

ICOSAHEDRON

Fig 3.2.1

An icosahedron is used as the basis for the most geodesic subdivision of the sphere. The spherical surface is divided into 20 equilateral spherical triangles. This is the maximum number of equilateral triangles into which the sphere can be divided. Buckminster Fuller suggested that, for domes of larger spans, each of these triangles can be subdivided into six triangles by drawing medians and bisecting the sides of each triangle. These medians follow great circles and are the extensions of the sides of the basic equilateral triangles into which a spherical icosahedron could be divided. Using this method, it is therefore possible to form 15 complete great circles regularly arranged on the surface of a sphere.

To obtain a more or less regular network of the bracing bars, the edges of the basic equilateral triangles are divided modularly. The number of modules into which each edge of the spherical icosahedron is divided depends mainly upon the size of the dome, its span and also the type of skin covering. This subdivision is usually referred to as a "frequency". It is merely the number of segments into which the icosahedronal edges have been divided by a particular type of breakdown, the number of different lengths increasing with the frequencies of the subdivision. It is obvious that, as the frequency of a particular subdivision increases, the member length or face edge reduces, the number of components increases and the number of different vertex angles, and therefore types of connectors, increases. This is reflected in the increase of the final price of the dome.

3.3 DATA GENERATION FOR GEODESIC DOMES

Following the technique introduced in Ref 16, one may use Fig 3.3.1 to introduce a general scheme of formex formulation for structural systems which can be subdivided in a number of symmetry parts.

Geodesic configuration showing basic symmetry part in thick line

Fig 3.3.1

The illustrated configuration can be obtained from mapping the triangulated faces of a regular icosahedron on the surface of a sphere. The term 'configuration' is used in a

general sense to refer to a collection of any kind of objects, such as an arrangement of structural elements.

The 20 equal faces of the icosahedron are conventionally grouped in a four regions, namely: North-Pole, North-Belt, South-Belt and South-Pole as it is indicated in Figs 3.3.1 and 3.3.2. Furthermore, Fig 3.3.2 shows the triangulated faces of the icosahedron mapped on the plane I1-I2. Also, the sub-structure labelled as Part-1 is identified as the basic symmetry part of the structure, whereas Parts 2 to 20 are interpreted as translations and reflections of the basic part.

Fig 3.3.2

If a formex F1 is taken to represent topological properties, either disposition of nodes or interconnection patterns, within the basic sub-structure, i.e. Part-1, then the corresponding topological properties of the remaining sub-structures, i.e. Part 2 to 20, can be represented as function of the formex F1. Thus,

The North-Pole, part 1 to 5, may be formulated as

$$NP = lib (k=0, 1): tran (2, k*2nf): F1$$

where "nf" is the 'frequency' or number of segments in which the typical edge of the icosahedron is subdivided to triangulate the typical face. An asterisk sign '*' indicates multiplication.

The North-Belt, Parts 6 to 10, may be represented as a reflection of the formex NP as:

$$NB = ref (1, 3nf): NP$$

The South-Belt, Parts 11 to 15, may be represented as a planar transformation of the formex NP as:

$$SB = tranid (3nf, nf): NP$$

The South-Pole, Parts 16 to 20, may be also represented as a planar translation, this time of the formex NB as:

$$SP = tranid (3nf, nf): NB$$

Finally, the whole configuration may be given as the composition of the formices representing the North and South Regions as:

$$F = NP \# NB \# SB \# SP$$

3.3.1 THE BASIC SUB-STRUCTURE.

The symbol $F1$ in the above formulation is clearly used in a general sense to represent the topological properties of the basic symmetry part. Thus, any kind of disposition of nodes or interconnection pattern can be assigned to the basic part via $F1$ or another symbol to obtain different topological arrangements for the (whole) system.

In this way, the set of 'basic' nodes represented with dots in Fig 3.3.2 may be given as

$$g1 = lib(i=0,nf): lib(j=0,i): projid(3i,nf-i+2j): [0,0,0]$$

where $g1$ replaces $F1$ in the general formulation and the signet $[0,0,0]$ act as a 'seed' or generant for the nodes.

The interconnection pattern of the basic part can be now conveniently obtained in term of $g1$ as

$$F1 = vin(2, 10^{**}0.5): g1$$

where, a double asterisk sign $**$ indicates the power. The vinculum function 'generates' all the two-plex cantles whose 'metrum' is between 2 and $10^{**}0.5$ and whose signets are all in $g1$. In Fig 3.3.2, a line segment represents a cantle and the metrum of this cantle is simply the length of the line segment.

3.3.2 GEOMETRIC PARTICULARS

The geometric definition of the configuration given in Fig 3.3.1 is obtained by numerically specifying the mapping of the previously treated topological properties on a sphere.

The three-dimensional Cartesian coordinate system in Fig 3.3.1 is the reference frame for the present coordinate specifications and its origin coincides with the centre of the chosen sphere. Thus, the coordinates x, y, z of a point whose signet is $[I1, I2, I3]$ are given as

$$\begin{aligned}x &= Lq1 \\y &= Lq2 \\z &= Lq3\end{aligned}$$

where $q1, q2, q3$ are the coordinates of a point Q at the surface of the icosahedron and L is a positive factor, which 'projects' the point onto the sphere and is given as

$$L = [r^{**2} / (q1^{**2} + q2^{**2} + q3^{**2})]^{**0.5}$$

with $(q1^{**2} + q2^{**2} + q3^{**2}) > 0$, because no point at the faces of the icosahedron coincides with the origin of the reference system. Here, ' r ' is the radius of the desired geodesic configuration.

The point $Q(q1,q2,q3)$ is obtained from symmetry operations on a corresponding point $P(p1,p2,p3)$ in the basic sub-structure. The number assigned to each sub-structure in Fig 3.3.3 determines the particular transformations for each part. The symmetry operations may be summarized as follows

$$Q = R_z (R_y P)$$

Fig 3.3.3

where R_y and R_z denote non-commutative rotations of the point P around the y and z axes, respectively. The corresponding transformation matrices are

$$R_y = \begin{vmatrix} \cos-T & 0 & -\sin-T \\ 0 & 1 & 0 \\ \sin-T & 0 & \cos-T \end{vmatrix}$$

with $T = T1$ for parts 1 to 5,
 or $= T1 + 2Tr$ for parts 6 to 10,
 or $= 180 - T1 - 2Tr$ for parts 11 to 15,
 or $= 180 - T1$ for parts 16 to 20.

Also, $Tr = \text{atan} (nf(3^{**}0.5)/3S),$

$T1 = \text{atan} (2nf(3^{**}0.5)/3S)$

and $S = nf [(5 + 6\cos72) / 3]^{**}0.5,$

being geometric constants of the icosahedron expressed in

terms of the frequency nf , as illustrated in Fig 3.3.3.

In a similar way

$$R_z = \begin{vmatrix} \cos G & -\sin G & 0 \\ \sin G & \cos G & 0 \\ 0 & 0 & 1 \end{vmatrix}$$

with $G = (n-1)*72$ for parts 1 to 10.
 or $= (n-1)*72 + 36$, for parts 11 to 20.

The point $P(p_1, p_2, p_3)$ is in turn obtained as follows

$$\begin{aligned} p_1 &= (3**0.5) * (I_1 - nf*n_1) / 3 \\ p_2 &= I_2 - (m_1*nf + m_2*2nf) \\ p_3 &= S \end{aligned}$$

where nf = is the frequency of subdivision of the
 geodesic configuration

with

$n_1 = 2$
 $m_1 = 1$ for the
 $m_2 = 0, 1, 2, 3, 4$ for parts North pole
 1, 2, 3, 4, 5, respectively

$n_1 = 4$
 $m_1 = 1$ for the
 $m_2 = 0, 1, 2, 3, 4$ for parts North belt
 6, 7, 8, 9, 10, respectively

$n_1 = 5$
 $m_1 = 2$ for the
 $m_2 = 0, 1, 2, 3, 4$ for parts South belt
 11, 12, 13, 14, 15, respectively

$n1 = 7$
 $m1 = 2$ for the
 $m2 = 0,1,2,3,4$ for parts South pole
 16,17,18,19,20 respectively

and

$$S = nf \left[(5 + 6\cos 72) / 3 \right]^{*0.5},$$

being the radius of the insphere of a regular icosahedron with a side length of $2nf$. The insphere touches the mid-point of every face in the icosahedron, as sketched in Fig 3.3.3.

The above specifications for the point P may be interpreted in the intrinsic plot as the translations which make the mid-point of every symmetry part coincide with the origin of the x-y coordinate system. In plan view, the x and y axes coincide in turn with the I1 and I2 axes of the intrinsic plot, respectively. In addition, the sub-structures are reduced by a factor of $(3^{*0.5})/3$ along direction I1 to obtain the equilateral triangular faces of the icosahedron and the former are placed at a distance $p3$ above the plane x-y.

As it may be appreciated, the geodesic definition of the above given geodesic configuration is rather complex. However, once the coordinate specifications are available, they apply to any type of topological properties represented through the general formex formulation. Furthermore, the above coordinate specifications may be implemented in such a way that a computer process may require as input data only the frequency 'nf' and the radius 'r', if any of a geodesic structure to generate the necessary geometric information, such as node coordinates.

3.4 STRUCTURAL ANALYSIS AND DESIGN

The preliminary analysis was carried out assuming identical cross-sectional area for members and pin-connected end conditions, under the influence of symmetrical uniformly distributed load LA and also unsymmetric snow load LB , as described in section 2.5.

Having obtained the member forces, design was done by considering the minimum number of various cross-sectional areas of the members.

With the approximate sizes of the members, an exact linear elastic analysis of the skeletal structure was carried out under the four load cases. The results of each analysis were checked for the tension capacity and compression resistance.

As the structure has a rather high rise-to-span ratio, the linear elastic analysis was accepted as a reliable method for determining the forces.

3.5 GEODESIC DOME : Configuration GD1

Layout and structural details

3.5.1 SPECIFICATIONS

The dome shown in Fig 3.5.1 is the configuration GD1 of a geodesic dome. The dome has a diameter of 50 m, a rise of 15.45 m and it covers an area of 1835 m² in horizontal plane, and the spherical surface area is 2446 m². A height-to-diameter ratio of 1/3.2 is evident from these dimensions.

The structural framework is composed of 775 circular tubular members, and 276 joints. Figure 3.5.2 shows the detail of member lengths. The members with the same length are categorized as a type of member.

The type of bracing used for this dome is based on the North-pole of the geodesic subdivision of an icosahedron, using the frequency of 10.

3.5.2 DATA PREPARATION

Configuration GD1

The formex formulation for this dome is

```
:NF,R:
G1=lib(i=0,NF):lib(j=0,i):projid(3*i,NF-i+2*i):[0,0,0]
F1=vín(2, 3.1623):G1
NP=lib(k=0,4):tran(2,k*2*Nf):F1
K1=lib(i=1,4):[0,(2*i+1)*NF,0; 0,NF,0]
K2=lib(i=1,NF):[3*i,(9*Nf+i),0; 3*i,(1*Nf-i),0]
K3=lib(i=1,NF):[3*i,(3*Nf-i),0; 3*i,(1*Nf+i),0]
```

GEODESIC DOME
CONFIGURATION GD1
Height to diameter ratio = $1/3.2$

Fig 3.5.1

GEODESIC DOME

Configuration 6D1

TYPE OF ELEMENTS

No. of nodes = 276

No. of elements = 775

Diameter of dome = 50.0 m

Radius of dome = 27.95 m

TYPE No.	No. OF MEMBERS	LENGTH m
1	20	2.637
2	30	2.831
3	20	2.808
4	30	3.020
5	15	3.037
6	30	3.111
7	20	3.150
8	30	3.190
9	30	3.215
10	30	3.290
11	30	3.321
12	20	3.334
13	30	3.310
14	30	3.354
15	30	3.397
16	15	3.403
17	30	3.400
18	20	3.435
19	30	3.440
20	30	3.509
21	60	3.516
22	30	3.542
23	15	3.565
24	15	3.625
25	30	3.633
26	30	3.664
27	15	3.600

Fig 3.5.2

```
K4=lib(i=1,NF):[3*i,(5*NF-i),0; 3*i,(3*NF+i),0]
K5=lib(i=1,NF):[3*i,(7*NF-i),0; 3*i,(5*NF+i),0]
K6=lib(i=1,NF):[3*i,(9*NF-i),0; 3*i,(7*NF+i),0]
K=K1 # K2 # K3 # K4 # K5 # K6
GD1=nov(K):NP
GD=pex:GD1
G=ram(tap(1,2)):GD
D1=dic(G):GD
D=ras(tap(1,2)):D1
USE MINE(NF, R)
DRAW GD
```

where NF and R are 10 and 27.95 m, respectively.

3.5.3 LOAD CASES

Configuration GD1

Figure 3.5.3 to 3.5.6 show the load cases and the amount of the loads for each node. The determination of imposed, unsymmetrical snow and wind loads have been also explained on the figures. furthermore, the combination of snow and wind loads has been illustrated in Fig 3.5.6.

3.5.4 BOUNDARY CONDITIONS

Configuration GD1

The dome has been analysed for two different boundary conditions as illustrated in Fig 3.5.7.

GEODESIC DOME

Configuration 6D1

LOAD CASE LA

$$LA = 1.4 DL + 1.6 IL$$

DL=0.10 kN/m² on sphere

$$IL = I_m \cdot A_{ep}$$

$$I_m = 0.75 \text{ kN/m}^2$$

A_{ep} = Area on plan

IMPOSED LOAD

Fig 3.5.3

GEODESIC DOME

Configuration 6DI

LOAD CASE LB

$LB = 1.4 DL + 1.6 SL$

$DL = 0.40 \text{ kN/m}^2$ on sphere

$SL = U \cdot S_e \cdot A_{ep}$

$S_e = 0.75 \text{ kN/m}^2$

$A_{ep} = \text{Area on plan}$

SNOW LOAD

Fig 3.5.1

GEODESIC DOME Configuration 6D1

LOAD CASE LC

LC = 1.4 DL + 1.4 WL

DL=0.10 kN/m² on sphere

WL = C_{pe} · q · A_{es}

q=0.537 kN/m²

A_{es}=Area on sphere

C_{pe} | A= 0.0
B= -1.0
C= -0.2

WIND LOAD

Fig 3.5.5

GEODESIC DOME

Configuration GD1

LOAD CASE LD

$$LD = 1.2 DL + 1.2 SL + 1.2 WL$$

$DL = 0.10 \text{ kN/m}^2$ on sphere

$$WL = Cpe \cdot q \cdot Aes$$

$$q = 0.537 \text{ kN/m}^2 \quad Cpe \quad B = -1.0$$

$$Aes = \text{Area on sphere} \quad C = -0.2$$

WIND LOAD

$$SL = U \cdot Se \cdot Aep$$

$$Se = 0.75 \text{ kN/m}^2$$

$$Aep = \text{Area on plan}$$

SNOW LOAD

Fig 3.5.6

Fig 3.5.7

3.5.5 DESIGN

Configuration GD1

The design of members for support types S1 and S2 are shown in Figs 3.5.8 and 3.5.9, respectively. The members of the dome with support type S1 are obtained from four types of cross-sectional area, with different diameters and different thicknesses. However, the dome with support type S2 is obtained from only two cross-sectional areas, with the same diameter but different thicknesses. For support type S1 the members near the supports have been designed with cross-section three, and only five members next to the nodes with complete translational constraint, are designed using cross-section four.

The dome with support type S1 is a slightly heavier than the other one.

3.5.6 CAPACITY CHECK

Configuration GD1

The ratios of the internal forces to the capacities of members, under the four load cases, for support types S1 and S2, were obtained in graphical form.

These showed that all the internal forces are less than the capacities of the members, in all cases. Samples of capacity check plots are in Figs 3.5.10 and 3.5.11.

GEODESIC DOME

Configuration GD1

DESIGN OF MEMBERS

Support Type S1

Steel Circular Hollow Sections

CS1 | D= 76.1 mm
t= 3.2 mm

CS2 | D= 88.9 mm
t= 3.2 mm

CS3 | D= 114.3 mm
t= 3.6 mm

CS4 | D= 139.7 mm
t= 6.3 mm

Weight = 91.4 N/m²

TYPE No.	LENGTH m	No. OF MEMBERS WITH X-SECTION OF			
		CS1	CS2	CS3	CS4
1	2.637	5	10		5
2	2.831	20		10	
3	2.908	5	10	5	
4	3.020	20	10		
5	3.097	5		10	
6	3.111	20		10	
7	3.150	5	10	5	
8	3.190	20	10		
9	3.245	30			
10	3.290	10	20		
11	3.321	30			
12	3.334	5	5	10	
13	3.348	20	10		
14	3.354	30			
15	3.397	30			
16	3.403	15			
17	3.408	30			
18	3.435	5	5	10	
19	3.440	20	10		
20	3.509	20	10		
21	3.516	10	20		
22	3.512	30			
23	3.565	15	30		
24	3.625	15	30		
25	3.633	10	20		
26	3.664		30		
27	3.688		15		

Fig 3.5.8

GEODESIC DOME

Configuration GD1

DESIGN OF MEMBERS

Support Type S2

Steel Circular Hollow Sections

CS1 | D= 76.1 mm
| t= 3.2 mm

CS2 | D= 76.1 mm
| t= 1.8 mm

Weight = 87.9 N/m²

TYPE No.	LENGTH m	No. OF MEMBERS WITH X-SECTION OF	
		CS1	CS2
1	2.637	20	
2	2.831	30	
3	2.908	20	
4	3.020	20	10
5	3.097	15	
6	3.111	20	10
7	3.150	20	
8	3.190	20	10
9	3.215	30	
10	3.298	10	20
11	3.321	20	10
12	3.331	20	
13	3.348	20	10
14	3.351	30	
15	3.397	20	10
16	3.403	15	
17	3.408	30	
18	3.435	20	
19	3.448	20	10
20	3.509	20	10
21	3.516	10	20
22	3.542	20	10
23	3.565	15	30
24	3.625	15	30
25	3.633	10	20
26	3.661		30
27	3.688		15

Fig 3.5.9

GEODESIC DOME

Configuration GD1

CAPACITY CHECK

Ratio of the internal Force to the capacity of member.

Load Case LA

Support Type S1

Fig 3.5.10

GEODESIC DOME

Configuration GD1

CAPACITY CHECK

Ratio of the internal force to the capacity of member.

Load Case LB

Support Type S2

Fig 3.5.11

3.6 DISCUSSION OF RESULTS

Configuration GD1

The member forces, nodal deflections and support reactions obtained from analysis of the geodesic dome have been discussed for the two types of supports, i.e. S1 and S2.

The discussion of support type S1 is in section 3.6.1. This is followed by a discussion of support type S2 in section 3.6.2.

3.6.1 The Study of Support Type S1

(A) AXIAL FORCES

Configuration GD1

Support type S1

Figures 3.6.1.1 to 3.6.1.4 illustrate the stress distributions in the dome, with support type S1, for each load case.

As the figures show, the compressive axial forces increase rapidly as they approach the supports with fully translational restraint. The axial forces for the rest of the members are reasonably uniform.

The maximum tensile force varies from 40% to 57% of the maximum compressive force, under the four load cases.

The maximum force in the dome, under load case LB, is the largest as compared with the other load cases.

The application of load case LA, which is a combination of dead and imposed loads, produces symmetrical stress distribution.

The maximum axial forces on one side of the dome, under the load cases LB and LD, are 30% larger than the forces on the other side, because of the unsymmetrical snow load.

The member forces for load case LC, which is a combination of dead and wind loads, are significantly smaller than the other load cases.

GEODESIC DOME

Configuration GD1

AXIAL FORCE COEFFICIENTS.

Support Type S1

Load Case LA

Factor = 3.97 kN

Fig 3.6.1.1

GEODESIC DOME

Configuration 6D1

AXIAL FORCE COEFFICIENTS

Support Type S1

Load Case LB

Factor = 5.01 kN

Fig 3.6.1.2

GEODESIC DOME

Configuration GD1

AXIAL FORCE COEFFICIENTS

Support Type S1

Load Case LC

Factor = 2.67 kN

Fig 3.6.1.3

GEODESIC DOME

Configuration GD1

AXIAL FORCE COEFFICIENTS

Support Type S1

Load Case LD

Factor = 4.73 kN

Fig 3.6.1.1

(B) DEFLECTIONS

Configuration GD1

Support type S1

The deflections are represented by contour lines and also in the form of dots, as the Figs 3.6.1.5 to 3.6.1.8 show.

The dome has the maximum deflection under the load case LA, which produces symmetrical deflections.

The dome lifts vertically near the fully translational constraint points by 30% to 41% of the maximum downward deflection, for various load cases.

The maximum deflection for load cases LB and LD is on the side with high intensity of snow. Load case LC produces smaller deflections than the others.

Fig 3.6.1.5

Fig 3.6.1.6

Factor = .295 mm

DEFLECTION COEFFICIENTS AND SUPPORT ARRANGEMENT

DEFLECTION COEFFICIENT CONTOUR LINES

DEFLECTION COEFFICIENT
CONTOUR LINES

LEGEND
○ Vertical Constraint
● Complete Translational Constraint

NODAL DEFLECTION
COEFFICIENTS

LEGEND
□ Vertical Constraint
■ Complete Translational Constraint

GEODESIC DOME
Configuration 601

DEFLECTION COEFFICIENTS AND SUPPORT ARRANGEMENT

Support Type S1
Load Case LC
Factor = .228 mm

Fig 3.6.1.7

DEFLECTION COEFFICIENT
CONTOUR LINES

- LEGEND
- Vertical Constraint
 - Complete Translational Constraint

NODAL DEFLECTION
COEFFICIENTS

- LEGEND
- Vertical Constraint
 - Complete Translational Constraint

GEODESIC DOME
Configuration 601

DEFLECTION COEFFICIENTS AND SUPPORT ARRANGEMENT

Support Type S1
Load Case LD
Factor = .295 mm

Fig 3.6.1.8

(C) SUPPORT REACTIONS

Configuration GD1

Support type S1

The distribution of support reactions in the dome for the four load cases are displayed in Figs 3.6.1.9 to 3.6.1.12.

As the figures show, the support reactions increase rapidly as they approach the translationally constrained nodes.

The horizontal reactions on the vertically restrained support points are zero.

The application of load case LA, which is a combination of dead and imposed loads, produced symmetrical reactions.

The reactions on one side of the dome under load cases LB and LD, are larger than the reactions on the other side. This is due to unsymmetrical snow load involved in these load cases.

The respective maximum vertical reaction are 390, 487, 248 and 444 kN for load cases LA, LB, LC and LD.

GEODESIC DOME

Configuration 6D1

SUPPORT REACTIONS

Support Type S1

Load Case LA

Unit = kN

Fig 3.6.1.9

Fig 3.6.1.10

Fig 3.6.1.11

GEODESIC DOME

Configuration 601

SUPPORT REACTIONS

Support Type S1

Load Case LD

Unit = kN

Fig 3.6.1.12

3.6.2 The Study of Support Type S2

(A) AXIAL FORCES

Configuration GD1

Support type S2

The stress distribution in the members is almost uniform.

The maximum axial forces are near the supports which are not lying on the symmetrical diameter.

The axial forces in the members connecting two consecutive support nodes are zero, (see Figs 3.6.2.1 to 3.6.2.4).

The behaviour of the dome under load cases LB and LD, is almost the same, but the axial forces under load case LB is larger than those under load case LD.

The maximum tensile forces are 56%, 26%, 45% and 38%, of the maximum compressive forces for load cases LA, LB, LC and LD, respectively.

The maximum axial force is 95 kN under load case LB.

GEODESIC DOME

Configuration 6D1

AXIAL FORCE COEFFICIENTS

Support Type S2

Load Case LA

Factor = .75 kN

Fig 3.6.2.1

GEODESIC DOME

Configuration GD1

AXIAL FORCE COEFFICIENTS

Support Type S2

Load Case LB

Factor = .95 kN

Fig 3.6.2.2

GEODESIC DOME

Configuration GD1

AXIAL FORCE COEFFICIENTS

Support Type S2

Load Case LC

Factor = .54 kN

Fig 3.6.2.3

GEODESIC DOME

Configuration 6D1

AXIAL FORCE COEFFICIENTS

Support Type S2

Load Case LD

Factor = .85 kN

Fig 3.6.2.1

(B) DEFLECTIONS

Configuration GD1

Support type S2

Figures 3.6.2.5 to 3.6.2.8 show the nodal deflections in the dome. The figures show the deflection in the form of contour lines together with dots. The deflection in each node can be amended by the size of the dots and also the coefficient along each node. The hollow circle indicates the upward deflections.

The symmetrical load case LA produces symmetrical deflections and the maximum deflection which is on the apex of the dome, 3.6.2.5.

The maximum deflection for load case LC is on the apex of the dome but overall deflections are not symmetric, Fig 3.6.2.7.

All the nodes next to support nodes lift vertically under load cases LA and LB. For load cases LC and LD, the nodes only at the windward and leeward edge lift on the nodes next to support points.

GEODESIC DOME

Configuration 6D1

DEFLECTION COEFFICIENTS AND SUPPORT ARRANGEMENT

Support Type S2

Load Case LA

Factor = .268 mm

DEFLECTION COEFFICIENT
CONTOUR LINES

LEGEND

- Vertical Constraint.
- Complete Translational Constraint

NODAL DEFLECTION
COEFFICIENTS

LEGEND

- Vertical Constraint
- Complete Translational Constraint

Fig 3.6.2.5

DEFLECTION COEFFICIENT
CONTOUR LINES

NODAL DEFLECTION
COEFFICIENTS

GEODESIC DOME

Configuration 6D1

DEFLECTION COEFFICIENTS AND SUPPORT ARRANGEMENT

Support Type S2

Load Case LB

Factor = .167 mm

LEGEND
Vertical Constraint
Complete Translational Constraint

LEGEND
Vertical Constraint
Complete Translational Constraint

Fig 3.6.2.6

Fig 3.6.2.7

DEFLECTION COEFFICIENT
CONTOUR LINES

LEGEND
Vertical Constraint.
Complete Translational Constraint

GEODESIC DOME
Configuration 601

DEFLECTION COEFFICIENTS AND SUPPORT ARRANGEMENT

Support Type S2
Load Case LD
Factor = .183 mm

NODAL DEFLECTION
COEFFICIENTS

LEGEND
Vertical Constraint
Complete Translational Constraint

Fig 3.6.2.8

(C) SUPPORT REACTIONS

Configuration GD1

Support type S2

The distribution of the support reactions in the dome with support type S2 is almost uniform, Figs 3.6.2.9 to 3.6.2.12.

The horizontal reactions on all the support points are directed inward the structure. It follows that the dome is under compressive stresses, which is obvious from the dominance of compressive forces in most of the members.

The magnitude of vertical reactions are larger than those of the horizontal reactions, which indicates the stability of the dome.

The maximum vertical and horizontal reactions are 102 and 66, respectively, under load case LB.

HORIZONTAL
REACTIONS

VERTICAL
REACTIONS

GEODESIC DOME

Configuration 601

SUPPORT REACTIONS

Support Type S2

Load Case LA

Unit = kN

Fig 3.6.2.9

Fig 3.6.2.10

Fig 3.6.2.11

Fig 3.6.2.12

3.7 GEODESIC DOME : Configuration GD2

Layout and Structural Details

3.7.1 SPECIFICATIONS

The type of bracing for this dome is based on the North-pole of the geodesic subdivision of an icosahedron, using the frequency 15. However, only 10 out of 15 frequency is used to obtain the configuration of the dome. Therefore, the dome of configuration GD2 is shallower than configuration GD1, see Fig 3.7.1.

The diameter of the dome is 50 m and its height is 10 m. It follows that, the height-to-diameter ratio is 1/5. This dome is covering an area of 1670 m² in horizontal plane. However, the spherical surface area is found to be 1884 m².

Figure 3.7.2 shows the types of members together with the total number of nodes and members. The members having the same length are categorised as a type of member. There are 775 members in total along with 276 nodes. The members are divided into 43 groups according to their lengths.

3.7.2 DATA PREPARATION

Configuration GD2

The formex used to generate the data is

```
:NF,R:
G11=lib(i=0,NF):lib(j=0,i):projid(3*i,NF-i+2*j):[0,0,0]
E1=rin(2,16,2):[45,0,0]
E2=rin(2,15,2):[42,1,0]
E3=rin(2,14,2):[39,2,0]
```

GEODESIC DOME
CONFIGURATION GD2
Height to span ratio = $1/5$

Fig 3.7.1

GEODESIC DOME

Configuration 6D2

TYPE OF ELEMENTS

No. of nodes = 276

No. of elements = 775

Diameter of dome = 50.0 m

Radius of dome = 36.41 m

TYPE No.	No. OF MEMBERS	LENGTH m
1	5	2.251
2	10	2.361
3	5	2.410
4	10	2.472
5	10	2.527
6	5	2.564
7	10	2.580
8	10	2.641
9	5	2.645
10	20	2.683
11	5	2.705
12	10	2.735
13	10	2.750
14	20	2.773
15	10	2.798
16	10	2.813
17	10	2.824
18	5	2.826
19	5	2.830
20	30	2.848
21	10	2.876
22	30	2.903
23	10	2.913
24	20	2.919
25	20	2.930
26	30	2.933
27	30	2.939
28	20	2.978
29	30	2.992
30	10	2.998
31	30	3.021
32	30	3.029
33	30	3.038
34	20	3.060
35	30	3.063
36	60	3.105
37	30	3.119
38	15	3.128
39	20	3.154
40	30	3.166
41	30	3.175
42	15	3.199
43	20	3.202

Fig 3.7.2

```

E4=rin(2,13,2):[36,3,0]
E5=rin(2,12,2):[33,4,0]
E=E1 # E2 # E3 # E4 # E5
G1=lux(E):G11
F1=vin(2, 3.1623):G1
NP=lib(K=0,4):tran(2,K*2*NF):F1
K1=lib(i=1,4):[0,(2*i+1)*NF,0; 0,NF,0]
K2=lib(i=1,NF):[3*i,(9*NF+i),0; 3*i,(1*NF-i),0]
K3=lib(i=1,NF):[3*i,(3*NF-i),0; 3*i,(1*NF+i),0]
K4=lib(i=1,NF):[3*i,(5*NF-i),0; 3*i,(3*NF+i),0]
K5=lib(i=1,NF):[3*i,(7*NF-i),0; 3*i,(5*NF+i),0]
K6=lib(i=1,NF):[3*i,(9*NF-i),0; 3*i,(7*NF+i),0]
K=K1 # K2 # K3 # K4 # K5 # K6
GD1=nov(K):NP
GD=pex:GD1
G=ram(tap(1,2)):GD
D1=dic(G):GD
D=ras(tap(1,2)):D1
USE MINE(NF, R)
DRAW GD

```

where NF and R are 15 and 36.41 m, respectively.

3.7.3 LOAD CASES

Configuration GD2

The design of four load cases and the amounts of loads on each node are shown in Figs 3.7.3 to 3.4.6. Also, the description of combination of load cases are illustrated in the figures.

GEODESIC DOME

Configuration GD2

LOAD CASE LA

$LA = 1.4 DL + 1.6 IL$

$DL = 0.10 \text{ kN/m}^2$ on sphere

$IL = Im \cdot Aep$

$Im = 0.75 \text{ kN/m}^2$

$Aep = \text{Area on plan}$

IMPOSED LOAD

Fig 3.7.3

GEODESIC DOME

Configuration 6D2

LOAD CASE LB

LB = 1.4 DL + 1.6 SL

DL = 0.10 kN/m² on sphere

SL = U · Se · λ_{ep}

Se = 0.75 kN/m²

λ_{ep} = Area on plan

SNOW LOAD

Fig 3.7.1

GEODESIC DOME

Configuration GD2

LOAD CASE LC

$$LC = 1.4 DL + 1.4 WL$$

$DL = 0.40 \text{ kN/m}^2$ on sphere

$$WL = C_{pe} \cdot q \cdot A_{es}$$

$$q = 0.537 \text{ kN/m}^2$$

$A_{es} = \text{Area on sphere}$

$$C_{pe} \begin{cases} A = -0.15 \\ B = -0.75 \\ C = -0.20 \end{cases}$$

WIND LOAD

Fig 3.7.5

GEODESIC DOME

Configuration GD2

LOAD CASE LD

$$LD = 1.2 DL + 1.2 SL + 1.2 WL$$

$DL = 0.10 \text{ kN/m}^2$ on sphere

$$WL = Cpe \cdot q \cdot Aes$$

$$q = 0.537 \text{ kN/m}^2 \quad Cpe \quad \begin{array}{l} A = -0.15 \\ B = -0.75 \\ C = -0.20 \end{array}$$

$Aes = \text{Area on sphere}$

WIND LOAD

$$SL = U \cdot Se \cdot Aep$$

$$Se = 0.75 \text{ kN/m}^2$$

$Aep = \text{Area on plan}$

SNOW LOAD

Fig 3.7.6

3.7.4 BOUNDARY CONDITIONS

Configuration GD2

All the boundary nodes are supported in two ways, as described in Fig 3.7.7. The support nodes are considered to be free to rotate in any direction.

3.7.5 DESIGN

Configuration GD2

The design of members for both support types have been described in Figs 3.7.8 and 3.7.9.

Four types of cross-section with different diameters and thicknesses, have been used to design the members of the dome, with support type S1.

The dome with support type S2 has been designed with the same diameter of the tubes but with different thicknesses.

The dome with support type S1 is heavier than the other one.

3.7.6 CAPACITY CHECK

Configuration GD2

Figures 3.7.10 and 3.7.11 show the ratios of the internal forces to the capacities of the members for load case LD.

The ratios in the figures show that the design for each support type, is satisfactory for load case LD.

The ratios of the internal forces to the capacities of members, under the other three load cases, for support types

S1 and S2, were plotted. Those plots also show that all the internal forces are within the capacities of the members in all cases.

Fig 3.7.7

GEODESIC DOME

Configuration GD2

DESIGN OF MEMBERS

Support Type S1

Steel Circular Hollow Sections

CS1 | D= 76.1 mm
t= 3.2 mm

CS2 | D= 88.9 mm
t= 3.2 mm

CS3 | D= 114.3 mm
t= 5.0 mm

CS4 | D= 139.7 mm
t= 6.3 mm

Weight = 106.2 N/m²

TYPE No.	LENGTH m	No. OF MEMBERS WITH X-SECTION OF			
		CS1	CS2	CS3	CS4
1	2.251	5			
2	2.361	10			
3	2.410	5			
4	2.472	10			
5	2.527	10			
6	2.564	5			
7	2.588	10			
8	2.611	10			
9	2.615	5			
10	2.683	20			
11	2.705	5			
12	2.735	10			
13	2.758	10			
14	2.773	10		10	
15	2.798	10			
16	2.813	10			
17	2.824	10			
18	2.826	5			
19	2.830	5			
20	2.848	30			
21	2.876	10			
22	2.903	30			
23	2.913	10			
24	2.919	15			5
25	2.930	20			
26	2.933	30			
27	2.939	20		10	
28	2.978	10	5	5	
29	2.992	20	10		
30	2.998	5		5	
31	3.021		20	10	
32	3.029	10	20		
33	3.038		30		
34	3.060	20			
35	3.063		20	10	
36	3.105		30	30	
37	3.119		30		
38	3.128		15		
39	3.154	10		10	
40	3.166		10	20	
41	3.175		10	20	
42	3.199			15	
43	3.282		10	10	

Fig 3.7.8

GEODESIC DOME

Configuration GD2

DESIGN OF MEMBERS

Support Type S2

Steel Circular Hollow Sections

CS1 | D= 76.1 mm ———
| t= 3.2 mm

CS2 | D= 76.1 mm ———
| t= 4.8 mm

Weight = 85.7 N/m²

TYPE No.	LENGTH m	No. OF MEMBERS WITH X-SECTION OF	
		CS1	CS2
1	2.251	5	
2	2.361	10	
3	2.410	5	
4	2.472	10	
5	2.527	10	
6	2.561	5	
7	2.580	10	
8	2.641	10	
9	2.645	5	
10	2.683	20	
11	2.705	5	
12	2.735	10	
13	2.750	10	
14	2.773	20	
15	2.798	10	
16	2.813	10	
17	2.824	10	
18	2.826	5	
19	2.830	5	
20	2.840	30	
21	2.876	10	
22	2.883	30	
23	2.913	10	
24	2.919	20	
25	2.930	20	
26	2.933	30	
27	2.939	30	
28	2.978	10	10
29	2.992	10	20
30	2.998	5	5
31	3.021		30
32	3.029	20	10
33	3.038	20	10
34	3.060	20	
35	3.063	10	20
36	3.105		60
37	3.119		30
38	3.128		15
39	3.154	20	
40	3.166		30
41	3.175	20	10
42	3.199		15
43	3.202	10	10

Fig 3.7.9

GEODESIC DOME

Configuration GD2

CAPACITY CHECK

Ratio of the internal force to the capacity of member.

Load Case LD

Support Type S1

Fig 3.7.10

GEODESIC DOME

Configuration GD2

CAPACITY CHECK

Ratio of the internal force to the capacity of member.

Load Case LD

Support Type S2

Fig 3.7.11

3.8 DISCUSSION OF RESULTS

Configuration GD2

The member forces, nodal deflections and support reactions are obtained from pin-connected analysis of the geodesic dome for the four load cases and with two types of supports. These results are represented graphically and a discussion of the forces, deflections and support reactions is made below.

3.8.1 The Study of Support Type S1

(A) AXIAL FORCES

Configuration GD2

Support type S1

As the Figs 3.8.1.1 to 3.8.1.4 show, for all load cases, the stress distribution in the dome is almost uniform except for the members around the supports which are translationally constrained, where, the compressive stress is increased rapidly. So, those members have to be designed separately.

The overall axial forces in this configuration is larger than those on configuration GD1.

The tensile forces are limited to the area near the supports. The maximum tensile force for none of the load cases is more than 50% of the maximum compressive forces.

Load case LB produces the maximum axial force, whilst the maximum axial force for load case LA is 80% of the maximum compressive force for load case LB.

GEODESIC DOME

Configuration 6D2

AXIAL FORCE COEFFICIENTS

Support Type S1

Load Case LA

Factor = 4.94 kN

Fig 3.8.1.1

GEODESIC DOME

Configuration GD2

AXIAL FORCE COEFFICIENTS

Support Type S1

Load Case LB

Factor = 5.98 kN

Fig 3.8.1.2

GEODESIC DOME

Configuration 6D2

AXIAL FORCE COEFFICIENTS

Support Type S1

Load Case LC

Factor = 3.00 kN

Fig 3.8.1.3

GEODESIC DOME

Configuration GD2

AXIAL FORCE COEFFICIENTS

Support Type S1

Load Case LD

Factor = 5.68 kN

Fig 3.8.1.4

(B) DEFLECTIONS

Configuration GD2

Support type S1

The nodal deflections in configuration GD2 are larger than those in configuration GD1, though they are still small with respect to diameter of the dome, Figs 3.8.1.5 to 3.8.1.8.

The maximum deflection is on the apex of the dome, for load cases LA and LC, though, the maximum deflections for load cases LB and LD are on one side of the dome with high intensity of snow.

As the figures show, the nodes near the fully translational constraint have vertically lifted about 40% of the maximum downward deflection.

DEFLECTION COEFFICIENT
CONTOUR LINES

LEGEND

- Vertical Constraint
- Complete Translational Constraint

GEODESIC DOME

Configuration 602

DEFLECTION COEFFICIENTS AND SUPPORT ARRANGEMENT

Support Type S1

Load Case LA

Factor = .476 mm

NODAL DEFLECTION
COEFFICIENTS

LEGEND

- Vertical Constraint
- Complete Translational Constraint

Fig 3.8.1.5

DEFLECTION COEFFICIENT
CONTOUR LINES

LEGEND
Vertical Constraint
Complete Translational Constraint

NODAL DEFLECTION
COEFFICIENTS

LEGEND
Vertical Constraint
Complete Translational Constraint

GEODESIC DOME
Configuration 602

DEFLECTION COEFFICIENTS AND SUPPORT ARRANGEMENT

Support Type S1
Load Case LB
Factor = .425 mm

Fig 3.8.1.6

DEFLECTION COEFFICIENT
CONTOUR LINES

LEGEND
Vertical Constraint
Complete Translational Constraint

GEODESIC DOME Configuration 6D2

DEFLECTION COEFFICIENTS AND SUPPORT ARRANGEMENT

Support Type S1
Load Case LC
Factor = .276 mm

NODAL DEFLECTION
COEFFICIENTS

LEGEND
Vertical Constraint
Complete Translational Constraint

Fig 3.8.1.7

Fig 3.8.1.8

(C) SUPPORT REACTIONS

Configuration GD2

Support type S1

The support reactions of the configuration GD2 of geodesic dome with support type S1 are represented graphical as shown in Figs 3.8.1.9 to 3.8.1.12.

As the figures show the vertical reactions at the fully translational supports are about 15 times more than the maximum vertical reactions for the other support nodes.

The nodes next to the translationally constrained points have small negative vertical reactions.

The horizontal reactions on the nodes which are vertically supported are zero. Though the distribution of vertical reactions is almost uniform on these nodes.

The maximum vertical and horizontal reactions are 542 and 630 kN under load case LB.

Fig 3.8.1.9

Fig 3.8.1.10

GEODESIC DOME

Configuration 602

SUPPORT REACTIONS

Support Type S1

Load Case LD

Unit = kN

Fig 3.8.1.12

3.8.2 The Study of Support Type S2

(A) AXIAL FORCES

Configuration GD2

Support type S2

Figures 3.8.2.1 to 3.8.2.4 describe the stress distributions for the dome, under four load cases with support type S2. As the figures show, all the members are carrying compressive axial forces.

The stress distributions in this case are almost uniform, and the axial forces between two consecutive supports are zero.

The maximum axial force is under load case LB.

The application of load case LB and LD, because of the high intensity of snow load on one side of the structure, produces unsymmetrical stress distributions. However, the forces in the dome under load case LD is generally smaller than those under load case LB.

The member forces for load case LC, which is a combination of dead and wind loads are smaller than the other three load cases.

GEODESIC DOME
Configuration 6D2
AXIAL FORCE COEFFICIENTS
Support Type S2
Load Case LA
Factor = .76 kN
Fig 3.8.2.1

GEODESIC DOME
Configuration GD2
AXIAL FORCE COEFFICIENTS
Support Type S2
Load Case LB
Factor = 1.00 kN
Fig 3.8.2.2

GEODESIC DOME
Configuration GD2
AXIAL FORCE COEFFICIENTS
Support Type S2
Load Case LC
Factor = .47 kN
Fig 3.8.2.3

GEODESIC DOME
Configuration GD2

AXIAL FORCE COEFFICIENTS
Support Type S2

Load Case LD
Factor = .86 kN

Fig 3.8.2.1

(B) DEFLECTIONS

Configuration GD2

Support type S2

Figures 3.8.2.5 to 3.8.2.8 show the deflection diagrams for four load cases with support type S2.

The maximum deflection is under load case LA.

The dome under load case LB lifts vertically, on the apex, as much as 5% of the maximum downward deflection.

The maximum deflections for load case LA and LC are on the apex of the dome. However, the maximum deflection for load cases LB and LD, are on the side with high intensity of snow load.

The maximum deflection on one side of the dome under load cases LB and LD are two times that of those on the other side.

The value of the maximum deflection for load LC does not differ from that for load case LD.

GEODESIC DOME
Configuration 602

DEFLECTION COEFFICIENT
CONTOUR LINES

DEFLECTION COEFFICIENTS AND SUPPORT ARRANGEMENT

Support Type S2

Load Case LA

Factor = .295 mm

LEGEND

- Vertical Constraint
- Complete Translational Constraint

NODAL DEFLECTION
COEFFICIENTS

LEGEND

- Vertical Constraint
- Complete Translational Constraint

Fig 3.8.2.5

DEFLECTION COEFFICIENT
CONTOUR LINES

LEGEND
 Vertical Constraint
 Complete Translational Constraint

NODAL DEFLECTION
COEFFICIENTS

LEGEND
 Vertical Constraint
 Complete Translational Constraint

GEODESIC DOME Configuration 602

DEFLECTION COEFFICIENTS AND SUPPORT ARRANGEMENT

Support Type S2
 Load Case LB
 Factor = .193 mm

Fig 3.8.2.6

Fig 3.8.2.7

Fig 3.8.2.8

(C) SUPPORT REACTIONS

Configuration GD2

Support type S2

The distribution of support reactions in the configuration SD2 of Schwedler dome, with support type S2 are shown in Figs 3.8.2.9 to 3.8.2.12.

The figures show that the horizontal reactions on all the support points are directed inward the dome.

The magnitude of the horizontal reactions in this configuration are generally larger than the vertical reactions. It can be attributed to the relatively shallow depth of configuration GD2.

Load case LA produced symmetrical reactions. The reactions for load case LC are smaller than those of the other load cases.

The reactions on one side of the dome under load cases LB and LD are larger than those on the other side. This is due to the unsymmetrical loading.

Fig 3.8.2.11

Fig 3.8.2.12

3.9 CONCLUDING DISCUSSION

The stress distribution in the dome shows that most of the members are carrying compressive axial forces, whilst the extent of tensile axial forces is limited to the area near the supports. Further, the maximum tensile force for any load case is not more than 60% of the maximum compressive forces.

The maximum axial forces and maximum vertical displacements in both configurations for the four load cases and two boundary conditions are recorded in Table 3.10.1 (in section 3.10).

As the Table shows with support type S1, the maximum axial forces in configuration GD2 are 12% to 25% more, for different load cases, than those in configuration GD1. However, for support type S2, the maximum axial forces in both configurations are almost the same.

The reduction in deflections in the dome, with support type S1, for configuration GD1 compared with configuration GD2, varies from 20% to 40%, for different load cases.

The maximum deflections for support type S2 in configuration GD1 are almost smaller than those in configuration GD2, except for load case LD, where the maximum deflection in configuration GD1 is a bit larger than configuration GD2.

For both configurations with the support type S1, the compressive axial forces are found to increase rapidly as they approach the supports which have complete translational restraint movements. Further, tensile forces are found to be dominant in the members near the supports having only vertical constraints.

However, the stress distribution for rest of the members in the dome is almost uniform and much smaller than for the members near the supports.

For support type S2, the concentration of forces in the members near the supports is relatively less severe, and the resulting stress distribution in this case is almost uniform. The maximum axial forces for support type S2 is only 20% of those for boundary condition S1, Table 3.10.1.

The dominance of member forces near the supports for support type S1, is the direct result of the lateral displacements at the vertical restraint points. Consequently, the axial forces in the members connecting two consecutive complete translational constraints for support type S2, are zero.

The comparison of axial forces in the dome with two types of supports, under the influence of the four load cases, for configurations, GD1 and GD2, are illustrated in Figs 3.9.1 to 3.9.8. The value of the axial forces relates to the thickness of the line representing each member. The axial force in a member can also be obtained by directly multiplying the value shown along the member, with the factor given in the diagram.

In both configurations the application of load case LA, which is the combination of dead and imposed loads, produces symmetrical stress distributions.

In load case LB, because of the high intensity of snow loading on one side of the structure, the forces in the members are larger than those of the other side. The maximum axial forces on one side of the dome is 30% larger than the forces on the other side of the dome.

The forces in part of the dome which is under higher intensity of snow load, for load case LB is larger than that for load case LA, though, the deflections are found to be considerably larger for load case LA, (see Table 3.1).

The influence of the two boundary conditions on the stress distribution in the dome for the other two load cases is not significantly different to the first two cases.

However, both the member forces and resulting nodal deflections for load case LC are significantly smaller than those for the other three load cases.

The behaviour of the dome under load case LD does not differ significantly from that of load case LB.

The dome is subjected to the maximum deflection under load case LA.

The dome with support type S1 lifts vertically near the fully translational constraint points by 40% of the maximum downward deflection. The maximum lift in the dome with support type S2 is 10% of the maximum downward deflection.

The comparison of deflections in both configurations, for four load cases through the symmetrical diameter, (with respect to each load case), have been illustrated in Figs 3.9.9 and 3.9.10 for configurations GD1 and GD2, respectively. In each case, the deflections are obtained from the nodes lying on the symmetrical diameter.

The reduction in deflections in the dome with support type S2 compared with support type S1 varies from 30% to 55% for different load cases, (see Figs 3.9.9 and 3.9.10).

Fig 3.9.1

GEODESIC DOME

Configuration 100

AXIAL FORCE COEFFICIENTS

Load Case LB

Factor = 5.0

Fig 3.9.2

Fig 3.9.3

Fig 3.9.4

Support type S2

LEGEND

- Vertical Constraint
- Complete Translational Constraint

Support type S1

LEGEND

- Compression
- - - Tension

GEODESIC DOME

Configuration 6D2

AXIAL FORCE COEFFICIENTS

Load Case LA
Factor = 4.94 kN

Fig 3.9.5

Support type S2

LEGEND

- Vertical Constraint
- Complete Translational Constraint

Support type S1

LEGEND

- Compression
- - - Tension

GEODESIC DOME

Configuration 602

AXIAL FORCE COEFFICIENTS

Load Case LB
Factor = 5.98 kN

Fig 3.9.6

Fig 3.9.7

GEODESIC DOME
Configuration 602

Support type S2

AXIAL FORCE COEFFICIENTS

Load Case LD
Factor = 5.68 kN

LEGEND

Compression —
Tension - - - -

LEGEND

Vertical Constraint ●
Complete Translational Constraint ■

Fig 3.9.8

GEODESIC DOME

Configuration 6D1

COMPARISON OF DEFLECTIONS FOR VARIOUS LOAD CASES WITH
SUPPORT TYPE S1

COMPARISON OF DEFLECTIONS FOR VARIOUS LOAD CASES WITH
SUPPORT TYPE S2

Fig 3.9.9

GEODESIC DOME

Configuration 6D2

COMPARISON OF DEFLECTIONS FOR VARIOUS LOAD CASES WITH
SUPPORT TYPE S1

COMPARISON OF DEFLECTIONS FOR VARIOUS LOAD CASES WITH
SUPPORT TYPE S2

Fig 3.9.10

3.10 CONCLUSIONS

The maximum axial forces and maximum vertical displacements in both configurations for the four load cases and two boundary conditions are tabulated in Table 3.10.1.

Load Case	Configuration GD1				Configuration GD2			
	Support Type S1		Support Type S2		Support Type S1		Support Type S2	
	Maximum AXIAL FORCE	Maximum DEFLECTION	Maximum AXIAL FORCE	Maximum DEFLECTION	Maximum AXIAL FORCE	Maximum DEFLECTION	Maximum AXIAL FORCE	Maximum DEFLECTION
	kN	mm	kN	mm	kN	mm	kN	mm
LA	-397	37.7	-75	26.8	-194	17.6	-76	29.5
LB	-501	29.5	-95	16.7	-598	12.5	-100	19.3
LC	-267	22.8	-54	16.3	-300	27.6	-17	17.1
LD	-173	29.5	-85	18.3	-568	39.2	-86	17.3
Weight	91.4	N/m ²	87.9	kN/m ²	106.2	N/m ²	85.7	N/m ²

COMPARISON OF STRESS DISTRIBUTION AND DEFLECTION

Table 3.10.1

From the stress distributions, nodal deflections and support reactions, the following comments can be used:

1- The configuration GD1 shows a more rigid behaviour than that of configuration GD2. That is to say, the larger height to diameter ratio results in a stiffer dome.

2- The support arrangement type S2 results in a relatively uniform stress distribution and increases the rigidity of the dome significantly as compared with support type S1.

3- The member axial forces for the unsymmetrical snow load are found to be critical.

4- The maximum deflection in the dome occurred under load case LA.

5- In both configurations, with two types of supports and various load cases the maximum deflections are significantly small.

6- In both configurations, with support type S1, the vertical and horizontal support reactions for fully constrained supports are considerably high.

7- The weight per square meter is almost similar for all cases except for support type S1 of configuration GD2, which is heavier than the others.

4

SCHWEDLER DOMES

4.1 INTRODUCTION

A Schwedler dome, one of the most popular domes, consists of meridional ribs connected together to a number of horizontal polygonal rings. To stiffen the resulting structure so that it will also be able to take unsymmetric loads, each trapezium formed by intersecting meridional ribs with horizontal rings is divided into two triangles by the introduction of a diagonal member, (see Fig 4.1.1), Ref 2.

SCHWEDLER DOMES

Fig 4.1.1

The simplest forms of braced domes consists of ribs of curved meridional bars connected together to a number of

horizontal polygonal rings. Since these domes can be prefabricated and speedily erected on site with little scaffolding, therefore, the cost of construction is low. Such a dome requires only a small central tower to provide temporary support for the upper ends of the ribbed units, before these are interconnected at the common apex during erection.

J.W. Schwedler, a German engineer, who introduced this type of domes in 1863, built numerous braced domes during his lifetime. Schwedler steel domes are frequently used to cover large column-free areas. Such domes are usually of the "open type", i.e. the meridional ribs terminate at the lantern ring and do not form a crown joint. There are various types of bracing arrangement for the apex of a dome consisting of a large number of ribs, (Fig 4.1.2), Ref 17.

SCHWEDLER DOMES

Fig 4.1.2

Since the circle allows the greatest number of seats to be placed very close to the stage or the arena floor, therefore, the domical shape leads to a very economic structure. Experience shows that for the large, clear spans required for public assembly buildings, steel Schwedler domes provide a solution combining the economy of material with that of cost, Ref 2.

This chapter incorporates first a discussion of various details of the Schwedler dome including data preparation (section 4.3), and the analysis and design (section 4.4). This is followed by a description of configuration SD1 of Schwedler dome in section 4.5. The results of configuration SD1 are discussed in section 4.6. Specification of the configuration SD2 are given in section 4.7, and its results are discussed in section 4.8. This chapter is concluded with a discussion of the structural behaviour of the Schwedler dome.

4.2 SPECIFICATIONS OF THE DOME

The dome consists of 48 ribs, only 6 of them are connected at the apex and the rest of them are connected to the horizontal rings. The ribs stiffened by 9 horizontal rings and 8 rows of diagonal members, forming a fully triangulated network.

The structural framework is composed of 870 circular hollow section members and 307 joints. It covers an area of 1963 m².

4.3 DATA GENERATION FOR SCHWEDLER DOMES

Formex algebra have been used to generate the element topology and nodal coordinates for the structural analysis of the Schwedler dome.

The configurations are generated by the rotation of radially symmetric component with respect to a fixed point. Formices are used to represent the interconnection patterns of these configurations and a spherical retronorm is used to obtain spherical coordinate. This retronorm is defined by coordinate equations of the form

$$r=b1 \ U1$$

$$\theta=b2 \ U2$$

and

$$\phi=b3 \ U3$$

These equations represented a retronorm which is referred to as a basispherical retronorm.

Each one of the entities $b1$, $b2$ and $b3$ is a coefficient which is referred to as a basifactor. There are two types of basifactor, linear basifactor and angular basifactor. A linear basifactor should be given in terms of a unit of length and an angular basifactor should be given in terms of a unit of angle.

If b is an angular basifactor and if

$$Nb=2\pi$$

Then one may specify b directly by giving the value of b , or one may specify b indirectly by giving the value of N . For

Here,

$$b_2 = \pi/10$$

and

$$b_3 = \pi/8$$

and thus the retronorm may be referred to as a 20-16-sect retronorm.

The above method of specification of angular basifactors for various retronorms is referred to as the sectorial notation. In using the sectorial notation, the terms N and M need not necessarily be integers.

4.4 STRUCTURAL ANALYSIS AND DESIGN

In order to determine the nodal deflections and detailed stress distribution within the members, the dome was analysed using 'LUSAS', a finite element computer package. The dome was initially analysed under load case LA, for each configuration, assuming prismatic members with identical cross-sectional areas and pin-connected end conditions. Cladding is connected to the nodes of the dome, thus ensuring nodal point loading and avoiding any possible local bending. Consequently, the members are designed to cater for axial forces only, on the basis of BS 5950: part 1: 1985, which considers the limit state method of design.

The other load cases were subsequently investigated and the design of members checked accordingly. Hence, the dome is provided with members having different cross-sectional areas to satisfy all the load cases for each configuration.

4.5 SCHWEDLER DOME : Configuration SD1

Layout and Structural Details

4.5.1 SPECIFICATIONS

The diameter of the dome is 50 m and the height is 16.66 m above the ring. It follows that a height-to-diameter ratio of 1/3 is evident from these dimensions, Fig 4.4.1.

The radius of the dome is 27.08 m. This dome covers an area of 1963 m², and the corresponding spherical area is 2836 m².

Figure 4.5.2 shows the number of nodes and members in the dome. It also shows that 870 members are divided into 17 types according to the member lengths. The member lengths in the dome varies from 2.153 m to 4.746 m.

However, the majority of the members, i.e. 264 rib members, have the same length of 3.536 m. The figure also indicates that the ring and diagonal members of each row are of the same length.

4.5.2 DATA PREPARATION

Configuration SD1

The formex formulation used to generate the element topology and nodal coordinates for the configuration SD1 of the Schwedler dome is

::

```
E1 = rinit(6,9,8,1) : [1,0,0; 1,0,1]
E2 = rinit(6,7,8,1) : [1,4,2; 1,4,3]
E3 = rinit(12,6,4,1) : [1,2,3; 1,2,4]
E4 = rinit(24,4,2,1) : [1,1,5; 1,1,6]
```

```

E  = E1 # E2 # E3 # E4
F1 = rin(2,6,8) : [1,0,1; 1,8,1]
F2 = rin(2,12,4) : [1,0,2; 1,4,2]
F3 = rinit(24,2,2,1) : [1,0,3; 1,2,3]
F4 = rinit(48,5,1,1) : [1,0,5; 1,1,5]
F  = F1 # F2 # F3 # F4
R1 = rin(2,6,8) : lam(2,4) : [1,0,1; 1,4,2]
R2 = rin(2,12,4) : lam(2,2) : [1,0,2; 1,2,3]
R3 = rin(2,12,4) : lam(2,2) : [1,2,3; 1,0,4]
R4 = rin(2,24,2) : lam(2,1) : [1,0,4; 1,1,5]
R5 = rin(2,24,2) : lam(2,1) : [1,1,5; 1,0,6]
R6 = rin(2,24,2) : lam(2,1) : [1,0,6; 1,1,7]
R7 = rin(2,24,2) : lam(2,1) : [1,1,7; 1,0,8]
R8 = rin(2,24,2) : lam(2,1) : [1,0,8; 1,1,9]
R  = R1 # R2 # R3 # R4 # R5 # R6 # R7 # R8
WH = E # F # R
K1 = lib(I=1,6) : [1,8*I,0; 1,0,0]
K2 = rin(3,9,1) : [1,48,1; 1,0,1]
K  = K1 # K2
SD1 = nov(K) : WH
SD  = pex : SD1
G  = ram(tap(3,2)) : SD
D1 = dic(G) : SD
D  = ras(tap(1,2)) : D1
USE BS(27.0833, 7.5, 7.4867)
DRAW SD

```

Where 27.0833 is the radius of the dome in metres and 7.5 and 7.4867 are angular basifactors in degrees for directions 2 and 3.

SCHWEDLER DOME

CONFIGURATION SD1
Height to diameter ratio = $1/3$

Fig 1.5.1

SCHWEDLER DOME

Configuration SD1

TYPE OF ELEMENTS

No. of nodes = 307

No. of elements = 870

Diameter of dome = 50.0 m

Radius of dome = 27.08 m

TYPE No.	No. OF MEMBERS	LENGTH m
1	48	2.153
2	48	2.502
3	24	2.701
4	48	2.807
5	48	3.065
6	48	3.270
7	30	3.529
8	264	3.536
9	12	3.622
10	48	4.039
11	24	4.176
12	48	4.230
13	12	4.373
14	48	4.419
15	48	4.594
16	24	4.695
17	48	4.746

Fig 4.5.2

4.5.3 LOAD CASES

Configuration SD1

Four load cases were considered for design of the dome, as shown in Figs 4.5.3 to 4.5.6. The amount of load on each node together with the determination of combinations of load cases are illustrated in these figures.

The respective total magnitude of loads are 3931, 4248, 2490 and 4134 kN for the load cases LA, LB, LC and LD.

4.5.4 BOUNDARY CONDITIONS

Configuration SD1

The dome is supported on all the boundary nodes, as described in Fig 4.5.7. In support type S2, the complete translational movements of all the boundary nodes are constrained. In support type S1, only 6 of them have complete translational constraint and the rest are only vertically supported. Nevertheless, all the support nodes are free to rotate in any direction.

4.5.5 DESIGN

Configuration SD1

The size of the steel tubular members used for the dome with support type S1 varies between 76.1 to 114.3 mm in diameter, with the thickness varying between 3.2 to 3.6 mm. This is true with the exception of the six rib members, which are next to the complete translational constraints. These members are designed by a 139.2 mm diameter and 6.3 mm thick, circular hollow section. These details of the members are shown in Fig 4.5.8.

The steel tubes forming the bracing of the dome with support type S2 have an outside diameter of 76.1 mm. The wall thickness of the tubes varies according to their location and stress, between 3.2 to 5.0 mm, as shown in Fig 4.5.9.

The dome with support type S2 is 1.1 N/m² lighter than the dome with support type S1.

4.5.6 CAPACITY CHECK

Configuration SD1

Figures 4.7.10 and 4.7.11 show the ratios of the internal forces to the capacities of the members for load case LB.

The ratios in the figures show that the design for each support type, is satisfactory for load case LB.

The ratios of the internal forces to the capacities of members, under the other three load cases, for support types S1 and S2, were plotted. Those plots also show that all the internal forces are within the capacities of the members in all cases.

SCHWEDLER DOME Configuration SD1

LOAD CASE LA

$LA = 1.4 DL + 1.6 IL$

$DL = 0.10 \text{ kN/m}^2$ on sphere

$IL = Im \cdot A_{ep}$

$Im = 0.75 \text{ kN/m}^2$

$A_{ep} = \text{Area on plan}$

IMPOSED LOAD

Fig 4.5.3

SCHWEDLER DOME Configuration SD1

LOAD CASE LB

$$LB = 1.4 DL + 1.6 SL$$

DL = 0.10 kN/m² on sphere

$$SL = U \cdot S_e \cdot A_{ep}$$

$$S_e = 0.75 \text{ kN/m}^2$$

A_{ep} = Area on plan

SNOW LOAD

Fig 1.5.4

SCHWEDLER DOME Configuration SD1

LOAD CASE LC

LC = 1.4 DL + 1.4 WL

DL = 0.40 kN/m² on sphere

WL = $C_{pe} \cdot q \cdot A_{es}$

$q = 0.537 \text{ kN/m}^2$

A_{es} = Area on sphere

C_{pe} | $\lambda = 0.0$
| $\theta = -1.0$
| $c = -0.2$

WIND LOAD

Fig 4.5.5

SCHWEDLER DOME

Configuration SD1

LOAD CASE LD

$$LD = 1.2 DL + 1.2 SL + 1.2 WL$$

DL = 0.40 kN/m² on sphere

$$WL = C_{pe} \cdot q \cdot A_{es}$$

$$q = 0.537 \text{ kN/m}^2 \quad C_{pe} \begin{cases} A = 0.8 \\ B = -1.0 \\ C = -0.2 \end{cases}$$

$$A_{es} = \text{Area on sphere}$$

WIND LOAD

$$SL = U_s \cdot S_e \cdot A_{ep}$$

$$S_e = 0.75 \text{ kN/m}^2$$

$$A_{ep} = \text{Area on plan}$$

SNOW LOAD

Fig 4.5.6

Fig 4.5.7

SCHWEDLER DOME

Configuration SD1

DESIGN OF MEMBERS

Support Type S1

Steel Circular Hollow Sections

CS1	D= 76,1 mm t= 3,2 mm
CS2	D= 88,9 mm t= 3,2 mm
CS3	D= 114,3 mm t= 3,6 mm
CS4	D= 139,7 mm t= 6,3 mm

Weight = 115.8 N/m²

TYPE No.	LENGTH m	No. OF MEMBERS WITH X-SECTION OF			
		CS1	CS2	CS3	CS4
1	2.153	48			
2	2.502	48			
3	2.701	24			
4	2.007	48			
5	3.065	48			
6	3.270			48	
7	3.529	6	24		
8	3.536		250		6
9	3.622		12		
10	4.039		48		
11	4.176		24		
12	4.230		48		
13	4.373		12		
14	4.419		48		
15	4.594			48	
16	4.695		24		
17	4.746			48	

Fig 1.5.8

SCHWEDLER DOME

Configuration SD1

DESIGN OF MEMBERS

Support Type S2

Steel Circular Hollow Sections

CS1 | D= 76.1 mm ———

t= 3.2 mm

CS2 | D= 76.1 mm ———

t= 4.0 mm

CS3 | D= 76.1 mm ———

t= 5.0 mm

Weight = 114.7 N/m²

TYPE No.	LENGTH m	No. OF MEMBERS WITH X-SECTION OF		
		CS1	CS2	CS3
1	2.153	48		
2	2.582	48		
3	2.781	24		
4	2.887	48		
5	3.065	48		
6	3.270	48		
7	3.529		24	
8	3.536		128	144
9	3.622		12	
10	4.039		48	
11	4.176		24	
12	4.230		48	
13	4.373		12	
14	4.419		48	
15	4.594		48	
16	4.695		24	
17	4.746			48

Fig 4.5.9

SCHWEDLER DOME

Configuration SD1

CAPACITY CHECK

Ratio of the internal force to the capacity of member

Load Case LB

Support Type S1

Fig 4.5.10

SCHWEDLER DOME

Configuration SD1

CAPACITY CHECK

Ratio of the internal force to the capacity of member

Load Case LB

Support Type S2

Fig 4.5.11

4.6 DISCUSSION OF RESULTS

Configuration SD1

Results of this configuration have been discussed for the two types of supports, i.e. S1 and S2. These results include member forces, nodal deflections and support reactions

4.6.1 The Study of Support Type S1

(A) AXIAL FORCES

Configuration SD1

Support Type S1

The distribution of axial forces in the dome, for the four load cases are shown in Figs 4.6.1.1 to 4.6.1.4.

In these figures, the member axial forces are recorded along the corresponding members in the form of coefficients. A factor is given for each load case. The axial force in the member can be obtained by multiplying the factor with the member coefficient. The distribution of the force can also be assessed from the thickness of line representing a member. A member is drawn according to the magnitude of force in it.

These figures show that the axial forces in the 6 rib members, which are next to the complete translational constraint nodes, are 3.6 to 4.5 times higher than the maximum axial force in rest of the members. This is true for all the load cases.

All the bottom ring members are carrying tensile axial forces. The maximum tensile force is 48% of the maximum compressive force, except for load case LC, where the maximum tensile force is 54% of the maximum compressive force.

All the members on four bottom rings under load case LA, and two bottom ring members under load case LB are carrying tensile axial forces.

The diagonal members generally carry compressive forces, except the two members next to the fully constrained nodes, which have tensile forces. The maximum tensile forces in diagonal members are not more than 37% of the maximum compressive forces, for any load case.

The maximum compressive force is 481 kN under unsymmetrical snow load LB.

SCHWEDLER DOME

Configuration SD1

AXIAL FORCE COEFFICIENTS

Support Type S1

Load Case LA

Factor = 3.70 kN

Fig 4.6.1.1

SCHWEDLER DOME

Configuration SD1

AXIAL FORCE COEFFICIENTS

Support Type S1

Load Case LB

Factor = 4.81 kN

Fig 4.6.1.2

SCHWEDLER DOME

Configuration SD1

AXIAL FORCE COEFFICIENTS

Support Type S1

Load Case LC

Factor = 2.28 kN

Fig 4.6.1.3

SCHWEDLER DOME

Configuration SD1

AXIAL FORCE COEFFICIENTS

Support Type S1

Load Case LD

Factor = 4.41 kN

Fig 4.6.1.4

(B) DEFLECTIONS

Configuration SD1

Support Type S1

Figures 4.6.1.5 to 4.6.1.8 show the nodal deflections in the dome, for four load cases

These figures show the deflection in the form of contours together with dots. A dot is drawn with respect to the amount of deflection of the corresponding node. Along each node a coefficient is also given which can be used to obtain the deflection by multiplying it with the common factor.

The maximum deflection for all the load cases is on the third ring row from the apex. The deflection on the apex node, is varying from 14% to 68% of the maximum deflection for different load cases.

The maximum deflection is 25.3 mm and this is for load case LB. This small deflection showed the high rigidity of the dome.

The nodes next to fully constrained point lift 21% to 30% of the maximum downward deflection, under various load cases. However, the upward deflections are small and are not significant.

Fig 4.6.1.5

SCHWEDLER DOME

Configuration SD1

DEFLECTION COEFFICIENT
CONTOUR LINES

DEFLECTION COEFFICIENTS AND SUPPORT ARRANGEMENT

Support Type S1

Load Case LB

Factor = .253 mm

LEGEND

Vertical Constraint

Complete Translational Constraint

LEGEND

Vertical Constraint

Complete Translational Constraint

Fig 4.6.1.6

SCHWEDLER DOME

Configuration SD1

DEFLECTION COEFFICIENTS AND SUPPORT ARRANGEMENT

Support Type S1

Load Case LC

Factor = .138 mm

NODAL DEFLECTION COEFFICIENTS

LEGEND

Vertical Constraint

Complete Translational Constraint

DEFLECTION COEFFICIENT CONTOUR LINES

LEGEND

Vertical Constraint

Complete Translational Constraint

Fig 4.6.1.7

SCHWEDLER DOME

Configuration SD1

DEFLECTION COEFFICIENT
CONTOUR LINES

DEFLECTION COEFFICIENTS AND SUPPORT ARRANGEMENT

Support Type S1

Load Case LD

Factor = .242 mm

LEGEND

Vertical Constraint

Complete Translational Constraint

Vertical Constraint

Complete Translational Constraint

Fig 4.6.1.8

(C) SUPPORT REACTIONS

Configuration SD1

Support type S1

The distributions of support reactions in the dome for the four load cases are displayed in Figs 4.6.1.9 to 4.6.1.12.

As the figures show, the support reactions increase rapidly as they approach the translationally constrained nodes.

The horizontal reactions on the vertical restrained support points are zero.

The dome has maximum vertical and horizontal reactions of 395 and 184 kN under the load case LB, which is a combination of dead and unsymmetrical snow load.

The maximum reactions for load cases LB and LD are on the one side subjected to the high intensity of snow.

Load case LA produced symmetrical reactions, and load case LC produced smaller reactions than the others.

SCHWEDLER DOME

Configuration SD1

SUPPORT REACTIONS

Support Type S1

Load Case LA

Unit = kN

Fig 4.6.1.9

HORIZONTAL
REACTIONS

VERTICAL
REACTIONS

SCHWEDLER DOME
Configuration SD1

SUPPORT REACTIONS
Support Type S1

Load Case LB
Unit = kN

Fig 4.6.1.10

SCHWEDLER DOME

Configuration SD1

SUPPORT REACTIONS

Support Type S1

Load Case LC

Unit = kN

Fig 4.6.1.11

SCHWEDLER DOME

Configuration SD1

SUPPORT REACTIONS

Support Type S1

Load Case LD

Unit = kN

Fig 4.6.1.12

4.6.2 The Study of Support Type S2

In a manner similar to section 4.6.1, axial forces, deflections and support reactions in the configuration SD1 of the Schwedler dome, with support type S2 are discussed for all the load cases.

(A) Axial Forces

Configuration SD1

Support Type S2

The maximum axial force in the dome with support type S2 is 4 to 5 times smaller than those with support type S1, for various load cases.

All the rib members are carrying compressive axial forces, Figs 4.6.2.1 to 4.6.2.4.

The forces in the bottom ring members are zero, due to the complete translational support nodes.

The tensile axial forces are generally in the members of the two rings next to the bottom ring of the dome. The maximum tensile forces are not more than 44% of the maximum compressive forces, for all the load cases with the exception of load case LA. For load case LA, the maximum tensile force is 62 to 63% of the maximum force.

The unsymmetrical load cases, i.e. LB and LD, the maximum forces are larger than the other two load cases (Figs 4.6.2.1 and 4.6.2.4).

The respective maximum forces are 75, 95, 57 and 94 kN for the four load cases.

SCHWEDLER DOME

Configuration SD1

AXIAL FORCE COEFFICIENTS

Support Type S2

Load Case LA

Factor = .75 kN

Fig 4.6.2.1

SCHWEDLER DOME

Configuration SD1

AXIAL FORCE COEFFICIENTS

Support Type S2

Load Case LB

Factor = .95 kN

Fig 4.6.2.2

SCHWEDLER DOME

Configuration SD1

AXIAL FORCE COEFFICIENTS

Support Type S2

Load Case LC

Factor = .57 kN

Fig 4.6.2.3

SCHWEDLER DOME

Configuration SD1

AXIAL FORCE COEFFICIENTS

Support Type S2

Load Case LD

Factor = .94 kN

Fig 4.6.2.1

(B) Deflections

Configuration SD1

Support Type S2

The maximum deflection for each load case is on the third top ring from the apex, (see Figs 4.6.2.5 to 4.6.2.8).

The respective deflections of the apex node are 66%, 54% and 1% of the corresponding maximum deflection for load cases LA, LC and LD. Furthermore, the apex node lifts 14% of the maximum deflection under load case LB.

For all the load cases the nodes in the ring next to the boundary ring have a slight upward deflections. This is true with the exception of load cases LC and LD, where the nodes only at the windward and leeward edge lift vertically on the second bottom ring.

The maximum lift varies between 13% to 17% of the maximum deflection under different load cases.

The maximum deflection is 17.1 mm and 17.3 mm, under load cases LA and LB, respectively.

Fig 4.6.2.5

SCHWEDLER DOME

Configuration SD1

DEFLECTION COEFFICIENT
CONTOUR LINES

DEFLECTION COEFFICIENTS AND SUPPORT ARRANGEMENT

Support Type S2

Load Case LB

Factor = .173 mm

LEGEND

Vertical Constraint
Complete Translational Constraint

LEGEND

Vertical Constraint
Complete Translational Constraint

Fig 4.6.2.6

Fig 4.6.2.7

SCHWEDLER DOME

Configuration S01

DEFLECTION COEFFICIENT
CONTOUR LINES

DEFLECTION COEFFICIENTS AND SUPPORT ARRANGEMENT

Support Type S2

Load Case LD

Factor = .167 mm

LEGEND

Vertical Constraint
Complete Translational Constraint

LEGEND

Vertical Constraint
Complete Translational Constraint

Fig 4.6.2.8

(C) SUPPORT REACTIONS

Configuration SD1

Support type S2

The distribution of the support reactions in the dome with support type S2 is almost uniform, Figs 4.6.2.9 to 4.6.2.12.

The horizontal reactions on all the support points are directed inward the structure. It follows that the dome is under compressive stresses, which is obvious from the dominance of compressive forces in most of the members.

The maximum vertical and horizontal reactions are about 3 times smaller than those with support type S1, for all the load cases.

The maximum vertical reaction is 134 kN under load case LD. Though, the maximum horizontal reaction is 67 kN under load case LB.

HORIZONTAL
REACTIONS

VERTICAL
REACTIONS

SCHWEDLER DOME

Configuration SD1

SUPPORT REACTIONS

Support Type S2

Load Case LA

Unit = kN

Fig 1.6.2.9

SUPPORT REACTIONS
Support Type S2
Load Case LB
Unit = kN

Fig 4.6.2.10

HORIZONTAL
REACTIONS

VERTICAL
REACTIONS

SCHWEDLER DOME

Configuration SD1

SUPPORT REACTIONS

Support Type S2

Load Case LC

Unit = kN

Fig 4.6.2.11

HORIZONTAL
REACTIONS

VERTICAL
REACTIONS

SCHWEDLER DOME Configuration SD1

SUPPORT REACTIONS

Support Type S2

Load Case LD

Unit = kN

Fig 1.5.2.12

4.7 SCHWEDLER DOME : Configuration SD2 Layout and Structural Detail

4.7.1 SPECIFICATIONS

Figure 4.7.1 shows the configuration SD2 of a Schwedler dome with a 50 m diameter and 10 m depth from bottom ring to crown and a radius of 36.25 m.

The spherical surface is 2270 m², which covers a surface area of 1963 m². Similar to the configuration SD1, this dome consists of 870 members and 307 nodes.

The type of the members are described in Fig 4.7.2. The members are categorised in 18 types with respect to their lengths. The member lengths vary from 1.946 m to 4.370 m. The majority of members i.e. rib members, have the same length. Generally, the ring and diagonal member lengths increase as the ring gets longer. However in a row both the ring as well as diagonal members have the same length.

4.7.2 DATA PREPARATION Configuration SD2

The formex formulation for configuration SD2 of the Schwedler dome is

```
::
E1 = rinit(6,9,8,1) : [1,0,0; 1,0,1]
E2 = rinit(6,7,8,1) : [1,4,2; 1,4,3]
E3 = rinit(12,6,4,1) : [1,2,3; 1,2,4]
E4 = rinit(24,4,2,1) : [1,1,5; 1,1,6]
E  = E1 # E2 # E3 # E4
F1 = rin(2,6,8) : [1,0,1; 1,8,1]
```

```

F2 = rin(2,12,4) : [1,0,2; 1,4,2]
F3 = rinit(24,2,2,1) : [1,0,3; 1,2,3]
F4 = rinit(48,5,1,1) : [1,0,5; 1,1,5]
F = F1 # F2 # F3 # F4
R1 = rin(2,6,8) : lam(2,4) : [1,0,1; 1,4,2]
R2 = rin(2,12,4) : lam(2,2) : [1,0,2; 1,2,3]
R3 = rin(2,12,4) : lam(2,2) : [1,2,3; 1,0,4]
R4 = rin(2,24,2) : lam(2,1) : [1,0,4; 1,1,5]
R5 = rin(2,24,2) : lam(2,1) : [1,1,5; 1,0,6]
R6 = rin(2,24,2) : lam(2,1) : [1,0,6; 1,1,7]
R7 = rin(2,24,2) : lam(2,1) : [1,1,7; 1,0,8]
R8 = rin(2,24,2) : lam(2,1) : [1,0,8; 1,1,9]
R = R1 # R2 # R3 # R4 # R5 # R6 # R7 # R8
WH = E # F # R
K1 = lib(I=1,6) : [1,8*I,0; 1,0,0]
K2 = rin(3,9,1) : [1,48,1; 1,0,1]
K = K1 # K2
SD1 = nov(K) : WH
SD = pex : SD1
G = ram(tap(3,2)) : SD
D1 = dic(G) : SD
D = ras(tap(1,2)) : D1
USE BS(36.25, 7.5, 4,8448)
DRAW SD

```

Where 36.25 is the radius of the dome in metres and 7.5 and 4.8448 are angular basifactors in degrees for directions 2 and 3.

SCHWEDLER DOME

CONFIGURATION SD2
Height to diameter ratio = $1/5$

Fig 4.7.1

SCHWEDLER DOME

Configuration SD2

TYPE OF ELEMENTS

No. of nodes = 307

No. of elements = 870

Diameter of dome = 50.0 m

Radius of dome = 36.25 m

TYPE No.	No. OF MEMBERS	LENGTH m
1	18	1.946
2	48	2.304
3	24	2.375
4	18	2.616
5	48	2.968
6	6	3.062
7	264	3.064
8	24	3.140
9	12	3.150
10	48	3.270
11	48	3.529
12	24	3.629
13	48	3.725
14	12	3.794
15	48	3.935
16	24	4.105
17	48	4.152
18	48	4.370

Fig 4.7.2

4.7.3 LOAD CASES

Configuration SD2

The dome were analysed under four load cases shown in Figs 4.7.3 to 4.7.6.

The magnitude and distribution of loads for each node and the determination of combination of loads are described in the figures.

The total loads are 3621, 4020, 2109 and 3809 kN for the load cases LA, LB, LC and LD.

4.7.4 BOUNDARY CONDITIONS

Configuration SD2

The two types of boundary conditions are shown in Fig 3.7.7. The figure also shows the type of the support for each boundary node. The support nodes are considered to be free to rotate in any direction.

4.7.5 DESIGN

Configuration SD2

The steel tubes forming the bracing of the dome with support type S1 having the size which vary between 76.1 mm to 139.7 mm in diameter, and thickness of 3.2 mm to 8.0 mm, according to their lengths and stresses, Fig 4.7.8.

The dome with support type S2 have been designed by three different sizes of members. Figure 4.7.9 shows the diameters and the thicknesses of the tubes.

The unit dead weight of the steel structure is 121.1 N/m² and 97.6 N/m² for support type S1 and S2, respectively.

4.7.6 CAPACITY CHECK

Configuration SD2

The design of the members for both support types have been checked for each analysis, and the samples of the capacity checkes are shown in Figs 4.7.10 and 4.7.11.

The figures show that the design of the members are satisfactory for all the support types and load cases.

SCHWEDLER DOME Configuration SD2

LOAD CASE LA

LA = 1.4 DL + 1.6 IL

DL = 0.40 kN/m² on sphere

IL = Im · Aep

Im = 0.75 kN/m²

Aep = Area on plan

IMPOSED LOAD

Fig 4.7.3

SCHWEDLER DOME Configuration SD2

LOAD CASE LB

$$LB = 1.4 DL + 1.6 SL$$

DL = 0.10 kN/m² on sphere

$$SL = U \cdot S_e \cdot A_{ep}$$

$$S_e = 0.75 \text{ kN/m}^2$$

A_{ep} = Area on plan

SNOW LOAD

Fig 4.7.1

SCHWEDLER DOME Configuration SD2

LOAD CASE LC

$$LC = 1.4 DL + 1.4 WL$$

DL = 0.10 kN/m² on sphere

$$WL = C_{pe} \cdot q \cdot A_{es}$$

$$q = 0.537 \text{ kN/m}^2$$

A_{es} = Area on sphere

$$C_{pe} \begin{cases} A = -0.45 \\ B = -0.75 \\ C = -0.20 \end{cases}$$

WIND LOAD

Fig 4.7.5

SCHWEDLER DOME

Configuration SD2

LOAD CASE LD

$$LD = 1.2 DL + 1.2 SL + 1.2 WL$$

$$DL = 0.10 \text{ kN/m}^2 \text{ on sphere}$$

$$WL = Cpe \cdot q \cdot Aes$$

$$q = 0.537 \text{ kN/m}^2 \quad Cpe \quad B = -0.75$$

$$Aes = \text{Area on sphere} \quad C = -0.20$$

WIND LOAD

$$SL = U \cdot Se \cdot Aep$$

$$Se = 0.75 \text{ kN/m}^2$$

$$Aep = \text{Area on plan}$$

SNOW LOAD

Fig 1.7.6

Support type S2

Support type S1

SCHWEDLER DOME Configuration SD2

- LEGEND
- Vertical Constraint
 - Complete Translational Constraint

Fig 4.7.7

SCHWEDLER DOME

Configuration SD2

DESIGN OF MEMBERS

Support Type S1

Steel Circular Hollow Sections

CS1	D= 76.1 mm t= 3.2 mm	
CS2	D= 88.9 mm t= 3.2 mm	
CS3	D= 114.3 mm t= 5.0 mm	
CS4	D= 139.7 mm t= 8.0 mm	

Weight = 121.1 N/m²

TYPE No.	LENGTH m	No. OF MEMBERS WITH X-SECTION OF			
		CS1	CS2	CS3	CS4
1	1.946	48			
2	2.301	48			
3	2.375	24			
4	2.646		48		
5	2.958		48		
6	3.062		6		
7	3.061	120	138		6
8	3.140		24		
9	3.158		12		
10	3.270			48	
11	3.529		48		
12	3.629		24		
13	3.725		48		
14	3.791		12		
15	3.935			48	
16	4.105		24		
17	4.152			48	
18	4.370			48	

Fig 4.7.8

SCHWEDLER DOME

Configuration SD2

DESIGN OF MEMBERS

Support Type S2

Steel Circular Hollow Sections

CS1	D= 76.1 mm	—
	t= 3.2 mm	—
CS2	D= 88.9 mm	==
	t= 3.2 mm	==
CS3	D= 114.3 mm	===
	t= 3.6 mm	===

Weight = 97.6 N/m²

TYPE No.	LENGTH m	No. OF MEMBERS WITH X-SECTION OF		
		CS1	CS2	CS3
1	1.916	48		
2	2.301	48		
3	2.375	24		
4	2.616	48		
5	2.968	48		
6	3.062		6	
7	3.061	120	144	
8	3.140		24	
9	3.158		12	
10	3.270	48		
11	3.529		48	
12	3.629		24	
13	3.725		48	
14	3.781		12	
15	3.935		48	
16	4.105		24	
17	4.152			48
18	4.370			48

Fig 4.7.9

SCHWEDLER DOME

Configuration SD2

CAPACITY CHECK

Ratio of the internal force to the capacity of member

Load Case LA

Support Type S1

Fig 4.7.10

SCHWEDLER DOME

Configuration SD2

CAPACITY CHECK

Ratio of the internal force to the capacity of member

Load Case LA

Support Type S2

Fig 4.7.11

4.8 DISCUSSION OF RESULTS

Configuration SD2

The member forces, nodal deflections and support reactions are obtained from pin-connected analysis of the Schwedler dome for the four load cases and with two types of supports. These results are represented graphically and a discussion of the forces, deflections and support reactions is made below.

4.8.1 The Study of Support Type S1

(A) AXIAL FORCES

Configuration SD2

Support type S1

Figures 4.8.1.1 to 4.8.1.4 show the distribution of axial forces in the dome for the four load cases with support type S1. This distribution of force is shown in the form of coefficients recorded along lengths of the corresponding members. The value of a member force can be obtained by multiplying the coefficient of a member with the given factor on each figure. Also, the thickness representing a member is proportional to the magnitude of the force in it.

The compressive axial force in a member can be identified by a negative sign preceding its coefficient. In addition, the members with compressive force are represented by firm lines as against dotted lines for the plotting of the member with tensile axial forces.

The concentration of axial forces is in the members near the

fully translational support nodes. This is particularly true for the compressive type of force. The maximum forces in all the four load cases are of compressive type and they are in the rib members next to the completely translational support nodes.

The tensile forces are mainly produced in the outermost ring. However, they are not larger than 43% of the maximum force in any case. Although the extent of tensile forces is up to the second and third ring from the bottom ring, this is limited to a few members around the fully constrained supports. Similarly, the diagonal members around this type of support nodes have considerable tensile forces. The magnitude of these forces is not more than 41% in any case.

It follows that the forces in all the members in the central zone of the dome are relatively negligible. Also, the forces in central zone are of the compressive type.

The maximum force is 746 kN for the load case LB. Further, the distribution of member forces follows the pattern of load applications. It follows that the members under relatively heavier loading have to resist larger forces than those on the other side of the dome.

SCHWEDLER DOME

Configuration SD2

AXIAL FORCE COEFFICIENTS

Support Type S1

Load Case LA

Factor = 6.03 kN

Fig 4.8.1.1

SCHWEDLER DOME

Configuration SD2

AXIAL FORCE COEFFICIENTS

Support Type S1

Load Case LB

Factor = 7.46 kN

Fig 4.8.1.2

SCHWEDLER DOME

Configuration SD2

AXIAL FORCE COEFFICIENTS

Support Type S1

Load Case LC

Factor = 3.55 kN

Fig 4.8.1.3

SCHWEDLER DOME

Configuration SD2

AXIAL FORCE COEFFICIENTS

Support Type S1

Load Case LD

Factor = 6.91 kN

Fig 4.8.1.4

(B) DEFLECTIONS

Configuration SD2

Support Type S1

The deflections are represented by contour lines and also, in the form of dots, as displayed in Figs 4.8.1.5 to 4.8.1.8.

The nodal deflections in configuration SD2 are larger than those in configuration SD1.

The maximum deflection is on the third ring from the apex for load case LA. However, for the other load cases the maximum deflection is on the third ring from the boundary ring.

The maximum deflection is 44.3 mm, under load case LB. The respective maximum deflection are 34.8, 21.6 and 42.3 for load cases LA, LC and LD.

The nodes next to the fully constrained point lift by maximum up to 39%, 27%, 37% and 25% from the maximum downward deflection for load cases LA, LB, LC and LD respectively.

The deflections in one side of the dome under load cases LB and LD are larger than those on the other side. It indicates that the deflections have followed the pattern of the application of loads.

DEFLECTION COEFFICIENT
CONTOUR LINES

LEGEND
Vertical Constraint
Complete Translational Constraint

SCHWEDLER DOME
Configuration S02

DEFLECTION COEFFICIENTS AND SUPPORT ARRANGEMENT

Support Type S1
Load Case LA
Factor = .348 mm

NODAL DEFLECTION
COEFFICIENTS

LEGEND
Vertical Constraint
Complete Translational Constraint

Fig 4.8.1.5

SCHWEDLER DOME

Configuration SD2

DEFLECTION COEFFICIENT
CONTOUR LINES

DEFLECTION COEFFICIENTS AND SUPPORT ARRANGEMENT

Support Type S1

Load Case LB

Factor = .443 mm

LEGEND

Vertical Constraint

Complete Translational Constraint

Fig 4.8.1.6

SCHWEDLER DOME

Configuration SD2

DEFLECTION COEFFICIENT
CONTOUR LINES

DEFLECTION COEFFICIENTS AND SUPPORT ARRANGEMENT

Support Type S1

Load Case LC

Factor = .216 mm

LEGEND

Vertical Constraint

Complete Translational Constraint

LEGEND

Vertical Constraint

Complete Translational Constraint

Fig 4.8.1.7

SCHWEDLER DOME

Configuration SD2

DEFLECTION COEFFICIENT
CONTOUR LINES

DEFLECTION COEFFICIENTS AND SUPPORT ARRANGEMENT

Support Type S1

Load Case LD

Factor = .423 mm

LEGEND

- Vertical Constraint
- Complete Translational Constraint

NODAL DEFLECTION
COEFFICIENTS

LEGEND

- Vertical Constraint
- Complete Translational Constraint

Fig 4.8.1.8

(C) SUPPORT REACTIONS

Configuration SD2

Support type S1

The support reactions of the configuration SD2 of Schwedler dome with support type S1 are represented graphically as shown in Figs 4.8.1.9 to 4.8.1.12.

The horizontal reactions in configuration SD2 are more than 3 times larger than those in configuration SD1. So, configuration SD1 is stiffer than configuration SD2.

As the figures show that the vertical reactions on the fully constrained nodes are about 10 times larger than the maximum vertical reaction on the other support points.

The horizontal reactions on the nodes which are vertically supported are zero. The distribution of vertical reactions is almost uniform on these nodes.

The maximum vertical and horizontal reactions are 480, 541 kN under load case LB.

HORIZONTAL
REACTIONS

VERTICAL
REACTIONS

SCHWEDLER DOME
Configuration SD2

SUPPORT REACTIONS
Support Type S1

Load Case LA
Unit = kN

Fig 4.8.1.9

SCHWEDLER DOME Configuration SD2

SUPPORT REACTIONS

Support Type S1

Load Case LB

Unit = kN

Fig 1.8.1.10

SCHWEDLER DOME
Configuration SD2

SUPPORT REACTIONS
Support Type S1

Load Case LC

Unit = kN

Fig 4.8.1.11

SCHWEDLER DOME

Configuration SD2

SUPPORT REACTIONS

Support Type 51

Load Case LD

Unit = kN

Fig 4.8.1.12

4.8.2 The Study of Support Type S2

The axial forces, nodal deflections and support reactions in the configuration SD2 of the Schwedler dome, with the support type S2 are discussed in this section for all the load cases.

(A) AXIAL FORCES

Configuration SD2

Support type S2

The distribution of axial forces in the configuration SD2 of the Schwedler dome, with support type S2 are shown in Figs 4.8.2.1 to 4.8.2.4.

The figures show that all the members are carrying compressive axial forces under the four load cases. The stress distribution is almost uniform. The axial forces in the members connecting two consecutive support nodes are zero.

The maximum axial force in the dome with support type S2 is about 7 times smaller than those with the support type S1.

The maximum axial force is on the bottom row rib members for load case LA, but the maximum axial force under load cases LB and LD is in the bottom row of diagonal members.

The behaviour of the dome under load cases LB and LD are almost the same but the maximum axial force in load case LB is larger than the maximum axial force in load case LD. The axial forces for load case LC is smaller than the other three load cases.

The maximum axial force for load case LA, LB, LC and LD are 83, 114, 53 and 100 kN respectively.

SCHWEDLER DOME

Configuration SD2

AXIAL FORCE COEFFICIENTS

Support Type S2

Load Case LA

Factor = .83 kN

Fig 4.8.2.1

SCHWEDLER DOME

Configuration SD2

AXIAL FORCE COEFFICIENTS

Support Type S2

Load Case LB

Factor = 1.14 kN

Fig 1.8.2.2

SCHWEDLER DOME

Configuration SD2

AXIAL FORCE COEFFICIENTS

Support Type S2

Load Case LC

Factor = .53 kN

Fig 1.8.2.3

SCHWEDLER DOME

Configuration SD2

AXIAL FORCE COEFFICIENTS

Support Type S2

Load Case LD

Factor = 1.00 kN

Fig 1.0.2.1

(B) DEFLECTIONS

Configuration SD2

Support Type S2

Figures 4.8.2.5 to 4.8.2.8 show the deflection diagrams for the four load cases.

The dome under load cases LB and LD has an upward deflection at the apex equal to 45% and 21%, respectively, of the maximum deflection.

For load cases LA and LC some of the nodes on the ring next to the boundary ring have a slight upward deflections. Load case LA produces symmetrical deflections. The deflections in load case LC are smaller than those for other load cases.

The deflections on one side of the dome under load cases LB and LD is larger than those on the other side, because of the unsymmetrical loading.

The maximum downward deflection for load cases LA, LB and LD is almost the same, i.e 24.0, 25.0 and 24.6 mm. For load case LC the maximum deflection is 13.7 mm, which is significantly smaller than the others.

Fig 4.8.2.5

Fig 4.8.2.6

SCHWEDLER DOME

Configuration SD2

DEFLECTION COEFFICIENT
CONTOUR LINES

DEFLECTION COEFFICIENTS AND SUPPORT ARRANGEMENT

Support Type S2

Load Case LC

Factor = .137 mm

LEGEND

Vertical Constraint
Complete Translational Constraint

LEGEND

Vertical Constraint
Complete Translational Constraint

Fig 1.8.2.7

SCHWEDLER DOME

DEFLECTION COEFFICIENT
CONTOUR LINES

DEFLECTION COEFFICIENTS AND SUPPORT ARRANGEMENT

LEGEND
Vertical Constraint
Complete Translational Constraint

Support Type S2
Load Case LD
Factor = .246 mm

NODAL DEFLECTION
COEFFICIENTS

LEGEND
Vertical Constraint
Complete Translational Constraint

Fig 1.8.2.8

(C) SUPPORT REACTIONS

Configuration SD2

Support type S2

The distribution of support reactions in the configuration SD2 of Schwedler dome, with support type S2 are shown in Figs 4.8.2.9 to 4.8.2.12.

The figures show that the horizontal reactions on all the supports points are directed inward the dome.

The magnitude of the horizontal reactions in this configuration is generally larger than the vertical reactions. It can be attributed to the shallow depth of configuration SD2.

The application of load cases LB and LD, because of the high intensity of snow load on one side of the structure, produces unsymmetrical reactions. However, the reactions on the dome under load case LD are generally smaller than those under load case LB.

Load case LA produces symmetrical reactions. The reactions for load case LC which is a combination of dead and wind loads, are smaller than the other three cases.

Fig 4.8.2.9

HORIZONTAL
REACTIONS

SCHWEDLER DOME

Configuration SD2

SUPPORT REACTIONS

Support Type S2

Load Case LB

Unit = kN

Fig 4.8.2.10

VERTICAL
REACTIONS

Fig 4.8.2.11

SCHWEDLER DOME

Configuration S02

SUPPORT REACTIONS

Support Type S2

Load Case LD

Unit = kN

Fig 4.8.2.12

4.9 CONCLUDING DISCUSSION

In the previous sections, member forces, nodal deflections and support reactions of the dome for both the configurations with two types of supports have been discussed. This section summarizes the conclusions drawn above and discusses the salient points.

The maximum axial forces and maximum vertical displacements in both the configurations for the four load cases and two boundary conditions are recorded in Table 4.10.1 (in section 4.10). The comparison of force in the dome with two types of supports is made in Figs 4.9.1 to 4.9.8. The value of the axial forces relates to the thickness of the line representing each member. The axial force in a member can also be obtained by directly multiplying the value shown along the member, with the factor given in the diagram.

The deflections for the two configurations with two types of supports have been illustrated in the form of deflection curves for the four load cases, Figs 4.9.9 and 4.9.10.

The configuration SD1, which has a relatively greater rise, deflect less than the configuration SD2, despite the fact that the loading in all the four cases are comparatively larger. Similarly, the forces in the configuration SD1 are considerably smaller than the others. Furthermore, the horizontal reactions in configuration SD1 is significantly smaller of those in configuration SD2. It follows that the rigidity of the structure increases with the increase of the structural height.

The majority of members in both the configurations have compressive forces for all the four load cases with the two types of the supports. The concentrations of forces in case

of the support type S1 are in the members mainly near the translationally constrained nodes.

The stress distribution in the dome shows that most of the members are carrying compressive axial forces, whilst the extent of tensile axial forces is limited to the area near the supports. Further, the maximum tensile force for any load case is not more than 54% of the maximum compressive forces.

As the Table 4.10.1 shows that for the support type S1 the maximum axial forces in configuration SD2 are 55% to 63% more, for different load cases, than those in configuration SD1. However, for support type S2, the maximum axial forces in both configurations are almost the same.

The reduction in deflections of the dome, with support type S1, for configuration SD1 compared with configuration SD2, varies from 31% to 43%, for different load cases.

The maximum deflections for support type S2 in configuration SD1 are slightly smaller than those in configuration SD2.

For both configurations with the support type S1, the compressive axial forces are found to increase rapidly as they approach the supports which have complete translational restraint. Furthermore, tensile forces are found to be dominant in the members near the supports having only vertical constraints.

However, the stress distribution for rest of the members in the dome is almost uniform and much smaller than for the members near the supports.

For support type S2, the concentration of forces in the

members near the supports is relatively less severe, and the resulting stress distribution in this case is almost uniform. The maximum axial forces for support type S2 is only 25% of those for boundary condition S1, Table 4.10.1.

The dominance of member forces near the supports for support type S1, is the direct result of the lateral displacements at the vertical restraint points. Consequently, the axial forces in the members connecting two consecutive complete translational constraint for support type S2, are zero.

In both configurations the application of load case LA, which is the combination of dead and imposed loads, produces symmetrical stress distributions.

In load case LB, because of the high intensity of snow loading on one side of the structure, the forces in the members are larger than those of the other side. The maximum axial forces on one side of the dome is 30% larger than the forces on the other side of the dome.

The support reactions in part of the dome which is under higher intensity of snow load, for load case LB is larger than those on the other side, for both configurations.

The horizontal reactions in configuration SD2 are about 3 and 2 times of those on configuration SD1, for support types S1 and S2 respectively. The opposite is true for the vertical reactions which are generally smaller in configuration SD2.

The maximum vertical and horizontal reactions are under load cases LB and LD, for the both configurations and supports types.

The influence of the two boundary conditions on the stress distribution in the dome for the other two load cases is not significantly different to the first two cases.

However, both the member forces and resulting nodal deflections for load case LC are significantly smaller than those for the other three load cases.

The behaviour of the dome under load case LD does not differ significantly from that of load case LB.

The dome is subjected to the maximum deflection under load case LB.

The dome with support type S1 lifts vertically near the fully translational constraint points between 3.2 to 13.6 mm. In support type S2, the dome with configuration SD2 lifts 11.3 and 5.2 mm for load cases LB and LD, respectively.

The comparison of deflections in both configurations, for four load cases through the symmetrical diameter, (with respect to each load case), have been illustrated in Figs 4.9.9 and 4.9.10 for configurations SD1 and SD2, respectively. In each case, the deflections are obtained from the nodes lying on the symmetrical diameter.

SCHWEDLER DOME

Configuration S01

Support type S2

AXIAL FORCE COEFFICIENTS

Load Case LA

Factor = 3.78 kN

LEGEND

Vertical Constraint

Complete Translational Constraint

LEGEND

Compression

Tension

Fig 1.9.1

Fig 4.9.2

SCHWEDLER DOME
Configuration SD1

AXIAL FORCE COEFFICIENTS

Load Case LC
Factor = 2.28 kN

SCHWEDLER DOME
Configuration S2

LEGEND

Compression —
Tension - - -

LEGEND

Vertical Constraint ●
Complete Translational Constraint ■

Fig 1.9.3

SCHWEDLER DOME

Configuration S01

Support type S1

Support type S2

LEGEND

Compression ———
Tension - - - - -

LEGEND

Vertical Constraint ●
Complete Translational Constraint ■

AXIAL FORCE COEFFICIENTS

Load Case LD
Factor = 4.41 kN

Fig 4.9.1

Fig 4.9.5

Fig 4.9.6

Fig 1.9.7

Fig 1.9.8

SCHWEDLER DOME

Configuration S01

DISTANCE m : From extreme left hand

DISTANCE m : From extreme left hand

COMPARISON OF DEFLECTIONS FOR VARIOUS LOAD CASES WITH
SUPPORT TYPE S1

COMPARISON OF DEFLECTIONS FOR VARIOUS LOAD CASES WITH
SUPPORT TYPE S2

Fig 1.9.9

SCHWEDLER DOME

Configuration S02

COMPARISON OF DEFLECTIONS FOR VARIOUS LOAD CASES WITH
SUPPORT TYPE S1

COMPARISON OF DEFLECTIONS FOR VARIOUS LOAD CASES WITH
SUPPORT TYPE S2

Fig 1.9.10

4.10 CONCLUSIONS

The maximum axial forces and maximum vertical displacements in both configurations for the four load cases and two boundary conditions are tabulated in Table 4.10.1.

SCHWEDLER DOME

Load Case	Configuration SD1				Configuration SD2			
	Support Type S1		Support Type S2		Support Type S1		Support Type S2	
	Maximum AXIAL FORCE kN	Maximum DEFLECTION mm	Maximum AXIAL FORCE kN	Maximum DEFLECTION mm	Maximum AXIAL FORCE kN	Maximum DEFLECTION mm	Maximum AXIAL FORCE kN	Maximum DEFLECTION mm
LA	-370	23.9	-75	17.1	-603	31.8	-83	21.0
LB	-181	25.3	-95	17.3	-716	11.3	-114	25.0
LC	-228	13.8	-57	9.5	-355	21.6	-53	13.7
LD	-111	21.2	-94	16.7	-691	12.3	-100	21.6
Weight	115.8	N/m ²	114.7	N/m ²	121.1	N/m ²	97.6	N/m ²

COMPARISON OF STRESS DISTRIBUTION AND DEFLECTION

Table 4.10.1

From the stress distributions, nodal deflections and support reactions, the following points can be concluded:

- 1- The configuration SD1 shows a more rigid behaviour than that of configuration SD2. That is to say, the larger height to diameter ratio results in a stiffer dome.
- 2- The support arrangement type S2 results in a relatively uniform stress distribution and increases the rigidity of the dome significantly as compared with support type S1.
- 3- The member axial forces for the unsymmetrical snow load are found to be critical.

4- The maximum deflection in the dome occurred under load case LB.

5- In both configurations, with two types of supports and various load cases the maximum deflections are significantly small.

6- In both configurations, with support type S1, the vertical and horizontal support reactions for fully constrained supports are considerably high.

7- The weight per square metre for configuration SD1 is not much different for the two support types. However, for configuration SD2 the dome with support type S1 is 23.5 N/m² heavier than the dome with support type S2.

5

THREE-WAY GRID DOMES

5.1 INTRODUCTION

Three-way grid domes are frequently used in many European countries. There are several recent examples of braced tubular steel domes built in this configuration by the French designer, Stephane du Chateau.

The three-dimensional system introduced by S. du Chateau and known as the SDC system, was developed for the specific application, a steel tubular dome of 42 m diameter, covering an electric power station. This project led to a whole series of structures, frequently similar in their layout and using the same basic principle of single-layer welded tubular construction.

This space system, first introduced in 1958 in France, has been used subsequently for numerous realizations, confirming its technical and architectural qualities. It is characterized by the use of

- (a) a steel tube as the main structural component;
- (b) a prefabricated node connector as the base of the system;
- (c) arc welding applied to the assembly of all component parts.

The node connector is made up of two slightly curved parts, which superimposed and provide a complete unit with six circular apertures to allow the connection of six tubular members at the same nodal point. The tubular components can be adjusted longitudinally within certain limit simply by sliding into the node; at the same time, the connector allows a certain amount of angular adjustment, permitting a gradual change of the curvature of the surface of the dome. This freedom to position the bars is one of the most important characteristics of the node. In effect, for shallow domes, all the bars can be cut to the same length and on penetration into the node the slight differences in length required can be accommodated without any problem. At the same time, the small angular changes required by the spherical surface can be obtained using the same type of connector.

These two characteristics-penetration and angular adjustment permit the absorption of all the geometrical deformation of the space framework. They allow the designer to produce various three-dimensional surfaces whose rigidity is provided through the continuous triangulation of framework, Ref 1.

This chapter contains a discussion of three-way grid domes (section 5.2), data generation (section 5.3) and analysis and design (section 5.4). A description of configuration TW1 of the three-way grid dome in section 5.5, followed by the results of configuration TW1 in section 5.6. The

details of configuration TW2 is given in section 5.7, and its results are discussed in section 5.8. The concluding discussion of the behaviour of the three-way grid dome, and the conclusions are given in sections 5.9 and 5.10, respectively.

5.2 DISCUSSION ON THE THREE-WAY GRID METHOD

The great virtue of geodesic dome is that the variation in length of their component members is quite small. In the three-way grid subdivision, the variation in length is even smaller than that in the geodesic dome.

This results in a regular network and leads to substantially uniform stress distribution in all the members of the dome under the applied loading.

However, both the subdivisions i.e. geodesic and three-way grid domes, also have a disadvantage; in practice, the geodesic geometry near the base has to be modified if the structure has to rest on a horizontal base ring. If this happens, then the joints along the base ring have to be adjusted as well as the length of the infilling members in the lower part of the dome.

5.3 DATA GENERATION FOR THREE-WAY GRID DOMES

The mapping of structural system onto the surface of a sphere in this particular method is achieved by projecting lines from any chosen observation point through the structural system and onto the surface of the sphere.

The pre-projected structural system is represented by formex algebra. The formex formulation represents the topological properties of the given configuration. The geometric properties (the coordinates of the nodal points with respect to the chosen coordinate system) are specified separately.

Figure 5.3.1 shows an example of a simple structural system.

Fig 5.3.1

The formex formulation for the configuration is represented by

```

E1 = ([1,2; 3,2], [3,2; 3,4], [3,4; 2,4], [2,4; 1,2])
E2 = ([2,4; 3,4], [3,4; 3,6], [3,6; 2,4])
E  = E1 # E2
F  = pex : lam(1, 3) : E

```

5.3.1 GEOMETRIC PARTICULARS

Figure 5.3.2 shows the reference frame as a three dimensional Cartesian coordinate system. The centre of the sphere, point S, is represented by the coordinates x_s , y_s , z_s . The origin of projection lines, point O, is represented by the coordinates x_o , y_o , z_o . The formex points representing the structural system nodal points are identified as x_1 , y_1 , z_1 . The projected points on the sphere surface are the unknown points x , y , z .

The centre of the dome, the origin of the projection lines and the formex formulation are all specified as topological points. Also specified are the scale factors to convert the topological points to geometric coordinates. The third dimension, the z value, is automatically taken care of by specifying the radius (or radii) of the dome (or domes).

For the purpose of double layer grides, both the top and bottom layer radii must be specified. These are identified in the formex formulation by the U3 value of either 0 or 1 to indicate top or bottom layer respectively.

Fig 5.3.2

5.3.2 GENERAL PROCEDURE

The unknown point P on the sphere surface with coordinates x , y , z is obtained by equating the equations of the straight line OUP and the sphere with centre S and radius R .

The two points form of the equation of a straight line is

$$(x-x_0)/(x_1-x_0) = (y-y_0)/(y_1-y_0) = (z-z_0)/(z_1-z_0) \quad (a)$$

The equation of a sphere of radius R is

$$x^{**2} + y^{**2} + z^{**2} = R^{**2}$$

with centre at the origin

and

$$(x-x_s)^{**2} + (y-y_s)^{**2} + (z-z_s)^{**2} = R^{**2} \quad (b)$$

with centre at S.

From (a) substitute x for y and z into (b)

$$y = ((x-x_0)*(y_1-y_0)/(x_1-x_0)) + y_0$$

$$z = ((x-x_0)*(z_1-z_0)/(x_1-x_0)) + z_0$$

(b) becomes

$$(x-x_s)^{**2} + [((x-x_0).(y_1-y_0)/(x_1-x_0)+y_0)) + y_s]^{**2} + [((x-x_0).(z_1-z_0)/(x_1-x_0)+z_0)) + z_s]^{**2} \quad (c)$$

To solve for x, the above expression is defined as a quadratic equation.

(c) becomes

$$(lx-a)^{**2} + (mx-b)^{**2} + (nx-c)^{**2} = R^{**2} \quad (c)$$

where

$$l = 1$$

$$a = x_s$$

$$m = (y_1-y_0)/(x_1-x_0)$$

$$b = [(x_0.(y_1-y_0)/(x_1-x_0)) - y_0 + y_s]$$

$$n = (z1-z0)/(x1-x0)$$

$$c = [(x0.(z1-z0)/(x1-x0)) - z0 + zs]$$

Expanding (c) we obtain

$$\begin{aligned} 1^{**2} &. x^{**2} + a^{**2} - 2.l.a.x + \\ m^{**2} &. x^{**2} + b^{**2} - 2.m.b.x + \\ n^{**2} &. x^{**2} + c^{**2} - 2.m.c.x = R^{**2} \end{aligned}$$

$$\begin{aligned} \text{i.e. } (1^{**2}+m^{**2}+n^{**2}) &. x^{**2} + (-2.l.a-2.m.b-2.n.c) . x \\ &+ (a^{**2} + b^{**2} + c^{**2} - R^{**2}) = 0 \end{aligned}$$

which simplifies to

$$A1 . x^{**2} + A2 . x + A3 = 0 \quad (d)$$

solving for x

$$x = (-A2 + (A2^{**2} - 4.A1.A3)^{**1/2})/2.A1$$

or

$$x = (-A2 - (A2^{**2} - 4.A1.A3)^{**1/2})/2.A1$$

y and z can now be solved by substituting into equation (a)

The above expression represents the general procedure for obtaining the required coordinates of points on a sphere.

This procedure for the calculation of the geometric coordinates may be implemented in a computer program. The program would take the form of a subroutine which in turn would be accepted by Formian, the main computer program which deals with formex algebra.

The subroutine will transfer all specifications as input

THREE-WAY GRID DOMES

data through its arguments which in this case includes the following:

1. Inner radius
2. xs, x coordinate of sphere centre
3. ys, y coordinate of sphere centre
4. zs, z coordinate of sphere centre
5. xo, x coordinate of observation point
6. yo, y coordinate of observation point
7. zo, z coordinate of observation point
8. sx, x scale factor
9. sy, y scale factor
10. Outer radius

To initiate the procedure contained in the subroutine, which will be named "MINE", simply type in

```
USE MINE (1, 2, 3, 4, 5, 6, 7, 8, 9, 10)
```

The return values will be the values of the geometric coordinates of the formex formulation on the surface of a sphere. For a visual check, the projected formex can be drawn on a VDU screen on the command DRAW F, F representing the original formex formulation.

5.4 STRUCTURAL ANALYSIS AND DESIGN

In an attempt to determine the approximate size of the members, LUSAS system based on the finite element stiffness method was used assuming uniformly distributed load case LA and unsymmetrical load case LB, and pin-connected joints.

Having obtained the member forces, design was done by considering the minimum number of various cross-sectional area of the members.

Using the approximations size of the members, an exact linear elastic analysis of the skeletal structure was carried out under the four load cases. The results of each analysis were checked for both the tensile capacity and compression resistance.

5.5 THREE-WAY GRID DOME : Configuration TW1

Layout and structural details

5.5.1 SPECIFICATIONS

The dome consists of a single-layer fully triangulated three-way grid of spherical shape, Fig 5.5.1.

The dome has a diameter of 50 m, a radius of curvature of 27.08 m and a rise of 16.66 m. Therefore, the height-to-diameter ratio is 1/3.

The surface area is 2365 m², which covers an area of 1755 m².

The lengths of the members differ slightly, depending on their location, Fig 5.5.2. The 756 members are divided into 47 types according to their lengths. The maximum length is 3.678 m and the minimum length is 2.943 m. There are altogether 271 nodes.

5.5.2 DATA PREPARATION

Configuration TW1

The formex formulation used to generate the data is

```
::
E11=([9,0,0; 11,0,0], [11,0,0; 10,1,0], [10,1,0; 9,0,0])
E22=([9,0,0; 10,1,0], [10,1,0; 8,1,0], [8,1,0; 9,0,0])
E1 = lib(J=0, 8):rin(1, J+9, 2):tranid(-J, J):E11
E2 = lib(J=0, 8):rin(1, J+10, 2):tranid(-J, J):E22
E = E1 # E2
TW11 = pex : E
```

THREE-WAY GRID DOME

CONFIGURATION TW1

Height to diameter ratio = $1/3$

Fig 5.5.1

THREE-WAY GRID DOME

Configuration TW1

TYPE OF ELEMENTS

No. of nodes = 271

No. of elements = 756

Diameter of dome = 50.0 m

Radius of dome = 27.08 m

TYPE No.	No. OF MEMBERS	LENGTH m
1	6	2.943
2	12	2.947
3	12	2.959
4	12	2.982
5	12	3.019
6	12	3.052
7	12	3.059
8	12	3.072
9	12	3.094
10	12	3.130
11	18	3.153
12	12	3.159
13	12	3.172
14	12	3.194
15	12	3.229
16	24	3.240
17	12	3.248
18	12	3.261
19	12	3.283
20	18	3.312
21	24	3.317
22	12	3.324
23	12	3.337
24	12	3.359
25	36	3.376
26	12	3.387
27	12	3.397
28	12	3.402
29	36	3.424
30	24	3.431
31	12	3.436
32	12	3.450
33	36	3.460
34	24	3.466
35	12	3.475
36	54	3.482
37	12	3.489
38	36	3.493
39	18	3.501
40	6	3.516
41	36	3.523
42	6	3.545
43	12	3.561
44	12	3.577
45	6	3.584
46	12	3.627
47	6	3.678

Fig 5.5.2

```
TW = pex : lam(2,9) : TW11
G = ram(tap(2,1)) : TW
D1 = dic(G) : TW
D = ras(tap(2,1)) : D1
USE MINE(1, 18,9,0, 18,9,-54.1666, 1.1852,2.0528 ,27.0833)
DRAW TW
```

where MINE is the program described in section 5.3.

5.5.3 LOAD CASES

Configuration TW1

The design of four load cases and the amount of loads in each nodes are shown in Figs 5.5.3 to 5.5.6. The determination of imposed, unsymmetrical snow, wind and the combination of snow and wind loads are illustrated in the figures.

The respective total magnitude of loads are 3430, 3664, 2163 and 3609 for the load cases LA, LB, LC and LD.

5.5.4 BOUNDARY CONDITIONS

Configuration TW1

The dome is supported on all the boundary nodes, as shown in Fig 5.5.7. In support type S2, the complete translational movement of all the boundary nodes are constrained. In support type S1, only 6 of them have complete translational constraint and the rest are only vertically supports. Nevertheless, all the support nodes are free to rotate in any direction.

THREE-WAY GRID DOME

Configuration TW1

LOAD CASE LA

$$LA = 1.4 DL + 1.6 IL$$

DL = 0.40 kN/m² on sphere

$$IL = I_m \cdot A_{ep}$$

$$I_m = 0.75 \text{ kN/m}^2$$

$$A_{ep} = \text{Area on plan}$$

IMPOSED LOAD

Fig 5.5.3

THREE-WAY GRID DOME Configuration TW1

LOAD CASE LB

$$LB = 1.4 DL + 1.6 SL$$

DL = 0.40 kN/m² on sphere

$$SL = U \cdot Se \cdot A_{ep}$$

$$Se = 0.75 \text{ kN/m}^2$$

A_{ep} = Area on plan

SNOW LOAD

Fig 5.5.4

THREE-WAY GRID DOME

Configuration TWI

LOAD CASE LC

$$LC = 1.4 DL + 1.4 WL$$

DL = 0.40 kN/m² on sphere

$$WL = C_{pe} \cdot q \cdot A_{es}$$

$$q = 0.537 \text{ kN/m}^2$$

A_{es} = Area on sphere

$$C_{pe} \begin{cases} A = 0.0 \\ B = -1.0 \\ C = -0.2 \end{cases}$$

WIND LOAD

Fig 5.5.5

THREE-WAY GRID DOME

Configuration TW1

LOAD CASE LD

$$LD = 1.2 DL + 1.2 SL + 1.2 WL$$

$$DL = 0.40 \text{ kN/m}^2 \text{ on sphere}$$

$$WL = C_{pe} \cdot q \cdot A_{es}$$

$$q = 0.537 \text{ kN/m}^2 \quad C_{pe} \begin{cases} A = 0.0 \\ B = -1.0 \\ C = -0.2 \end{cases}$$

$$A_{es} = \text{Area on sphere}$$

WIND LOAD

$$SL = U \cdot S_e \cdot A_{ep}$$

$$S_e = 0.75 \text{ kN/m}^2$$

$$A_{ep} = \text{Area on plan}$$

SNOW LOAD

Fig 5.5.6

Support type S2

Support type S1

THREE-WAY GRID DOME

Configuration TW1

- LEGEND
- Vertical Constraint ○
 - Complete Translational Constraint ●

Fig 5.5.7

5.5.5 DESIGN

Configuration TW1

The design of members for both the support type have been described in Figs 5.5.8 and 5.5.9. The size of the steel tubular members used for the dome with two support types is 76.1 mm in diameter, with the thickness varying from 3.2 to 4.0 mm.

This is true with the exception of the members around the fully translational constraint nodes in support type S1. These member are designed as circular hollow sections of 114.3 and 139.7 mm in diameter, with the thickness of 3.6 and 5.0, respectively.

The respective unit dead weight of the dome are 105.4 and 96.0 N/m² for support type S1 and S2.

5.5.6 CAPACITY CHECK

Configuration TW1

The ratios of the internal forces to the capacity of members, under four load cases, for support types S1 and S2, are plotted in graphical forms and the samples of them are shown in Figs 5.5.10 and 5.5.11.

The figures show all the internal forces are within the capacity of the members, for each load case.

THREE-WAY GRID DOME

Configuration TW1

DESIGN OF MEMBERS

Support Type S1

Steel Circular Hollow Sections

CS1	D= 76.1 mm	————
	t= 3.2 mm	————
CS2	D= 76.1 mm	=====
	t= 4.0 mm	=====
CS3	D= 111.3 mm	=====
	t= 3.6 mm	=====
CS4	D= 139.7 mm	=====
	t= 5.0 mm	=====

Weight = 105.4 N/m²

TYPE No.	LENGTH m	No. OF MEMBERS WITH X-SECTION OF			
		CS1	CS2	CS3	CS4
1	2.943		6		
2	2.947		12		
3	2.959		12		
4	2.982		12		
5	3.019			12	
6	3.052	12			
7	3.059	12			
8	3.072	12			
9	3.094	12			
10	3.130		12		
11	3.153	18			
12	3.159	12			
13	3.172	12			
14	3.194	12			
15	3.229	12			
16	3.240	24			
17	3.248	12			
18	3.261	12			
19	3.283	12			
20	3.318		18		
21	3.317		24		
22	3.324	12			
23	3.337	12			
24	3.359	12			
25	3.376		36		
26	3.387		12		
27	3.397		12		
28	3.402		12		
29	3.424		30		
30	3.431		24		
31	3.436		12		
32	3.458		12		
33	3.460		36		
34	3.466		24		
35	3.475		12		
36	3.482		54		
37	3.489		12		
38	3.493		36		
39	3.501		18		
40	3.516			6	
41	3.523			36	
42	3.545			6	
43	3.561			12	
44	3.577			12	
45	3.594			6	
46	3.627				12
47	3.678				6

Fig 5.5.8

THREE-WAY GRID DOME

Configuration TW1

DESIGN OF MEMBERS

Support Type S2

Steel Circular Hollow Sections

CS1 | D= 76.1 mm
| t= 3.2 mm

CS2 | D= 76.1 mm
| t= 1.0 mm

Weight = 96.0 N/m²

TYPE No.	LENGTH m	No. OF MEMBERS WITH X-SECTION OF	
		CS1	CS2
1	2.913	6	
2	2.917	12	
3	2.959	12	
4	2.982	12	
5	3.019	12	
6	3.052	12	
7	3.059	12	
8	3.072	12	
9	3.094	12	
10	3.130	12	
11	3.153	18	
12	3.159	12	
13	3.172	12	
14	3.194	12	
15	3.229	12	
16	3.240	24	
17	3.248	12	
18	3.261	12	
19	3.283	12	
20	3.318	18	
21	3.317		24
22	3.324		12
23	3.337		12
24	3.359		12
25	3.376		36
26	3.387		12
27	3.397		12
28	3.402		12
29	3.424		30
30	3.431		24
31	3.436		12
32	3.450		12
33	3.460		36
34	3.466		24
35	3.475		12
36	3.482		54
37	3.489		12
38	3.493		36
39	3.501		18
40	3.516		6
41	3.523		36
42	3.545		6
43	3.561		12
44	3.577		12
45	3.594		6
46	3.627		12
47	3.678		6

Fig 5.5.9

THREE-WAY GRID DOME

Configuration TW1

CAPACITY CHECK

Ratio of the internal force to the capacity of member

Load Case LD

Support Type S1

Fig 5.5.10

THREE-WAY GRID DOME

Configuration TW1

CAPACITY CHECK

Ratio of the internal force to the capacity of member

Load Case LD

Support Type S2

Fig 5.5.11

5.6 DISCUSSION OF RESULTS

Configuration TW1

The member forces, nodal deflections and support reactions obtained from analysis of the three-way grid dome have been discussed for the two types of supports, i.e. S1 and S2.

The discussion of support type S1 is in section 5.6.1. This is followed by a discussion of support type S2 in section 5.6.2.

5.6.1 The Study of Support Type S1

(A) AXIAL FORCES

Configuration TW1

Support type S1

The distribution of axial forces in the dome for the four load cases are displayed in Figs 5.6.1.1 to 5.6.1.4.

In these figures, the distribution of the axial forces can be assessed from the thickness of the line representing a member, and the coefficients which are recorded along the members.

As the figures show, the compressive axial forces increase rapidly as they approach the fully restrained supports. Though, the axial force for the rest of the members are reasonably uniform.

The maximum axial force in the dome is 397 kN, under load case LB.

The maximum tensile force varies from 48% to 54% of the maximum forces, under the four load cases.

The axial forces on one side of the dome, under load cases LB and LD, are larger than the forces on the other side, because of the unsymmetrical snow load.

The application of load case LA produces symmetrical stress distribution.

The member forces for load case LC, which is a combination of dead and wind load are smaller than those for the other load cases.

THREE-WAY GRID DOME

Configuration TW1

AXIAL FORCE COEFFICIENTS

Support Type S1

Load Case LA

Factor = 3.10 kN

Fig 5.6.1.1

THREE-WAY GRID DOME

Configuration TW1

AXIAL FORCE COEFFICIENTS

Support Type S1

Load Case LB

Factor = 3.97 kN

Fig 5.6.1.2

THREE-WAY GRID DOME

Configuration TW1

AXIAL FORCE COEFFICIENTS

Support Type S1

Load Case LC

Factor = 2.06 kN

Fig 5.6.1.3

THREE-WAY GRID DOME

Configuration TW1

AXIAL FORCE COEFFICIENTS

Support Type S1

Load Case LD

Factor = 3.81 kN

Fig 5.6.1.4

(B) DEFLECTIONS

Configuration TW1

Support type S1

The deflections are represented by contour lines and also in the form of dots, as the Figs 5.6.1.5 to 5.6.1.8 shows.

The dome has the maximum deflection of 29.5 mm under the load case LA, which produces symmetrical deflections.

The dome lifts vertically near the fully constrained points by 25% to 45% of the maximum downward deflection, for various load cases.

The maximum deflection for load cases LB and LD is on the side with high intensity of snow. The maximum deflection for load cases LA and LC is at the apex of the dome.

Load case LC produced smaller deflections than the others.

THREE-WAY GRID DOME

Configuration TW1

DEFLECTION COEFFICIENTS AND SUPPORT ARRANGEMENT

Support Type S1

Load Case LA

Factor = .295 mm

NODAL DEFLECTION COEFFICIENTS

LEGEND

Vertical Constraint

Complete Translational Constraint

DEFLECTION COEFFICIENT CONTOUR LINES

LEGEND

Vertical Constraint

Complete Translational Constraint

Fig 5.6.1.5

DEFLECTION COEFFICIENT
CONTOUR LINES

LEGEND
○ Vertical Constraint
● Complete Translational Constraint

NODAL DEFLECTION
COEFFICIENTS

LEGEND
□ Vertical Constraint
■ Complete Translational Constraint

THREE-WAY GRID DOME

Configuration TW1

DEFLECTION COEFFICIENTS AND SUPPORT ARRANGEMENT

Support Type S1

Load Case LB

Factor = .256 mm

Fig 5.6.1.6

DEFLECTION COEFFICIENT
CONTOUR LINES

LEGEND
Vertical Constraint
Complete Translational Constraint

NODAL DEFLECTION
COEFFICIENTS

LEGEND
Vertical Constraint
Complete Translational Constraint

THREE-WAY GRID DOME

Configuration TW1

DEFLECTION COEFFICIENTS AND SUPPORT ARRANGEMENT

Support Type S1

Load Case LC

Factor = .169 mm

Fig 5.6.1.7

DEFLECTION COEFFICIENT
CONTOUR LINES

LEGEND

Vertical Constraint

Complete Translational Constraint

NODAL DEFLECTION
COEFFICIENTS

LEGEND

Vertical Constraint

Complete Translational Constraint

THREE-WAY GRID DOME

Configuration TW1

DEFLECTION COEFFICIENTS AND SUPPORT ARRANGEMENT

Support Type S1

Load Case LD

Factor = .255 mm

Fig 5.6.1.8

(C) SUPPORT REACTIONS

Configuration TW1

Support type S1

Figures 5.6.1.9 to 5.6.1.12 show the vertical and horizontal support reactions in the dome with support type S1, for all the load cases.

As the figures show, the vertical reactions increase rapidly as they approach the supports, which are translationally constrained.

The dome has negative reactions, at the nodes next to the fully constrained points. The magnitude of the negative reactions are small and they are not considerable.

The horizontal reactions on the vertically restrained nodes are zero, due to horizontal movements.

The application of load case LA, which is a combination of dead and imposed loads, produced symmetrical reactions.

The reactions on one side of the dome under load cases LB and LD, are larger than the reactions on the other side. This is due to unsymmetrical snow load involved in these load cases.

The respective maximum vertical reaction are 405, 505, 251 and 466 kN for load cases LA, LB, LC and LD.

SUPPORT REACTIONS

Support Type S1

Load Case LA

Unit = kN

Fig 5.6.1.9

THREE-WAY GRID DOME
Configuration TW1

SUPPORT REACTIONS
Support Type S1
Load Case LC
Unit = kN

Fig 5.6.1.11

5.6.2 The Study of Support Type S2

(A) AXIAL FORCES

Configuration TW1

Support type S2

The stress distribution in the dome with support type S2 is almost uniform. The maximum axial force is about 5 times smaller than those with support type S1 for all load cases.

The axial force in the member connecting two consecutive support nodes are zero, Figs 5.6.2.1 to 5.6.2.4.

In the figures the compressive axial force in a member can be identified by a negative sign preceeding its coefficient. In addition, the members with compressive force are represented by firm lines as against dotted lines for the plotting of the member with tensile axial forces.

The maximum tensile forces are not more than 37% of the maximum compressive forces for all the load cases, with the exception of load case LA. For load case LA the maximum tensile force is 74% of the maximum force.

The behaviour of the dome under load cases LB and LD, is the same. The maximum axial force is 80 kN under load case LD.

THREE-WAY GRID DOME

Configuration TW1

AXIAL FORCE COEFFICIENTS

Support Type S2

Load Case LA

Factor = .59 kN

Fig 5.6.2.1

THREE-WAY GRID DOME

Configuration TW1

AXIAL FORCE COEFFICIENTS

Support Type S2

Load Case LB

Factor = .79 kN

Fig 5.6.2.2

THREE-WAY GRID DOME

Configuration TW1

AXIAL FORCE COEFFICIENTS

Support Type S2

Load Case LC

Factor = .44 kN

Fig 5.6.2.3

THREE-WAY GRID DOME

Configuration TW1

AXIAL FORCE COEFFICIENTS

Support Type S2

Load Case LD

Factor = .80 kN

Fig 5.6.2.1

(B) DEFLECTIONS

Configuration TW1

Support type S2

Figures 5.6.2.5 to 5.6.2.8 show the nodal deflections in the dome. The figures show the deflections in the form of contour lines together with dots. The deflection at each node is depicted by the size of the dots and also the coefficient along each node. The hollow circle indicates the upward deflections.

The symmetrical load case LA produces symmetrical deflections and also the maximum deflection of 18.3 mm, which is at the apex of the dome.

The maximum deflection for load case LC is at the apex of the dome, but the overall deflections are not symmetric.

For all the load cases the nodes next to the boundary nodes have a slight upward deflections. This is true with the except of load cases LC and LD, where the nodes only at the windward and leeward edge lift at the nodes next to support points.

The maximum lift varies between 11% to 14% of the maximum deflection under the four load cases.

DEFLECTION COEFFICIENT
CONTOUR LINES

LEGEND
Vertical Constraint
Complete Translational Constraint

NODAL DEFLECTION
COEFFICIENTS

LEGEND
Vertical Constraint
Complete Translational Constraint

THREE-WAY GRID DOME

Configuration TW1

DEFLECTION COEFFICIENTS AND SUPPORT ARRANGEMENT

Support Type S2

Load Case LA

Factor = .183 mm

Fig 5.6.2.5

DEFLECTION COEFFICIENT
CONTOUR LINES

LEGEND

- Vertical Constraint
- Complete Translational Constraint

NODAL DEFLECTION
COEFFICIENTS

DEFLECTION COEFFICIENTS AND SUPPORT ARRANGEMENT

Configuration TW1

Support Type S2

Load Case LB

Factor = .129 mm

LEGEND

- Vertical Constraint
- Complete Translational Constraint

Fig 5.6.2.6

DEFLECTION COEFFICIENT
CONTOUR LINES

LEGEND
 Vertical Constraint
 Complete Translational Constraint

NODAL DEFLECTION
COEFFICIENTS

LEGEND
 Vertical Constraint
 Complete Translational Constraint

THREE-WAY GRID DOME
 Configuration TWI
 DEFLECTION COEFFICIENTS AND SUPPORT ARRANGEMENT
 Support Type S2
 Load Case LC
 Factor = .103 mm

Fig 5.6.2.7

DEFLECTION COEFFICIENT
CONTOUR LINES

LEGEND
● Vertical Constraint
● Complete Translational Constraint

NODAL DEFLECTION
COEFFICIENTS

LEGEND
□ Vertical Constraint
■ Complete Translational Constraint

THREE-WAY GRID DOME
Configuration TW1

DEFLECTION COEFFICIENTS AND SUPPORT ARRANGEMENT
Support Type S2
Load Case LD
Factor = .136 mm

Fig 5.6.2.8

(C) SUPPORT REACTIONS

Configuration TW1

Support type S2

The distribution of the support reactions in the dome is generally uniform. This is due to the complete translational constraint for all the support nodes.

The magnitudes of vertical reactions are larger than those of the horizontal reactions, which indicates the rigidity of the dome, Figs 5.6.1.9 to 5.6.1.12.

The respective maximum horizontal reaction are 53, 63, 33 and 61 kN for load cases LA, LB, LC and LD.

The maximum vertical reaction for the both load cases LB and LD is 65 kN, which is the maximum vertical reaction for all the load cases.

SUPPORT REACTIONS

Support Type S2

Load Case LA

Unit = kN

Fig 5.6.2.9

Fig 5.6.2.10

THREE-WAY GRID DOME
Configuration TW1

SUPPORT REACTIONS
Support Type S2
Load Case LC
Unit = kN

Fig 5.6.2.11

THREE-WAY GRID DOME
Configuration TW1

SUPPORT REACTIONS

Support Type S2

Load Case LD

Unit = kN

Fig 5.6.2.12

5.7 THREE-WAY GRID DOME : Configuration TW2

Layout and structural details

5.7.1 SPECIFICATIONS

Figure 5.7.1 shows the configuration TW2 of the three-way grid dome. It has a diameter of 50 m and a height-to-diameter ratio of 1/5. The radius of curvature is 36.25 m. This dome covers an area of 1670 m² and the spherical surface is 1882 m².

The structural framework is composed of 756 members, and 271 joints, Fig 5.7.2. The members having the same length are categorised as a type of members. The member length in the dome varies from 3.076 to 2.840 m, so that the difference of the length of the members is only 0.236 m. It follows that this dome is composed of the members with almost the identical lengths.

5.7.2 DATA PREPARATION

Configuration TW2

The formex used to generate the data is

```
::
E11=(19,0,0; 11,0,0], [11,0,0; 10,1,0], [10,1,0; 9,0,0])
E22=(19,0,0; 10,1,0], [10,1,0; 8,1,0], [8,1,0; 9,0,0])
E1 = lib(J=0, 8):rin(1, J+9, 2):tranid(-J, J):E11
E2 = lib(J=0, 8):rin(1, J+10, 2):tranid(-J, J):E22
E = E1 # E2
TW11 = pex : E
TW = pex : lam(2,9) : TW11
G = ram(tap(2,1)) : TW
```

THREE-WAY GRID DOME

CONFIGURATION TW2
Height to diameter ratio = $1/5$

Fig 5.7.1


```
D1 = dic(G) : TW
D = ras(tap(2,1)) : D1
USE MINE(1, 18,9,0, 18,9,-72.5, 1.0314,1.7865 ,36.25)
DRAW TW
```

where MINE is the program which projects the plan surface into the sphere.

5.7.3 LOAD CASES

Configuration TW2

The design of four load cases and the amounts of loads in each node are illustrated in Figs 5.7.3 to 5.7.6. The description of combination of load cases are illustrated in the figures.

The magnitudes of total load for load cases LA, LB, LC and LD are 3061, 3212, 1787 and 3149 kN.

5.7.4 BOUNDARY CONDITIONS

Configuration TW2

All the boundary nodes are supported by two arrangements, as shown in Fig 5.7.7. The support nodes are considered to be free to rotate in any direction.

5.7.5 DESIGN

Configuration TW2

The size of the steel tubular members for dome with support type S1 varies between 76.1 to 139.7 mm in diameter, with the thickness varying between 3.2 to 6.3 mm. The members

near the fully translational support nodes have been designed by cross-section four which has a diameter of 139.7 mm and a thickness of 6.3 mm, Fig 5.7.8.

The steel tubes forming the bracing of the dome with support type S2 have an outside diameter of 76.1 mm. The wall thickness of the tubes varies according to their location and stresses, between 3.2 to 4.0 mm as shown in Fig 5.7.9.

The respective unit weights for support type S1 and S2 are 102.2 and 80.2 N/m².

5.7.6 CAPACITY CHECK

Configuration TW2

The ratios of the internal forces to the capacities of members, under the four load cases, for support types S1 and S2, were obtained in graphical form.

These showed that all the internal forces are less than the capacities of the members, in all cases. Samples of capacity check plots are in Figs 5.5.10 and 5.5.11.

THREE-WAY GRID DOME

Configuration TW2

LOAD CASE LA

$$LA = 1.4 DL + 1.6 IL$$

DL = 0.40 kN/m² on sphere

$$IL = Im \cdot A_{ep}$$

$$Im = 0.75 \text{ kN/m}^2$$

A_{ep} = Area on plan

IMPOSED LOAD

Fig 5.7.3

THREE-WAY GRID DOME

Configuration TW2

LOAD CASE LB

$$LB = 1.4 DL + 1.6 SL$$

DL = 0.40 kN/m² on sphere

$$SL = U \cdot Se \cdot A_{ep}$$

$$Se = 0.75 \text{ kN/m}^2$$

$$A_{ep} = \text{Area on plan}$$

SNOW LOAD

Fig 5.7.1

THREE-WAY GRID DOME

Configuration TW2

LOAD CASE LC

LC = 1.4 DL + 1.4 WL

DL = 0.10 kN/m² on sphere

WL = $C_{pe} \cdot q \cdot A_{es}$

$q = 0.537 \text{ kN/m}^2$

A_{es} = Area on sphere

C_{pe} | A = -0.15
B = -0.75
C = -0.28

WIND LOAD

Fig 5.7.5

THREE-WAY GRID DOME

Configuration TW2

LOAD CASE LD

$$LD = 1.2 DL + 1.2 SL + 1.2 WL$$

DL = 0.40 kN/m² on sphere

$$WL = Cpe \cdot q \cdot Aes$$

$$q = 0.537 \text{ kN/m}^2 \quad Cpe \quad \begin{matrix} A = -0.15 \\ B = -0.75 \\ C = -0.20 \end{matrix}$$

$Aes = \text{Area on sphere}$

WIND LOAD

$$SL = U \cdot Se \cdot Aep$$

$$Se = 0.75 \text{ kN/m}^2$$

$$Aep = \text{Area on plan}$$

SNOW LOAD

Fig 5.7.6

Support type S2

Support type S1

THREE-WAY GRID DOME

Configuration TW2

LEGEND

- Vertical Constraint ○
- Complete Translational Constraint ●

Fig 5.7.7

THREE-WAY GRID DOME

Configuration TW2

DESIGN OF MEMBERS

Support Type S1

Steel Circular Hollow Sections

CS1	D= 76.1 mm t= 3.2 mm	——
CS2	D= 76.1 mm t= 4.0 mm	=====
CS3	D= 114.3 mm t= 3.6 mm	=====
CS4	D= 139.7 mm t= 6.3 mm	=====

Weight = 102.2 N/m²

TYPE No.	LENGTH m	No. OF MEMBERS WITH X-SECTION OF			
		CS1	CS2	CS3	CS4
1	2.840		18		
2	2.845		21		
3	2.850				12
4	2.864			21	
5	2.869		21		
6	2.894			12	
7	2.923			30	
8	2.928	21			
9	2.933	12			
10	2.957		36		
11	2.962	21			
12	2.967	12			
13	2.985		42		
14	2.991	21			
15	2.997	12			
16	3.010	18			
17	3.016	21			
18	3.021	12			
19	3.030	54			
20	3.035	24			
21	3.042	84			
22	3.050		102		
23	3.057			54	
24	3.068				18
25	3.076				6

Fig 5.7.8

THREE-WAY GRID DOME

Configuration TW2

DESIGN OF MEMBERS

Support Type S2

Steel Circular Hollow Sections

CS1 | D= 76.1 mm ———
| t= 3.2 mm

CS2 | D= 76.1 mm ———
| t= 4.0 mm

Weight = 80.2 N/m²

TYPE No.	LENGTH m	No. OF MEMBERS WITH X-SECTION OF	
		CS1	CS2
1	2.840	18	
2	2.845	24	
3	2.850	12	
4	2.884	24	
5	2.889	24	
6	2.894	12	
7	2.923	30	
8	2.928	24	
9	2.933	12	
10	2.957	36	
11	2.962	24	
12	2.967	12	
13	2.986	12	
14	2.991		24
15	2.997		12
16	3.010	18	
17	3.016		24
18	3.021		12
19	3.030	54	
20	3.035		24
21	3.042	84	
22	3.050	102	
23	3.057	54	
24	3.069	18	
25	3.076	6	

Fig 5.7.9

THREE-WAY GRID DOME

Configuration TW2

CAPACITY CHECK

Ratio of the internal force to the capacity of member

Load Case LB

Support Type S1

Fig 5.7.10

THREE-WAY GRID DOME

Configuration TW2

CAPACITY CHECK

Ratio of the internal force to the capacity of member

Load Case LB

Support Type S2

Fig 5.7.11

5.8. DISCUSSION OF RESULTS

Configuration TW2

The member forces, nodal deflections and support reactions of configuration TW2 of the three-way grid dome have been discussed for the two type of supports, in this section.

5.8.1 The Study of Support Type S1

(A) AXIAL FORCES

Configuration TW2

Support type S1

Figures 5.8.1.1 to 5.8.1.4 show the distribution of axial forces in the dome for the four load cases with support type S1. This distribution of force is shown in the form of coefficients recorded along lengths of the corresponding members. The value of a member force can be obtained by multiplying the coefficient of a member with the given factor on each figure. Also, the thickness representing a member is proportional to the magnitude of the force in it.

As the figures show, for all load cases, the stress distribution in the dome is almost uniform except for the members around the supports which are translationally constrained, where the compressive stress is increased rapidly. So, those members have to be designed separately.

The overall axial forces in this configuration are larger than those in configuration TW1.

The tensile forces are limited to the area near the supports. The maximum tensile force for none of the load

case is more than 50% of the maximum compressive force. The maximum force is 520 kN for the load case LB.

THREE-WAY GRID DOME

Configuration TW2

AXIAL FORCE COEFFICIENTS

Support Type S1

Load Case LA

Factor = 4.23 kN

Fig 5.8.1.1

THREE-WAY GRID DOME

Configuration TW2

AXIAL FORCE COEFFICIENTS

Support Type S1

Load Case LC

Factor = 2.59 kN

Fig 5.8.1.3

THREE-WAY GRID DOME

Configuration TW2

AXIAL FORCE COEFFICIENTS

Support Type S1

Load Case LD

Factor = 4.94 kN

Fig 5.8.1.4

(B) DEFLECTIONS

Configuration TW2

Support type S1

The deflections are represented by contour lines and also, in the form of dots, as displayed in Figs 5.8.1.5 to 5.8.1.8.

The nodal deflections in configuration TW2 are larger than those in configuration TW1, though they are still small with respect to the diameter of the dome.

The maximum deflection is at the nodes next to vertical restrained supports, for load cases LB, LC and LD. The maximum deflection is 41.5 mm under load cases LB and LD.

As the figures show the nodes near the fully constrained supports have lifts of maximum by 46%, 33%, 37% and 30% of the maximum downward deflection, for load cases LA, LB, LC and LD.

DEFLECTION COEFFICIENT
CONTOUR LINES

LEGEND
 Vertical Constraint
 Complete Translational Constraint

NODAL DEFLECTION
COEFFICIENTS

LEGEND
 Vertical Constraint
 Complete Translational Constraint

THREE-WAY GRID DOME

Configuration TW2

DEFLECTION COEFFICIENTS AND SUPPORT ARRANGEMENT

Support Type S1

Load Case LA

Factor = .355 mm

Fig 5.8.1.5

DEFLECTION COEFFICIENT
CONTOUR LINES

NODAL DEFLECTION
COEFFICIENTS

LEGEND
Vertical Constraint
Complete Translational Constraint

Support Type S1
Load Case LB
Factor = .415 mm

LEGEND
Vertical Constraint
Complete Translational Constraint

DEFLECTION COEFFICIENTS AND SUPPORT ARRANGEMENT

Fig 5.8.1.6

DEFLECTION COEFFICIENT
CONTOUR LINES

LEGEND
Vertical Constraint
Complete Translational Constraint

THREE-WAY GRID DOME
Configuration TW2

DEFLECTION COEFFICIENTS AND SUPPORT ARRANGEMENT

Support Type S1
Load Case LC
Factor = .220 mm

NODAL DEFLECTION
COEFFICIENTS

LEGEND
Vertical Constraint
Complete Translational Constraint

Fig 5.8.1.7

DEFLECTION COEFFICIENT
CONTOUR LINES

LEGEND
 Vertical Constraint ●
 Complete Translational Constraint ○

THREE-WAY GRID DOME
Configuration TW2

DEFLECTION COEFFICIENTS AND SUPPORT ARRANGEMENT

Support Type S1
 Load Case LD
 Factor = .415 mm

NODAL DEFLECTION
COEFFICIENTS

LEGEND
 Vertical Constraint □
 Complete Translational Constraint ■

Fig 5.8.1.8

(C) SUPPORT REACTIONS

Configuration TW2

Support type S1

The vertical and horizontal reactions in the dome for the four load cases are displayed in Figs 5.8.1.9 to 5.8.1.12.

As the figures show the vertical reactions at the fully translational supports are about 22 to 27 times more than the maximum vertical reactions for the other support nodes.

The nodes next to the translationally constrained points have small negative reactions.

The maximum reaction is 535 kN under the load case LB. The respective maximum reactions are 466, 275 and 513 kN for load cases LA, LC and LD.

The horizontal reactions on the vertically restrained supports are zero. This is due to the allowance of free horizontal movements at these points. The horizontal reactions in the complete translationally restrained supports are reasonably high. The respective maximum horizontal reaction are 545, 626, 321 and 597 kN for load cases LA, LB, LC and LD.

The distribution of reactions at various support points in case of boundary condition S1 also reveals the reason behind significantly large forces in the members next to fully constrained points.

THREE-WAY GRID DOME

Configuration TW2

SUPPORT REACTIONS

Support Type S1

Load Case LA

Unit = kN

Fig 5.8.1.9

Fig 5.8.1.10

HORIZONTAL
REACTIONS

VERTICAL
REACTIONS

THREE-WAY GRID DOME

Configuration TW2

SUPPORT REACTIONS

Support Type S1

Load Case LC

Unit = kN

Fig 5.8.1.11

THREE-WAY GRID DOME
Configuration TW2

SUPPORT REACTIONS
Support Type S1

Load Case LD
Unit = kN

Fig 5.8.1.12

5.8.2 The Study of Support Type S2

(A) AXIAL FORCES

Configuration TW2

Support type S2

The distribution of axial forces in the configuration TW2 of the three-way grid dome, with support type S2 are shown in Figs 5.8.2.1 to 5.8.2.4.

The figures show that all the members are carrying compressive axial forces under the four load cases. The stress distribution is almost uniform. The axial forces in the members between the two consecutive support nodes are zero.

The application of load case LB and LD, because of the high intensity of snow load on one side of the structure, produces unsymmetrical stress distributions. However, the forces in the dome under load case LD are generally smaller than those under load case LB.

The member forces for load case LC, which is a combination of dead and wind loads are smaller than the other three load cases.

The maximum axial forces for load case LA, LB, LC and LD are 62, 102, 41 and 92 kN.

THREE-WAY GRID DOME

Configuration TW2

AXIAL FORCE COEFFICIENTS

Support Type S2

Load Case LA

Factor = .62 kN

Fig 5.8.2.1

THREE-WAY GRID DOME

Configuration TW2

AXIAL FORCE COEFFICIENTS

Support Type S2

Load Case LB

Factor = 1.02 kN

Fig 5.8.2.2

THREE-WAY GRID DOME

Configuration TW2

AXIAL FORCE COEFFICIENTS

Support Type S2

Load Case LC

Factor = .41 kN

Fig 5.8.2.3

THREE-WAY GRID DOME

Configuration TW2

AXIAL FORCE COEFFICIENTS

Support Type S2

Load Case LD

Factor = .92 kN

Fig 5.8.2.1

(B) DEFLECTIONS

Configuration TW2

Support type S2

Figures 5.8.2.5 to 5.8.2.8 show the deflection diagrams for four load cases with supports type S2.

The maximum deflection is 23.1 mm, under load case LA.

The dome under load case LB lifts vertically, at the apex, as much as 11% of the maximum downward deflection.

The maximum deflections for load case LA and LC are at the apex of the dome. However, the maximum deflections for load cases LB and LD, are on the side with high intensity of snow load.

The maximum deflections for load cases LB, LC and LD is 20.6, 13.1 and 20.9 mm.

DEFLECTION COEFFICIENT
CONTOUR LINES

LEGEND

Vertical Constraint
Complete Translational Constraint

THREE-WAY GRID DOME

Configuration TW2

DEFLECTION COEFFICIENTS AND SUPPORT ARRANGEMENT
Support Type S2

Load Case LA
Factor = .231 mm

Fig 5.8.2.5

NODAL DEFLECTION
COEFFICIENTS

LEGEND

Vertical Constraint
Complete Translational Constraint

THREE-WAY GRID DOME

Configuration TW2

DEFLECTION COEFFICIENT
CONTOUR LINES

DEFLECTION COEFFICIENTS AND SUPPORT ARRANGEMENT

Support Type S2

Load Case LB

Factor = .206 mm

LEGEND

Vertical Constraint

Complete Translational Constraint

NODAL DEFLECTION
COEFFICIENTS

LEGEND

Vertical Constraint

Complete Translational Constraint

Fig 5.8.2.6

THREE-WAY GRID DOME

Configuration TW2

DEFLECTION COEFFICIENT
CONTOUR LINES

DEFLECTION COEFFICIENTS AND SUPPORT ARRANGEMENT

Support Type S2

Load Case LC

Factor = .131 mm

Fig 5.8.2.7

NODAL DEFLECTION
COEFFICIENTS

LEGEND

Vertical Constraint

Complete Translational Constraint

LEGEND

Vertical Constraint

Complete Translational Constraint

(C) SUPPORT REACTIONS

Configuration TW2

Support type S2

Figures 5.8.2.9 to 5.8.2.12 show the vertical and horizontal reactions for the four load cases.

The figures show that all the vertical reactions are positive under the four load cases. The vertical and horizontal reactions are almost uniform.

Load case LA produced symmetrical reactions. The reactions for load case LC are smaller than those of the other load cases.

The reaction on one side of the dome under load cases LB and LD are larger than those on the other side. This is due to the unsymmetrical loading.

Fig 5.8.2.10

HORIZONTAL
REACTIONS

VERTICAL
REACTIONS

THREE-WAY GRID DOME

Configuration TW2

SUPPORT REACTIONS

Support Type S2

Load Case LC

Unit = kN

Fig 5.8.2.11

5.9 CONCLUDING DISCUSSION

In the previous sections, member forces, nodal deflections and support reactions of the dome for the two types of configurations with two types of supports have been discussed. This section summarizes the conclusion drawn above and discusses the salient points.

The maximum axial forces and maximum vertical displacement in both the configurations for the four load cases and two boundary conditions are recorded in Table 5.10.1 (in section 5.10). The comparison of force in the dome with two types of supports is made from Figs 5.9.1 to 5.9.8.

The deflections for the two configurations with two types of supports have been illustrated in the form of deflection curves for the four load cases, Figs 5.9.9 and 5.9.10.

The stress distribution in the dome shows that most of the members are carrying compressive axial forces, whilst the extent of tensile axial forces is limited to the area near the supports. Furthermore, the maximum tensile force for any load case is not more than 67% of the maximum compressive forces.

As the Table 5.10.1 shows with support type S1 the maximum axial forces in configuration TW2 is increasing 20% to 27%, for different load cases, from those in configuration TW1. However, for support type S2, the maximum axial forces in both configurations are almost the same.

The reduction in deflection in the dome, with support type S1, for configuration TW1 compared with configuration TW2, varies from 17% to 38%, for different load cases.

The maximum deflections for support type S2 in configuration TW1 are almost smaller than those in configuration TW2.

For both configurations with the support type S1, the compressive axial forces are found to increase rapidly as they approach the supports which have complete translational constraint. Furthermore, tensile forces are found to be dominant in the members near the supports having only vertical constraints.

However, the stress distribution for rest of the members in the dome is almost uniform and much smaller than the members near the supports.

For support type S2, the concentration of forces in the members near the supports is relatively less severe, and the resulting stress distribution in this case is almost uniform. The maximum axial forces for support type S2 is only 26% of those for boundary condition S1, Table 5.10.1.

The dominance of member forces near the supports for support type S1, is the direct result of the lateral displacements at the vertical restraint points. Consequently, the axial forces in the members connecting two consecutive complete translational constraints for support type S2, are zero.

In both configurations the application of load case LA, which is the combination of dead and imposed loads, produces symmetrical stress distributions.

In load case LB, because of the high intensity of snow loading on one side of the structure, the forces in the members are larger than those of the other side. The maximum axial forces on one side of the dome is 30% larger than the forces on the other side of the dome.

The influence of the two boundary conditions on the stress distribution in the dome for the other two load cases is not significantly different to the first two cases.

However, both the member forces and resulting nodal deflections for load case LC are significantly smaller than those for the other three load cases.

The behaviour of the dome under load case LD does not differ significantly from that of load case LB.

The domes are subjected to the maximum deflection under load case LA, with the exception of configuration TW2 with support type S1, where the maximum deflections is under load LB.

The dome with support type S1 lifts vertically near the fully constrained points by maximum 11.5 and 16.3 mm for configurations TW1 and TW2. The maximum lift in the dome with support type S2 is 6.0 mm at the apex of the dome under load case LB, for configuration TW2.

The comparisons of deflections in both configurations, for four load cases through the symmetrical diameter, (with respect to each load case), have been illustrated in Figs 5.9.9 and 5.9.10 for configurations TW1 and TW2, respectively. In each case, the deflections are obtained from the nodes lying on the symmetrical diameter.

The reduction in deflections in the dome with support type S2 compared with support type S1 varies from 38% to 50% for different load cases, (see Fig 5.9.9).

Support type S2

LEGEND
● Vertical Constraint
■ Complete Translational Constraint

Support type S1

LEGEND
— Compression
- - - Tension

THREE-WAY GRID DOME

Configuration TW1

AXIAL FORCE COEFFICIENTS

Load Case LA
Factor = 3.10 kN

Fig 5.9.1

Support type S2

LEGEND

- Vertical Constraint
- Complete Translational Constraint

Configuration TW1

Support type S1

AXIAL FORCE COEFFICIENTS

LEGEND

- Compression
- - - Tension

Load Case LB

Factor = 3.97 kN

Fig 5.9.2

Support type S2

- LEGEND
- Vertical Constraint
 - Complete Translational Constraint

Support type S1

- LEGEND
- Compression
 - - - Tension

THREE-WAY GRID DOME
Configuration TWI

AXIAL FORCE COEFFICIENTS
Load Case LC
Factor = 2.06 kN

Fig 5.9.3

Support type S2

LEGEND

- Vertical Constraint
- Complete Translational Constraint

Support type S1

LEGEND

- Compression
- - - Tension

THREE-WAY GRID DOME

Configuration TW1

AXIAL FORCE COEFFICIENTS

Load Case LD
Factor = 3.81 kN

Fig 5.9.4

Support type S2

LEGEND

● Vertical Constraint
■ Complete Translational Constraint

Support type S1

LEGEND

— Compression
- - - - Tension

THREE-WAY GRID DOME

Configuration TW2

AXIAL FORCE COEFFICIENTS

Load Case LA
Factor = 4.23 kN

Fig 5.9.5

Fig 5.9.6

Support type S2

LEGEND

- Vertical Constraint
- Complete Translational Constraint

Support type S1

LEGEND

- Compression
- - - Tension

THREE-WAY GRID DOME

Configuration TW2

AXIAL FORCE COEFFICIENTS

Load Case LC
Factor = 2.59 kN

Fig 5.9.7

THREE-WAY GRID DOME

Configuration TW2

Support type S2

AXIAL FORCE COEFFICIENTS

Load Case LD
Factor = 4.94 kN

LEGEND

- Vertical Constraint
- Complete Translational Constraint

Support type S1

LEGEND

- Compression
- - - Tension

Fig 5.9.8

THREE-WAY GRID DOME

Configuration TW1

DISTANCE m : From extreme left hand

COMPARISON OF DEFLECTIONS FOR VARIOUS LOAD CASES WITH
SUPPORT TYPE S1

DISTANCE m : From extreme left hand

COMPARISON OF DEFLECTIONS FOR VARIOUS LOAD CASES WITH
SUPPORT TYPE S2

Fig 5.9.9

THREE-WAY GRID DOME Configuration TV2

DISTANCE m : From extreme left hand

COMPARISON OF DEFLECTIONS FOR VARIOUS LOAD CASES WITH
SUPPORT TYPE S1

DISTANCE m : From extreme left hand

COMPARISON OF DEFLECTIONS FOR VARIOUS LOAD CASES WITH
SUPPORT TYPE S2

Fig 5.9.10

5.10 CONCLUSIONS

The maximum axial forces and maximum vertical displacements in both configurations for the four load cases and two boundary conditions are tabulated in Table 5.10.1.

THREE-WAY GRID DOME

Load Case	Configuration TW1				Configuration TW2			
	Support Type S1		Support Type S2		Support Type S1		Support Type S2	
	Maximum AXIAL FORCE kN	Maximum DEFLECTION mm	Maximum AXIAL FORCE kN	Maximum DEFLECTION mm	Maximum AXIAL FORCE kN	Maximum DEFLECTION mm	Maximum AXIAL FORCE kN	Maximum DEFLECTION mm
LA	-310	29.5	-59	18.3	-123	35.5	-62	23.1
LB	-397	25.6	-79	12.9	-520	11.5	-102	20.6
LC	-206	16.9	-11	10.3	-259	22.0	-11	13.1
LD	-381	25.5	-80	13.6	-191	11.5	-92	20.3
Weight	105.4	N/m ²	96.0	N/m ²	102.2	N/m ²	80.2	N/m ²

COMPARISON OF STRESS DISTRIBUTION AND DEFLECTION

Table 5.10.1

From the stress distributions, nodal deflections and support reactions, the following points can be concluded:

- 1- The configuration TW1 shows a more rigid behaviour than that of configuration TW2. That is to say, the larger height to diameter ratio results in a stiffer dome.
- 2- The support arrangement type S2 results in a relatively uniform stress distribution and increases the rigidity of the dome significantly as compared with support type S1.
- 3- The member axial forces for the unsymmetrical snow load are found to be critical.
- 4- The maximum deflection in the dome occurred under load

case LA, except for configuration TW2 with support type S1, where the maximum deflection is under load cases LB and LD.

5- In both configurations, with two types of supports and various load cases the maximum deflections are significantly small.

6- In both configurations, with support type S1, the vertical and horizontal support reactions for fully constrained supports are considerably high.

7- The weight per square metre is much the same for both configurations with support type S1. However, the weight per square metre for configuration TW2 with support type S2 is considerably less than that for configuration TW1.

6

COMPARATIVE
STUDIES

6.1 INTRODUCTION

In the previous chapters, three types of braced domes are investigated. An attempt has been made in this chapter to compare the results of the investigation. The three types of bracing arrangement with two types of height to diameter ratio, are described below.

- (A) Types of pattern:
 - 1 Geodesic dome
 - 2 Schwedler dome
 - 3 Three-way grid dome
- (B) Types of height to diameter ratios:
 - 1 One third (Configuration 1)
 - 2 One fifth (Configuration 2)
- (C) Boundary conditions:
 - 1 Support type S1
 - 2 Support type S2
- (D) Load cases:
 - 1 Dead load and imposed load LA
 - 2 Dead load and unsymmetric snow load LB
 - 3 Dead load and wind load LC
 - 4 Dead load, snow load and wind load LD

A total of 48 analyses were carried out.

6.2 COMPARISON OF GEOMETRIC PROPERTIES

To compare the geometric properties of the domes, the diameter, radius, area in plan and surface, total length of members, number of members and nodes, number of different lengths of members, maximum and minimum of member lengths of the domes are recorded in Table 6.2.1. Furthermore, the total load of each dome and number of boundary nodes of the domes are also recorded in this Table.

DETAILS OF DOMES

PARTICULARS		GEODESIC DOMES		SCHWEDLER DOMES		THREE-WAY GRID DOMES	
		GD1	GD2	SD1	SD2	TW1	TW2
Diameter m		50	50	50	50	50	50
Radius m		27.95	36.41	27.08	36.25	27.08	36.25
Plan Area m2		1835	1670	1987	1963	1755	1670
Surface Area m2		2416	1884	2823	2270	2365	1882
Total Length m		2596	2286	3131	2805	2531	2260
No. of Members		775	775	870	870	756	756
No. of Nodes		276	276	307	307	271	271
No. of Member Types		27	43	17	18	47	25
Member Length m	Max	3.69	3.20	1.75	1.37	3.68	3.08
	Min	2.64	2.25	2.15	1.96	2.94	2.84
Load LA kN		3573	3059	3966	3621	3430	3061
Load LB kN		3811	3201	4311	4020	3664	3212
Load LC kN		2223	1786	2490	2109	2163	1787
Load LD kN		3736	3140	4182	3869	3609	3149
No. of Supports		50	50	48	48	54	54

Table 6.2.1

Despite the fact that the diameters of the domes are equal, the plan areas are not equal. Schwedler dome covers a larger area than the other two. This is due to the shape of the geodesic and three-way grid domes whose boundary nodes are not lying on a circle. For the same reason the number of members and nodes for Schwedler dome are more than the others.

The number of various member lengths for Schwedler dome is less than the others, though the difference between maximum and minimum member lengths for the Schwedler dome is more than the other two types.

The difference between maximum and minimum member lengths, of configuration TW2 of the three-way grid dome is only 0.24 m, and this is an advantage of this dome being composed of almost identical member lengths.

6.3 DESIGN AND DEAD WEIGHTS

The design of the dome in each case is optimized by choosing the required member sizes according to the magnitude of forces. For convenience in construction, the number of different cross-sections for a dome is kept to four.

The size of the tubular members for domes with support type S1 varies between 76.1 to 139.7 mm in diameter, with the thickness varying between 3.2 to 8.0 mm.

The steel tubes forming the bracing of the dome with support type S2 have an outer diameter of 76.1 mm. The wall thicknesses of the tubes vary between 3.2 to 4.0 mm. This is true with the exception of the Schwedler dome. In this

dome the size of members for configuration SD1 have an outside diameter of 76.1 mm, and the wall thicknesses of 3.2, 4.0 and 5.0 mm. The steel tubes for configuration SD2 of the Schwedler dome with support type S2, vary between 76.1 and 114.3 mm in diameter, having thickness of 3.2 to 3.6 mm.

The weight of each dome with the two support types are recorded in Table 6.3.1. As this Table shows, configuration SD2 of Schwedler dome is the heaviest, and configuration TW2 of the three-way grid dome is the lightest.

COMPARISON OF WEIGHT

	GEODESIC DOMES		SCHWEDLER DOMES		THREE-WAY GRID DOMES	
	GD1	GD2	SD1	SD2	TW1	TW2
Support Type S1						
Weight kN/m ²	91.1	106.2	115.8	121.1	105.4	102.2
Support Type S2						
Weight kN/m ²	87.9	85.7	114.7	97.6	96.0	80.2

Table 6.3.1

6.4 DOME PATTERNS

An ideal prefabricated system would be a structure consisting of identical elements jointed together by simple connectors, the same for all the joints. In such a case, the elements and connectors could be mass-produced with considerable economy. The geodesic and three-way grid domes are exceptionally good in this respect and allow full advantage to be taken of prefabrication, since the variation in length of their component members is quite small, particularly for small spans and shallow domes. This results in a regular network and leads to substantially uniform stressing of all members of the dome under the applied loading.

However, both the subdivisions i.e. geodesic and three-way grid domes, also have a disadvantage: in practice, the geodesic geometry near the base has to be modified if the structure has to rest on a horizontal base ring. If this happens, then the joints along the base ring have to be adjusted as well as the length of the infilling members in the lower parts of the dome.

Experience shows that for the large, clear spans required for public assembly buildings, steel Schwedler domes provide a solution combining the economy of material with that of cost, Ref 2. Since these domes can be prefabricated and speedily erected on site with little scaffolding, therefore, the cost of construction is low. Such a dome requires only a small central tower to provide temporary support for the upper ends of the ribbed units, before these are interconnected at the common apex during erection.

6.5 AXIAL FORCES

The member forces are obtained from pin-connected analysis of the geodesic, Schwedler and three-way grid domes for four load cases with two types of supports. For each dome, two height to diameter ratios are considered. The member forces are presented previously and are discussed below.

The stress distributions in all the domes show that most of the members are carrying compressive axial forces, whilst the extent of tensile axial forces is limited to the area near the supports. Furthermore, the maximum tensile force for any load case is not more than 67% of the maximum compressive force in the case of three-way grid dome. Tensile forces are relatively less in the other domes.

The maximum compressive and tensile forces in both the configurations of each dome for the four load cases and with two boundary conditions are recorded in Table 6.5.1.

The stress distributions in the domes for all load cases, with both support types are almost uniform. This is true with the exception of members near the translationally constrained nodes with support type S1, where the member forces have increased rapidly. Particularly, the compressive forces in the members next to these supports are considerably larger than anywhere else. Furthermore, the tensile forces are generally in the members in the two or three outer rings near the vertically constrained nodes.

COMPARISON OF AXIAL FORCES

				GEODESIC DOMES		SCHWEDLER DOMES		THREE-WAY GRID DOMES	
				GD1	GD2	SD1	SD2	TW1	TW2
Support Type S1	maximum Compressive AXIAL FORCE kN	Load Cases	LA	397	191	370	603	310	123
			LB	501	598	181	716	397	520
			LC	267	300	228	355	206	259
			LD	173	568	111	691	381	191
	maximum Tensile AXIAL FORCE kN	Load Cases	LA	226	212	178	211	167	207
			LB	276	275	212	291	206	239
			LC	150	111	123	116	138	122
			LD	251	261	212	283	190	222
Support Type S2	maximum Compressive AXIAL FORCE kN	Load Cases	LA	75	76	75	83	59	62
			LB	95	100	95	111	79	102
			LC	51	47	57	53	41	41
			LD	85	86	91	100	80	92
	maximum Tensile AXIAL FORCE kN	Load Cases	LA	12	0	17	0	11	0
			LB	35	0	12	0	26	0
			LC	25	0	11	0	16	0
			LD	32	0	37	0	25	0

Table 6.5.1

The overall axial forces in configurations 2 (with relatively small height to diameter ratios) are larger than those in configurations 1.

As Table 6.5.1 shows, in configurations 2 all members of domes are carrying compressive axial forces, under the four load cases with support type S2.

In each dome, the maximum force is the largest under load case LB as compared with that for the other load cases.

The application of load case LA, which is a combination of dead and imposed loads, produces symmetrical stress distribution.

The maximum axial forces on one side of the domes, under the load cases LB and LD, are 30% larger than the forces on the other side, because of the unsymmetrical snow loading.

The member forces for load case LC, which is a combination of dead and wind loads, are significantly smaller than those for the other load cases.

The maximum force is 746 kN for the load case LB in the case of configuration SD2 of the Schwedler dome with support type S1.

6.6 DEFLECTIONS

The maximum vertical displacements of the domes in both the configurations for the four load cases and two boundary conditions are tabulated in Table 6.6.1.

COMPARISON OF NODAL DEFLECTIONS

				GEODESIC DOMES		SCHWEDLER DOMES		THREE-WAY GRID DOMES	
				GD1	GD2	SD1	SD2	TW1	TW2
Support Type S1	maximum Downward DEFLECTION mm	Load Cases	LA	37.7	17.6	23.9	31.8	29.5	35.5
			LB	29.5	12.5	25.3	11.3	25.6	11.5
			LC	22.8	27.6	13.8	21.6	16.9	22.0
			LD	29.5	39.2	21.2	12.3	25.5	11.5
	maximum Upward DEFLECTION mm	Load Cases	LA	11.3	18.6	6.7	13.6	10.6	16.3
			LB	12.1	14.9	7.1	12.0	11.5	12.9
			LC	6.8	10.8	3.2	8.0	5.2	9.5
			LD	11.2	14.1	6.3	10.6	10.5	12.5
Support Type S2	maximum Downward DEFLECTION mm	Load Cases	LA	26.8	29.5	17.1	21.0	18.3	23.1
			LB	16.7	19.3	17.3	25.0	12.9	20.6
			LC	16.3	17.1	9.5	13.7	10.3	13.1
			LD	18.3	17.3	16.7	21.6	13.6	20.3
	maximum Upward DEFLECTION mm	Load Cases	LA	2.3	0	2.7	1.1	1.7	0
			LB	2.2	1.0	2.3	11.3	1.7	6.0
			LC	1.6	0	1.6	0.8	1.1	0
			LD	2.2	0	2.5	5.2	1.5	0

Table 6.6.1

The deflections in configurations 2 (i.e. relatively shallower) are larger than those in configurations 1, though they are still small with respect to diameter of the domes. It follows that the domes in general are rather stiff.

With support type S1 for the domes, the nodes next to fully constrained points lift vertically, under the four load cases. However, the upward deflections are small and are not significant. In the configuration 1 of the domes with support type S2 for all the load cases the nodes next to the support nodes have slight upward deflections. This is true with the exception of load cases LC and LD, where the nodes only at the windward and leeward edges lift vertically on the second bottom ring.

The maximum deflections in the geodesic and three-way grid domes, for load cases LA and LC are on the apex of the dome. However, the maximum deflections for load cases LB and LD, are on the side with high intensity of snow load.

The maximum deflection for all the load cases is on the third ring from the apex, for configuration SD1 of the Schwedler dome. In configuration SD2 of the Schwedler dome, the maximum deflection is on the third ring from the apex for load case LA. However, for the other load cases, the maximum deflection is on the third and fourth ring from the boundary.

All the configurations 2 of the domes, with support type S2, lift vertically on the apex, under load case LB.

COMPARATIVE STUDIES

6.7 SUPPORT REACTIONS

The maximum vertical and horizontal support reactions of the domes, in both the configurations for the four load cases and two boundary conditions are tabulated in Table 6.7.1.

COMPARISON OF SUPPORT REACTIONS

				GEODESIC DOMES		SCHWEDLER DOMES		THREE-WAY GRID DOMES	
				GD1	GD2	SD1	SD2	TW1	TW2
Support Type S1	maximum Vertical SUPPORT REACTION kN	Load Cases	LA	390	166	303	385	105	166
			LB	487	542	395	180	505	535
			LC	218	275	185	227	251	275
			LD	111	501	360	111	166	513
	maximum Horizontal SUPPORT REACTION kN	Load Cases	LA	221	546	118	136	205	515
			LB	281	630	184	511	257	626
			LC	176	315	77	256	130	321
			LD	255	587	166	500	236	597
Support Type S2	maximum Vertical SUPPORT REACTION kN	Load Cases	LA	80	66	101	95	78	67
			LB	102	80	130	128	95	75
			LC	58	41	80	62	54	41
			LD	95	78	131	121	95	71
	maximum Horizontal SUPPORT REACTION kN	Load Cases	LA	53	87	19	101	53	88
			LB	66	105	67	138	63	100
			LC	36	51	36	61	33	53
			LD	61	98	61	129	61	96

Table 6.7.1

The vertical reactions for all the domes are directed upward with the exception of three-way grid dome with support type S1. In three-way grid and the configuration GD2 of geodesic domes, the nodes next to the fully constrained points have a small negative reactions (downward) for all the load cases.

The horizontal reactions on all the support points are directed inward. It follows that the dome is under compressive stresses, which is obvious from the dominance of compressive forces in most of the members.

The horizontal reactions in configurations 2 are larger than those in configurations 1. So, configurations 1 are stiffer than configurations 2.

The magnitude of the horizontal reactions in configurations 2 are generally larger than the vertical reactions. The opposite is true for configurations 1. This can be attributed to the relatively shallow depth of configurations 2.

The support reactions increase rapidly as they approach the translationally constrained nodes.

The horizontal reactions of the vertically restraint points are zero. This is due to the allowance of free horizontal movements at these points. The horizontal reactions on the fully constrained supports are considerably high.

The distribution of reactions at various support points in case of boundary condition S1 also reveals the reason behind significantly large forces in the members next to fully constrained joints.

Load case LA produced symmetrical reactions. The reactions

for load case LC are smaller than those for the other load cases.

The reaction on one side of the dome under load cases LB and LD are larger than those on the other side. This is due to the unsymmetrical loading.

6.8 CONCLUDING REMARKS

In the previous sections, member forces, nodal deflections and support reactions of the domes for the two type of configurations with two type of supports have been discussed. This section summarizes the conclusion drawn above and discusses the salient points.

The maximum axial forces and maximum vertical displacements in both configurations of the domes for the four load cases and two boundary conditions are recorded in Table 6.8.1.

The configuration 1, which has a relatively greater rise, deflects less than the configuration 2, despite the fact that the loading in the four cases are comparatively larger. Similarly, the forces in configurations 1 are considerably smaller than the others. Furthermore, the horizontal reactions in configuration 1 are significantly smaller than those in configuration 2. It follows that the rigidity of the structure increases with the increase of the structural height.

The stress distributions in all the domes show that most of the members are carrying compressive axial forces, whilst the extent of tensile axial forces is limited to the areas near the supports.

The stress distribution in the domes for all load cases, with both the support types are almost uniform. This is true with the exception of members near the translationally constrained nodes with support type S1, where the member forces have increased rapidly. Particularly, the compressive forces in the members next to these support nodes are considerably larger than anywhere else.

COMPARISON OF RESULTS

			GEODESIC DOMES		SCHWEDLER DOMES		THREE-WAY GRID DOMES		
			GD1	GD2	SD1	SD2	TW1	TW2	
Support Type S1	maximum Compressive AXIAL FORCE kN	Load Cases	LA	397	494	370	603	310	423
			LB	501	598	481	746	397	520
			LC	267	300	228	355	206	259
			LD	473	568	441	691	381	494
	maximum Tensile AXIAL FORCE kN	Load Cases	LA	226	242	178	241	167	207
			LB	276	275	212	291	206	239
			LC	150	144	123	146	138	122
			LD	251	261	212	283	190	222
	maximum Downward DEFLECTION mm	Load Cases	LA	37.7	47.6	23.9	34.8	29.5	35.5
			LB	29.5	42.5	25.3	44.3	25.6	41.5
			LC	22.8	27.6	13.8	21.6	16.9	22.0
			LD	29.5	39.2	24.2	42.3	25.5	41.5
	maximum Upward DEFLECTION mm	Load Cases	LA	11.3	18.6	6.7	13.6	10.6	16.3
			LB	12.1	14.9	7.1	12.0	11.5	12.9
			LC	6.8	10.8	3.2	8.0	5.2	9.5
			LD	11.2	14.1	6.3	10.6	10.5	12.5
	Weight N/m2			91.4	106.2	115.8	121.1	105.4	102.2
Support Type S2	maximum Compressive AXIAL FORCE kN	Load Cases	LA	75	76	75	83	59	62
			LB	95	100	95	114	79	102
			LC	54	47	57	53	44	41
			LD	85	86	94	100	80	92
	maximum Tensile AXIAL FORCE kN	Load Cases	LA	42	0	47	0	44	0
			LB	35	0	42	0	26	0
			LC	25	0	11	0	16	0
			LD	32	0	37	0	25	0
	maximum Downward DEFLECTION mm	Load Cases	LA	26.8	29.5	17.1	24.0	18.3	23.1
			LB	16.7	19.3	17.3	25.0	12.9	20.6
			LC	16.3	17.1	9.5	13.7	10.3	13.1
			LD	18.3	17.3	16.7	24.6	13.6	20.3
	maximum Upward DEFLECTION mm	Load Cases	LA	2.3	0	2.7	1.1	1.7	0
			LB	2.2	1.0	2.3	11.3	1.7	6.0
			LC	1.6	0	1.6	0.8	1.1	0
			LD	2.2	0	2.5	5.2	1.5	0
	Weight N/m2			87.9	85.7	114.7	97.6	96.0	80.2

Table 6.8.1

COMPARATIVE STUDIES

The dominance of member forces near the supports for support type S1, is the direct result of the lateral displacements at the vertically restraint points.

With support type S1 of the domes, the nodes next to fully constrained points lift vertically, under the four load cases. However, the upward deflections are small and are not significant. In configuration 1 of the domes, with support type S2 for all the load cases the nodes next to the support nodes have a slight upward deflections. This is true with the exception of load cases LC and LD, where the nodes only at the windward and leeward edges lift vertically on the second bottom ring.

The horizontal reactions on all the support points are directed inward. It follows that the dome is under compressive stresses, which is obvious from the dominance of compressive forces in most of the members.

The horizontal reactions in configuration 2 are generally larger than the vertical reactions. The opposite is true for configuration 1. This can be attributed to the relatively shallow depth of configuration 2.

In both the configurations the application of load case LA, which is the combination of dead and imposed loads, produces symmetrical stress distributions, nodal deflections and support reactions.

In load case LB, because of the high intensity of snow loading on one side of the structure, the forces in the members, deflections and support reactions are larger than those of the other side.

The member forces, nodal deflections and reactions for load

case LC are significantly smaller than those for the other three load cases.

The behaviour of the domes under load case LD does not differ significantly from that of load case LB.

REFERENCES

- 1 Du Chateau, S., Domes: their form, function and architecture, Chapter 21. In: Makowski, Z.S., ed. "ANALYSIS, DESIGN AND CONSTRUCTION OF BRACED DOMES", London: Granada Publishing 1984.
- 2 Makowski, Z.S., A history of the development of domes and a review of recent achievements world-wide. Chapter 1. In: Makowski, Z.S., ed. "ANALYSIS, DESIGN AND CONSTRUCTION OF BRACED DOMES", London: Granada Publishing 1984.
- 3 Walker, H.B., Design and construction of braced domes, Chapter 15. In: Makowski, Z.S., ed. "ANALYSIS, DESIGN AND CONSTRUCTION OF BRACED DOMES", London: Granada Publishing 1984.
- 4 Matsushita, F., Diamond domes systems. Chapter 17. In: Makowski, Z.S., ed. "ANALYSIS, DESIGN AND CONSTRUCTION OF BRACED DOMES", London: Granada Publishing 1984.
- 5 Kolosowski, J., An economic method for the subdivision of braced spherical domes with some recommendations for their design. Chapter 12. In: Makowski, Z.S., ed. "ANALYSIS, DESIGN AND CONSTRUCTION OF BRACED DOMES", London: Granada Publishing 1984.
- 6 Nooshin, H., "FORMEX CONFIGURATION PROCESSING IN STRUCTURAL ENGINEERING", London: Elsevier Applied Science Publishers 1984.

- 7 Yassaee, M.H., A formex approach to finite element mesh generation. Ph.D. thesis, University of Surrey, 1986.
- 8 Sanchez Alvarez, J.S., Formex formulation of braced domes. Chapter 6. In: Makowski, Z.S., ed. "ANALYSIS, DESIGN AND CONSTRUCTION OF BRACED DOMES", London: Granada Publishing 1984.
- 9 Baker, S., A comparison of the codes of practice used in different countries for the determination of wind loads on domes. Chapter 11. In: Makowski, Z.S., ed. "ANALYSIS, DESIGN AND CONSTRUCTION OF BRACED DOMES", London: Granada Publishing 1984.
- 10 Makowski, Z.S., Preface. In: Makowski, Z.S., ed. "ANALYSIS, DESIGN AND CONSTRUCTION OF BRACED DOMES", London: Granada Publishing 1984.
- 11 Nooshin, H., Rudiments of matrix structural analysis. Department of Civil Engineering, University of Surrey.
- 12 Robinson, S., A general program for the static linear elastic analysis of skeletal structures. Chapter 3. In: Makowski, Z.S., ed. "ANALYSIS, DESIGN AND CONSTRUCTION OF BRACED DOMES", London: Granada Publishing 1984.
- 13 Orlandi, A., Some recent realizations of a geodesic domes in Italy. Chapter 23. In: Makowski, Z.S., ed. "ANALYSIS, DESIGN AND CONSTRUCTION OF BRACED DOMES", London: Granada Publishing 1984.

- 14 Elliott, A.W., Triodetic domes.
Chapter 25. In: Makowski, Z.S., ed.
"ANALYSIS, DESIGN AND CONSTRUCTION OF BRACED DOMES",
London: Granada Publishing 1984.
- 15 Motro, R., Review of the development of geodesic
domes. Chapter 13. In: Makowski, Z.S., ed.
"ANALYSIS, DESIGN AND CONSTRUCTION OF BRACED DOMES",
London: Granada Publishing 1984.
- 16 Sanchez Alvarez, J.S., Formex processing of symmetric
structural systems. Paper 2.5. In: Nooshin, H.,
"THIRD INTERNATIONAL CONFERENCE ON SPACE STRUCTURES"
Proceeding of the Third International Conference on
Space Structures,
University of Surrey, Guildford, UK, 1984.
London: Elsevier applied science publishers 1984.
- 17 Makowski, Z.S., "STEEL SPACE STRUCTURES"
London: Michael Joseph, 1963.