All rights reserved

INFORMATION TO ALL USERS

The quality of this reproduction is dependent upon the quality of the copy submitted.

In the unlikely event that the author did not send a complete manuscript and there are missing pages, these will be noted. Also, if material had to be removed, a note will indicate the deletion.

Published by ProQuest LLC (2017). Copyright of the Dissertation is held by the Author.

All rights reserved.

This work is protected against unauthorized copying under Title 17, United States Code
Microform Edition © ProQuest LLC.

ProQuest LLC.
789 East Eisenhower Parkway
P.O. Box 1346
Ann Arbor, MI 48106 – 1346

Regulations for Higher Degrees: Copyright

Preamble

Dissemination of knowledge is one of the objects of the University. Therefore Members of the University and others who submit theses/dissertations for higher degrees are expected to relinquish to the University certain rights of reproduction and distribution.

Moreover it is recognised that applicants owe a duty to their Departments of study, the Academic Staff and sponsoring bodies for their respective contributions to the research. Within the limits of these requirements, the author's copyright is safeguarded.

Regulations

1. When submitting a thesis/dissertation for the purposes of a higher degree the applicant shall sign an irrevocable authority in prescribed form appointing the Librarian his attorney with the right to reproduce the thesis/dissertation by photocopy or in microfilm and to distribute copies to those institutions or persons who in the Librarian's opinion require them for academic (as distinct from commercial) purposes.
2. The Librarian in consultation with the appropriate Department of study or sponsoring body shall have the right to refuse to provide copies, or to impose such conditions as he thinks fit on the provision of copies, with the object of safeguarding the applicant's copyright and the interests of the University and the sponsoring body.
3. These Regulations are subject to requirements of any body under whose sponsorship the research project giving rise to the thesis/dissertation is carried on.

1220128 (5912012)

KIRK,D/ HEATING OF FO

THE HEATING OF FOODSTUFFS IN A MICROWAVE OVEN

DAVID KIRK BSc. AIFST.

<u>CONTENTS</u>	<u>Page</u>
<u>SUMMARY</u>	3
<u>1. INTRODUCTION</u>	4
<u>2. LITERATURE SURVEY</u>	9
2.1 The development of microwave heating	10
2.2 The nature of electromagnetic radiation	16
2.3 The dielectric properties of materials	19
2.4 Power absorption and temperature rise	32
2.5 Microwave equipment	38
2.6 Methods of measuring the energy distribution in a resonant cavity	44
Tables 2.1 to 2.9	48-54
Figures 2.1 to 2.17	55-67
<u>3. EXPERIMENTAL</u>	68
3.1 Details of the microwave oven used in the experiments	69
3.2 Energy distribution in the oven cavity	71
3.3 Total power absorption by water and simple foods	84
3.4 Measurement of the absorption co-efficient	95
3.5 Temperature distribution in solids of high water content	109
Tables 3.1 to 3.27	115-135
Figures 3.1 to 3.34	136-164
<u>4. SIMULATION OF THE TEMPERATURE PROFILE</u>	164
4.1 Introduction	165
4.2 Semi-infinite solid with microwave radiation normal to the surface	167
4.3 Infinite slab with radiation normal to both surfaces	173
4.4 Heat transfer	174
4.5 Simulation for materials other than water	181
4.6 Results of the simulation	186
4.7 Comparison of simulated and experimental temperature profiles	188
Tables 4.1 to 4.8	195-200
Figures 4.1 to 4.25	201-218

	<u>Page</u>
<u>5. DISCUSSION OF RESULTS</u>	219
5.1 Discussion of results	222
5.2 Recommendations of further work	229
<u>6. CONCLUSIONS</u>	231
6.1 Energy distribution in the cavity	232
6.2 Total power absorption	233
6.3 Temperature profile	234
REFERENCES	236
APPENDICES	249
ACKNOWLEDGEMENTS	267

SUMMARY

A catering microwave oven was used to investigate the microwave heating of foodstuffs. The oven used for the experimental work, a Philips 1.2 kW model, operated at a frequency of 2450 MHz and the energy applicator was in the form of a resonant cavity.

Heat generated in food in a microwave resonator is caused by an interaction between "lossy" components of the food and the electrical field of the microwave radiation. The heating effect depends upon the characteristics of both the resonator and the food. The experimental work was designed to investigate factors affecting this heating effect.

The total power absorbed by food in a microwave oven is dependent upon its chemical composition and its geometry. It was found that power absorption increased with volume up to a maximum value, above which power absorption was independent of volume. Power absorption was also affected by the geometry of the food but it was not a function of the food's dielectric properties.

Heat which is dissipated in the food, as a result of power absorption, is not uniformly distributed throughout the food. The distribution of heat in solid foods was investigated by measuring temperature profiles in slabs of agar after microwave heating; simple foodstuffs were also incorporated in the agar.

In order to investigate factors which affect the temperature distribution in food, resulting from microwave heating, a computer simulation of microwave heating was developed. Good agreement was obtained between the measured and simulated profiles for agar slabs, although modifications to the simulation were required for actual foodstuffs.

SECTION 1 - INTRODUCTION

1. INTRODUCTION

The origins of this research project lie in a survey, by the Department of Hotel and Catering Management of the University of Surrey (Kirk, 1971), which comprised of a number of interviews with caterers, food manufacturers supplying the catering industry and catering equipment manufacturers and was designed to highlight current and future problem areas connected with food preparation and service in the catering industry. A number of these areas were identified and from these possible research topics were suggested. These are summarised in Appendix I.

Of the problem areas identified in the survey, several arise from the use of microwave ovens in catering establishments. The applications of these ovens, by caterers, can be divided into three main areas: the thawing of frozen foods; the reheating of chilled pre-cooked foods; and the cooking of raw foods. The majority of practical catering applications are in the first two of these areas (see section 2.1.3).

Most of the problem areas in the use of microwave ovens, as highlighted by the survey, involved either the thawing of frozen foods or the reheating of chilled foods. Microwave ovens are often sold on the basis of their ability to rapidly thaw and reheat frozen foods. In practice this requires considerable skill, if cold spots in the food are to be avoided which, apart from any aesthetic considerations, could constitute a possible food poisoning risk. The ice spots are caused by the difference in dielectric properties between ice and water. Water heats up much more rapidly than ice, so that the liquid phase can reach boiling point before the ice has thawed. A solution to the problem lies in two areas: the design of the microwave applicator and microwave frequency can have a considerable effect on the suitability of an oven for thawing; also, the

formulation, size, shape and packaging of the food influence the results. Caterers who frequently use microwave ovens for the thawing and reheating of frozen foods learn, by experience, the correct method of reheating a particular food.

The use of microwave ovens for reheating cooked chilled foods forms the largest single catering application. Microwave ovens are finding widespread application in pubs and snack bars, as part of a 'fast food' service; the National Catering Inquiry on 'Food in Pubs' (1970) indicated that about 6% of pubs use a microwave oven. Microwave ovens are also proving of value as part of an integrated vending service for feeding night and shift workers in industrial catering. A report by the Industrial Society (1972) showed that there was an increase, from 23% in 1970 to 27% in 1972, in the number of industrial caterers who use a microwave/vending system to provide meals for their nightstaff.

With most conventional forms of heating, internal temperature rise is due to conductive heat transfer from the surface; microwaves are unique in that the heat is generated internally. It is often assumed that, because of this internal heat generation, the temperature throughout the food is even: this is often quoted in the oven manufacturers advertising and trade literature:-

"This heat is not just on the outside of the food but throughout the food. Cooking is taking place on the sides, top and inside. It is cooking all at once, rather than taking time for the heat to penetrate as does the dry heat method."

- Amana Radarange, Iowa, U.S.A.

"Heat is generated right inside the food and the whole portion is heated simultaneously."

- Husqvarna Ltd., Stansted, Essex.

"This action rubs the food molecules together, causing heat which is evenly distributed throughout the food."

- Teleton Electro (U.K.), Chelmsford.

"(microwave energy) - cooks inside and out simultaneously."

- Dysona, Wokingham, Berkshire.

Caterers using microwave ovens soon learn that careful control over food size, positioning on the plate and positioning in the oven is required, if uniform heating is to be achieved. Non-uniformity in the rate of heating can be caused by three different factors:

1. non-uniformity in the energy distribution in the cavity;
2. the effect of dielectric properties and geometry of the food on the total power absorption;
3. temperature variations in the food prior to heating.

These causes of non-uniformity of heating have been investigated and the results are shown in Section 3 of this thesis. Many methods have been described in the literature for assessing the uniformity of energy distribution in a microwave oven (section 2.6). Several of these methods have been compared, as described in section 3.2. The following section reports on an investigation of the effect of the samples' volume, geometry and composition on its energy absorption.

The temperature distribution in a food, following a period of microwave heating, was investigated in two ways. Measurements

were made of the absorption co-efficient (which controls the rate of power absorption in the food) and of the temperature profile in a number of simple foodstuffs (sections 3.4. and 3.5 respectively). A theoretically calculated temperature profile was also prepared, incorporating a temperature dependant absorption co-efficient and internal and surface heat transfer; this is described in Section 4, which also contains a comparison of the experimental and simulated temperature profiles (section 4.7).

A discussion of the results and their implications for the use of microwave ovens in a catering situation is given in section 5; this section also includes a number of possible improvements to the simulation together with a number of suggestions for further research, which could yield valuable information. Section 6 summarises the important findings of the research.

All tables and diagrams referred to in the text are located at the end of the relevant section.

SECTION 2 - LITERATURE SURVEY

2. LITERATURE SURVEY

2.1. THE DEVELOPMENT OF MICROWAVE HEATING

2.1.1. Historical Introduction

Until the theoretical work of Maxwell (1865) there had been no understanding of the link between the various electromagnetic phenomena and light rays. Maxwell elucidated a set of equations connecting the known features of electrical and magnetic fields; one solution of these equations predicted the existence of an electromagnetic field in the form of a time periodic wave. This wave was found to have the same velocity of propagation as that of light. Thus Maxwell's equations postulated the possibility of having a continuum of electromagnetic waves, of varying frequency and wavelength, all having the same velocity as light.

Maxwell's theories were not confirmed experimentally until 20 years later; in 1888 Hertz was able, for the first time, to generate low frequency radio waves. These waves were found to have all the properties predicted by Maxwell.

The heating effect of these waves on certain substances, including biological tissues, was soon discovered. D'Arsonval (1893) showed that 10 KHz. radiation could be used to heat body tissue; tissue heating by radio frequency waves has since become a routine technique in physiotherapy. There was also experimental work on the use of these waves to destroy bacteria and insects.

As the sophistication of electronic equipment increased so did the availability of high frequency generators at high power levels. ~~Continuous microwave~~ ^{Radio frequency} generators, operating at up to 30 MHz., became commercially available during the 1930's. The use of microwave frequencies for radar led to the rapid development of equipment. The cavity magnetron, operating at 3000 MHz.,

became available during the late 1940's; this meant that microwave energy could be used for medical and industrial applications (Roberts and Cooke, 1952).

2.1.2. Food processing applications

Commercial application of microwave heating was hindered by the large size and poor reliability of the generators (Moore, 1968). During the years between 1940 and 1966 there was a great deal of experimental work on applications, but little in the way of full scale commercial application. The experimental work included many food processing applications: e.g. dehydration, blanching, thawing, the destruction of mould spores, pasteurisation of bread (Tape, 1969), the destruction of weevils in flour, and the pasteurisation of milk and beer (Brown, et al 1947).

During the period from 1965-1970 the cost of high power generating devices fell (Shelton, 1969); this was accompanied by increased reliability. Even allowing for these factors, the use of microwave heating as part of the process involves high capital expenditure, compared with more conventional heat processing methods. Most feasible commercial applications are economic because of the unique characteristics of microwaves, leading to some advantage over conventional processing methods eg. increase in yield, reduction in processing time etc. (Jeppson, 1964)

In conventional heating processes, heat is applied to the surface of the food, either by convection or radiation, and internal heating is due to conduction heat transfer from the surface to the inside of the food. Radio frequency heating is unique, because of the way that the waves are converted into heat actually inside the object which is being heated, (internal heating can also be achieved by Joulian heating using dc and low frequency currents). Some examples of commercial applications of microwave heating are given below.

1. In package sterilization of cakes: the shelf life of cakes can be increased from 10 days to 20 days, by the use of a microwave

process after packaging. A 25 KW plant operating at 896 MHz, is used by Cadbury Bros. Ltd. (Evans and Taylor, 1967).

2. Microwave proofing of doughnuts: by using microwave energy, it is possible to reduce the proofing time of doughnuts, from 30 to 2½ mins. (Schiffman et.al., 1971) The equipment works on a frequency of 2450 MHz.

3. Pasta dehydration: a pilot scale plant has been developed for the production of a fast rehydrating pasta (Maurer et.al., 1972). The process uses two, 25 kW heaters, operating at 915 MHz. The pasta can be dehydrated in about a twentieth of the time required for a conventional process and the pasta rehydrates in half the conventional time.

4. Finish drying of potato crisps: this represents the largest single application of microwaves in food processing (O'Meara, 1968). The process allows the use of potatoes with a higher sugar content than could normally be used for crisp manufacture. It also extends the life of the frying oil and increases the shelf life of the product. The microwave processor is used as a finish drier, reducing the moisture content of the crisp from 8 to 2%. The process uses a frequency of 896-915 MHz.

5. Continuous poultry cooking: the combined use of steam and microwave energy leads to a reduced cooking time and a 3% yield improvement, compared with conventional processes, using steam alone or hot water (May, 1969). Commercial applications of this process use a frequency of 2450 MHz.

2.1.3. Catering applications

The first commercial microwave oven was developed by Dr. R. Spencer, of the Raytheon Company (Decareau, 1968a). This oven was powered by a magnetron which had been initially developed for radar. Early ovens were large and cumbersome; they needed high current power supplies, because of the poor electrical efficiency; and they needed a supply of cooling water. Ovens are now available which run off 13 amp. electricity supplies and are cooled by air; for a given power output they are much smaller and lighter.

For catering applications the most common type of oven is the box type resonant cavity (see section 2.4); continuous ovens are available where a larger throughput is required (Copson and Decareau, 1968).

Microwave ovens are restricted to a limited number of catering applications:- cooking a restricted range of foods, reheating pre-cooked chilled foods and thawing frozen foods (Napleton, 1967). The use of microwave ovens to cook foods is limited to those foods which require a short moist cooking process; thus a microwave oven can be used to poach fish, to boil vegetables such as cabbage, cauliflower and peas and for the production of 'steamed' sponges. Normal microwave ovens produce no surface browning and can not therefore be used to produce roast, baked, fried or grilled type foods. These must either be done using a two stage process (pre-searing followed by microwave heating), or using a combination oven such as the Micro-aire (Mealsteam U.K. Ltd.), which combines microwave heating with forced air convection. This oven combines rapid surface colouring with quick internal cooking.

Microwave ovens are ideal for heating most pre-cooked foods; these may either be items which have been pre-cooked and cooled on the catering premises, or bought in convenience foods.

Moisture control is often critical with these products. Thus moist foods may require some form of covering to prevent dehydration.

Thawing, using a microwave oven, is normally done as a two stage process; if thawing is carried out too rapidly there is the danger of residual ice crystals in the otherwise thawed food. This is a particular problem with foods which are being heated straight from the frozen state. Heating in two stages allows equilibration of the temperature, which avoids run away heating and the danger of residual ice crystals.

Microwave ovens, although providing a very fast method of heating foods, cannot deal with large volumes of foods. Because of the high capital cost of an oven, it is not usually economic to have the large number of ovens which would be needed to supply large numbers of meals over a short period of time. Napleton (1967) lists the most common applications of microwave ovens in catering; these are:-

1. Central kitchen systems. Microwave ovens can be used to reheat meals which have been prepared in a central kitchen at a number of diverse service points. An example of this is the system used in the Nacka hospital in Sweden; with this system, food, prepared in the normal manner is packed in air tight plastic bags, and reheated at the service point, using microwave ovens. A trial in an American hospital showed that considerable savings in labour could be made by reheating food, prepared in advance, in a microwave oven prior to service (Decareau, 1969).
2. Standby in restaurant and canteen. Microwave ovens are very effective for reheating food quickly to order to compensate for unexpected orders or for floor service in hotels.
3. As shown by the National Catering Inquiry (1970), Microwave ovens are commonly used in pubs and snack bars for 'fast food' service; there is also a potential market for microwave ovens in 'take away' food service.

4. Many airlines use prepared foods, which are reheated to order; one way of carrying out this reheating is by the use of microwave ovens.

2.2. THE NATURE OF ELECTROMAGNETIC RADIATION

Electromagnetic radiation is a form of energy which has a periodic wave motion; the periodic properties are associated with electric and magnetic fields. In its simplest form the electric and magnetic fields and the direction of radiation are all mutually perpendicular, as shown in fig.2.1. (Harvey, 1963).

When propagating through free space, there is no loss of energy from an electromagnetic wave and the instantaneous electric and magnetic waves are related by the expressions:

$$E_{zt} = E_0 \cdot [j(\omega t - \beta z)] \dots\dots\dots (2.1)$$

$$H_{zt} = H_0 \cdot [j(\omega t - \beta z)] \dots\dots\dots (2.2)$$

where E_{zt} is the instantaneous value of the electric field, at a time t , and at a distance z from the reference point E_0 .

E_0 is the maximum value of the field,

β is known as the phase constant,

ω is the angular frequency of the wave ($=2\pi f$, where f is the frequency in Hertz).

(A full list of all symbols used in this text is given in Appendix II)

When an electromagnetic wave propagates through a physical medium, there is an attenuation of the wave; this can be accounted for in equations 2.1 and 2.2 by the addition of an attenuation coefficient, α which allows for this exponential attenuation of the wave. (see fig.2.2).

$$E_{zt} = E_0 \exp. [j(\omega t - \beta z) - \alpha \cdot z] \dots\dots\dots (2.3)$$

α and β can be combined in the form of a complex constant γ , the propagation co-efficient.

$$\gamma = \alpha + j\beta = j\omega(\epsilon^* \mu^*)^{1/2} \dots\dots\dots (2.4)$$

The attenuation co-efficient represents the exponential attenuation, with distance, of the field:

$$E_z = E_0 \exp. (-\alpha.z) \dots\dots\dots (2.5)$$

The energy which is lost from the wave as a result of this attenuation is dissipated in the propagating medium as heat.

2.2.2. The electromagnetic spectrum

In any propagating media, the wavelength and frequency of an electromagnetic wave are inversely proportional and are related by the velocity of propagation. In free space the velocity of propagation is equal to the speed of light:

$$\lambda.f = c \dots\dots\dots (2.6)$$

Waves of different frequencies have different properties and applications, as shown in Table 2.1. There is no precise division of these waves into different categories; the classification in the table is based on the different applications of the wave.

The I.S.M. frequencies are those frequencies which may be used for industrial, scientific and medical uses. They are based on international agreements (International Telecommunication and Radio Conference, Geneva, 1959). If any non-ISM frequencies are used for commercial applications, they must be enclosed in a radiation proof area, to prevent interference with telecommunication transmissions.

The heating of a material by electromagnetic radiation may utilise one of three possible techniques: Induction heating utilises the magnetic component of a wave to heat ferromagnetic

materials; dielectric heating is the heating of a 'lossy dielectric' (see section 2.3.1) placed between two electrodes, which are connected to a source of high frequency electrical oscillation; microwave heating is the heating of a lossy dielectric placed in an electromagnetic field.

Induction heating is only applicable to ferromagnetic materials or to materials which can be heated by contact with a ferromagnetic material. The frequencies used are in the region of 1-10 KHz (Nicholls 1971)

With dielectric heating, the material which is to be heated is placed between two electrodes between which the electromagnetic field is developed. The most commonly used frequency for dielectric heating is 27 MHz; this is because of the wide bandwidth which can be used at this frequency (Cox, 1971).

Of the ISM frequencies in the microwave region of the electromagnetic spectrum, those of 900 MHz and 2450 MHz are most commonly used. Of these two, the latter is the more common in terms of the number of commercial units in operation (Meredith 1971). Microwave and dielectric heating both utilise the power loss from an electromagnetic wave when it is propagated through a polar material (see section 2.3); the difference between the two techniques is the method by which the field is generated at radio and microwave frequencies and in the different methods of application. The heating effect in a material is a function of its dielectric properties.

2.3. THE DIELECTRIC PROPERTIES OF MATERIALS

2.3.1. Theory

2.3.1.1 Permittivity and permeability.

As indicated in section 2.2 the generation of heat in a material placed in an electromagnetic field depends on the attenuation of energy by that material. The attenuation co-efficient of a material is itself a function of its electrical and magnetic properties (equation 2.4).

The permittivity (or dielectric constant) is usually measured relative to the permittivity of free space.

$$K = \frac{\epsilon}{\epsilon_0} \dots\dots\dots (2.7)$$

ϵ is the absolute value of the permittivity,

ϵ_0 is the absolute permittivity of free space,

and K is the relative permittivity.

The permittivity of a material is a measure of its ability to store charge, or its polarisability. In a perfect dielectric all of this polarisation charge is completely reversible. In a practical dielectric not all of this charge will be released from the material when the electrical field is removed. This loss can be represented, either as a conductivity (although it is not solely made up of the motion of ionic particles), or as the imaginary part of a complex permittivity:

$$\epsilon^* = (\epsilon' - j\epsilon'') \dots\dots\dots (2.8)$$

or in terms of the relative permittivity:

$$K^* = (K' - jK'') \dots\dots\dots (2.9)$$

where K' is the real part of the relative permittivity and K'' is the imaginary part.

K' is a measure of the reversible charge holding capacity of the material. The imaginary part K'' is a measure of the losses in the dielectric; it is often expressed as a conductivity and is made up from a number of factors which are discussed in the next section.

$$\sigma = \omega \cdot K'' \cdot \epsilon_0 \dots\dots\dots (2.10)$$

where σ is the conductivity in mhos/m. ϵ_0 is the permittivity of free space and has a value of 0.88×10^{-12} F/m. The ratio of K'' to K' is often referred to as the "lossiness" or "loss tangent" of a material (Copson, 1962).

The magnetic properties of a material are described in terms of its permeability; as with permittivity this is usually expressed relative to the free space value.

$$\mu_r = \frac{\mu}{\mu_0} \dots\dots\dots (2.11)$$

For all materials (including foodstuffs), other than ferromagnetics, the relative permeability is very close to unity and magnetic effects can be ignored.

2.3.1.2. Polarisation.

The polarisation of material, in the presence of an electric field, is due to the existence of charged dipoles. These dipoles can either be permanent, because of the presence of an asymmetrically charged molecule, or they can be induced. There are four basic types of polarisation, as shown in fig. 2.3. (von Hippel, 1954). Each of these types of polarisation is associated with a particular group of frequencies (Püshner, 1966),

Orientational polarisation	$10^9 - 10^{14}$	H.F. and Microwaves,
Vibrational (atomic)	$10^{14} - 10^{17}$	Infra red
Electronic	$10^{17} - 10^{20}$	Visible and Ultra violet.

Because of these changes with frequency, it follows that the dielectric properties of a material will be frequency dependant; the change of relative permittivity with frequency is known as dispersion.

2.3.1.3 Dispersion.

There are two types of dispersion, each associated with a different form of polarisation. Resonance dispersion is associated with changes in electronic and atomic polarisation (see Fig.2.4); relaxation dispersion is caused by changes in the orientational polarisation of polar molecules (see Fig.2.5). Any atom, molecule or mixture will exhibit dispersion at characteristic frequencies (identified by the resonant frequency f_r). Thus any atom or molecule will have a number of dispersion regions over the whole of the electromagnetic spectrum, as indicated in Fig.2.6 (Hartshorn, 1949).

2.3.1.4 Relaxation time.

Each polarisation, and its resultant dispersion is characterised by a relaxation time T_r . This constant is related to the time taken for the build up and decay of the polarisation effect. The inverse of the relaxation time gives the angular frequency at the centre point of the dispersion region the resonant frequency f_r .

$$T_r = \frac{1}{2 \cdot \pi \cdot f_r} = \frac{1}{\omega_r} \dots\dots\dots (2.12)$$

At this frequency, the material will be at its most lossy, as indicated by the maximum value of K'' (Copson, 1962).

The relationship between the complex relative permittivity and the relaxation time was originally developed by Debye (1929). The original relationship could be used to satisfactorily predict The behaviour of polar substances in non-polar solvents, but

it was necessary to modify these relationships to explain the behaviour of polar solvents. Using these modifications, the following relationships have been developed (Lane and Saxton, 1952a):-

$$K' = K_0 + \frac{(K_s - K_0)}{1 + \omega^2 \cdot \tau_r^2} \dots\dots\dots (2.13)$$

$$K'' = \frac{\omega \cdot \tau_r \cdot (K_s - K_0)}{1 + \omega^2 \cdot \tau_r^2} \dots\dots\dots (2.14)$$

K_s is the static (low frequency) value of the relative permittivity,

K_0 is the high frequency value.

For a molecule or atom having a single relaxation time, the relationship between K' and K'' is in the form of a semi-circle (Cole, 1941), as shown in Fig.2.7. For an atom or molecule having a spread of relaxation times the semi-circle will have skewed geometry.

2.3.2. The dielectric properties of water.

The dielectric properties of water can be described in terms of its complex relative permittivity K^* ; this is both frequency and temperature dependant. The imaginary part of the permittivity K'' is a measure of the loss component of the polarisation current of the material. The magnitude of the ratio of K''/K' , is known as the loss tangent or 'lossiness'.

Lossiness depends on dispersion phenomena; therefore at any given frequency K'' is made up from a number of different factors. At microwave frequencies, K'' for water is made up of two factors, ionic conductivity and dipole polarisation.

The ionic conductivity of water is of the order of 1.1×10^{-2} $\mu\text{mho/m.}$; in terms of its contribution to the relative imaginary

permittivity this is 0.08.
(using equation 2.10).

Equations 2.13 and 2.4 can be used to predict the dielectric properties of water, from a knowledge of the relaxation time of the water molecule. Saxton (1952) showed that these equations were valid for water, over a temperature range of 0 to 50 °C. A value of 4.9 was used for K_0 , the high frequency value of the relative permittivity, and this was taken to be temperature independent. K_s and T_r are temperature dependant. Values for these two constants can be obtained from measurements of the dielectric properties at various frequencies (Lane and Saxton, 1952); tabulated values are given in Table 2.2. Hasted (1961) showed that the static dielectric constant could be calculated from the expression:

$$K_s = (87.74) - (0.4)t + (9.398 \times 10^{-4})t^2 + (1.41 \times 10^{-6})t^3 \quad \dots\dots\dots (2.15)$$

where t is the temperature in °C.

The relaxation time T_r is related to the viscous drag on a molecule; Debye (1929.) calculated the drag on a molecule caused by its rotation in a viscous fluid, using a relationship of the form:

$$T_r = \frac{4 \cdot \pi \cdot \eta \cdot a^3}{k \cdot T} \quad \dots\dots\dots (2.16)$$

where T is the absolute temperature,
 a is the molecular radius,
and η is the macroscopic viscosity.

Saxton (1952) showed that the ratio T_r/η is a constant over the temperature range 0 to 50 °C. The relationship between temperature and viscosity is exponential; from this it follows that the relationship between temperature and T_r will also be exponential.

Von Hippel (1954) gives figures for water of K' and K''/K' , over the range of temperatures 0 to 95 °C. The results for water are shown in figs. 2.8 and 2.9. These graphs show the dispersion region of water in relation to I.S.M. frequencies. Fig 2.8 shows the variation with frequency, at a temperature of 25 °C, while fig.2.9 shows the variation with temperature at a frequency of 3000 MHz.

Using the data given by von Hippel (1954) at various frequencies and temperatures, it is possible to calculate values of T_r and K_s over the temperature range 0 to 95 °C, using equations 2.13 and 2.14. These calculated values are shown in Table 2.3 and are compared with the literature values of Lane and Saxton (1952a) in figs. 4.2 and 4.3 in section 4.

2.3.3 Water / solid mixtures.

Van Beek (1967) gives formulae for calculating the dielectric properties of heterogeneous mixtures of two components. The static dielectric constant for a mixture of non-polar materials suspended in water is given by the relationship (Hasted, 1961);

$$K_{\text{cont}} - K_{\text{mixt}} = \frac{V}{1 - V} \cdot (K_{\text{mixt}} - K_{\text{disp}}) \cdot G \dots\dots\dots(2.17)$$

where K_{cont} is the static dielectric constant for continuous phase,

K_{mixt} is the static dielectric constant for mixture

K_{disp} is the static dielectric constant for dispersed phase,

V is the volume concentration of non-polar solid,

G is a geometric factor (1.5 for spheres, 1.6 for needles)

The reduction in conductivity due to the presence of non-polar solids in a continuous water phase can also be calculated using a relationship similar to that given in equation 2.17.

2.3.4. Electrolyte solutions

The presence of electrolytes modifies the dielectric properties of a polar solvent, such as water. Salts affect the dielectric properties in three ways:

1. they increase the ionic conductivity;
2. they cause a change in the value of K_s ;
3. they affect the relaxation time of the water molecule.

2.3.4.1 Ionic conductivity.

For salt solutions, the ionic conductivity increases, until its contribution (K'' ionic) to the imaginary relative permittivity is of the same order as that contributed by dipole relaxation (K'' dipole).

Table 2.4 gives the value of the specific conductance for solutions of sodium chloride solutions at 20 °C. These can be converted to relative permittivities, using the relationship:

$$K''_{\text{ionic}} = 60. \lambda \cdot \sigma \dots\dots\dots (2.18)$$

λ , the wavelength is in cm.,

σ , the conductivity is in Mho/cm.

(This is derived from equation 2.10)

Ionic conductivity is also temperature dependant. Schwan and Li (1953) measured the ionic conductivity of salt solutions and body tissues; the change in resistance with temperature can be expressed as:-

$$\rho_t = \rho - c.t. \dots\dots\dots (2.19)$$

The temperature co-efficient C is given by Schwan and Li as 1.3.

2.3.4.2 Static relative permittivity.

Lane and Saxton (1952b) give values for the static relative permittivity of aqueous salt solutions; these figures are shown graphically in Fig.2.10. Work done by Hasted et. al (1948) indicates that it can be calculated, for any electrolyte solution, from equation 2.20.

$$\epsilon_{sol} = \epsilon_{water} - 2. \delta . m \dots\dots\dots(2.20)$$

where m is the concentration of the electrolyte in moles/litre and δ is a constant which depends on the nature of electrolyte. Values of δ for several electrolytes are given in Table 2.5. Lane and Saxton demonstrated that equation 2.20 holds for solutions of sodium chloride in water, over the temperature range 0 to 40 °C.

2.3.4.3 Relaxation time.

The relation between relaxation time and salt concentration is shown in Fig.2.11 (Lane and Saxton 1952 b). This graph shows that the change in relaxation time with salt concentration is most pronounced at low temperatures. At 10 °C the decrease in relaxation time between water and a 3N salt solution is 24%; at 20 °C it is 23% and at 40 °C, 12%.

2.3.4.4 Calculation of the overall effect on K' and K'' .

The effect of salt content on K_s can be calculated using equation 2.20. Knowing this K' and K''_{dipole} can be calculated, using equations 2.13 and 2.14. The value of K''_{ionic} can be obtained from Table 2.4. Thus it should be possible to calculate K' and K'' (where $K'' = K''_{ionic} + K''_{dip}$. Cook 1951b) for any salt solution, up to a strength of 3 N. Von Hippel (1954) gives values

of K' and the loss tangent for salt solutions of various strengths; these are compared with calculated values at the same strength in Table 2.6.

The calculated values of K' and K'' compare well with the experimental values of von Hippel. It can be seen that for salt solutions over 0.3 M, the contribution to K'' by K''_{ionic} is very significant. The change in the value of Tr has very little effect on the value of K' , because $(\omega \cdot \text{Tr})$ is very much less than one for water, and its solutions at microwave frequencies. This means that $1 + \omega^2 \cdot \text{Tr}^2 \simeq 1$.

2.3.5 The dielectric properties of foods

The relaxation frequency of most food components, other than water, occurs below those frequencies used for microwave heating. For example the relaxation time of proteins is in the region of 10^{-7} seconds, equivalent to a frequency of 1 MHz (Roberts and Cook, 1952) and starch has a similar relaxation frequency (Abadie et al, 1953). There is some evidence that water bound to hydrophillic materials produces a separate dispersion region at a frequency of 300 MHz, intermediate between values for ice (5 KHz) and free water (19 GHz) (Schwan, 1965). This means that a food with a large bound water component will behave differently from the predicted behaviour for a mixture of a non-polar solid and water (equation 2.17). Table 2.7 gives the amount of bound water associated with some food components.

There is a discrepancy in some of these results particularly in those giving the amount of bound water associated with proteins. Thus the figure for horse methaemyoglobin quoted by Buchanan et.al (1952) is outside the range of bound water figures for protein of Schwan (1965). These differences probably occur because of different techniques used to measure this bound water.

As discussed above, the bound water can cause a shift in the relaxation time of water. Also this water is incapable of rotation and thus causes a reduction in the static relative permittivity. The value of K_s for systems containing bound water can still be calculated from equation 2.17, but in this case the bound water is included in V , the volume concentration of the non-polar dispersed phase. De Loor and Meijboom (1966) used this relationship to calculate the bound water associated with agar and milk protein. These workers found that there was very little shift in the value of T_r for these materials, indicating that the bound water did not have its own relaxation time. Their values for T_r , K_s and ionic conductivity are shown in Table 2.8 and these figures have been used to calculate K''_{ionic} , K''_{dip} and K' for water, 4% agar, 8% agar, potato, 25% starch and milk.

There are many references to the dielectric properties of food materials; it is often difficult to utilise this information because of the many different frequencies and temperatures used for these measurements. Much of the data was obtained with a particular application in view; thus there is quite a lot known about changes in dielectric properties from the frozen to the thawed state because of the interest in microwave and dielectric thawing. Similarly many measurements have been made on the effect of changes in moisture content on the dielectric properties because of the potential application of microwaves for dehydration.

One difficulty in utilising the literature data arises from the many different ways of measuring and presenting the data. Thus the lossiness may be presented as conductivity, resistivity, imaginary relative permittivity or loss tangent. In some literature sources K'' contains both the ionic and dipole losses (von Hippel, 1952), whereas in others the ionic component is excluded (Hasted et al, 1948)

Dunlap and Makower (1945) measured the dielectric properties of dehydrated carrots over a frequency range of 18kHz. to 5MHz. Morse and Revercomb (1947) studied the changes in dielectric properties (K' , $\tan\delta$ and D_1) between -15 and $+23$ °C. These measurements were made at a frequency of 1000 MHz. As part of a study of microwave diathermy, Schwan and Li (1953) obtained values of K' and resistivity for human body tissues and obtained relationships to express the effect of changes in frequency and temperature on these properties. Using frequencies of 200 kHz, 2 MHz and 20MHz, Ede and Haddow (1951) obtained measurements of conductivity, dielectric constant and loss tangent on a wide range of food materials, over a temperature range of -3 to 100 °C. Buchanan (1954) studied the effect of frequency on the dielectric properties of fatty acids and their esters; he showed that these compounds showed no dispersion over a range of 1 to 40 GHz. Bengtsson et al (1963) obtained measurements on the dielectric properties of lean beef and cod at -25 and $+10$ deg.C, over a frequency range of 10 to 200 MHz.

The oven used for the experimental work, described in Section 3, operated at a frequency of 2450 MHz; therefore any measurements made close to this frequency are of particular relevance. Information available at this frequency is summarised by Bengtsson and Risman (1970): these workers also obtained measurements of K' and K'' , for a wide range of foods, over a temperature range of -20 to $+60$ deg.C. and at a frequency of 3 GHz. Some of the data available at this frequency is summarised in Table 2.9. Bengtsson and Risman also made measurements on ham, pork, liver, cod, carrots, gravy, vegetable soup and broth; All of these measurements were made over a temperature range of -20 to $+60$ °C.

Equation 2.17 can be used to predict the effect of non-polar solids dispersed in a polar liquid. DeLoor (1966) showed that

this equation could be extended to allow for any water which is irrotationally bound to the non-polar solid. It is interesting to compare these theoretical equations with values of K' and K'' obtained experimentally for mixtures of water and carbohydrates over a wide range of moisture contents (Roebuck et al, 1972). The carbohydrates investigated include starch (potato), glucose and sucrose.

For the work on starch, these workers used both granular and gelatinised forms; the form of the results they obtained is shown in Fig.2.12. With both granular and gelatinised starch, there was a discontinuity in the results between 20 and 40% moisture. This was partly due to the fact that two methods of measurement were used, one for low solids content liquids and the other for solid samples. The discontinuity occurs for samples which cannot be satisfactorily handled by either technique. Also in this region very small changes in the moisture content caused large changes in the value of K' and K'' . Samples with less than 30% moisture had a value of K' of 6 and K'' of 0.6. Granulated starch had lower values of both K' and K'' than gelatinised starch at the same moisture content. These results were for the total K'' and these values were not split up into individual contributions of K''_{dipole} and K''_{ionic} . Because of this it is impossible to ascertain whether this deviation from the continuous one predicted from theory is caused by changes in ionic conductivity, changes in the amount of irrotationally bound water, or dielectric relaxation occurring at microwave frequencies in the bound water (Abadie et al, 1953; Ono et al. 1958)

Values obtained for water/sucrose mixtures are also shown in Fig 2.12. Here there is no discontinuity in dielectric properties, although values of K'' do not follow the gradual decline with moisture content, as indicated by equation 2.17. Here again the

value of K'' refers to the sum of both ionic and dipole losses so that the cause of this discrepancy cannot be ascertained.

From equations given in Section 2.3 it is possible to calculate the theoretical dielectric properties of a foodstuff from a knowledge of the dielectric properties of its components. Work done by Mudgett et al (1971) highlights the inherent dangers in this approach. These workers compared the values of K'' for a skim milk powder, with a simple synthetic milk powder (of similar composition to the natural milk) and with the individual components of the synthetic milk. From the values of K'' for the components they calculated the contribution of each to the synthetic milk. They then compared this value with the measured values of K'' for both the synthetic and skim milk. At a concentration of 8g/100ml. they obtained the following results:

Predicted value for synthetic milk	24
Measured value for synthetic milk	18
Measured value for skim milk	14

Upon further investigation it was found that the discrepancies were due to two main causes: one effect which caused a reduction in the value of K'' in the mixture was the effect of ion binding by the milk protein, causing a reduction in the value of K'' ionic; the other factor was a reduction in the amount of dissociation of salts in the mixture, compared with the dissociation in aqueous solution.

This work indicates that with a complex food material, a knowledge of the dielectric properties of its components is only of limited value in predicting the dielectric properties of the food.

2.4 POWER ABSORPTION AND TEMPERATURE RISE

2.4.1. Total Power Absorption

The power absorption, from an electromagnetic field, for unit volume of a material is a function of frequency, electric field strength and the dielectric properties of the material (Pushner, 1966).

$$P(\text{loss}) = \omega \cdot \epsilon_0 \cdot K'' \cdot E^2 \dots\dots\dots (2.21)$$

where E^2 is mean square electric field strength (volts / cm)

$P(\text{loss})$ is the power absorbed by the material (watts/cm³)

This energy, which is absorbed from the field, is converted into heat in the material, where it may result in a rise in temperature of the material, evaporation of a volatile component of the material and a rise in temperature of the surroundings, caused by loss of heat from the body.

The energy loss can be calculated from a knowledge of the temperature rise in the material and the amount of evaporation (for accurate results the temperature rise must be corrected for loss of heat to the surroundings).

$$\text{Energy loss} = J.(M.S.\Delta t + m.L.) \dots\dots\dots (2.22)$$

where M is the mass of material, m is the weight loss due to evaporation, S is the specific heat and L is the Latent heat of evaporation and J is the mechanical equivalent of heat in joules/calorie.

The energy loss will be in Joules.

If the heating time is τ secs, the power absorption will be:

$$P(\text{loss}) = \frac{J}{\tau} (M.S.\Delta t + m.L.) \quad (\text{watts}) \dots\dots\dots (2.23)$$

Equations 2.21 and 2.23 can be equated:

$$\Delta t = \frac{1}{M.S} \frac{(\omega \cdot \epsilon_0 \cdot K'' \cdot E^2 \cdot \tau - m \cdot L)}{J} \dots\dots\dots (2.24)$$

Thus equation 2.24 shows that the temperature rise in a material is a function of the imaginary relative permittivity, and that if all other factors are constant that there will be a linear relationship between rate of temperature rise and K'' .

In practice, this relationship is difficult to apply, because of variations in the value of the electric field (time periodic variations are not important, because equation 2.24 uses the mean square voltage). In the case of dielectric heating, where the material is placed between the plates of a capacitor, it is possible to measure the field strength. In the case of a propagating electromagnetic wave in a waveguide, the field strength at any point depends upon the mode of propagation. Thus to determine the heating effect in a unit volume of the material, it would be necessary to integrate the field within this volume. With materials of high loss factor, the field will be distorted by the material in the waveguide. With a resonant cavity, the material in the cavity forms a part of the resonating system and the nature of the material will therefore affect the amount of energy in the cavity (see Section 2.5.3).

Experiments of Van Zante (1968) highlight the difficulty of using equations of the same type as 2.24, to study the heating effect of foods in a resonant cavity. The increase in enthalpy in constant volumes of various high water content solutions, was converted to power absorption (after allowing for evaporation and heat loss to the surroundings). If equation 2.21 holds in this situation, it would be expected that the power loss would be directly proportional to the imaginary dielectric constant. Van Zante found that for 1000 ml. of solution, the greatest power

loss was in water. Other solutions (salt and simple sugars) absorbed less energy, with the salt solution (15%) absorbing least of all. Values of K'' for water and salt solutions, calculated from dielectric data of von Hippel (1954), are contrary to the findings of van Zante, salt solutions having higher values of K'' than water, at the same temperature.

2.3.2. Temperature distribution

As an electromagnetic wave penetrates through a material, the r.m.s. field strength will decrease exponentially, according to the relationship given in equation 2.5.

$$E_z = E_0 \cdot \exp (-\alpha \cdot z)$$

The power associated with an electrical field is proportional to the square of the field strength, so that power will vary with distance of penetration, decaying exponentially.

$$P_z = P_0 \cdot \exp (-2\alpha \cdot z) \dots\dots\dots (2.25)$$

The equation may also be written using an absorption co-efficient (k), where:

$$k = 2\alpha$$

Equation 2.25 then becomes:

$$P_z = P_0 \cdot \exp (-k \cdot z) \dots\dots\dots (2.26)$$

The attenuation co-efficient and the absorption co-efficient are related to the dielectric properties of the propagating medium. Solution of equation 2.4 (Section 2.2) in terms of the real and imaginary relative permittivities, gives an equation of the form (von Hippel, 1954):

$$\alpha = \frac{2\pi}{\lambda_0} \left[\frac{1}{2} K' (\sqrt{1 + \tan^2 \delta} - 1) \right]^{\frac{1}{2}} \dots\dots\dots (2.27)$$

For materials with a low loss factor, ($\tan \delta$ less than 1), Pushner (1966) gives a simplified form of this equation:

$$\alpha = \frac{\pi \cdot K''}{\lambda_0 \sqrt{K'}} \dots\dots\dots (2.28)$$

Experimental measurements have been made of the temperature distribution in a foodstuff after a microwave heating process. Van Zante (1968) demonstrated the temperature distribution in a simulated food: for this she used large agar cylinders. She also investigated the effect of bone in a joint of meat, using a core of bone meal in the agar cylinder; it was found that the heating effect was enhanced in the proximity of the bone. Decareau (1965) investigated the different temperature distribution resulting from microwave heating at 915 and 2450 MHz, and found little difference in temperature distribution at the two frequencies was obtained. In contrast, Copson (1962) states that at 915 MHz core heating results, whereas at 2450 MHz the hottest point is about one inch in from the surface. Copson's results were obtained by heating cylinders of bacteriological agar (9" high by 10" in diameter.)

Several workers have calculated the temperature distribution in material heated by microwave energy. Because of the interest in the use of microwave energy for diathermy, many of these investigations have been on human body tissue. Cook (1952) used an equation, of the same type as 2.25, to calculate the temperature rise in human tissue. For this calculation a constant value of attenuation co-efficient was used and no correction was made for other modes of heat transfer; since the tissue temperature rise was of the order of 10 °C, it was considered that these changes would be insignificant.

Schwann and Li (1956) relate the dielectric properties of skin, subcutaneous fat and muscle tissue, to the percentage of air borne radiation absorbed by a flat body surface, normal to the incident radiation. At 3000 MHz there was found to be a complex relationship between skin thickness, fat thickness and the absorption of radiation. With zero skin thickness, there was found to be 100% absorption with a fat thickness of approximately 1 cm. Absorption was less than this for both greater and lesser fat thicknesses. With a 0.2 cm layer of skin, the maximum absorption was for 0.2 cm of fat (60%), with a second maximum of 40% for a fat thickness of 2.5 cm. The complexity in the absorption of energy was explained in terms of impedance matching between source and the tissue. Certain thicknesses of skin and fat caused good matching between the source and the load, whereas with other thicknesses almost complete mis-matching occurred. These workers also investigated the distribution of this absorbed energy, between the three types of tissue, again relating it to thickness of skin and fat layer.

Guy (1971a) measured the temperature distribution in 'phantom' tissue models. These models, made to the dimensions of parts of the human body, were constructed out of non-biological materials but with the same dielectric properties as the tissue being modelled. The models were made in sections so that, immediately following the heating process, the internal temperature could be measured, using a scanning infra-red sensitive camera. These temperatures were then compared with theoretically derived temperature distributions (Guy, 1971b). By calculating the field radiating from a microwave applicator, the absorption of energy by the tissue was calculated, using the dielectric properties of human tissue. Good agreement was found between theoretical and experimentally determined temperature distributions for a wide range of applicators and model dimensions.

Ohlsson and Bengtsson (1971) simulated the temperature distribution in slabs of food material. They also illustrated the important part played by internal conduction in the heating of large volumes of food material. Internal heat generation in the food was calculated using a relationship of the type given in equation 2.26. The attenuation co-efficient was calculated from the dielectric properties of the food material measured at different temperatures (Risman and Bengtsson, 1971); a linear relationship between temperature and k was assumed (Bengtsson, 1972). From this theoretical temperature distributions for beef, salted ham and simulated meat were calculated. Convection and conduction heat transfer was calculated, using a finite difference method, using the method of Manson et al for measuring the lethality of a heat process on rectangular blocks of food material (Manson et al, 1970). The calculated temperature distributions were compared with experimentally measured values, using the same food materials. After the heating cycle had been completed, the temperature at different depths in the material was measured, using thermocouples; these temperatures were then corrected to give an estimate of the value at the end of the heating cycle. Despite limitations of both the model and the experimental results, good agreement was found.

2.5 MICROWAVE EQUIPMENT

2.5.1. Introduction

Although there are many ways of applying microwave energy to foods, all techniques use the same basic components (Copson and Decareau, 1968) These are:

1. Generation system
 - 1.1. Power supply
 - 1.2. Microwave generator
2. Applicator
 - 2.1. Transmission line
 - 2.2. Coupling devices
 - 2.3. Oven cavity
 - 2.4. Energy distribution devices
3. Operating controls
4. Energy sealing and trapping devices.

2.5.2. Generation system

The range of electronic devices available for the generation of electromagnetic radiation at microwave frequencies is reviewed by Hall (1968) and Shelton (1969). At the frequencies and power levels required for microwave heating the magnetron is the most common oscillator. The construction and operating characteristics of a magnetron are described by Püschner (1966). Although magnetrons were initially developed for use in radar applications, those used for heating applications operate under different conditions and with different constraints; for heating applications the magnetron has to be able to withstand large fluctuations in load and hence large values of reflected waves. The tolerance to varying load conditions is provided at the expense of frequency stability: this may vary by $\pm 8\text{MHz}$, but since the permitted band width at

2450 MHz is ± 50 MHz this is not important. The life of a magnetron is shortened by operation under low load conditions, as in the case of the oven being operated with an empty cavity. To minimise this damage the cavity, and its fittings (trays, mode stirrer etc.) are designed to absorb a small proportion of the energy, thus reducing the reflected wave to an acceptable level. (Schmidt, 1960)

For microwave heating, magnetrons are available with operating frequencies of 900 and 2450 MHz. The choice of frequency depends upon the dimensions of the material to be heated. At 2450 MHz the energy is quickly attenuated by a lossy material, such as a high water content food, so that with large objects (greater than 3 inches diameter) the heating effect is very uneven. At 900 MHz attenuation is less so that a greater penetration is achieved (Decareau, 1965).

2.5.3. Applicators

The generated electromagnetic wave is transmitted to the site of application using a transmission line; this may either be a waveguide or a coaxial cable. Waveguides are metal tubes of either circular or rectangular cross-section, the size of the tube being governed by the frequency in use and the mode of propagation (Dunn, 1967; Harvey, 1963). Two techniques are used for applying the energy to the material being heated: in one method the material to be heated is placed inside the waveguide (travelling wave applicator) and the energy is attenuated by the material as the energy passes down the waveguide; in the second technique the transmission line is terminated by a resonant cavity, in which the material is placed (standing wave applicator).

2.5.3.1 Travelling wave applicators.

As electromagnetic radiation passes down a waveguide, it is attenuated; the rate of attenuation depending on the

dielectric properties of the material in the waveguide. This attenuated energy will cause a rise in temperature of the material. Therefore, provided the foodstuff will fit inside the waveguide, it can be heated by passing it through the waveguide, as shown in Fig. 2.13. The water load is necessary to absorb any residual energy at the end of the waveguide; the length of the conveyor belt will be sufficient to ensure that the maximum utilisation of energy is achieved, so that little energy will reach the end of the waveguide except when the belt is not completely filled with product. Since the heating varies down the length of the waveguide, this system is only used for continuous applications. The speed of the conveyor belt can be used to control the temperature rise in the food.

Experimental methods of processing liquids have been developed; the liquid is passed down a tube (made of microwave transparent material eg. glass Teflon.) which is itself built into a waveguide (Hamid et al, 1969), as indicated in Fig.2.14.

At 915 MHz a standard waveguide will have dimensions 9.8" by 4.9", and at 2450 MHz, 3.4" by 1.7". Because of this applications of the type shown in Fig.2.15 are limited to the processing of small packages of food material. For use with wide conveyor belts, material is passed transversely through the waveguide. Commercial applications are in operation using double (Heenan, 1968) and multiple passes; these may either be of the meander (fig.2.15) or the folded waveguide type (fig.2.16). The number of passes required depends upon the degree of heat process, the speed of the conveyor belt and the lossiness of the material being processed. The height of the material on the conveyor belt depends upon the frequency of radiation being used (Meridith, 1971): the conveyor belt enters through a slot in the waveguide, and this must be restricted to prevent leakage of energy from the processor. At 915 MHz, a slot of 6" can be used without any radiation hazards, whereas at 2450 MHz, the maximum slot height is 4".

2.5.3.2 Standing wave applicator.

The dimensions of a metal walled cavity can be used to determine the resonant frequency of the cavity; at resonance the wave will be in the form of a standing wave. The presence of a standing wave in the cavity will lead to very uneven energy distribution through out the volume of the cavity. To overcome this unevenness a cavity resonator is designed to have a large number of modes of resonance - the multimode cavity principle (James et al, 1968). Resonant cavities are used for both batch and continuous heating systems.

The domestic and catering microwave ovens use a resonant cavity as the applicator, the door of the oven forming one wall of the cavity. The number and types of resonant modes in an oven cavity will depend on the operating frequency of the generator, the dimensions of the cavity, the nature of the material in the cavity, together with any specifically designed mode changing devices (Crapuchettes, 1966). Copson (1962) describes a number of these mode changing devices, designed to increase the uniformity of energy distribution in the cavity. These include mode stirrers, rotating coupling devices, paddle wheels and oscillating cavity walls. An alternative approach is to use rotating turntables to support the material being heated, thus ensuring that the material does not reside in a region of high or low energy density.

As well as affecting the distribution of energy, the material in the cavity also forms a part of the resonating system. Thus the material in the cavity will affect the impedance of the cavity and, because of this, the coupling of energy into the cavity. A microwave oven is designed to tolerate variations in load and it is tuned to give optimum coupling into a typical oven load (Crapuchettes, 1966). The effect of volume of material in the cavity on efficiency of energy absorption can

be seen in fig.2.17, (taken from work done by James et al, 1968). They showed that conversion efficiencies varied from 53% to 98% as the filling factor varied from 0.13 to 3%. (The volume of the cavity was 78 litres, so that 0.13% corresponded to a load of 100 ml and 3% to approximately 2.4 litres.)

Two systems are available for the utilisation of resonant cavities for continuous applications. The cavity may be supplied with energy from a single large generator (Goldblith, 1966), or the system can be made up from a number of 2.5 kW modules (Copson and Decareau, 1968). As well as the rectangular resonant cavity, parabolic radiators (Püschner, 1966) and resonant fields concentrated over a very small volume have been used. The latter method can be used to heat process free falling viscous liquids (Meredith, 1971) and in this way overcome the problem of scaling.

2.5.4. The safety of microwave ovens

The fail safe operation of a microwave heating device is of great importance, particularly in the case of domestic and catering ovens which are to be used by unskilled and unsupervised operators.

The thermal effects of electromagnetic radiation are well understood (Schwan, 1971); the threshold level, at which thermal effects become deleterious, occurs with radiation in excess of $100 \text{ mW} / \text{cm}^2$. At lower power levels conflicting evidence has been found, some workers saying that there are physiological and neurological changes, after exposure to radiation levels below those at which thermal effects are observed, other workers finding no evidence of these changes (Schwan, 1969).

Leakage of radiation from a microwave oven can be readily detected, with one of a wide range of power density meters (Moore et al, 1971). The Medical Research Council have issued recommended maximum levels for exposure to microwaves; for continuous exposure this level is 10 mW/cm^2 . Surveys of microwave ovens actually in use in America have shown that a high percentage of ovens exceed these levels. Surveys by Mafrici (1970) and Elder et al (1971) found that between 10 and 30% of ovens, during normal operation, exceed the level of 10 mW/cm^2 , and that this increased to over 40% at the time when the oven door was being opened.

The main cause of leakage arises from wear of the hinges and sealing surfaces, and the build up of food particles and dirt between the sealing surfaces. These dangers can be overcome by efficient design of door seals (McConnell, 1972) and by regular maintenance and cleaning (Elder et al, 1971).

2.6. METHODS OF MEASURING THE ENERGY DISTRIBUTION IN A RESONANT CAVITY

All practical methods for assessing the distribution of energy in a microwave oven cavity use the heating effect of the electrical field at a point in the cavity . The temperature rise at a point in a material placed in an electrical field is a function of the electrical field at that point, the lossiness of the material and the physical and thermal properties of the material. The field itself is dependant upon the nature and quantity of material in the cavity, and upon attenuation of the energy. Thus it is often difficult to compare the results of tests on the distribution of energy in a microwave oven, because of the effect of the method of testing upon the thing being measured.

Many methods have been described for assessing the distribution of energy in a microwave oven cavity. Most tests can be classified into one of three categories:

1. measurement of the temperature at one, or a number, of points in the cavity;
2. the production of a two dimensional heating pattern, using a media which undergoes a chemical or physical change upon heating;
3. measurement of the temperature at all points on the surface of a solid material which has been heated in the oven.

2.6.1. Temperature measurements at fixed points in the oven cavity

For this method a lossy material is distributed throughout the oven cavity, either in a regular pattern of small quantities or else as a continuous layer. Methods are available for measuring the temperature during the heating process, or for measurement after the heating cycle has finished.

Because metals disturb the heating pattern (and may also cause damage to the magnetron) thermocouples and mercury in glass thermometers cannot be used in the oven whilst it is switched on. For this reason there are only a limited number of methods available for monitoring the temperature during the actual heating process. Liquid expansion thermometers have been developed for use in microwave ovens (Copson, 1962); these use a low loss liquid, such as toluene, connected by a thin flexible tube to a manometer which is situated outside the cavity. It is difficult to produce an accurate and reliable thermometer of this type and they also have the disadvantage of a large time lag (of the order of 15 seconds). Many microwave ovens have small holes in the door which make it possible to monitor the Infra-red radiation emitting from a hot surface inside the cavity (see Section 2.6.3.).

Thermocouples can be fastened inside a large volume of material in the cavity, so that the temperature can be quickly measured, immediately the heating has finished. There is still the danger that the temperature will not be a true measurement of the energy at that point, because of distortions in the field due to a metallic object.

Any method of temperature measurement can be used once the sample has been removed from the oven, or once the oven door has been opened. The time lag between the termination of the heating cycle and the measurement of temperature is critical and correction is required to allow for the fall in temperature during this period (Sluce, 1969).

Two ways are commonly used for arranging the sample(s) in the oven. Equal volumes of a lossy material (usually water) can be arranged in a regular array in the oven, or a thin layer of a solid lossy material can be placed at a specified level in the cavity.

Of these two methods, that using an array of samples is the most common. The results may either be presented as a single dimensional graph of the distribution across a line in the oven (James et al, 1968) or as a two dimensional graph of the distribution across a particular plane in the oven. Püschner (1966) Schmidt (1960) and Copson (1962) use a 5 by 5 array of beakers. Goodall (1970) uses 16 beakers, arranged in the form of a circle. Kenyon et al. (1969) use a 4 x 4 array of beakers. All of the above methods use water as the lossy material. Several workers use foodstuffs: Van Zante (1968) uses a 3 by 3 array of beakers containing egg white; Peterson (1971) uses a 3 by 4 array of cup cakes.

When measuring the temperature distribution in a thin layer of material it is important that the material is solid, to prevent mixing by convection currents and by physical disturbances. Sluce (1969) used a 2.7% agar solution and measured the temperature at 40 positions in the oven, using thermocouples mounted in a fixed array.

2.6.2. Two-dimensional heating pattern

Any material which undergoes a physical or chemical change with temperature can be used to produce a pattern of the distribution of energy in the oven cavity; if the material has a low loss factor it must be combined with some other material with a high loss factor. The results can be used to demonstrate the location of high and low energy density areas; a number of these patterns, obtained for different heating times can be combined to give an isotherm diagram.

Schmidt (1960) described a method which uses a change of state from solid to liquid to assess the evenness of energy distribution. Tape (1969) made use of the colour change of cobalt chloride when it changes from the hydrated to the dehydrated form. Anhydrous cobalt chloride was hydrated with

water until all the crystals changed from blue to pink; these were then spread in a uniform layer on a tray. On heating this material in an experimental microwave oven, high energy density areas were indicated because of the reversal to the blue colour on dehydration. Chemical changes associated with a rise in temperature can also be used in the same manner. Wilhelm et al (1971) used the coagulation of egg white, spread in a uniform layer on a tray of the same size as the oven cavity. Using this technique, the effect of tray position in the cavity was investigated and a comparison made of several commercial microwave ovens. Peterson (1971) used the colour changes in a sponge mix on heating to investigate energy distribution.

An extension of this method is to convert the heating pattern obtained into an isothermal pattern in a material, after it has been heated in the oven. It is possible to measure the temperature of the material by measuring the infra-red radiation emitted; levels of radiation are small, so that infra-red sensitive film is not suitable. Bengtsson and Lyke (1969) used a scanning infra-red camera, mounted in front of the oven door, so that the temperature on the surface of food heated in the oven could be converted into isotherms. Guy (1971 a) used a single dimensional scanning camera to measure the temperature along a single line of the material; using this technique, the results can be obtained in the form of a graph of temperature against distance.

Table 2.1 The electromagnetic spectrum

Frequency-Hz	Designation	
0	D.C.	
10^0		
10^1	A.C. power transmission	
10^2		
10^3		
10^4	Induction heating	
10^5	LW	Radio Waves
10^6	MW	
10^7	SW	
10^8	VHF	Micro-waves
10^9	UHF	
10^{10}	SHF	
10^{11}	EHF	
		<u>ISM frequencies</u>
		13.56 MHz $\pm$ 6.78 KHz
		27.16 MHz $\pm$ 160 KHz
		40.68 MHz $\pm$ 20 KHz
		896 MHz $\pm$ 10MHz (G.B. only)
		915 MHz $\pm$ 25 MHz (not G.B.)
		2450 MHz $\pm$ 50 MHz
		5800 MHz $\pm$ 75 MHz
		22125 MHz $\pm$ 125 MHz
10^{12}	Infra red	
10^{13}		
10^{14}		
10^{15}	Visible light	
10^{16}		
10^{17}	Ultra violet	
10^{18}		
10^{19}	X-rays	
10^{20}		
10^{21}	Gamma rays	

Table 2.2. Relaxation time and static dielectric constant of water. (Lane and Saxton 1952)

$T \text{ }^{\circ}\text{C}$	K_s	$T_r \text{ (X } 10^{12})$
0	88.2	18.7
10	84.2	13.6
20	80.4	10.1
30	76.7	7.5
40	73.1	5.9
50	69.8	4.7

Table 2.3. Relaxation time and K_s , calculated from the data of von Hippel (1954)

$T \text{ }^{\circ}\text{C}$	K_s	$T_r \text{ (X } 10^{12})$
1.5	87.6	17.8
5	86.0	15.4
15	81.7	11.7
25	78.1	9.0
35	74.7	7.2
45	71.3	6.0
55	68.0	5.2
66	64.5	4.6
75	61.0	4.1
85	56.8	3.7
95	52.1	3.4

Table 2.4. Specific conductance of sodium chloride solutions

(R.C. Weast, 1972)

% Salt	Conductivity mMho/cm.	K ["] _{ionic}
1.0	16.0	11.5
2.0	30.2	21.6
3.0	44.0	31.6
4.0	57.3	41.2
5.0	70.1	50.3

Table 2.5 Values of δ for electrolytes (Hasted et al, 1948)

Electrolyte	δ
H Cl	10
Na Cl	5.5
K Cl	5.0
Na OH	10.5
Mg Cl ₂	15
Na ₂ SO ₄	11

Table 2.6 Calculated values and experimental values of K' and K'' for salt solutions

Salt content		Calculated values							Experimental values (Von Hippel 25 deg.C)	
M	%	ϕ	K'' _{ionic}	Ks	Tr	K'	K'' _{dip}	K'' _{total}	K'	K''
0.1	0.58	9.8	7.0	77	9.9	75.7	10.7	17.7	75.6	18.8
0.3	1.8	27.2	19.5	72	9.6	70.6	9.7	29.2	69.3	32.2
0.5	2.9	44.0	31.6	69	9.4	67.7	9.1	40.7	67.4	42.2

Table 2.7 Bound water associated with some food components

<u>Material</u>	<u>Bound water (g/g)</u>	<u>Reference</u>
Agar	0.8	de Loor et.al.,1966
Milk protein	0.2	" " " " "
Protein	0.2 to 0.5	Schwan, 1965
Horse methaemyoglobin	0.14	Buchanan et al,1952
Bovine serum albumin	0.23	" " " "
Egg albumin	0.18	" " " "
β lacto globulin	0.24	" " " "
lysozyme	0.23	" " " "
Gelatin	0.20	" " " "

Table 2.8 The dielectric properties of certain foods at 20 °C.

Substance (1.)	Composition Water %(1)	Ks	Shift in Conductivity Tr. (1)	mmhos/cm (1.)	K'' _{ionic} (2.)	K'' _{dip} (2.)	K'' _{total} (2.)	K' (2.)
Water	100	80	-	-	-	12.2	12.2	78.4
Agar 4%	96	73	No shift	0.8	0.6	12.4	13.0	71.2
Agar 8%	92	66	No shift	1.7	1.2	11.2	12.4	64.4
Potato	77 starch 19% protein 2%	77	slight shift	0.33	0.2	10.5	10.7	60.5
Starch + Agar	74 starch 25% agar 2%	74	slight shift	2.3	1.6	9.8	11.4	56.9
Milk	88	69	slight shift	4.1	3.0	11.7	14.7	67.2

1. Data of de Loor and Mejiboom (1966)

2. Calculated from data.

Table 2.9. Dielectric properties of foodstuffs at 3 GHz

Food	Temp (°C)	K'	K''	Reference (see page 54)
Raw lean beef	37	47.0	15.0	1
Human muscle	37	50.0	17.5	2
" "	37	45-48	13.5	3
Cooked lean beef	-20	5.0	0.65	1
" " "	-18	3.95	0.3	4
" " "	-12	4.4	0.47	4
" " "	-10	6.0	1.0	1
" " "	-7	7.3	1.27	4
" " "	+4	8.3	1.73	4
" " "	+4	37.5	14.0	1
" " "	+25	36.0	12.0	1
" " "	+25	40.0	12.0	5
" " "	+40	33.9	10.7	1
" " "	+60	32.1	10.6	1
Mashed potato	+20	65.5	22.0	1
Raw potato	+20	62.0	16.7	6
" "	+25	57-69	15.7-17.2	7
Lard	+25	2.52	0.10	1
"	+25	2.50	0.18	7
"	+49	2.59	0.14	1
"	+49	2.52	0.17	7
Corn oil	+25	2.63	0.16	1
" "	+25	2.53	0.14	8
" "	+49	2.66	0.17	1
" "	+49	2.57	0.17	8
Cooked peas	-20	4.1	0.29	1
" "	+3	64.3	22.0	1
" "	+40	58.9	13.8	1

Reference:

1. Bengtsson and Risman, 1971.
2. Cook, 1951.
3. Puschner, 1964.
4. Van Dyke et al, 1969.
5. Von Hippel, 1954.
6. De Loor and Meejiboom, 1966.
7. Pace et al, 1968 a.
8. Pace et al, 1968 b.

Fig.2.1 The relationship between fields and direction of propagation

Fig.2.2 The attenuation of an electromagnetic wave

Fig.2.3 Types of polarisation

FIELD	NO FIELD
- +	
(a) electronic polarisation

Induced dipole caused by distortion of the electron cloud.

(b) atomic polarisation

A change in the equilibrium positions of atoms in a molecule.

(c) orientational polarisation

Permanent dipoles experience a torque which tends to orientate them in the direction of the field.

(d) space charge polarisation

Macroscopic field distortions caused by the impedance of free charge carriers, either at an interface or at an electrode.

Fig.2.4 Resonance dispersion

Fig.2.5 Relaxation dispersion

Fig.2.6 Dispersion phenomena and the electromagnetic spectrum

Fig.2.7 The relationship between K' and K''

Fig.2.8 Dielectric properties of water at 25 ° C.

Fig.2.9 The dielectric properties of water at 3000 MHz.

Fig.2.10 The static relative permittivity for
aqueous solutions of sodium chloride

Fig.2.11 The relationship between T_r and salt content

Fig.2.12 The dielectric properties of water/carbohydrate mixtures
at 3000 MHz.

(a) potato starch

(b) sucrose

Fig.2.13 Schematic diagram of a travelling wave applicator

Fig.2.14 Travelling wave applicator for heat processing liquids.

Fig.2.15 Meander waveguide system (Goldblith, 1966)

Fig.2.16 Folded waveguide system (Meredith, 1971)

Fig.2.17 Energy conversion efficiency for water at 20 °C.

SECTION 3 - EXPERIMENTAL

3. EXPERIMENTAL

3.1. DETAILS OF THE MICROWAVE OVEN USED IN THE EXPERIMENTS

For the experimental work described in this Section, the oven used was a Phillips 1.2 kW model (Model number HN 1102). This oven operates at a frequency of 2450 MHz $\pm$ 25 MHz, and has a rated input of 2.8 kW.

The power consumption was measured, using a Wattmeter (Hartmann and Braun Ltd. Wembley); the oven had a standby power consumption of 300 watts and an operating consumption of 2,240 watts. The power consumption of the oven was found to be independent of the size and nature of the load in the oven.

The oven is fitted with four controls, which are:

1. Off- isolates oven from power supply;
2. On - switches oven into the standby mode;
3. Power on - activation of the heating process and initiation of the process timer;
4. Timer - allows the selection of one of a number of specified values of heating time; these are 10, 20, 30, 40, 50 secs., 1, $1\frac{1}{4}$, $1\frac{1}{2}$, $1\frac{3}{4}$, 2, $2\frac{1}{2}$, 3, 4, and 5 mins.

As well as these manually operated controls, there are a number of automatic safety devices, which ensure the fail safe operation of the oven. Thus the heating cycle is terminated if the door is opened, in the middle of a cycle. Similarly, the heating cycle cannot be initiated, if the oven door is open.

Since the timer was to be used for the subsequent experimentation, it was first of all necessary to measure its accuracy and reproducibility. By operating the timer (with a water load in the oven) and comparing the duration of the heating time for a particular timer setting, against a stop-watch, the results

shown in Table 3.1 were obtained. Each average time shown in the Table is the mean of ten measurements. The co-efficient of variation was also calculated on each set of results.

$$(\text{Co-efficient of variation} = \frac{\text{Standard Deviation}}{\text{mean}} \times 100)$$

A schematic diagram of the oven, showing the location of its main components, is given in Fig.3.1; details and dimensions of the oven cavity are shown in Fig.3.2.

3.2. ENERGY DISTRIBUTION IN THE OVEN CAVITY

3.2.1 Introduction

One of the main problems in designing a resonant cavity microwave oven is to obtain a uniform energy distribution throughout the cavity (see Section 2.5.3). In Section 2.6, Several methods have been described, for assessing the uniformity of energy distribution. As a preliminary to experimental work, it was necessary to first of all investigate the energy distribution in the oven which was to be used. The methods described in Section 2.6, fall into two categories: those using a single continuous material, which covers the whole oven cavity area and those using a number of equal size, regularly spaced containers. In the description of experimental work which follows, several methods in the first category were investigated, using: heat sensitive pigments; silica gel/cobalt chloride crystals; agar gel; and agar gel with egg albumin. For the second category of methods water was used as the lossy material contained in glass beakers and arranged in several different arrays.

3.2.2 Methods

3.2.2.1 Thermocolours.

There are many heat sensitive pigments, available in the form of powders and crayons, and covering a wide range of temperatures. For this test a 'thermocolour' was used (Headland Engineering Developments Ltd.), having a colour change, from light green to blue, at 60 °C. The pigment, available in the form of a powder, can be applied to any solid surface. The method of application is to disperse the powder in alcohol and to then 'paint' the surface with this dispersion. On evaporation of the alcohol the thermocolour is left as a thin, pale green layer on the surface and it is then ready for use.

Since the pigment is not itself lossy, it is necessary to apply it to a solid surface which becomes hot in the microwave field. Most plastics and glasses have a low loss factor (Von Hippel, 1954), but it was found that a one-eighth inch thick glass sheet heated up sufficiently in the electromagnetic field to cause a colour change in the pigment.

When a glass plate, coated with the heat sensitive pigment, was heated in the microwave oven, an irregular pattern of hot areas was produced, as indicated by the colour change of the pigment from pale green to blue. It was necessary to confirm that this colour change was due to differences in energy distribution, and not to some other factor, such as a variation in lossiness between different parts of the glass plate. To do this the glass plate was heated in the oven and the pattern recorded as shown in Fig. 3.3. To obtain a record of the pattern a photograph of the glass plate was taken; the negative could then be projected into a sheet of paper and a scale diagram produced. After the glass sheet had cooled down, and the pigment had reverted to a uniform colour, it was reheated again, for an equal period of time, but this time turned through 180 degrees from the previous position - the result obtained is shown in Fig. 3.4. If the pattern had been due to some difference in the structure of the glass, the pattern should have changed through 180 degrees; but if the pattern were due to the energy distribution in the oven, the pattern should remain the same. Reference to Figs. 3.3 and 3.4. shows that the pattern obtained was a function of position in the oven, rather than of the structure of the glass plate, implying that the pattern was a measure of the distribution of the energy in the cavity, under these particular test conditions. There were minor differences in the patterns produced in the two positions, as shown by an 'X' in the diagram; these could be caused by an irregularity, either in the thermocolour layer, or in the structure of the glass.

3.2.2.2 Silica gel crystals.

When used for dehydration purposes, silica gel crystals are combined with cobalt chloride, which indicates the hydration state of the crystals: the dehydrated gel has a bright blue colour, which, when it becomes hydrated, changes to pink. The reverse of this change, from pink to blue, can be used as an indicator of hot spots in the oven.

If hydrated silica gel is placed in the microwave oven, it becomes hot, because the water of hydration acts as a lossy dielectric. This heat causes evaporation of the water and hence a change in the colour, from pink to blue.

A tray, one half inch deep and of the same area as the oven cavity (49.5 by 26 cm.), was constructed out of $\frac{1}{8}$ " perspex. This was filled with finely ground silica gel crystals to a depth of 1 cm. In practice it was difficult to obtain a completely uniform layer of crystals. In order to determine if this variation in depth had any effect on the pattern produced, the same technique as had been used for the glass plate was employed. The heating was repeated with the tray in two different positions, allowing time for the crystals to revert to the uniform pink colour between the two heating processes. It was found that the pattern produced, relative to position in the oven, was unchanged, indicating that small non-uniformities in the depth of silica gel had no effect on the pattern produced.

3.2.2.3 Agar gel.

A gel can be made using agar and water, which contain a high percentage of water capable of rotation in an electromagnetic field. The presence of a gelling agent slows down redistribution of heat, by preventing convection heat transfer

processes. This means that if agar is moulded into a thin gel, of the same area as the oven cavity, any non-uniformity in temperature caused by unevenness of the electric field can be measured, after the agar has been removed from the oven. The temperatures were measured using thermocouples mounted in a foamed polystyrene sheet, in the form of a three by three array. The measuring instrument used did not allow simultaneous measurement of these nine thermocouples, so that temperatures had to be measured sequentially. (Fig.3.5a)

During the delay between the end of the heating process and the measurement of the temperature at the first thermocouple, heat will be lost from the surface. Although the thermocouples are mounted in foamed polystyrene, which will reduce convective heat transfer, some change in temperature will occur during the time required to measure all nine temperatures. The rate of loss of heat was measured as shown in Fig.3.5 (b). The agar was moulded in the perspex tray, which was described for the silica gel method. To ensure that the depth of the agar layer was uniform, a spirit level was used to level the tray before pouring in the 1% Ionagar (Oxoid Ltd.) Fig.3.5(b) shows the rate of cooling: there was a delay of one minute between the termination of the heating cycle and the measurement of the first temperature, after which readings were taken at 10 second intervals.

Since the actual value of the temperature at the end of the heating period does not have any special significance, it is not necessary to extrapolate all temperature readings to zero time; it is sufficient to convert all temperatures to the same time. The nine temperature measurements take a total of 16 seconds. A diagram of the position of the thermocouples is shown in Fig. 3.6. It is possible to measure each temperature twice, reversing the sequence after the first set

of measurement, as shown below.

Time (seconds)	60	62	64	66	68	70	72	74	76	78	80	82	84
Position	A1	B1	C1	A2	B2	C2	A3	B3	C3	C3	B3	A3	C2

Time (seconds)	86	88	90	92	94
Position	B2	A2	C1	B1	A1

An estimate of the temperature after 77 seconds can be obtained by averaging the two measurements taken at each position. This assumes a linear cooling curve and the maximum error would occur at position A1. Reference to Fig. 3.5.(b) shows that the temperatures after 60, 77 and 94 seconds are 69.0, 63.8, 64.0 and 59.0 °C; the estimate of the temperature after 77 seconds, using a linear interpolation of the temperatures at 60 and 94 seconds is obtained by averaging these two temperatures. In this case the average is 64.0, an error of 0.2 from the measured value of 63.8. For lower temperatures the error will be less because of the decreasing slope of the time/temperature graph. Even at its maximum value of 0.2 it is of the same order as that for the temperature measurement. Therefore, this method of converting all temperatures to a time of 77 seconds after the end of the heating process is, in this case, satisfactory as a method of converting all array temperatures to the same time datum.

For the measurements of energy distribution, two 3 by 3 arrays of thermocouples were used: one having 6 cm. spacings between thermocouples and the other 2 cm spacings; these are shown in Figs. 3.6 (a) and 3.6 (b). The 2 cm array measures variation of temperature over a small area of the oven and the oven and the 6 cm array measures the variation over a larger area of the oven.

3.2.2.4 Agar/egg white gel.

The technique described above for measuring the temperature at

fixed points, although providing quantitative information, cannot be used to provide information over the whole area of the oven, unless a very large number of thermocouples are used. By incorporating egg white in with the agar it is possible to assess the variability over the whole of the oven area.

For this experiment 1% Ionagar was used. Dried egg white (United Yeast Company Ltd.) was dissolved in water and warmed to 45 °C; this was then mixed with prepared liquid agar, also at 45 °C. After mixing, the combined egg white/agar/water was poured into the pyrex trays, described previously in this Section. Gels were prepared with egg white solid contents from 1 to 10%. The sharpest differentiation between uncoagulated and coagulated egg white was obtained at a concentration of 5%; this coagulation occurred over the temperature range of 57-59 degrees C.

3.2.2.5 Array of beakers.

One of the commonest methods for assessing the uniformity of energy distribution in the oven is to use an array of beakers (see Section 2.6). These methods, as described in the literature, use various arrays and different volumes of liquid, which in the majority of cases is water. To examine the significance of volume and spacial array, a 4 by 5 array of 100 ml of water was compared with a 3 by 2 array of 10ml of water, as shown in Fig.3.7. In both of these methods the beakers were all heated at the same time, after which the temperatures were measured sequentially and corrected to the same time value, as described for the agar sheet.

For the 4 by 5 array the water was contained in 100ml glass beakers; temperatures were measured using a mercury in glass thermometer, with an accuracy of ± 0.2 °C. This was used to

stir the sample for 5 seconds after which the temperature reading was taken. Thus it took a total of 80 seconds, to measure the temperature twice at each location. Averaging the results for each array position gave an estimate of the temperature 42 seconds from the termination of the heating process.

The 10 ml samples these were contained in plastic 15 ml sample bottles, which were fitted with polythene caps. They were mounted in a block of foamed polystyrene, which served both to locate the samples in the correct positions and also to reduce surface heat losses. The cap prevented evaporation of water from the sample. After the termination of the microwave heating, the polystyrene block, complete with sample tubes, was removed from the oven and inverted four times, to ensure thorough mixing of the water. A thermocouple, mounted in a hyperdermic needle, was used to measure the temperature in each bottle; this was done twice, reversing the sequence for the second set of measurements, as described previously. Polystyrene has a very low loss tangent (von Hippel, 1954 gives a value of 0.0003, equivalent to a K'' of 0.0029); this means that the presence of a block of polystyrene is unlikely to have any influence on the energy distribution in the cavity.

An alternative approach is to heat the beakers individually at each of the positions, with only one beaker in the oven during each heating cycle. The 4 by 5 array of beakers was used, each containing 100 ml of water, allowing direct comparison of the results. After the heating cycle had terminated the beaker was removed from the oven and stirred with a calibrated thermometer ($\pm 0.2^\circ\text{C}$); the reading on the thermometer was taken after an interval of 20 seconds from the end of the heating cycle.

3.2.3. Results

A comparison of the pattern produced, at the same shelf position in the oven, for silica gel, thermocolour and egg white/agar gel is given in Figs. 3.8 (a), (b) and (c).

These patterns were all obtained at shelf position 2; the heating time was varied for each, to give a clearly discernable pattern. This time was different for each method because:

1. the lossiness of each material was different;
2. the thermal capacity of each material was different;
3. the temperature at which the visible change in the media occurred was different for each of the three materials.

Fig. 3.9 shows the effect on the coagulation pattern of varying the volume of egg white/agar gel; these patterns were produced using $\frac{1}{2}$, 1 and 2 litres of agar, corresponding to depths of 4, 8 and 15 mm. Patterns were obtained, for each of the three display methods, at each of the three shelf positions, as shown in Figs. 3.10, 3.11 and 3.12.

Results for the temperature measurements on the sheet of agar are given in Tables 3.2 and 3.3; 3.2 refers to the 6 cm array (Fig 3.6a) and 3.3 to the 2 cm one. The letters refer to the array positions given in Figs 3.6 (a) and (b). Each temperature rise is the average of five measurements and the figure in brackets is the standard deviation of these five measurements. 1 litre of agar was used, at an initial temperature of 20 °C and using a 30 second heating time, at shelf position 1.

The results for the 5 by 4 array of beakers, each containing 100 ml of water, are shown in Table 3.5. The initial temperature of the water was 20 °C and the results show the

average increase in temperature, for 5 measurements at shelf position 1. Alpha-numeric array positions refer to the arrangement shown in Fig. 3.6 and the figures in brackets are the standard deviation of the five measurements at that position.

Table 3.4 shows the results for 100 ml aliquots of water, heated for 20 seconds, at each of the 20 array positions as in Table 3.4. Each figure in the Table is the average of three results at that position and is the increase in temperature from an initial temperature of 20 °C. Table 3.4 (a) refers to measurements in shelf position 1, 3 4 (b) to shelf position 2 and 3.4 (c) to shelf position 3; the results of each of these Tables are summarised in Table 3.4 (d).

For the 2 by 3 array of 10ml aliquots of water, results are given in Table 3.6. These results give the increases in temperature, from an initial temperature of 20°C, and are the average of 19 measurements.

3.2.4 Discussion of results

Many methods are described in the literature for demonstrating the distribution of energy in a resonant cavity microwave oven. All of these methods utilise the generation of heat in a lossy material; the heat generated is a function of the frequency of microwave radiation, the dielectric properties of the material and the electric field strength. Therefore, provided that the frequency and dielectric properties are constant, the heat generated at any point will be dependant on the electric field strength at that point. Although the frequency is dependant on the load in the oven, it is constant throughout the cavity at any point in time. The dielectric properties may change during the heating process; thus, dehydration may reduce the lossiness. In this case the generation of heat would tend to be more even than in a case where the higher temperature causes an increase in the lossiness.

As discussed in Section 2.5.3., the load in a resonant cavity is an integral part of the resonant system. Thus, the material in the oven influences the number and types of resonant modes, and hence the energy distribution in the cavity. This is clearly illustrated by reference to Fig.3.8

Three different methods were examined, which produce a visual display of the energy distribution - thermocolour, silica gel and egg white agar. By comparing Figs. 3.8 (a), (b) and (c), which were obtained by each of the three methods at the same oven shelf position, it can be seen that each method produces a different pattern. The glass plate and thermocolour, pyrex tray and silica gel and pyrex tray and egg white agar gel all represent different loads to the microwave generator; and because of this, they produce a different resonant mode.

Fig. 3.9 also illustrates the effect of the load in the oven, on the distribution of energy. In this case three different volumes of the egg white agar gel were heated in the oven; it is clear that the pattern produced varies as the amount of material changes, even though the load in each case has the same dielectric properties. It was found that the pattern produced with two litres of the gel was more uniform than for the half and one litre loads, as shown by the fact that fewer small hot spots occurred and by the fact that large areas of the material coagulated at the same time.

The results for the agar sheet and the arrays of water are summarised in Table 3.7; this Table shows the variance (expressed as the Co-efficient of Variation, because of the different overall average temperature rise in each material),

The variance at a single position is a measure of errors caused by variation in the heating time and inaccuracies in the temperature measurement. The overall variance, as well as containing these errors, is largely a result of spacial variation in the electric field strength. This variation in field strength is considerably greater than the errors in temperature measurement.

It is interesting to note the difference in the Co-efficient of Variation between rows 3 and 4. Row 3 refers to twenty, 100 ml aliquots of water, heated simultaneously in the oven, whilst row 4 was obtained for a single 100 ml sample, both determinations using the same array positions. The higher value of the single position Co-efficient of Variation for the twenty beakers is to be expected, since there is a greater error in the temperature measurement, than is the case for the single beaker. The surprising thing is the high overall

variability in the case of the twenty beakers. This means that the determination of variability in the temperature for an array of beakers is not an accurate indication of the energy distribution for a single sample of food, placed at different points in the oven.

Despite the disparate results, obtained for the visual methods, it is possible to make some conclusions on the energy distribution in the oven cavity. Thus comparing the results for the three visual methods, in shelf position 1, (Figs. 3.10a, 3.11a and 3.12a), they all show the presence of a 'hot spot' in the centre of the cavity area. This 'hot spot' was also noticeable on the results for the 4 by 5 array of beakers (position 3 c in Tables 3.4 and 3.5a) and also for the layer of agar.

Results at other shelf levels are not so consistent; thus with egg white gel (fig 3.12) silica gel (3.11) and for the 4 by 5 array of 100 ml water samples, (Table 3.4), there is evidence of a central 'hot spot' at all three shelf levels, but with the thermocolour this is absent at positions 2 and 3 (Fig. 3.10). Table 3.4 (d) indicates that the variability is less at shelf position 2 (standard deviation 2.2), than at the two other shelf positions (3.6 at shelf 1 and 3.8 at shelf 2).

There is no significant difference between the results for the 10ml and 100ml arrays. If there were highly localised variations in the energy distribution, a 100ml sample might be expected to 'average out' these differences, which would be found in the smaller 10ml. samples. Since there is no difference between the estimated variability in 10ml and 100ml of water, this indicates that there are no localised regions of high and low energy density.

From a comparison of several typical methods of assessing the distribution of energy in a resonant microwave oven, it is

clear that the technique of measurement has such a large effect on the energy distribution, that no one technique is universally applicable. Thus a technique for assessing the energy distribution must be related to the use which is being made of the oven. It is not possible to talk in absolute terms of the energy distribution; this is dependant on the load in the oven. For this reason it is important that this is assessed for each application or experiment, since in each case a unique pattern will be obtained.

3.3 TOTAL POWER ABSORPTION BY WATER AND SIMPLE FOODS

3.3.1 Introduction

Although the rated power consumption of the oven is 2.8 kW, its actual consumption was measured as 2.4 kW; this was constant and independent of the amount and nature of the material in the oven. The purpose of the experimental work in this section was to determine what proportion of this power was absorbed by the material placed in the oven.

Most of the power consumption of the oven will occur at the magnetron; this is subject to high losses, which appear as heat in and around the magnetron. The operating efficiency of magnetrons is continually being improved and current models have an efficiency of the order of 65% (Pickering and Lewis, 1971). Small amounts of power will be consumed by ancillary equipment, such as the cooling fan, mode stirrer and oven light. With the exception of the mode stirrer, these are all operating whilst the oven is in the standby condition, which was measured as having a power consumption 300 W (see Section 3.1).

Of the power which is radiated from the magnetron, some will be absorbed by the walls and fittings in the oven, some will be absorbed by the materials in the cavity, some will leak from the cavity (largely through the door seals) and the rest will be reflected back down the waveguide to the magnetron, where it will be dissipated as heat.

Von Hippel (1954) gives a relationship, which expresses the power absorbed by a material in an electromagnetic field as a function of the electric field strength and the conductivity of the material.

$$P = \frac{\sigma \cdot E^2}{2} \dots\dots\dots (3.1)$$

where P = power/unit volume

Converting the conductivity to the imaginary relative permittivity (Equation 2.10), equation 3.1 becomes:-

$$P = 2 \cdot \pi \cdot f \cdot \epsilon_0 \cdot K'' \cdot E^2 \dots\dots\dots (3.2)$$

which was given in Section 2.4.1. as equation 2.21.

The experimental work which is described in the following section, is an investigation of the effect of the amount and nature of the material in the oven, on the power which it absorbs; this can then be related to the dielectric properties of the material.

3.3.2 Experimental

3.3.2.1 The effect of the volume of the material.

Water is amongst the most lossy of materials at microwave frequencies and its physical properties are well documented. For these reasons it was used as the basic material for the investigations.

The relationship between energy absorption and temperature rise, with allowance for the evaporation of volatile material, is given by equation 2.22 (Section 2.4.1). This can be converted to power absorption, in Watts, by dividing by the heating time (Equation 2.23), assuming a constant rate of power absorption.

$$P \text{ (abs)} = \frac{J}{\Delta t} (M.s.\Delta t. + m.L) \dots\dots\dots (3.3)$$

To obtain a true value for the power absorption, it is necessary to correct the right hand side of equation 3.3, to allow for heat losses. Cooling curves for various volumes of water, contained in 100ml pyrex glass beakers, are shown in Fig. 3.13. From a knowledge of the time interval between the end of the heating cycle and the temperature measurement, it is possible to correct this temperature to its true value at the end of the heating period. (There will also be some loss of heat during the actual heating period; this is difficult to estimate, since the temperature is increasing with time.)

Some of the heat which is generated in the water will be used to heat up the walls of the glass beaker. The specific heat of glass is 0.199 (Robson, 1967) and the glass beaker used in the experiments has a mass of 45g; therefore, the thermal capacity of the glass beaker is 8.96 cal^s °C. In practice

not all of the walls of the beaker are in contact with the water and, since glass has a low thermal conductivity, only that part of the glass in contact with the water will be heated. An estimate of the heat loss to the glass was made by calculating the mass of glass in contact with the water and calculating the thermal capacity of this portion of the beaker, as shown in Table 3.8.

The power loss due to evaporation of water contained in a 100ml glass beaker, over the temperature range 20 to 90 °C is shown in Fig 3.4. The results are expressed in terms of the rate of heat loss (Watts). This is calculated from the following expression:

$$\text{Rate of heat loss (Watts)} = \frac{Ev \cdot L \cdot J}{60} \dots\dots (3.4)$$

where Ev is the rate of evaporation from the surface (g / min.)

L is the latent heat of evaporation at the appropriate temperature.

Using the data in Figs. 3.13 and 3.14 and Table 3.8, the temperature measurement on the water in a 100ml beaker can be corrected to give an estimate of the true temperature at the end of the heating period; and also an estimate of the total power absorption. Thus, considering 100ml of water heated for 60 seconds in a microwave oven, if the temperature, measured 30 seconds after the end of the heating period is 50 °C, the true temperature, at the end of the heating will be 50.45. (Reference to Fig 3.13 shows that the rate of cooling for 100 ml at 50 °C is 0.9 °C/min.) The power required to raise the water and glass to this temperature is given by the relationship:

$$P \text{ (Watts)} = \frac{50 \times 45 \times}{60} \left((100 \times 1.06) + 9.0 \right) \times 4.2$$

To this figure must be added the heat lost by evaporation of water. At 50 °C this is equivalent to power loss of 2.6 watts.

To minimise the magnitude of the correction due to heat losses, it is advantageous to minimise the final temperature. This can be done by adjusting the heating time for each volume of liquid, so that the heating time is directly proportional to the volume of liquid. To do this, it is necessary to make the assumption that the power absorption is constant with time; this assumption was tested, as described below.

100ml of water, at an initial temperature of 20 °C, was heated for various times between 10 and 30 seconds, after which the temperature was measured to give the increase in temperature, as shown in Table 3.9. This was then corrected for heat losses, as described above, and the power absorption calculated. A total of 5 measurements was made at each temperature and the mean and Standard Deviation of these results calculated. The overall mean and S.D. was also calculated for all of the results. There was no significant difference between the calculated power absorption for the different heating times, indicating that the rate of energy absorption was constant.

Table 3.10 shows the effect of volume, on the power absorption. Column 2 is for water in unlagged glass beakers, corrected for heat losses as described above. Column 3 shows the results for water in 15ml polystyrene sample bottles mounted in a block of foamed polystyrene. Each bottle was filled with 10ml of water and a number of bottles used to make up the total volume. The block of polystyrene was fixed on the oven shelf and was bored with holes to provide locations for 10 bottles. To reduce the effects of variation in the energy distribution bottles were heated in all possible sample positions, and the results averaged.

In all cases it was found that there was a greater power absorption for the multiple sample volume than for the single. This could be because the single sample, which was always at the same point in the cavity, was in a region of low energy concentration or it could be because of the effect of the increased surface area of the multiple sample.

From these results, it appears that the power absorbed by a given volume of water is not constant, but depends on the sample geometry. To confirm these findings various arrangements of 60 ml of water were heated for 10 seconds in glass beakers. A 2 by 3 array of six beaker positions was used, the results, shown in Table 3.11, being based on an average of measurements in all six positions. For the multiple samples, the temperature rise in 60 ml was calculated by averaging the temperature rises in the individual beakers. Temperature rises were corrected for heat losses, as described previously, allowing for the thermal capacity of each beaker in the array and for evaporation from the liquid surface of each beaker.

These results confirm the findings in Table 3.10; for a given volume of water the total power absorbed is not constant, but depends upon the spacial arrangement of the samples. The

effect of energy variation in the cavity has been eliminated by using the same positional array for all samples, so that the difference is due to some other factor, such as surface area. The surface area of the water is shown in Table 3.10 together with the surface power density. It can be seen from these figures that, although the total power absorption increases with increase in surface area, the surface power density decreases.

3.3.2.2 The effect of the nature of the food

Fig. 3.15, shows a comparison of the power absorption by water and corn oil. The specific heat of corn oil was measured at 25°C, and was found to have a value of 0.41 cal/°C/gm. The oil was heated in single samples, as for the larger volumes of water. Because of the low values of power absorption, actual temperature rises were small and corrections for heat losses were small. Also, no correction was needed for evaporation of the sample.

For the remaining experiments in this section, the samples were contained in polystyrene sample bottles, mounted in the form of a 2 by 3 array, in a block of foamed polystyrene. Samples were heated in all locations, and the block of polystyrene was fastened to the oven shelf. These precautions were necessary to remove the effects of varying energy absorption, both at different points in the oven and also with different arrangements of a given volume. It was found that the polystyrene mounting, together with the capped sample bottle, reduced heat losses to a negligible amount, so that heat loss corrections were not required.

A 30% sucrose solution was prepared, using AR grade sucrose, and various volumes of this, between 10 and 90 ml, were heated in the oven. Six measurements were made at each volume and,

from the average temperature rise, the power absorption was calculated. Values of specific heat and density were obtained from Tables of the physical properties of sugar solutions (Norrish, 1972). A temperature intermediate between the initial and final values was used for these physical properties. The results are shown in Table 3.12.

Solutions and suspensions of egg albumin, starch (unhydrolysed), salt and sucrose were prepared at various concentrations. 60g samples (6 by 10g) of these solutions were heated in the oven (located in the polystyrene block), and the temperature rise measured. The six temperature rises were averaged, to give the temperature rise ; the heating process was repeated three times for each substance. Specific heats for the sucrose solutions were obtained from Tables; for the other materials they were calculated from the approximate relationship (Earle, 1966):

$$\text{Specific heat} = \frac{p}{100} + \frac{0.2 \times (100 - p)}{100} \dots\dots\dots (3.5)$$

This equation gives a value for the specific heat (cal/g. °C), where p is the percentage of solids in the material. Energy absorptions for these materials are shown in Table 3.13.

During all of these measurements, the power input to the oven was monitored; the standby consumption was 300 W and the operating consumption was a constant 2.4 kW, independent of the amount and nature of the load in the oven.

3.3.3. Discussion of results

Of the 2.4 kW consumed by the oven, 0.3 kW (standby consumption) is consumed by auxilliary equipment; most of the remaining 2.1 kW represents the power consumption of the magnetron.

Reference to Fig. 3.15 shows that the maximum power absorption was 820 watts into 800 ml of water. The corresponding figures for corn oil was 780 watts. Both of these figures are subject to errors caused by heat losses and specific heat values. Whilst the thermal properties of water are well documented no accurate information on the specific heat of corn oil could be found in the literature. For this reason the specific heat of corn oil was measured experimentally: this measured value has an error of $\pm 5\%$. Because of this error, the figure of 780 watts is not significantly different from the power absorption for water. A comparison of the results for water, 30% sucrose and corn oil indicates that, for large volumes of material, the power absorption is independant of the nature of the material. The maximum absorption for these large volumes of 820 watts is equivalent to an efficiency of 40%. The losses of 60% will arise from magnetron losses, transmission line losses and losses due to the oven cavity and fittings together with leakage of radiation from the cavity.

If equation 3.2 were to hold for a resonant cavity, the energy absorbed by a given volume of material would be a function of the loss factor of the material. K'' for water and oil are 11.3 and 0.15 respectively; from this it would be expected that oil would absorb 14% of the energy absorbed by water. In practice the ratio varied for different volumes, from 33% for 100ml to approximately 100% for volumes over 300 ml. Using equations 2.17 and 2.14 the value of K''_{dipole} for a 30% solution is 8, compared with a value for water of 11.2. Equation 3.2 predicts that, for a given volume, the absorption for a 30% sugar

solution is 73% of that for water. A comparison of the data for water and a 30% sugar solution is given in Fig. 3.16; as with the water and oil, there is not a constant difference between the absorption for water and a 30% sugar solution, It varies from 72% (for 18 ml.) to 95% (at 90 ml).

The reason that equation 3.2 does not hold for a resonant cavity is the effect of the load in the oven on the coupling of energy into the cavity. Although the power consumption of the oven is constant under different loads, energy coupling into the cavity depends upon the size and dielectric properties of the load, excess energy being reflected back to the magnetron, where it is dissipated as heat.

Using the same data as in Fig 3.16, Fig. 3.17 shows a plot of the power absorption for a 30% sugar solution against the weight of water in a given volume of the solution, compared with the absorption data for water. There is a very good fit between these two sets of data, indicating that, for this oven, there is a close relationship between the energy absorbed by a given solution and the mass of water contained in the solution.

This relationship is further confirmed by the data of Table 3.13; Figs. 3.18, 3.19, 3.20 and 3.21 show this data plotted in the same way as for the sucrose solution. With the exception of the salt solutions, the power absorption is equivalent to the absorption by an equal weight of water to that in the sample. Salt solutions, which have a higher value of K'' , than water, showed a lower absorption than for the equivalent weight of water. Also, this relationship cannot be applied to low water content materials, such as the corn oil.

These results are not absolutely reliable because of the lack of physical data for the solutions under investigation, and

also because only a small range of samples were investigated. It would also be useful to confirm these results for masses of material other than 60g.

The reason for this relationship between the water content of a material and its power absorption could be the way in which this type of resonant cavity oven is tuned. The electrical properties of a transmission line, coupled to a resonant cavity, can be adjusted to obtain maximum energy coupling, between the line and the cavity, under any desired working conditions. In this case it would seem that the oven has been tuned to give maximum efficiency into a water load. The relationship between the various solutions is similar to the findings of Van Zante (1968) which were discussed in Section 2.3.1.

3.4 MEASUREMENT OF THE ABSORPTION CO-EFFICIENT

3.4.1. Introduction

The decay in field strength of an electromagnetic wave as it penetrates into a propagating material, and the resultant decrease in power with depth of penetration is discussed in Section 2.3.2.

The exponential decay in power can be related to an absorption co-efficient (k), by equation 2.25.

$$P_z = P_o \cdot \exp(-k \cdot z); \quad P_x = P_o \cdot \exp(-k \cdot x)$$

where P_x and P_z are power fluxes

k can be related to the dielectric properties of the propagating material, using equations 2.27 and 2.28. (In some branches of the physical sciences the symbol k is also used to describe the attenuation of energy in a material, where k is given the value:

$$k = \frac{\alpha \cdot \lambda_o}{2 \cdot \pi}$$

In this discussion, k is always equal to $2 \alpha \cdot$.)

The energy absorbed by the material, as a result of attenuation of the wave, is converted into heat. Fig. 3.22 shows the relationship between power, power absorption and depth.

The power absorbed by a slab of material of thickness Δx when subject to electromagnetic radiation normal to the surface, is equal to the difference in power levels at the depths x and $x + \Delta x$.

$$P_a = P_x - P_x \cdot \exp(-k \cdot \Delta x)$$

Since $P_x = P_o \cdot \exp(-k \cdot x)$:-

$$P_a = P_o \cdot \exp(-k \cdot x) \left(1 - \exp(-k \cdot \Delta x) \right)$$

$$P_Q = P_0 \cdot \exp(-k \cdot x) [1 - \exp(-k \cdot \Delta x)] \quad (3.7)$$

The power absorbed P_a is converted into heat, according to the relationship:

$$\Delta t = \frac{P_a \cdot \Delta T}{J \cdot s \cdot \rho \cdot \Delta x} \quad (3.8)$$

Substituting equation 3.7 for P_a gives equation 3.9

$$\Delta t = \frac{C \cdot \Delta T \cdot \exp(-k \cdot x)}{J \cdot s \cdot \rho} \quad (3.9)$$

$$\text{where } C = \frac{P_0 \cdot [1 - \exp(-k \cdot \Delta x)]}{\Delta x \cdot J \cdot s \cdot \rho}$$

From equation 3.9, it can be seen that the rate of temperature rise also follows an exponential decay with depth into a material. The slope of this exponential decay is given by k , the absorption co-efficient. Therefore, from a knowledge of the temperature at various depths after a period of microwave heating it should be possible to calculate k ; graphical integration of this data will also permit the calculation of the total power absorption.

$$P_a \text{ (watts/cm}^2\text{)} = \frac{\rho \cdot s \cdot J}{\Delta T} \int_{x=0}^{x=\infty} \Delta t \cdot dx \quad (3.10)$$

This estimate of the power density of the incident wave does not include any energy which passes straight through the material without absorption, nor does it include any energy reflected from the surface.

The experimental work described in this Section was designed to investigate several factors. These are:

1. to measure the value of k in solid food materials;
2. to compare these experimental values of k with theoretical and literature values;
3. to obtain temperature profiles for semi-infinite solids and infinite slabs of food materials to allow comparison with a theoretically derived profile, described in Section 4.

In order to measure k from the temperature distribution in a food material, it is necessary that the incident radiation is normal to the surface and that the energy enters through only one surface, as shown in Fig. 3.23 (a). In a microwave oven, radiation enters a material in the oven through all surfaces. Two methods were investigated for achieving a measurement of the temperature distribution in a semi-infinite solid, as shown in Figs. 3.23(b) and 3.23(c).

One way of ensuring that the energy enters through one surface only, is to coat all but one surface with a layer of metal; this will reflect radiation away from these surfaces, thus permitting absorption through only one surface.

The other approach is to take a large block of material so that waves are attenuated to a very low level before they reach the centre and thus cause insignificant heating; in this way each surface will behave as though it were a semi-infinite solid.

3.4.2. Use of relective metal layer

3.4.2.1. Method.

The 'lossy' material used in these experiments was a gel of 1% lonagar (Oxoid Ltd.) in water; this has the advantage of having very similar dielectric properties to water and also it is solid so that there is no redistribution of heat by convection. This is important because temperatures cannot be monitored during the heating, but must be measured after the heating has finished.

To enable the temperatures to be quickly measured at fixed depth intervals, thermocouples were mounted on a plastic strip, which could be inserted into the agar at right angles to the surface, as shown in Fig. 3.2 3.(d). The thermocouples were mounted in the plastic strip at 1 cm intervals and located in position using 'Araldite' to ensure rigidity.

The agar gel was contained in a plastic bottle and the metal shielding was in the form of a can which was a close fit around the bottle.

Initial experimentation indicated that there were a considerable variation in temperature measurements when blocks of agar were heated for the same time period and at the same position in the oven.

Table 3.14 shows a summary of results obtained for 300 ml of agar at an initial temperature of 5°C , heated for 1 min. and using metal shielding as described above. These results are obtained from a total of 29 experiments. The mean value of Δt at each depth was calculated together with a co-efficient of variation. Also, a graph of $\log_{10} t$ against depth was plotted for each experiment and from this the slope of the graph at

4,5,6 and 7 cm was measured. This multiplied by 2.303 gave an estimate of k , the absorption co-efficient.

During the course of these experiments the power consumption of the oven was found to remain at a constant level even though the temperature measurements were subject to these wide variations.

The accuracy of the temperature measurement is 0.1°C . corresponding to 10% at a depth of 7 cm (1°C) and 0.2% at the surface (45°C); the measured variability is much greater than this. One reason for this is the effect of small errors in the positioning of the thermocouples. A small displacement of the thermocouple causes a large change in the temperature measurement. At lower depths the accuracy of the thermocouple becomes important.

The measurement of the slope of the graph was based on the temperature readings at 4,5,6 and 7 cm. Whereas the overall variability of these results is of the order of 30%, the estimate of the slope has a variability of only 10%; this indicates that one cause of the variability is the positioning of thermocouples. Displacement of the position of the thermocouple mounting strip will cause an equal percentage change in all temperature readings and will therefore not cause an error in the slope. Thus, although there is considerable variation in temperature, at any one depth, for all of the determinations, the relationship between the temperatures at different depths is much less variable.

Another cause of the variability in temperature at a particular depth could be because of variations in the surface power density. The variability in energy distribution in the oven was discussed in Section 3.2; it was demonstrated that, in any material heated in the oven, there will be a variation in

temperature caused by the non-uniformity of the energy distribution.

The temperature at a depth of 1 cm in a block of agar (complete with metal shielding) was measured at several points over the surface area, after it had been heated in the microwave oven. This was repeated at various heights in the oven, but always at the same position on the tray as was used for the measurement of temperature profiles. The range of temperatures at each height is shown in Fig.3.24. This shows that the variation is only 2°C at 8 cm, but at 16 cm this increases to 10°C . The height of the surface of the agar used in the measurement of temperature profiles was 12 cm, at this height the variation was 3°C , equivalent to a temperature variation of 7%. In practice, the temperatures were always measured around the centre point of the agar, and in this region the temperature did not vary by more than 1°C or 2%. It is therefore unlikely that a large error was introduced by variations in the energy distribution over the surface of the agar.

The metal can is used to simulate the situation of absorption of microwave energy by a semi-infinite solid. Any energy which reaches the bottom of the layer of agar is reflected and will distort the temperature rise at this point in the can. It is therefore important not to make temperature measurements near the base of the agar cylinder.

Measurements were made for the temperature profiles in cylinders of agar, in a metal can as described previously. The volume of agar was adjusted to determine the effect of the thickness of the layer of agar on the temperature profile obtained. The results, plotted as a graph of $\log_{10} \Delta t$ against depth, are shown in Fig.3.25.

From these results it can be seen that it is necessary to have

an agar depth of at least 4 cm between the lowest temperature measurement and the base of the agar. With a depth of less than this, the result will be higher than the true value for a semi-infinite solid, due to a reflected wave from the metal base of the container.

The effect of the heating time on the slope of the graph of $\log \Delta t$ against depth was also investigated. Agar cylinders were heated for varying periods of time and from the results a value of k was estimated. Results for 60 seconds heating time have previously been given (Section 2.4.2.1); results were also obtained for 30 seconds and 120 seconds.

30 seconds: mean value of k (10 results), 0.91; S.D, 0.09.

60 seconds: mean value of k (29 results), 0.94; S.D, 0.09.

120 seconds: mean value of k (10 results), 0.91; S.D., 0.11.

There is no significant difference between these estimates of the value of k , obtained for different heating times.

During the period of time required for the removal of the sample bottle from the oven, the insertion of the plastic thermocouple mounting strip and for the measurement of temperature, heat transfer will affect the measured temperature. Loss of heat from the surface will be caused by several processes; water will evaporate from the surface and the latent heat required will cause a cooling of the surface; radiation and convective heat transfer will remove heat from the surface; and heat will be transferred from the surface to the inner regions of the agar cylinder by conduction. Internally, heat will also be redistributed by conduction. Thus any delay between the end of the heating cycle and the temperature measurement can cause errors.

To determine the effect of these changes on the measured temperatures, and hence on the calculated value of k , a cylinder of agar was heated in the microwave oven and its temperature

measured after 30, 60, 90, and 120 seconds after the end of the heating cycle. Although the surface temperature did change rapidly, only small changes were detected at those depths used for the measurement of k . As shown in Fig. 3.26, only a slight change in the value of k between 30 and 60 seconds was found.

3.4.2.2. Measurements of the absorption co-efficient k .

Because of the variability of results, discussed above measurements of k were based on the average temperature rises from ten measurements; results based on the average of ten measurements on agar gels, at an initial temperature of 5°C , are shown in Fig. 3.27.

The increase in temperature was converted into a power absorption using equation 3.8 and taking x equal to one cm., which gives the power absorption in watts/cm^3 ; figures for power absorption are shown in Fig. 3.28. This experimental data deviates from the straight line exponential behaviour shown in Fig. 3.22. This deviation could be due to heat transfer (convection losses from the surface and internal heat conduction); or it could be that the relationship shown in Fig. 3.28 does not follow the theoretical behaviour given by equation 2.25.

If the deviation were caused by heat transfer changes, then the behaviour due to microwave heating alone would be given by the asymptote to the curve in Fig 3.28. Data for this asymptote is shown in Table 3.15. The total power absorption for both this asymptote and for the experimental data were calculated by graphical integration. The area under the graph of P_a (watts) against depth, gives the surface power density in watts/cm^2 . This, multiplied by the surface area of the agar, gives the total power absorbed through this surface. For the experimental data this was calculated as 360 watts whereas for the asymptote

this was 1200 watts (see Fig. 3.29).

The total power absorption into 300ml of water, in the same plastic bottle and with the same metal shielding, was calculated, as described in Section 3.2. It was found to be 400 watts. It is clear that the asymptote is much larger than the calculated power absorption and that errors caused by heat losses from the surface do not cause the non-linear curve for $\log_e P$ against depth. This means that the experimental absorption process is not described by an equation of the form:

$$P_x = P_0 \exp(-k \cdot x)$$

This deviation could either be because the absorption coefficient is not constant, or because the absorption does not follow an exponential decay.

Using either equation 2.27 or 2.28, k can be calculated for water from the data of von Hippel (1954). Calculated values are given in Table 3.16 using both equations; there is little difference between the approximate and accurate equations for water. These results show that k is a function of temperature. This would account for the non-linearity of the graph of $\log P$ against depth, particularly near the surface where temperature rises are highest.

The fact that k is a function of temperature means that it is not possible to calculate it, using the rise in temperature in a semi-infinite solid. The slope of the straight line portion of Fig. 3.28 can be measured; this slope is obtained for temperatures from 5 to 17 °C. Over this range of temperatures k varies from 1.01 to 0.77; this change of 20% in the value of k means that the slope of the graph is only an approximate

estimate of k at some intermediate temperature between 5 and 17. (The central point of the straight line portion corresponds to a temperature of $8^{\circ}\text{C}.$)

Provided the value of ΔT is small it is possible to obtain an approximate value of k , which can be compared with the data in Fig. 3.30. As the initial temperature is increased, so the accuracy should increase; this is because the change in k with temperature decreases as the temperature increases. In practice it was found that at higher temperatures a straight line portion of the graph was not obtained, results being similar to Fig. 3.25 for 7 cm. This was because at higher temperatures k is smaller, so that penetration is much greater so causing energy to be reflected from the base.

The experimentally measured value of k at an average temperature of 8°C (0.94) compares favourably with the literature value of k at 8°C (0.96).

3.4.3. Large cube of absorbant material to simulate semi-infinite solid

3.4.3.1 Method.

A 1% solution of Ionagar in water was moulded in the form of a 9cm cube and cooled to a temperature of 4 °C. The cube was heated in the oven for 1 minute, after which the temperature distribution along a central axis was measured, using thermocouples mounted on a plastic strip (see fig.3.31 a). The procedure was repeated using a different block of agar and a heating time of 2 minutes.

3.4.3.2. Results.

The results, plotted as a graph of $\log_{10} \Delta t$ against depth, are shown in Fig.3.32 (a). It can be seen from these results that even towards the centre of the block, where temperature rises are small, an exponential decay in power absorption is not obtained. This is because the microwave energy enters through all six surfaces. Thus, although 90% of the energy is absorbed by a layer of 4 cm of water, the actual energy at the centre of a cube will be six times as great as for a semi-infinite solid. The effect of this can be calculated, as shown in Table 3.17, by summing the power absorption for 1 cm cubes (see fig 3.31 b). This method will only give an approximation to the true temperature distribution: no account is taken in this calculation of changes in the value of k , as the temperature rises; also the energy in a cube in the centre of a large block of material may not be additive, because of the presence of standing waves; no account is taken of heat transfer effects on the temperature distribution.

For the calculation, a surface power density of 1.8 watts/cm² was used. This figure was obtained from the graphical integration

of the data obtained for the 9 cm cube. A value of 1 for k is used, equivalent to a temperature of 8°C . The 9 by 9 array in Table 3.17 represents a 1 cm slice from the centre of the cube, equidistant from the front and back surfaces. The measured temperatures are equivalent to those in column 5; cube 5A represents the temperature measurement at a depth of 0.5 cm, cube 5B a depth of 1.5 cm etc. The calculated results are compared with the experimental values in Fig. 3.32 (b). Good agreement was found between these two sets of data, considering the simplifications in the calculation. Results close to the surface are inaccurate for two reasons: no allowance is made for surface heat transfer changes; also a constant value of k is used which will lead to errors, particularly at the surface, where the greatest temperature rises occur. These errors could be eliminated from the calculation using a finite difference calculation (see Section 4).

Reference to Table 3.17 shows that a 9 cm cube is not large enough to simulate the effect of semi-infinite solid absorption through each face of the cube. The calculated temperature rise at the centre of the cube (5 E) is 1.6°C , whereas the rise at this point through a single surface is 0.2°C . The use of a larger cube leads to several practical difficulties: with a large cube of material, it is necessary to increase the heating time to produce a suitable rise in temperature; the top surface of a large cube would be subjected to greater variations in the energy distributions, and above a certain size it will not fit in the oven cavity; as the size of the cube is increased it becomes difficult to construct and to obtain a uniform initial temperature. For these reasons no further attempts were made to simulate the temperature distribution in a semi-infinite solid using this technique.

3.4.4. Discussion of results

The attenuation of electromagnetic radiation by a lossy material follows an exponential decay; the temperature profile, in the direction of propagation should also follow an exponential decay. Therefore it should be possible to deduce changes in power level, with depth in a material, by measuring the temperature profile. From this it should also be possible to measure the absorption co-efficient for the material.

To obtain an exponential absorption it is necessary for the radiation to be normal to a single surface of the absorbant material. Two methods were investigated for achieving this condition: one method utilised a cylinder of agar, with all but one surface shielded by a metal can; the second method used a large block of agar in the shape of a cube.

If the absorption does follow an exponential decay, a graph of $\log_{10} t$ against depth should be a straight line. With the first method this was only obtained at lower depths in the agar cylinder. The non-linearity near the surface is caused by the fact that the absorption co-efficient is temperature dependant and also by heat losses from the surface due to evaporation and convection.

It was found that the slope of the straight line portion of the graph could be used to calculate a value for the absorption co-efficient. For the agar gel at 8 °C (the mean of the temperature rise over which the slope was measured) a value of 0.94 was obtained. This compares with the literature value for water at this temperature of 0.96.

Using a cube of agar, and measuring the temperature profile across a single axis, it was not possible to obtain a straight

line portion to the graph. In theory a large slab of agar should attenuate a very large proportion of energy before it reaches the centre of the cube. In practice, with the size of cube which could be heated in the oven, the temperature rise at the centre of the cube was significant, because of energy penetration from all six sides of the cube.

In the case of the temperature profiles measured using the agar cylinder with metal shielding it was found that there was considerable variations in replicate temperature measurements at a single depth in the material. Several possible causes of this variability were investigated.

The major cause of this variability was due to changes in the position of the thermocouple between one set of measurements and the next. For each set of temperature measurements the position of the thermocouples was adjusted by aligning the top thermocouple with the surface of the agar; this can not be done precisely. Also the position of the other thermocouples, relative to the top one can vary. Reference to Fig.3.27 shows that a change of 0.1 cm at a depth of 2 cm can cause a temperature difference of 1 °C. Other sources of variability were investigated: variations in the surface power density; variations in the depth of the agar; variations in the heating time; and the effect of delays between the termination of the heating time and the temperature measurement. It was found that all of these factors could be controlled, by standardising precisely the conditions for replicates.

Because of the high variability, it is necessary to repeat measurements a large number of times and to calculate an average temperature profile. This technique is used in the next Section to measure temperature profiles for various high water content materials under varying conditions.

3.5 TEMPERATURE DISTRIBUTION IN SOLIDS OF HIGH WATER CONTENT

3.5.1. Introduction

The temperature distribution in a solid material, after radiation with microwaves normal to one surface, can be calculated using the exponential power absorption equation (Equation 2.26) and allowing for changes in the value of the absorption co-efficient with temperature and for conduction and surface heat transfer. A method for performing this calculation is given in Section 4. To validate this simulation, it is necessary to compare the results of the simulation with the actual temperature profiles, measured experimentally, in simple food materials after a microwave heating process.

For these measurements solutions or suspensions of a few simple food components were used; these were held in the form of a solid material by the use of 1% Ionagar as a gelling agent. The food components which were used were sugar, starch (hydrolysed and unhydrolysed) and sodium chloride. Temperature distributions were measured for semi-infinite solids (Section 3.5.2) and for slabs of various thicknesses (Section 3.5.3).

3.5.2 Semi-infinite solid

3.5.2.1 Method.

A method has previously been described for measuring the temperature profile in a solid food material, with microwave radiation normal to one surface only - see Section 3.4.2.1.

Because of the variability in temperature measurements for replicate determinations (see Table 3.14), each temperature profile in this Section was calculated by averaging the results from five separate experiments. For these replicates the volume of agar, position of the metal shield and the position of the sample in the oven were kept constant.

All results were plotted graphically and the total power absorption calculated by integration of the graph, using a planimeter to measure the area.

$$\text{Power density (watts/cm}^2\text{)} = \frac{J \cdot e \cdot S}{\tau} \cdot \int_{x=0}^{x=d} \Delta t \cdot dx \dots (3.11)$$

The total power absorbed can be calculated from a knowledge of the power density, given by equation 3.11, and from the surface area through which the microwave energy enters the sample. This calculated power absorption is subject to several sources of error: the surface power density is not uniform; the calculation excludes any energy which penetrates beyond a depth of d cm. (the depth of the lowest thermocouple); any heat generated which is lost from the surface due to radiation, convection and evaporation will also be excluded.

For mixtures of water and agar, the specific heats and densities were taken as being equal to those of water; the presence of 1% solid material will not significantly affect the results. For the other materials, literature values were used where available (also ignoring the 1% agar); otherwise these were obtained experimentally. Densities were calculated from the volume displacement of water by a known weight of the gel. Specific heats were measured, using the method of mixtures.

It is not possible to measure the temperature profile immediately at the end of the heating process; in practice measurements were made after an interval of 30 seconds. Although this delay will lead to inaccuracies in both the power absorption estimate and in the temperature profile, heat transfer changes can be built into the simulation, as described in Section 4. Thus the temperature profile for simulation and experiment can be obtained at the same point in time from the end of the heating cycle.

3.5.2.2. Results.

The effect of several processing and compositional variations were investigated, and all results are in Tables 3.18 to 3.24. The results are shown graphically in Section 4 (Figs. 4.12 to 4.20), where they are compared with the simulated heating profiles.

Tables 3.18 and Fig. 4.12 refer to the effect of heating times of 30, 60 and 90 seconds, for 300 ml of agar at an initial temperature of 5 °C.

Table 3.19 and Fig. 4.13 show the effect of initial temperatures of 5, 20 and 40 degrees C, for 300 ml of agar, heated for 60 seconds. Table 3.20 shows the effect of a delay between the end of heating and the measurement of the temperature profile.

Tables 3.21 to 3.24 are results for agar/water/food mixtures. The effect of salt at 1% and 2%, sugar from 10 to 40% and 10% starch were investigated. All of these results for a semi-infinite solid are summarised in Table 3.24.

3.5.3. Temperature profiles in agar slabs.

3.5.3.1 Method.

A method has been described for measuring the temperature profile in a solid material, with microwave radiation normal to one surface only - Section 3.4.2.1. This method can be extended to cover the situation of a solid with microwave radiation normal to two surfaces, which form the parallel ~~sides~~ ^{faces} of a slab, as indicated in Fig. 3.33 (b).

For these experiments, agar gel was used as the solid material; this was moulded in a polythene bottle, to give a known depth, d cm. The bottle was fastened inside a metal cylinder, so that the surfaces of the agar were equidistant from the ends of the cylinder. After the slab had been heated in the microwave oven, its temperature distribution was measured, using the mounted thermocouples inserted in the agar along the axis $X - X$ (Fig. 3.33b).

The area of a graph of Δt against depth gives the power absorbed by a rod, of unit cross-sectional area and length d cm. This multiplied by the cross-sectional area of the agar cylinder gives an estimate of the total power absorption of the agar cylinder, subject to the errors discussed in Section 3.5.2.1.

Power absorption occurs through two surfaces; if the surface power density is the same at both surfaces, the energy entering through each surface is equal to one half of the total power absorption. Reference to Fig. 3.34 shows one method of calculating the power absorption through each surface, when these are different. This method of ascribing the total energy absorption, to the two surfaces, will be inaccurate, for slabs of small depth which have asymmetric energy distribution to the

two surfaces. Thus in Fig. 3.34 (c) the area A' is an estimate of the area A , which can be used to calculate energy entering through the upper surface. The equality of A' and A will be closest when the areas - (b) and (d) are equal. For the case when energy distribution is greater at the upper surface than at the lower, area (b) will be larger than area (d). Therefore area A' will be an underestimate of area A . The calculation will also be affected by any standing wave pattern, produced where there is an overlap of the wavefronts from each of the surfaces.

3.5.3.2. Results

The measured temperature profiles for agar gels of varying thickness are given in Tables 3.25 to 3.27. As with the semi-infinite solid temperature profiles these are shown graphically in Section 4, where they are compared with simulated heating profiles. All of the results for temperature profiles in slabs are compared in Table 3.27. Two facts emerge from these results. There is a definite asymmetry between power absorbed through the two surfaces and the distribution between the two surfaces varies with the thickness of the slab. Thus for slabs of 12, and 10 cm the upper surface has the higher power density, whereas for slabs of 8 and 6 cm, the lower surface has the higher power density. Also total power absorption decrease as the sample thickness, and hence sample volume decreases; this confirms the findings of Section 3.3 on the effect of volume on power absorption.

Table 3.1 Determination of the accuracy and precision of the oven timer

<u>Timer settings (secs)</u>	<u>Measured time (secs)</u>	<u>Co-efficient of variation</u>
10	10.07	0.5%
20	19.93	0.5%
30	29.10	1.1%
40	39.8	0.8%
50	50.2	0.4%
60	60.3	0.4%

Table 3.2 Temperature rise at nine points. 6 cm apart. in a layer of agar.

	A	B	C
1	20.4 (1.0)	15.6 (0.8)	20.2 (1.2)
2	17.2 (0.9)	28.9 (1.0)	16.1 (1.1)
3	16.5 (0.8)	14.3 (0.9)	12.0 (1.1)

Average S.D. (standard deviation) in a single position:

0.97.

Overall S.D: 4.6 (based on 45 results).

Overall average temperature rise: 17.6 °C

Table 3.3 Temperature rise at nine points. 2cm apart. in a layer of agar

	A	B	C
1	14.2 (0.9)	14.5 (0.8)	14.0 (0.9)
2	22.0 (0.8)	28.8 (1.0)	22.5 (1.0)
3	18.4 (1.1)	18.2 (1.0)	16.0 (0.9)

Average of S.D.'s at a single position: 0.93

Overall S.D: 4.8.

Overall average temperature rise: 18.7 °C

Table 3.4 Temperature rise in a single 100ml aliquot of water(a) Shelf position 1

	A	B	C	D	E
1	20.5	26.0	28.5	25.7	22.7
2	20.2	29.7	27.3	27.0	20.5
3	21.0	24.0	34.5	24.2	20.8
4	25.5	24.0	29.0	25.0	25.5

(b) Shelf position 2

	A	B	C	D	E
1	26.8	26.8	27.8	28.3	27.5
2	26.0	26.3	24.0	24.3	24.3
3	23.8	24.8	29.8	23.5	24.8
4	27.0	30.0	30.0	27.0	27.5

(c) Shelf position 3

	A	B	C	D	E
1	23.5	17.5	28.0	18.0	23.0
2	27.5	17.5	23.5	17.0	26.5
3	23.0	22.5	28.5	23.0	24.0
4	17.0	18.5	20.5	17.5	17.0

(d) Summary of results

	Overall Average	Overall S.D.	Average of S.D.s in a single position
Shelf 1	25.1	3.6	1.1
Shelf 2	26.5	2.2	1.0
Shelf 3	21.7	3.8	1.1

Table 3.5 Temperature rise in twenty 100ml aliquots of water
in 5 by 4 array

Shelf position 1

	A	B	C	D	E
1	22.0(1.5)	28.7(1.6)	55.7(1.8)	30.7(1.7)	21.3(1.9)
2	26.0(2.0)	15.7(2.1)	21.0(1.1)	20.0(1.6)	22.7(1.9)
3	23.7(2.1)	16.0(2.0)	50.0(2.0)	21.0(2.0)	26.7(2.0)
4	9.7(1.8)	20.3(1.0)	46.3(2.1)	25.7(1.9)	16.0(1.5)

Average of S.D's in a single position: 1.8

Overall S.D: 8.2

Overall average temperature rise 22.1 °C

Table 3.6 Temperature rise in six, 10ml aliquots of water in a
3 by 2 array

	A	B	C
1	43.5(3.1)	41.8(5.9)	40.4(3.7)
2	34.1(3.3)	35.9(4.4)	28.4(2.4)

Average of S.D's in a single position: 3.8

Overall S.D.: 6.3

Overall average temperature rise: 37.0 °C

Table 3.7 Summary of results of temperature measurements

Method	Average C.V. in a single position	Overall C.V.
1. Agar sheet 6cm spacings	5.5%	26.1%
2. Agar sheet 2cm spacings	5.0%	25.7%
3. 20 by 100ml, in 4 by 5 array	8.1%	37.1%
4. Single 100ml sample in 4 by 5 array	4.3%	14.3%
5. 6 by 10 ml, in 2 by 3 array	10.3%	17.0%

Table 3.8 The effective thermal capacity of a glass beaker

Mass of beaker: 45 g.

Base area of beaker: 19 cm^2 .

Wall area of beaker: 85 cm^2 .

Total surface area of beaker: 104 cm^2 .

Volume of water ml.	100	90	80	70	60	50	40	30	20
Base area- cm^2 .	19	19	19	19	19	19	19	19	19
Wall area in contact with water- cm^2 .	85	77	68	60	51	43	34	26	17
Total beaker area in contact with water	104	96	87	79	70	62	53	45	36
Mass of beaker in contact with water grams	45	43	38	34	30	27	23	20	16
Effective thermal capacity-cals/ $^{\circ}\text{C}$.	9.0	8.3	7.5	6.8	6.0	5.3	4.7	3.4	3.0

Table 3.9. Effect of heating time on the power absorption

Increase in temperature in 100ml of water, in a glass beaker.

Time- secs.	Measured ΔT (5 results)	Corrected ΔT	Power abs. (water + beaker)	Evap.	Total Power Absorption	S.D.
10	11.1	11.4	521.7	0.8	522.5	7.1
15	16.7	17.0	519.1	1.0	520.1	6.5
20	22.4	22.8	522.1	1.5	523.6	6.5
25	28.0	28.4	519.5	2.4	521.9	8.1
30	33.6	34.0	518.8	3.2	522.0	7.8
over- all	-	-	-	-	522.0	9.06

Table 3.10 The effect of volume on power absorption

Volume ml (1)	Power absorbed - walls			P_m/P_s (4)
	Single sample (2) P_s	(average of 5 measurements)	Multiple 10ml (3) samples P_m	
20	212		400	1.88
30	320		540	1.69
40	390		608	1.56
50	410		640	1.53
60	440		708	1.61
70	460		711	1.54
80	485		762	1.57
90	500		761	1.52
100	520		770	1.48

Table 3.11 Power absorbed by 60 ml of water

Sample	ΔT	Corrected ΔT	Power- watts	P evap.	P total	Area	Watts/ cm ²
1 x 60ml	15.8	16.1	491	1 x 1.0	492	89	5.5
2 x 30ml	20.3	20.8	588	2 x 1.3	591	128	4.6
3 x 20ml	22.9	23.6	663	3 x 1.6	668	205	3.3
6 x 10ml	23.2	24.2	735	6 x 1.6	745	276	2.7

Table 3.12 Power absorption by a 30% sucrose solution

Weight - g	Volume - ml	weight of water in sample - g	Power Absorbed watts
20	18	14	300
40	36	28	520
60	55	38	600
80	73	51	680
100	91	70	720

Table 3.13 The energy absorption by 60g of some simple foodstuffs.

Material	Concentration g / 100 g	Pa-watts average range		% of absorption by water	Efficiency of oven %
Water	100	708	--	100	
Sucrose	10	655	646-663	88	27.3
	20	654	612-717	88	27.3
	40	530	480-570	71	22.1
	80	300	220-370	40	12.5
Sodium chloride	5	633	617-644	85	26.3
	10	565	545-593	76	24.6
	30 super- saturated	560	550-568	75	23.3
	60 " "	390	334-455	52	16.3
Corn starch (unhydrolised)	10 suspension	634	620-680	85	26.4
	30 "	593	560-620	80	24.7
	50 "	525	490-540	70	19.8
Egg albumin	10	661	632-691	89	27.6
	20	627	615-691	84	26.1
	50	551	540-586	74	23.0
Corn oil	100	110	--	16	5

Table 3.14 Variability in temperature at various depths(a) Temperature

Depth - cm.	Δt °C	Co-efficient of Variation
0	45	18
1	41.5	13
2	34.6	18
3	21.6	19
4	12.1	21
5	5.4	31
6	2.2	33
7	1.0	29

(b) Absorption co-efficient

mean value of k: 0.94.

Co-efficient of variation of k: 10%.

Table 3.15 Experimental data for temperature profile and data
for asymptote

Depth-cm	Experimental data			Data for asymptote	
	Δt ($^{\circ}\text{C}$)	P_a (watts/cm 2)	$\log_e P_a$	$\log_e P_a$	P_a
0	45	3.15	1.147	3.41	30
1	41.5	2.91	1.068	2.53	12.5
2	34.5	2.45	0.884	1.60	4.9
3	21.6	1.51	0.412	0.74	2.1
4	12.1	0.85	-0.163	-0.163	0.85
5	5.4	0.38	-0.968	-0.968	0.38
6	2.2	0.15	-1.897	-1.897	0.15
7	1.0	0.07	-2.659	-2.659	0.07

Table 3.16 Values of k for water, calculated from the
dielectric properties

Temp. (°C).	k	
	Equation 2.27	Equation 2.28
0	1.248	1.238
10	0.934	0.930
20	0.704	0.702
30	0.537	0.536
40	0.417	0.416
50	0.331	0.330
60	0.267	0.268
70	0.223	0.223
80	0.190	0.190
90	0.165	0.165
100	0.146	0.146

Table 3.17 Temperature rise in central slice from a 9 cm cube - calculated.

The underlined figures represent the total temperature rise in a 1 cm cube made up from individual temperature rises due to absorption through 6 faces.

	1	2	3	4	5	6	7	8	9	
top	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	
bottom	-	-	-	-	-	-	-	-	-	
front	.2	.2	.2	.2	.2	.2	.2	.2	.2	A
back	.2	.2	.2	.2	.2	.2	.2	.2	.2	
left	13.5	5	1.9	.7	.2	.1	-	-	-	
right	-	-	-	.1	.2	.7	1.9	5	13.5	
top	5	5	5	5	5	5	5	5	5	
bottom	-	-	-	-	-	-	-	-	-	
front	.2	.2	.2	.2	.2	.2	.2	.2	.2	B
back	.2	.2	.2	.2	.2	.2	.2	.2	.2	
left	13.5	5	1.9	.7	.2	.1	-	-	-	
right	-	-	-	.1	.2	.7	1.9	5	13.5	
top	1.9	1.9	1.9	1.9	1.9	1.9	1.9	1.9	1.9	
bottom	-	-	-	-	-	-	-	-	-	
front	.2	.2	.2	.2	.2	.2	.2	.2	.2	C
back	.2	.2	.2	.2	.2	.2	.2	.2	.2	
left	13.5	5	1.9	.7	.2	.1	-	-	-	
right	-	-	-	.1	.2	.7	1.9	5	13.5	
top	.7	.7	.7	.7	.7	.7	.7	.7	.7	
bottom	.1	.1	.1	.1	.1	.1	.1	.1	.1	
front	.2	.2	.2	.2	.2	.2	.2	.2	.2	D
back	.2	.2	.2	.2	.2	.2	.2	.2	.2	
left	13.5	5	1.9	.7	.2	.1	-	-	-	
right	-	-	-	.1	.2	.7	1.9	5	13.5	
top	.2	.2	.2	.2	.2	.2	.2	.2	.2	
bottom	.2	.2	.2	.2	.2	.2	.2	.2	.2	
front	.2	.2	.2	.2	.2	.2	.2	.2	.2	E
back	.2	.2	.2	.2	.2	.2	.2	.2	.2	
left	13.5	5	1.9	.7	.2	.1	-	-	-	
right	-	-	-	.1	.2	.7	1.9	5	13.5	
top	.1	.1	.1	.1	.1	.1	.1	.1	.1	
bottom	.7	.7	.7	.7	.7	.7	.7	.7	.7	
front	.2	.2	.2	.2	.2	.2	.2	.2	.2	F
back	.2	.2	.2	.2	.2	.2	.2	.2	.2	
left	13.5	5	1.9	.7	.2	.1	-	-	-	
right	-	-	-	.1	.2	.7	1.9	5	13.5	
top	1.9	1.9	1.9	1.9	1.9	1.9	1.9	1.9	1.9	
bottom	-	-	-	-	-	-	-	-	-	
front	.2	.2	.2	.2	.2	.2	.2	.2	.2	G
back	.2	.2	.2	.2	.2	.2	.2	.2	.2	
left	13.5	5	1.9	.7	.2	.1	-	-	-	
right	-	-	-	.1	.2	.7	1.9	5	13.5	
top	-	-	-	-	-	-	-	-	-	
bottom	5	5	5	5	5	5	5	5	5	
front	.2	.2	.2	.2	.2	.2	.2	.2	.2	H
back	.2	.2	.2	.2	.2	.2	.2	.2	.2	
left	13.5	5	1.9	.7	.2	.1	-	-	-	
right	-	-	-	.1	.2	.7	1.9	5	13.5	
top	-	-	-	-	-	-	-	-	-	
bottom	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	
front	.2	.2	.2	.2	.2	.2	.2	.2	.2	I
back	.2	.2	.2	.2	.2	.2	.2	.2	.2	
left	13.5	5	1.9	.7	.2	.1	-	-	-	
right	-	-	-	.1	.2	.7	1.9	5	13.5	

Table 3.18 Effect of heating time on temperature profile of semi-infinite solid.

Depth cm	Time					
	30 secs.		60 secs.		90 secs.	
	Δt	Range	Δt	Range	Δt	Range
0	33.0	25 - 38	45.0	41 - 50	52.0	48 - 60
1	25.0	21.2-26.1	41.5	35 - 46	54.3	47 - 58
2	15.5	10.7-21.4	34.5	27 - 40	44.3	43 - 51
3	7.8	2.9-10.6	21.6	15.- 25	27.8	25.0-30.6
4	4.0	2.3-6.1	12.1	7.2-14.2	16.1	15.0-18.0
5	2.0	0.6-2.7	5.4	2.8-7.0	8.4	7.5 -9.0
6	1.0	0.3-1.1	2.2	1.0-3.9	3.2	2.5-3.7
7	0.4	0.1-0.5	1.0	0.5-1.3	1.4	0.5-1.3

Material:- 1% Ionagar.

Initial temperature:- 5 °C

Power absorbed:- 30 secs, 348 watts (10.9 watts/cm.²)

60 secs, 343 watts (9.8 " ")

90 secs, 338 watts (9.66 " ")

Table 3.19 Effect of initial temperature

Depth cm	Initial temperature - °C					
	5		20		40	
	Δt	Range	Δt	Range	Δt	Range
0	45	41 - 50	38.8	32 - 42	29.3	25 - 36
1	41.5	35 - 46	38.3	32 - 40	33.0	27 - 35
2	34.5	27 - 40	30.6	26 - 34	27.5	24 - 31
3	21.6	15 - 25	17.0	16.0-20.1	20.6	16.8-22.0
4	12.1	7.2 -14.2	10.5	9.7-11.7	13.8	12.0-14.5
5	5.4	2.8-7.0	6.9	6.0 - 7.6	10.9	10.5-11.2
6	2.2	1.0-3.9	4.1	3.2-4.7	8.6	7.0-10.5
7	1.0	0.5-1.3	2.5	1.9-2.7	5.8	4.5-7.0

Material:- 1% Ionagar

Heating time:- 60 seconds.

Power absorbed:- 5 °C. , 341 watts (9.7 watts/cm²)

20 " , 343 " (9.7 " ")

40 " , 338 " (9.5 " ")

Table 3.20 Effect of delay between heating and temperature
Measurement.

Depth	Delay			
	30 seconds	60 seconds	10 mins.	40 mins
cm	Δt	Δt	Δt	Δt
0	38.8	38.0	22.5	16.0
1	38.3	36.9	29.5	23.5
2	30.6	29.6	27.5	22.5
3	17.0	20.6	18.5	20.5
4	10.5	10.4	15.0	15.2
5	6.9	6.8	11.0	10.5
6	4.1	4.0	6.2	5.6

Material:- 1% Ionagar.

Initial temperature:- 20 °C.

Air temperature:- 20 °C.

Table 3.21 temperature profiles for water/agar/salt mixtures

Depth	Salt concentration %					
	0		1		2	
cm.	Δt	Range	Δt	Range	Δt	Range
0	38.8	32 - 42	45.1	40 - 51	50.7	36 - 55
1	38.3	28.-40	29.4	21 - 36	26.6	20 - 30
2	30.6	26 - 34	13.6	10 - 15.1	11.3	10.0-15.2
3	17.0	16.0-20.1	5.8	4.1- 6.8	4.5	3.6-6.3
4	10.5	9.7-11.7	3.7	2.9 - 6.0	2.4	1.1-3.7
5	6.9	6.0-7.6	2.2	1.1 - 3.5	1.3	0.8-2.6
6	4.1	3.2-4.7	1.0	0 - 2.1	0.6	0.2-0.8
7	2.5	1.9 -2.7	-	0 - 0.3	-	0

Initial temperature: - 20 °C.

Heating time: - 60 seconds.

Values of S and ρ as for water.

Power absorption: - 0 % - 343 watts

1 % - 211 "

2 % - 157 "

Table 3.22 Temperature profiles for water/agar/sugar mixtures

Depth			Sugar concentration							
0			10		20		30		40	
cm	Δt	Range	Δt	Range	Δt	Range	Δt	Range	Δt	Range
0	45.0	35-48	48.0	38-52	52.2	49-53	49.3	47-54	50	48-56
1	41.5	30-46	40.0	36-42	38.0	31-40	36.3	32-42	38.0	33-41
2	34.5	22-40	27.0	25-32	25.0	22-27	24.3	20-25	22.5	17-33
3	21.6	12-25	11.8	6.7-15.2	10.8	8.3-12.5	8.0	7.2-9.8	9.7	6-14.5
4	12.1	7.2-14.2	6.3	5.6-7.1	5.8	4.7-8.0	3.8	2.9-5.0	5.5	4.8-5.8
5	5.4	2.8-7.0	5.3	3.7-6.0	4.3	3.1-5.7	2.9	1.8-4.0	3.2	2.2-5.6
6	2.2	1.0-3.9	2.9	1.9-4.9	2.1	0.9-3.4	1.4	0.3-2.8	1.6	0.4-4.5
7	1.0	0.5-1.3	1.5	0.8-1.7	1.1	0.9-1.5	0.8	0-1.4	1.0	0.2-2.0

Initial temperature:- 5 °C.

Heating time:- 30 seconds.

Values of S and ρ from Norrish (1967).

Power absorbed:- 0% - 344 watts. (10.1 watts/cm²)

10% - 332 " (9.5 " ")

20% - 263 " (7.5 " ")

30% - 235 " (6.8 " ")

40% - 228 " (6.5 " ")

Table 3.23 Temperature profile for water/agar/starch mixture (10%)

Depth	Hydrolysed		Raw	
	Δt	Range	Δt	Range
0	34.0	30 - 37	41.6	34 - 46
1	26.0	24 - 31	40.0	35 - 43
2	22.0	18 - 25	29.4	24 - 34
3	12.0	9 - 18	18.4	11 - 18
4	7.0	4 - 10	9.0	6 - 12
5	6.0	4 - 8	6.2	5.1 - 6.8
6	3.0	2.0 - 4.5	2.9	1.9 - 4.1
7	1.2	0.9 - 2.1	1.6	1.0 - 2.2

Starch:- 10%

Initial temperature:- 5 °C.

Heating time:- 60 seconds.

Power absorption:- Uncooked: 306 watts (8.7 watts/cm²)

Cooked: 228 " (6.5 " ")

Values of S and ρ measured experimentally.

Table 3.24 Temperature profile for semi-infinite solid

Composition			Time Seconds	Initial temp. °C	Power density watts/cm ²	Total Power absorb. watts.
Water %	Agar %	Other %				
99	1	-	30	5	10.20	348
99	1	-	60	5	9.80	343
99	1	-	90	5	9.66	338
99	1	-	60	5	9.73	343
99	1	-	60	20	9.76	343
99	1	-	60	40	9.66	338
<u>salt</u>						
99	1	0	60	20	9.80	343
98	1	1	60	20	6.02	211
97	1	2	60	20	4.48	157
<u>sugar</u>						
99	1	0	60	5	10.1	344
89	1	10	60	5	9.48	332
79	1	20	60	5	7.50	263
69	1	30	60	5	6.73	235
59	1	40	60	5	6.51	228
<u>starch</u>						
99	1	0	60	5	9.80	343
89	1	10-raw	60	5	8.70	306
89	1	10- cooked	60	5	6.50	228

Table 3.25 Temperature profiles for agar slabs-initial temperature 20 °C

Depth	Slab thickness - cm.			
	12	10	8	6
cm	Δt	Δt	Δt	Δt
0	45.0	45.0	33.5	29.5
1	41.5	39.0	26.8	25.7
2	35.5	30.0	26.0	23.3
3	26.3	24.3	19.5	22.7
4	19.0	16.9	17.8	25.7
5	15.3	14.5	22.8	28.0
6	13.6	15.5	33.5	32.1
7	13.5	21.0	40.0	-
8	16.3	28.0	45.0	-
9	22.3	35.0	-	-
10	27.0	40.0	-	-
11	35.3	-	-	-
12	42.6	-	-	-
P,abs. Upper	421	323	245	186
Lower	353	304	304	196
Total	774	627	549	382

Table 3.26 Agar slab at an initial temperature of 5 °C

Depth	Slab thickness - cm.	
cm	10	8
	Δt	Δt
0	53.0	38.0
1	44.1	33.8
2	32.0	26.0
3	20.9	16.0
4	12.3	12.6
5	8.9	15.0
6	10.5	26.0
7	15.6	39.5
8	25.9	45.1
9	38.1	—
10	46.0	—
P, abs. Upper	333	245
Lower	274	284
Total	607	529

Table 3.27 Temperature profiles for agar slabs

Composition of solid: water, 99%: Ionagar, 1%.

Slab Thickness cm.	Initial temp. Degrees C	Power density-watts/cm ²		Total P,abs -watts		
		Upper	Lower	Upper	Lower	Total
12	20	12.0	10.1	421	353	774
10	20	9.2	8.7	323	304	627
10	5	9.5	7.8	333	274	607
8	20	7.0	8.7	245	284	529
8	5	7.0	8.1	245	284	529
6	20	5.3	5.6	186	196	382

Fig.3.1 Major components of the microwave oven

3.1(a) schematic diagram

3.1(b) details of waveguide entry ports into the cavity

Fig.3.2 The oven cavity

3.2(a)top

3.2(b)front

SCALE:- 1 : 1/4

Fig.3.3 Temperature distribution using 'Thermocolour'

3.3. position 1

3.4. position 2

SCALE:- 1 : 1/4

Shaded areas represent hot regions.

Fig.3.5 Cooling curve for lagged agar gel

3.5(a)method

3.5(b)cooling curve

Fig.3.6 Arrangement of thermocouples in 3 by 3 array

3.6(a) 6cm. array

3.6(b) 2cm. array

Fig.3.7 Array positions for aliquots of water

3.7(a) 4 by 5 array

3.7(b) 2 by 3 array

Fig.3.8 Energy distribution pattern at shelf position 2

3.8(a)silica gel.

Shaded areas represent hot regions.

Front

3.8(b)thermocolour

Front

3.8(c)agar/egg white (1 litre)

Front

Fig.3.9 Effect of the volume of egg white/agar gel.

3.9(a) 1/2 litre

3.9(b) 1 litre

3.9(c) 2 litres

Fig.3.10 Effect of shelf position ~ 'thermocolour'

3.10(a)shelf position 1

Shaded areas represent hot regions.

3.10(b)shelf position 2

3.10(c)shelf position 3

Fig.3.11 Effect of shelf position - silica gel

3.11(a)shelf position 1

Shaded areas represent hot regions.

3.11(b)shelf position 2

3.11(c)shelf position 3

Fig.3.12 Effect of shelf position - egg white/agar gel.

3.12(a)shelf position 1

Shaded areas represent hot regions

3.12(b)shelf position 2

3.12(c)shelf position 3

Fig.3.13 Cooling curves for volumes of water contained in 100ml beakers

Ambient temperature: 20°C

Fig3.14 Power loss caused by evaporation of water from 100ml glass beaker

Fig. 3.15 Power absorption by water and corn oil

Fig.3.16 Power absorbed by 30% sucrose solution v. volume of solution

Fig.3.17 Power absorbed by 30% sucrose v weight of water in solution

Fig.3.18 Power absorption by 60 grams of egg albumin

Fig.3.19 Power absorption for sucrose solutions

Fig.3.20 Power absorption for 60 grams of salt solution

Fig.3.21 Power absorption for 60 grams of starch paste

Fig.3.22 Attenuation of power from an electromagnetic wave
with radiation normal to the surface of the propagating
medium.

Fig.3.23 Measurement of the absorption coefficient

(a) semi-infinite solid

(b) metal shielding

(c) large cube of material

(d) arrangement of thermocouples

Fig.3.24 Effect of oven shelf height on temperature variation

T_d = temperature at any point — temperature at coldest point

Fig.3.25 Effect of depth of agar on the temperature distribution

Fig. 3.26 Effect of delay between the end of the heating cycle
and the temperature measurement

3.26(a) Δt against depth

3.26(b) $\log \Delta t$ against depth

Fig. 3.27 Typical temperature profile in agar gel

Initial temperature: 5°C

Heating time: 60 seconds

Fig. 3.28

Power absorption for data in Fig. 3.27.

Fig.3.29 Calculation of the total power absorption
 For the experimental data and for the asymptote
 to the experimental curve.

	Experimental data	Asymptote
Area (cm ²)	2.55	8.44
Power density (watts/cm ²)	10.2	34.0
Total power (watts)	357.0	1190.0

Fig.3.30 Variation of the absorption coefficient with temperature

Fig.3.31 Temperature distribution in a 9 cm cube

3.31(a) Experimental arrangement

3.31(b) Calculated temperature profile

Fig.3.32(a) Temperature distribution in a 9 cm cube of agar

Fig.3.32(b) Comparison of experimental and calculated temperature distribution

Fig.3.33 Temperature profiles for agar slabs

3.33(a) Theoretical arrangement for infinite slab

3.33(b) Experimental arrangement

Fig. 3.34 Power absorption for slab

3.34(a) P_{upper} 3.34(b) P_{lower} 3.34(c) $P_{\text{upper}} + P_{\text{lower}}$

SECTION 4 - SIMULATION OF THE TEMPERATURE PROFILE

4 SIMULATION OF THE TEMPERATURE PROFILE IN HIGH WATER CONTENT

SOLIDS

4. 1 INTRODUCTION.

The rate of temperature rise, at a depth of x cm in a semi-infinite solid, with microwave radiation normal to the surface, is given by an equation of the form:

$$\frac{dt}{dT} = C \cdot \exp(-k \cdot x) \dots\dots\dots (4.1)$$

$$\text{where } C = \frac{(1 - e^{-k \cdot \Delta x}) \cdot P_0}{J.S. \cdot \rho \cdot \Delta x}$$

(The derivation of these equations is given in Section 3.4.1, equation 3.9) The absorption co-efficient k , describes the attenuation of energy in the direction of propagation of the radiation. As shown in Section 3.1 this varies with temperature, because of the temperature dependance of K_s , T_r and K''_{ionic} (discussed in Section 2.3.2).

Therefore, where appreciable temperature rises occur, equation 4.1 becomes complex and difficult to integrate. Also, the temperature rise at any point will be modified because of heat transfer processes. Finite difference methods are commonly used for solving transient heat transfer problems (Gebhart, 1971); this technique can be modified to incorporate internal heat generation caused by the absorption of microwave energy.

The finite difference method of calculating internal heat generation in a semi-infinite solid is described in Section 4.2; this is restricted to the case of a solid material, with the same dielectric properties as water. The simulation is

extended to the case of an infinite slab in Section 4.3. In the following section, a finite difference method for calculating the effect of conduction and convection heat transfer is described and this is incorporated in the simulation. The application of this technique to foodstuffs is discussed in Section 4.5. Results from the simulation are compared with the experimental data of Section 3 in Section 4.6 and in the last section use of the simulation in a predictive mode is described.

4.2 SEMI-INFINITE SOLID WITH MICROWAVE RADIATION NORMAL TO SURFACE

4.2.1. Finite difference method

A semi-infinite solid has a single plane surface, extending to infinity in all other directions. For the purposes of this simulation it is assumed that the microwave radiation is normal to the plane surface, as shown in Fig.4.1. The incident radiation has a power density of P_0 watts/cm². The slab is divided into a number of thin slabs, each of thickness Δx cm, identified by the suffix n . The heating period is divided into a number of incremental time intervals, of duration $\Delta \tau$ seconds and identified by the suffix p . Thus Δt_{np} refers to the rise in temperature at the n th slab and at the p th time interval. This temperature rise can be calculated from a knowledge of the difference in the power levels at the faces of the slab.

$$\Delta t_{np} = (P_{n-1} - P_n) \cdot \frac{\Delta \tau}{J \cdot S \cdot \rho \cdot \Delta x} \dots\dots\dots (4.2)$$

where P_{n-1} is the power density at the front face of the incremental slab and P_n is the power density at the far face. The relationship between these two power levels is given by equation 2.25, which can be incorporated in 4.2 giving:

$$\Delta t_{np} = P_{n-1} (1 - e^{-k \cdot \Delta x}) \cdot \frac{\Delta \tau}{J \cdot S \cdot \rho \cdot \Delta x} \dots\dots (4.3)$$

From this equation the temperature rise in the first time period can be calculated ($P_{n-1} = P_0$) for each incremental slab, starting with the first and using the calculated value

of P_n as the value of P_{n-1} for the subsequent slab. Values of k can be selected for the material which is being simulated at its initial temperature.

This can be repeated for a number of time intervals until the value of $(p, \Delta \tau)$ is equal to the total heating time for the simulation. For any incremental slab, the total temperature rise can be calculated from the summation of the incremental temperature rises:

$$\Delta t_n = \sum_{p=0}^{p=m} \Delta t_{np} \dots\dots\dots (4.4)$$

where m is the number of time intervals. In practice the values of temperature rise are summed after each time increment, so that a value of k can be chosen for the subsequent time interval at the appropriate temperature.

The accuracy of a finite difference method depends on using small values for the depth and time increments (with unsteady state heat transfer the ratio of increments is also important - see Section 4.4). For this reason a computer was used for the solution of the temperature profile simulation.

The simulation was performed on the computer of the University of Surrey Computing Unit. The programs discussed in this section were written in Algol 60, programs and data prepared on punched cards and output was taken from the line printer. The symbols used in the program are described in appendix III.

4.2.2 Selection of a suitable value for k

For a food material whose dielectric properties are known over a wide range of temperatures, a graph of k against temperature can be prepared, using equation 2.27; this is done for water in Fig. 3.30. This information can then be included in the program, either in the form of a regression equation, or as a set of data, each component of the set referring to a known temperature range. An alternative approach is to calculate the dielectric properties for the material, using equations 2.13 and 2.15 from which k can be calculated, using equation 2.27. To facilitate comparison of these techniques, and to allow flexibility of the program for materials of varying dielectric properties, a 'Procedure' was used for the calculation of k , identified by the name 'SELECT K'.

4.2.2.1 Array of values of k .

From the data in Fig 3.30, values of k for water, at two degree intervals, were prepared and these were stored in the computer in the form of a 50 element array, each location being identified by a number from 1 to 50. When calculating the value of Δt_{np} , a temperature of (Initial temp + t_{np-1}) is used.

This corresponds to the temperature, at the same location in the solid, at the end of the previous heating period. This is stored in an array from 1 to N , where N is the total number of incremental slabs. Thus, for the n th slab the temperature is stored in location Temp (n). The procedure used for selecting a value of k , appropriate to this temperature, is given in Appendix IV (1).

4.2.2.2 Calculation of k from T_r and K_s

For some materials, such as water, values of K_s , T_r and K_o are known over a wide range of temperatures. From these K' and

and K''_{dip} can be calculated. For materials of low conductivity, K''_{dip} is the same as K''_{total} ; therefore k can be calculated from K' and K''_{dip} using either equation 2.27, or equation 2.28. These are rewritten in the form of k below.

$$k = \frac{2\sqrt{2}\pi\sqrt{K'}}{\lambda_0} \left[(1 + \tan^2 \delta)^{\frac{1}{2}} - 1 \right]^{\frac{1}{2}} \dots\dots\dots (4.5)$$

$$k = \frac{2\pi K''}{\lambda_0 \sqrt{K'}} \dots\dots\dots (4.6)$$

4.5 is the accurate form of the equation, the simplified form being suitable for materials for which $\tan \delta \ll 1$.

The relationship between temperature and K_s is discussed in Section 2.3.2. K_s was calculated using the first two terms of equation 2.15 and taking K_s at 0 degrees C as 87.7; calculated values are compared with the literature values in Fig.4.2. The simplified equation:

$$K_{s_t} = K_{s_0} - (0.4 \times t) \dots\dots\dots (4.7)$$

was considered to be sufficiently accurate for the simulation.

Saxton (1952) demonstrated that, over the temperature range 0 to 50 °C. the ratio of viscosity and Tr is constant. Since the relationship between viscosity and temperature is exponential, it follows that Tr will also have an exponential relationship with temperature. Values of Tr for water were obtained from the data of Lane and Saxton (1952a) and Von Hippel (1954); the best fit to this data was given by the expression:

$$Tr_t = \left[16.3 \times \exp(-0.033 \times t) + 2.4 \right] \times 10^{-12}$$

..... (4.8)

(see fig. 4.3) K_0 is independent of temperature and Hasted (1961) gives it a value of 5.5.

K_0 , K_s and Tr can then be used to calculate K' and K''_{dip} , which can in turn be used to calculate the value of k at any temperature between 0 and 100 °C. A procedure for calculating k by this technique is given in Appendix IV(2).

4.2.3. Numbering of incremental slabs

A numbering system is required for the array which is to store the temperature, at a point in time, for each element of the solid. The temperature rise in an incremental slab, using equation 4.3, is an estimate of the overall temperature rise in that slab. If this is taken to represent the centre point of the slab, it will represent a temperature at a point $(n + \frac{1}{2})$. Δx cm from the surface of the slab.

For the simulation, a large number of incremental slabs, of small thickness, are used. The result of the simulation are not required for all of these slabs: the program is designed to select integer depth values to present as the output. With the numbering system in Fig. 4.1 it is not possible to select exact integer values. An alternative numbering system is shown in Fig. 4.5: with this system the centre of the incremental slab is sited at a depth $(n \cdot \Delta x)$, so that, in this case, exact integer values can be chosen. The calculation of power absorption is still the same as for the numbering system given previously, except in the case of the first slab. This will have a thickness of $\Delta x/2$, so that the temperature will represent

a depth of $\Delta x/4$. This temperature is used as an estimate of the surface temperature.

When comparing the results of the simulation with practically measured temperature profiles, and with the addition of surface heat transfer processes, it is necessary to provide a far surface. This surface slab will also have a thickness of $\Delta x/2$, so that the total depth of the slab will be equal to:

$$\frac{\Delta x}{2} + (\Delta x \cdot n - 1) + \frac{\Delta x}{2} = n \cdot \Delta x.$$

But, in this case $n + 1$ storage locations are required, because of the two slabs of half thickness. If n is equal to the depth of the slab divided by the thickness of a single increment, then an array of $n + 1$ elements is required to store the temperatures - $TEMP(0:N)$, where $TEMP(0)$ refers to the front surface temperature and $TEMP(N)$ stores the temperature at the rear face.

An example of a program used to calculate the temperature profile in a solid, with microwave radiation from one side only, is given in Appendix IV(3).

4.3 INFINITE SLAB WITH MICROWAVE RADIATION NORMAL TO BOTH FACES

For the simulation, it is assumed that the radiation is normal to the surfaces. Interference effects between the two wave-fronts are not considered and the heating effects of the two waves are taken as being additive. The program used for this simulation is essentially the same as that for the infinite solid, except that in this case a store is required to add power absorption, for each of the waves. Thus the power absorption is calculated for the wave incident to the upper surface (P_u) and this is stored in an array - POWER (0:N). This operation is repeated for the lower incident wave (P_l) and the power absorption is added into that already calculated for the upper wave. The combined power absorption is then used to calculate the temperature rise in each slab. After each time increment, the temperature rise is stored into the appropriate location in the array TEMP (0:N) and the Power array is zeroed.

The complete program for producing the simulation is given in Appendix IV(4). The program reads in a set of data (density, initial food temperature, specific heat, depth of slab, depth increment Δx , heating time, time increment Δt , and the surface power density P_u and P_l). After completing the sequence of calculations, it prints out a set of tabulated results together with a list of the input data. A flow diagram of the program is given in Fig. 4.4. If P_u or P_l is zero, the simulation simplifies to that for a semi-infinite solid.

4.4. HEAT TRANSFER

Many finite difference methods are available for calculating one, two and three dimensional unsteady state heat transfer (Gebhart, 1971). In the case of semi-infinite solids and infinite slabs, heat transfer is restricted to a single dimension.

A finite difference method is available for calculating temperature changes, allowing for internal heat generation, which could be caused by the absorption of microwave energy. However since a program for calculating this internal heat generation had already been prepared and tested, the finite difference heat transfer calculation was used as a correction to this existing program.

4.4.1 Finite difference methods for calculating heat transfer changes.

The slab is divided up into incremental slabs as in the previous section - see Fig. 4.5. Fig 4.6 shows the slab location for an internal incremental slab.

Heat flow in - heat flow out = change in enthalpy

$$\frac{Kc \cdot t_{(m-1)p} - t_{mp}}{\Delta x} - \frac{Kc \cdot t_{mp} - t_{(m+1)p}}{\Delta x} = \frac{S \cdot \rho \cdot \Delta x \cdot t_{m(p+1)} - t_{mp}}{\Delta \tau}$$

$$t_{(m-1)p} - 2 \cdot t_{mp} + t_{(m+1)p} = \frac{S \cdot \rho}{Kc} \cdot \frac{\Delta x^2}{\Delta \tau} \cdot (t_{m(p+1)} - t_{mp})$$

$$= \frac{\Delta x^2}{\alpha \cdot \Delta \tau} (t_{m(p+1)} - t_{mp}) \dots \dots \dots (4.9)$$

(α , the thermal diffusivity, is equal to $Kc/S \cdot \rho$)

Equation 4.9 can be used to calculate the change in temperature in the m th slab, at the $(p+1)$ th time interval. For a convergent solution, the ratio of $\Delta x^2 / \alpha \cdot \Delta \tau$ must not be less than 2 (Gebhart, 1971b). Equation 4.9 can be further simplified by choosing an integer value for this ratio. (This ratio is the reciprocal of the Fourier No). For example, if this is set at its minimum value for a convergent solution of 2, equation 4.9 becomes:

$$t_{m(p+1)} = \frac{t_{(m-1)p} + t_{(m+1)p}}{2} \dots\dots\dots (4.10)$$

Thus the temperature for the m th slab at a time interval of $p+1$ can be calculated from a knowledge of the temperature of the two adjacent slabs at the previous time interval.

If the ratio $(1/F_0)$ is made equal to 4, a more complex solution is obtained:

$$t_{m(p+1)} = \frac{t_{(m-1)p} + 2 \cdot t_{mp} - t_{(m+1)p}}{4} \dots\dots\dots (4.10)$$

The disadvantage with these simplified solutions is that the thermal conductivity is fixed, whereas in practice it is itself a function of temperature. For materials whose thermal conductivity is known over a wide range of temperatures, equation 4.9 will give the most accurate solution. This data is not available for most food materials; also the amount of thermal conduction which occurs during a 60 second heating period is small. (It does however become important where a long delay time is used, or where thick objects are heated (Ohlsson and Bengtsson, 1971). The Fourier No, F_0 , is equal to $\frac{\Delta \tau \cdot K_c}{\Delta x^2 \cdot \rho \cdot S}$)

The slab location at the surface is shown in Fig 4.7. An overall surface heat transfer co-efficient is used; this

includes convective and radiative heat transfer changes.

Heat gained from surroundings + heat gained from adjacent slab =
increase in enthalpy.

$$h.(t_f - t_{op}) + Kc (t_{lp} - t_{op}) = \frac{s \cdot \rho \cdot \Delta x}{\Delta \tau \cdot 2} (t_{o(p+1)} - t_{op})$$

$$\frac{\Delta x \cdot h}{Kc} (t_f - t_{op}) + t_{lp} - t_{op} = \frac{1}{2 \cdot F0} (t_{o(p+1)} - t_{op}) \dots (4.11)$$

Equation 4.11 is equivalent to 4.9 for the internal slab. If $h, Kc, \Delta x, \Delta \tau, s, \rho, t_f, t_{op}$ and t_{lp} are known, 4.11 can be used to calculate $t_{o(p+1)}$ the surface temperature after the first time increment.

$$t_{o(p+1)} = \frac{\Delta x \cdot h}{Kc} (t_f - t_{op}) + t_{lp} \dots (4.12)$$

The most accurate method of simulating heat transfer changes is to calculate Kc for each slab at each time interval and to use this to calculate a value for $F0$. This method was used by Manson et al (1970) for calculating the thermal history of materials heated in a rectangular container, and also by Ohlsson and Bengtsson (1972) for producing temperature profiles of foods heated in a microwave oven.

For the simulation described in this section, the effect of conductivity is less than that of internal heat generation. Typically, practical measurements of temperature profiles were made 90 seconds after the commencement of the heating cycle, during which time heat transfer effects will be small except at the surface of the solid. The value of the thermal conductivity of water changes from 1.488×10^{-3} cal/sec. cm. $^{\circ}\text{C}$ at 10°C to 1.629×10^{-3} at 100°C . Therefore if a value at an intermediate temperature is used the error will be of the order of 5%. For

most food materials, values of the thermal conductivity are not known to this degree of accuracy. It was therefore considered that a simulation using a fixed value of K_c would be suitable. This limitation must be considered if the simulation is used in a situation where there is a long heating time, where there is a large delay between the end of the heating time and the measurement of temperature and where thick slabs are being heated (which rely on conduction for their internal heating).

4.4.2 Choice of values for thermal properties

Accurate values for the thermal conductivity of water are available (Gebhart, 1971). These were used for the simulation of the heating effect in 1% agar gels. Surface heat transfer co-efficients are known for a limited number of food materials, or they can be calculated from formulae (Earle, 1966). Because of the unreliability of these results surface heat transfer co-efficients were measured practically using the simulation discussed above, but in the absence of any microwave heating.

Internal heat transfer:

For the simulation, the dimensionless constant FO must have a value of $\frac{1}{2}$; this means that depth and time increments can not be chosen at random.

$$FO = \frac{\Delta T \cdot K_c}{\Delta x^2 \cdot \rho \cdot S}$$

Therefore if $FO = \frac{1}{2}$

$$\frac{\Delta T}{\Delta x^2} = \frac{\rho \cdot S}{K_c \cdot 2}$$

Using a value of K_c for water at 50 °C, the ratio of $\Delta T / \Delta x^2$ is 338 seconds/cm². If the value of Δx is fixed by the dimensions

of the incremental slab, then the value of ΔT is also fixed.

If $\Delta x = 1$ cm, then $\Delta T = 338$ seconds

" " 0.1 " " " = 3.4 "

" " 0.01 " " " = 0.034 "

For the simulation values of 0.1 cm for Δx and 3.4 seconds for ΔT were used. A more accurate simulation could be obtained using 0.01 cm but this requires excessive store locations.

To obtain values for h measurements were made on agar gel cylinders of the same proportions as were used for the microwave heating experiments (see Section 3.5). A known constant initial agar temperature was used and the agar placed in a constant temperature incubator. Temperature were measured at 1 cm intervals in the slab using thermocouples. Since the heat transfer simulation is valid only for single dimension heat transfer, it was necessary to lag the walls of the cylinder to minimise any heat transfer through these walls.

Results of measurements are shown in Fig. 4.8; this shows the temperature profile in the agar after 30 mins. The upper curve shows the rate of cooling, from an initial agar temperature of 40°C and an air temperature of 20°C . The lower curve relates to the heating of a block of agar from an initial temperature of 20°C , after 30 minutes in a constant temperature cabinet at 40°C .

The computer program used in the simulation is given in Appendix IV(5). Different values are used for the surface heat transfer co-efficient at the upper and lower surfaces and for when the surface was heating and cooling. These are identified as:

- h'_{tsa} - Upper surface, surface hotter than air,
- h_{tas} - Upper surface, air hotter than surface,
- h_{bsa} - Lower surface, surface hotter than air,
- h_{bas} - Lower surface, air hotter than surface.

The program incorporates equations 4.9 and 4.12: equation 4.12 is used for the two surface incremental slabs and 4.9 for the internal incremental slabs. Starting at a time increment of zero, the program calculates the temperature at the first slab (0), after one time interval and repeats this for all of the slabs up to the depth of the complete slab. The whole operation is then repeated for the second time increment and for subsequent increments, until the sum of all of the time increments is equal to the total process time.

Two stores are required for storing temperature values: TEMP 1 (0: n) for t_{np} and TEMP 2 (0: n) for $t_{n(p+1)}$. After each time increment TEMP 1 (0: n) is made equal to TEMP 2 (0: n).

Using a trial and error method, values of the four heat transfer co-efficients were adjusted to give the 'best fit' to the experimental data. This is shown in Fig 4.8 for which values of surface heat transfer co-efficients were as follows:-

$$\begin{aligned} h_{tas} &= 2.7 \times 10^{-4} \text{ cal/sec.cm}^2 \cdot ^\circ\text{C} \\ h_{tsa} &= 7.0 \text{ " " " " } \\ h_{bas} &= 1.0 \times 10^{-3} \text{ " " " " } \\ h_{bsa} &= 5.3 \times 10^{-4} \text{ " " " " } \end{aligned}$$

4.4.3 Complete simulation for water, with microwave heating and heat transfer

The two simulations, for microwave heating alone (Appendix IV4) and for heat transfer alone (Appendix IV5), can be readily combined to give a simulation of the full heat transfer mechanisms involved in the microwave heating of a semi-infinite solid and an infinite slab. A simplified flow diagram of the complete simulation is given in Fig 4.9; the complete program, including the procedure used for printing out results, is given in Appendix IV (6). A typical result printout is shown in Appendix IV (7). The results

obtained from the simulation are compared with the measured temperature profiles of Section 3 in Section 4.6.

The 'equilibration time', referred to in Fig 4.9, is a simulation of the time delay between the end of the heating process and the measurement of temperature.

4.5 SIMULATION FOR MATERIALS OTHER THAN WATER

4.5.1. Methodology

The simulation given in Section 4.1 to 4.4 enables the production of the temperature profile in a slab of solid material, with the same physical and dielectric properties as water. For materials other than water, the procedure 'Select K' can be modified to give a value of k for any material whose dielectric properties are known.

As in the case of water (Section 4.2.2.) there are several possible approaches to the selection of a value of k at any temperature. Using the method of De Looze, discussed in Section 23, it is possible to calculate the effect of non-polar solids on the dielectric properties of water; these modified dielectric properties can then be used to calculate K' , K'' and k .

There are many cases where this approach leads to erroneous results; in Section 2.3.5 it was shown that it was not possible to predict the dielectric properties of skim milk from a knowledge of the dielectric properties of its ingredients. Also these methods do not give any information on the effect of temperature on these calculated dielectric properties.

An alternative approach is available for those materials whose dielectric properties are well documented, over a wide temperature range. For these materials, a regression equation, of k as a function of temperature, can be used as the basis of the procedure 'Select K'. Ohlsson and Bengtsson (1971) used this approach for calculating the temperature profile in meat products, after a microwave heating process. Using a linear extrapolation of K' and K'' at 20, 40 and 60 °C, the value of k was calculated, this was used in finite difference computer program which produced a temperature profile.

These two alternative approaches to the preparation of the temperature profile in a food material, are discussed in Section 4.5.2 and 4.5.3.

4.5.2 calculation of the dielectric properties of a mixture

4.5.2. 1 Non-polar solids and water:

Equation 2.18 can be used to calculate the static dielectric constant for a mixture of water and a non-polar solvent. As an example, for a 20% sucrose solution, the volume concentration is 0.12, which, assuming that the particles are spherical, gives a value of K_s for the mixture of:

$$K_s = 0.83 \times K_{s_{\text{water}}} + 0.83 \dots\dots\dots (4.13)$$

Equation 4.13 can easily be added to the procedure 'Select K' given in Appendix VI (2); it is necessary to assume that the relationship between temperature and $K_{s_{\text{water}}}$ is not affected by the presence of the solid. Equation 4.13 is added to the program after the calculation of K_s at the temperature appropriate to the slab location.

The only other modification to the program is to use the physical properties for the sugar solution; for the sugar solutions these can be obtained from tables (Norrish, 1967).

Equation 2.17 can also be used to calculate K_s for a water solid mixture, in which a proportion of the water is irrotationally bound to the solid. Table 2.7 gives the amount of bound water associated with some food materials. For a 10% solution of a solid in water, the volume concentration v is 0.6: if 1g of water is bound to each gram of solid, v will have a value of 0.12, the same as for a 20% solution with no bound water. Thus an equation of the same type as 4.13 should be suitable for the case of non-

polar solid with bound water.

4.5.2.2 Aqueous sodium chloride solutions:

Salt has a profound effect on the dielectric properties of water. This was discussed in Section 2.3.4. It decreases the value of the static dielectric constant, causes a shift in the value of the relaxation time and increase the value of K'' total because of ionic conductivity.

The effect on K_s is given by equation 2.20. For a 1% solution of sodium chloride, this reduces to the form:

$$K_s = K_{s, \text{ water}} - 1.87 \quad \dots\dots\dots (4.14)$$

and can be added to the procedure 'Select K', as described in the previous section.

Ionic conductivity can be converted to K''_{ionic} , using equation 2.18; Table 2.4 shows, that for a 1% sodium chloride solution, K''_{ionic} has a value of 11.5. This can be added to the calculated value of K''_{dipole} to give the value of K''_{total} . Since ionic conductivity is a function of temperature it is necessary to have an equation expressing this temperature dependence. Equation 2.20 gives this relationship, in terms of the temperature co-efficient of resistivity; this can be rearranged to give:

$$K''_{\text{ionic}} = \frac{720}{[63 - 0.819 (t-20)]} \quad \dots\dots\dots (4.15)$$

The relationship between salt content and relaxation time is shown in Fig.2.1. For a 1% salt solution (0.17N) this is not significantly different than the value for water, except at lower temperatures. For the purposes of the simulation, it was assumed that T_r for a 1% salt solution was the same as that for water.

4.5.2.3 Comparison of calculated values of dielectric properties of food with measured values. Fig. 4.10 shows the theoretical effect of mixtures of water with a non-polar solid; the three lines on the graph show the effect of water content on K' , for solids with 0, 0.5 and 1.0 g/g of bound water. Also on the graph are shown the value of K' for some foodstuffs of known water content. The majority of foods were found to fall within the three curves on the graph, indicating that equation 2.17 does provide a reasonable model for the behaviour of foods.

Fig. 4.11 shows the same results for calculated and experimental values of K'' . The calculated value of K'' is due to dipole relaxation only; it does not include an estimate of K'' ionic. It can be seen from the graph that ionic conductivity is a large contributor to the value of K'' total, the experimentally measured values.

Unfortunately little information is available on the ionic conductivity of food materials (some information is given in Table 2.8). Some of the data given by Bengtsson and Risman (1971) is for meat products with high, known salt contents. The ionic conductivity can be calculated for this salt, which can then be used to calculate K'' ionic: this very approximate method of calculating the dielectric properties for materials of high salt content is compared with the experimentally measured values of Bengtsson and Risman in Table 4.1.

Column 3 gives the conductivity of a pure aqueous salt solution. This is corrected for the presence of other solid material, as discussed in Section 2.33, which causes a reduction in the value of the ionic conductivity. Column 4 shows this correction, assuming that there is no bound water whilst column 5 gives the corrected value, assuming 1g/g of bound water. This is then converted to relative permittivity (columns 6 and 7) and added to the calculated K'' dipole (shown in columns 8 and 9) to give the total value of K'' , shown in columns 10 and 11. For

comparison, the experimental value of K'' for the meat product is given in column 12.

Schwann (1955) gives a range of 0.2 to 0.5 for the amount of bound water found in protein. In the case of meats with 3.7 and 6.1% salt, the range of the calculated values does encompass the experimental value. In the case of the meat with no sodium chloride it would appear that the naturally occurring meat salts do contribute to the value of K'' total, as shown by the higher results obtained experimentally compared with the value calculated on the basis of dipole relaxation alone.

4.5.3 Use of literature values of K' and K'' of foods to calculate k

If values of K' and K'' are known for a food material, over a wide range of temperatures, it is possible to calculate k directly from these values. The calculated value of k can then be used in the procedure 'Select K' ', either in the form of a regression equation, or as a set of temperature related data in a procedure of the form discussed in Section 4.2.2.1.

The only difficulty which arises in using this technique is that the required information on dielectric properties over a wide range of temperatures. The most comprehensive source of data is given by Bengtsson and Risman (1971). This survey includes many food materials, but only over the range of 0 to 60 °C: extrapolation of this data to temperatures over 60 °C could lead to significant errors. Fig. 3.30 shows that for water the rate of change of k with temperature decreases with temperature, so that a linear extrapolation of data over 60 °C would give erroneous values. This method should however give good results for temperature rises up to this temperature. This method was used for some meat products, and the temperature profile compared with the experimentally measured profile of Ohlsson and Bengtson (1971).

4.6 RESULTS OF THE SIMULATION

4.6.1 A comparison of the simulated temperature profiles with experimental results.

Figures 4.12 to 4.16 give a comparison of temperature profiles measured on agar gels with simulated profiles utilising the dielectric properties of water, using the methods described in Sections 4.2, 4.3 and 4.4. Results of the simulation are given in Tables 4.2 to 4.8. Fig. 4.12 illustrates the effect of using three different heating times while Fig. 4.13 shows the effect of the initial temperature of the solid. The effect of a delay between the end of the heating time and the time at which the temperature is measured is shown in 4.14. Results for agar slabs, with microwave radiation incident to two faces, are shown in Figs. 4.15 and 4.16

Figs 4.17 to 4.21 show the results of simulations on food materials. Fig. 4.17 shows simulated and experimental results for solids containing 1% salt; the simulation uses the methods discussed in Section 4.5.2. In Fig. 4.18, a comparison is made between simulations for a mixture of 90% water and 10% non-polar solid, with experimental results on a 10% sucrose solution. The effect of ~~irrotationally~~ bound water associated with a non-polar solid is illustrated in Fig. 4.19 and these results are compared with profiles for raw and cooked corn starch in Fig. 4.20.

All of the results given above use values of K_s , K_o and T_r to calculate K' and K'' , which are then used to calculate k ; for the example given in Fig. 4.21, values of K' and K'' for beef, over a range of temperatures, are used to calculate k .

Literature values of the dielectric properties for beef were taken from the work of Bengtsson and Risman (1971) and the

computed temperature profile is compared with experimental values on beef (Ohlsson and Bengtsson, 1971).

4.6.2 The use of the simulation to predict temperature distributions

The results given above can be used to define the conditions for which the simulation of the temperature profile is valid. The simulation was also used in a predictive mode: one of the main advantages of a computer simulation is that, once it has been validated, it can be quickly and easily used to investigate the effect of differing processing conditions. In fig. 4.22 the effect on the temperature profile of a range of air temperatures from +20 to +200 °C is illustrated and in Fig. 4.23 a comparison of the two common microwave frequencies is shown.

4.7 COMPARISON OF SIMULATED AND EXPERIMENTAL TEMPERATURE PROFILES

Temperature profiles, measured experimentally on agar gels, are compared with profiles produced by the simulation in Figs 4.12 to 4.16. For the simulations k was calculated from the dielectric properties of water, as described in Section 4.2.2.2. There are limitations in both sets of data which must be taken into account in any comparison. Errors associated with experimental results include:

1. high variability in temperature measurements;
2. the presence of metal shielding could affect the field pattern;
3. variations in the surface power density;
4. there is no way of ensuring that microwave radiation is normal to the surface.

Similarly the accuracy of the simulation is affected by the following factors:

1. the surface heat transfer co-efficient was obtained experimentally over a temperature range of 20 to 40 °C and has not been validated outside this range;
2. a temperature independent value for the thermal conductivity was used.
3. the effect of any standing wave interference effects in slabs of material were ignored.

Despite these limitations in both the experimental and simulated results reasonable agreement between the two sets of data was achieved.

Fig. 4.12 illustrates the effect of varying the heating time on the temperature profile. There was good agreement between the two sets of results except close to the surface. For the two longer heating times the measured surface temperature was lower than the predicted value. Since this surface temperature is greater than 40°C the deviation could be caused by too low a value for 'h' in the simulation. At these higher temperatures it is to be expected that 'h' would increase due to surface evaporation. A low value of 'h' in the simulation would result in a higher surface temperature. This apparent explanation of the facts is not confirmed by the results shown in Fig. 4.13 which gives temperature profiles for various initial temperatures. Here there was good agreement between experimental and simulated results even with a surface temperature as high as 70°C .

The results shown in Fig 4.14 confirm that the heat transfer section of the simulation is reasonably accurate, even though it contains several simplifications. These results compare experimental and simulated temperature profiles after time intervals of 10 and 40 minutes from the end of the heating period. After 10 minutes there was little difference between the two sets of results and even after 40 minutes the maximum deviation was only 5°C , which occurred at a depth of 1 cm. Thus, even with the simplifications in the value of 'h' and 'Kc', the heat transfer section of the program provides a satisfactory simulation for the water/agar gel.

Results for slabs of varying thickness are given in Figs 4.15 and 4.16 and these results also showed good agreement between experimental and simulated profiles. The values of P_u and P_l used in the simulation were obtained by graphical integration of the averaged experimental profile: this value is an underestimate of the true value since it does not include energy which is lost, as heat and by evaporation, from the surface. Also where

the energy absorption at the two surfaces is not uniform there will be an error in this calculated value of surface power density, as described in Section 3.5.3.1. A comparison of the results given in Figs 4.15 and 4.16 indicates that in all cases the simulation under estimates the true temperature value at the centre of the slab, the error varying between 1 and 4 °C. This could be caused by interference between the two wave fronts where they cross at the centre of the slab. With a lossy material such as water there is little energy left in the wave after a penetration depth of several centimetres so that this effect is not large.

The power absorbed through the two faces of the slab were not symmetrical: since the simulated power levels were based on experimental levels these were also not symmetrical. This asymmetry could be because of the uneven energy distribution in the cavity or it could be caused by distortions to the field by the metal shielding.

Simulations and experimental temperature profiles for solids containing simple foods are given in Figs 4.17 to 4.21. For these simulations specific heats and densities of the relevant aqueous solutions were used in the simulations and for the calculation of the surface power density. The surface heat transfer co-efficient and thermal conductivity used in the simulation had the same values as those used for the water/agar gel simulations. Values of k , the absorption co-efficient, are calculated by modifications to values of T_r and K_s for water, as described in Section 4.5.2. The simulation shown in Fig. 4.21 was calculated from measurements on the dielectric properties of beef (Bengtsson and Risman, 1971) and the simulated profile is compared with the experimentally measured profile for beef (Ohlsson and Bengtsson, 1971).

Fig 4.17 shows experimental results for a gel containing 1% salt compared with profiles for water, both after 60 seconds heating. The simulation for a 1% salt solution terminated before a period of 60 seconds had expired, because the surface temperature reached 100 °C. For comparison purposes Fig. 4.17b shows simulated profiles for 1% salt and water.

Both the simulated and experimental results for 1% salt display a pronounced surface heating effect compared with water. This is because the conductivity increases with the temperature causing both K' and K'' to have a positive temperature co-efficient whereas for water they have a negative temperature co-efficient. The positive co-efficient, in the case of salt causes a 'runaway' heating effect at the surface. This effect was greater in the case of the simulation, hence the surface temperature rapidly rose to 100 °C. This could be because of the constant value of surface heat transfer co-efficient; at these higher temperatures it is likely that the co-efficient would increase because of evaporation and hence increase the rate of surface cooling. in the case of the experimental results.

Fig 4.18b shows the experimental data for a 10% sucrose solution compared with the simulated profile for a mixture of 90% water and 10% non-polar solid, with none of the water bound to the solid: these results demonstrate a reasonable fit. Similar results for 40% sugar solution (shown in Fig. 4.18b) show poor agreement. The model used in the simulation uses a linear relationship between the dielectric properties and the solids content, whereas practical measurements for sugar solutions show a non-linear relationship between K'' and solids content (see Fig. 4.24a). This would account for the poor agreement for the higher solid content simulation. Thus at 40% solids the simulation uses a value of 8 for K'' whereas the true value

is 20. At 10% solids the deviation is not so marked.

A better fit for the simulation could be achieved by using literature values of K' and K'' in the simulation, as was done for the beef. Unfortunately the data of Roebuck et al (1972) is only at one temperature.

A similar comparison for starch is given in Fig. 4.25. Here again there is a discrepancy between the calculated value for non-polar solids and water with literature values for gelatinized and granular starch. As with the sucrose this discrepancy becomes more pronounced at higher solids content.

Fig. 4.19 shows the effect on the simulated temperature profile of bound water at two power levels. The effect of the bound water is to reduce the surface temperature, because of a reduction in the value of K'' caused by the irrotationally bound water. Fig. 4.20 shows a comparison between the simulations for a mixture of 10% non-polar solids and water and experimental temperature profiles for unhydrolised and hydrolised starch. It can be seen that for unhydrolised starch, the experimental results are similar to the simulation for 10% non-polar solids with 1 gram/gram of bound water. In the case of the hydrolised starch neither of the simulations gives similar results to the experimental profile. As well as the difference in the profile between hydrolised and unhydrolised starch, there is also a significant difference in the surface power density (8.7 watts/cm² in the case of unhydrolised and 6.5 for the hydrolised). From these results it would seem that the change in structure which occurs during starch hydrolysis causes a change in the electrical load in the cavity, and hence reduces the surface power density. Measurements on the dielectric properties of starch (Roebuck et al, 1972) show that

there is only a slight difference between unhydrolysed and hydrolysed starch. Therefore the cause of this difference needs further investigation before a simulation for hydrolysed starch can be achieved.

For materials, such as hydrolysed starch, whose dielectric properties cannot be successfully predicted from those of water together with a knowledge of the solids content, the percentage of bound water etc., it is still possible to obtain a simulation of the temperature profile if values of K' and K'' are known over a wide temperature range. The results in Fig. 4.21 shows the simulated temperature profile for beef compared with an experimentally measured profile for beef. Bengtsson and Risman (1971) give values of K' and K'' for beef at 0, 20, 40 and 60 °C. These were converted into single values of k (using equation 4.5) which were then extrapolated to give a range of values between 0 and 100 °C. These were then used in the simulation, as outlined in Section 4.2.2.1. Despite the dangers of extrapolating outside the range of experimental values, and although the heat transfer characteristics used in the simulation were those for water, there was a very good fit between the measured and simulated profiles.

The value of a simulation is that, once it has been validated, it can be used in a predictive mode, without the need for lengthy experimental work. The profile in Fig. 4.22 shows how the simulation can be used to demonstrate the effect of varying ambient air temperatures. The results are for a 60 second heating period and an air temperature of 20, 100 and 200 °C. The simulation could also be easily modified to allow for forced convection and radiant heating; thus the model could be extended to combined heat transfer processes.

The procedure 'Select K' ' can be easily modified to simulate any desired microwave frequency. Fig. 4.23 shows a comparison of

simulations in slabs of a solid, with the same dielectric properties as water, at 2450 and 915 MHz. The results obtained from the simulation indicate that at the lower frequency a more uniform heating effect is achieved. However interpretation of these results must be approached with care, as the simulation has only been validated experimentally at 2450 MHz.

An overall evaluation of the results in this Section indicates that the simulation technique, based on the dielectric properties of water, is accurate in predicting the temperature profile in high moisture content solid foods. However for materials with large amounts of solids and with electrolytes, the theoretical knowledge is insufficiently understood to allow prediction of the dielectric properties from those of water. For most foodstuffs, which are complex mixtures, a more accurate simulated profile can be achieved by using measured values of the dielectric properties (K' and K''). The disadvantage of this is that, at present, there is insufficient information available on the dielectric properties of foods over the temperature range 0 to 100 °C.

Table 4.1 Experimental and calculated values of K" for Pork At 20°C

Composition		Calculated values								Experimental value K"
Water	Salt	Conductivity	Conductivity		K" ionic		K" dipole		K" total	
		Water	Mixture		B=0 B=1		B=0 B=1		B=0 B=1	
		mMho/cm	B=0	B=1	B=0	B=1	B=0	B=1	B=0 B=1	
73	0	0	0	0	0	0	9.9	7.3	9.9.7.3	15.7
73	3.7	53.4	40.8	30.1	29.4	21.7	9.8	7.2	39.2 28.9	30.8
73	6.1	83.6	64.0	47.2	46.1	34.0	8.4	6.2	54.5 40.2	51.6

Table 4.2 Simulation: effect of heating time (t °C)

Pu 10 watts ; PL 0 ;

Initial temp. 5 °C ; Air temperature .20°C;

Density 1.000 g/ml ; Specific heat 1.000 cal/g/°C;

Equilibration time 30 secs; Depth 10 cm.

Depth	Heating time - secs.		
	30	60	90
cm	Final agar temp. °C		
0	38.4	56.1	68.1
1	30.2	51.3	66.9
2	18.0	36.2	52.0
3	10.5	22.9	37.0
4	7.1	13.4	23.7
5	5.7	8.4	14.0
6	5.3	6.2	8.7
7	5.1	5.4	6.3

Table 4.3 Simulation: effect of initial temperature.

Pu 10 watts: PL 0 ;
 Air temp. 20 °C, Density 1.000 g/ml ;
 Specific heat 1.000 ; Equilebration time 30 secs;
 Depth 10 cm ; Heating time 60 secs.

Depth cm	Initial temp. °C		
	5	20	40
	Final agar temp.		
0	56.1	60.3	67.7
1	51.3	59.1	70.7
2	36.2	48.6	64.2
3	22.9	39.4	58.5
4	13.4	32.1	53.8
5	8.4	27.0	50.0
6	6.2	23.8	47.1
7	5.4	22.0	45.0

Table 4.4. Simulation: effect of delay before temperature measurement.

Initial temp 20 °C; Air temp 20 °C ; Pu 10 watts.

Depth cm	Equilibration time		
	30 secs.	10 mins	40 mins.
	Final agar temp.		
0	60.3	43.9	32.0
1	59.1	50.1	36.4
2	48.6	47.4	38.0
3	39.4	40.6	37.0
4	32.1	33.8	34.3
5	27.0	28.5	30.1
6	23.8	25.0	27.7

Table 4.5 Simulation : slab at an initial temperature of 20 °C

	Slab thickness - cm.			
	12	10	8	6
Power- Pu	12	10	7	6
density _{PL}	10	9	9	6

Depth - cm	Final temperature: °C			
0	65.6	60.5	52.3	49.6
1	-	59.5	50.9	48.5
2	54.2	49.4	42.9	42.4
3	-	40.9	38.1	40.1
4	36.5	35.1	37.3	42.4
5	-	32.7	40.7	48.6
6	28.9	35.1	47.7	50.6
7	-	39.0	57.0	
8	33.5	46.8	59.4	
9	-	56.6		
10	49.0	59.1		
11	-			
12	61.8			

Table 4.6. Simulation: agar slab at an initial temperature of 5 °C.

Slab thickness - cm		
	10	8
Power P_u	10	7
density P_L	8	9
Depth - cm	Final temperature °C	
0	56.1	46.4
1	51.4	40.4
2	36.3	27.0
3	23.1	18.1
4	14.2	16.2
5	10.5	21.8
6	11.8	33.5
7	18.3	48.0
8	29.7	54.3
9	44.1	
10	50.8	

Table 4.7. Simulation: 1% sodium chloride at 20 °C

Heating time : 30 secs.

Pu : 8.5 watts

P_L : 0 watts

Depth	0% salt	1% salt
<hr/>		
0	41.7	71.8
1	38.3	39.6
2	31.2	25.0
3	26.3	21.3
4	23.4	20.3
5	21.7	20.1
6	20.9	20.0
7	20.4	20.0

Table 4.8 Simulation : non-polar solid and water at 5 °C.

Pu - watts					
	9	10	10	7	7
% solids	10%	10%	10% & 1g/g bound water	10% & 1g/g bound water	40%
Depth - cm					
0	52.4	55.5	51.9	43.0	44.5
1	47.6	51.1	48.8	38.5	40.1
2	33.5	36.8	36.5	26.8	28.8
3	21.3	23.9	25.0	16.3	19.2
4	12.8	14.4	15.8	10.9	12.5
5	8.2	9.0	10.4	7.5	8.6
6	6.2	6.6	7.0	6.1	6.6
7	5.5	5.6	5.8	5.4	5.7

Fig.4.1 Representation of a semi-infinite solid as a
number of incremental slabs

Fig.4.2 The relationship between K_s and temperature for water Fig.4.3 The relationship between Tr_t and temperature for water

Fig.4.5 Modified slab location system for the simulation

Fig.4.6 slab location for internal incremental slab

Fig 4.7 slab location for surface incremental slab

Fig 4.8 A comparison of experimental and simulated heat transfer

Fig.4.9 Simplified flow diagram for the calculation of microwave heating in a semi-infinite solid and infinite slabs

Fig. 4.10 A comparison of values of K' for food materials with calculated values for solid/water mixtures

Fig. 4.11 A comparison of experimental and calculated values of K''

Fig.4.12 Effect of heating time on the temperature profile

(a) 30 seconds

Initial temp: 5°C

(b) 60 seconds

(c) 90 seconds

Fig.4.13 Effect of initial temperature

(a) 5°C (b) 20°C (c) 40°C

Fig.4.14 Effect of delay between heating and measurement of temperature

(a) 30 seconds delay

(b) 10 minutes delay

(c) 40 minutes delay

depth - cm

Fig.4.15 Temperature profiles in agar slabs at 20 °C.

Fig.4.16 Temperature profiles in agar slabs at 5 °C.

Fig.4.17 Temperature profile for agar gel containing 1% salt

(a) experimental measurements: 60 seconds heating

(b) simulation: 30 seconds

Fig.4.18 Measured temperature profiles for agar gel containing sugar compared with a simulation for a mixture of water and non-polar solid

(a) 10% sugar and solid

(b) 40% sugar and solid

Fig.4.19 Simulation for water containing 10% non-polar solid and with bound water on the solid

Fig.4.20 Temperature profiles for agar gel containing corn starch

(a) uncooked starch

(b) cooked starch

Fig.4.21 Experimental and simulated temperature profiles for beef

— simulation: FU 2.5 watts, PL 0.3 watts, 3 min heating time

experimental data: Ohlsson and Bengtsson (1971)

Fig.4.22 Effect of air temperature on the simulated temperature profile

Initial temperature: 5°C

PU: 10 watts

Heating time: 60 seconds

Equilibration time: 30 seconds

————— + 20 °C
 - - - - - +100 °C
 +200 °C

Fig.4.23 A comparison of the simulated heating profiles at 2450 and 915 MHz for slabs of water at an initial temperature of 20°C

(a) 12 cm slab

(b) 6 cm slab

PU: 12 watts, PL: 10 watts

Fig.4.24 K'' for sucrose solutions at 25°C Fig.4.25 K'' for starch at 25°C

SECTION 5 - DISCUSSION

5. DISCUSSION

Microwave heating is now an established technique for heating foodstuffs. It is the only methods, currently used by caterers, which utilises internal heat generation. (Rf frequencies and the Joulian effect can also be used for internal heating).

During a recent survey of the catering industry, it became clear that there were many misconceptions about the nature and characteristics of microwave heating (Kirk, 1971). Some could be ascribed to erroneous or over simplified trade literature; in other cases it appeared that there was a genuine lack of knowledge about the characteristics of microwave heating in a catering microwave oven. The aim of this research was to study some of the areas which were not fully understood.

One of the more common problem areas is the use of a microwave oven for the thawing of frozen foods but since much research has already been carried out in this field, it was not considered in the present study.

Only "liquid" foods were considered with particular attention directed to: the distribution of energy in the oven cavity; the rate of energy absorption by food in the cavity; and the temperature distribution in the food after a period of heating. (The reasons for concentrating on these areas have already been discussed in the Introduction - Section 1.)

The experimental work was carried out in a typical microwave oven (Philips 1.2 kW Microwave Oven Model) designed for use by caterers. Some of the results will only be valid for this particular oven eg. the energy distribution forms a unique pattern even for ovens of the same make and model. However the results for the total power absorption should be generally applicable for all types of resonant cavity ovens, although

cavities can be tuned to maximise the efficiency of power absorption into any desired load. In addition the results on the temperature profile should hold for all types of microwave heating, including both resonant and travelling wave applicators.

5.1. DISCUSSION OF RESULTS

5.1.1. Energy distribution in the cavity

There are many methods described in the literature for measuring the energy distribution in a resonant microwave cavity; several of these methods are compared in Section 3.2.

Of the methods investigated, three demonstrated the energy distribution in the form of a two dimensional pattern for each shelf position in the oven. Using this method it is not possible to obtain a measure of the magnitude of the difference between the hotter and cooler areas. It was found that each of the techniques produced a different energy pattern; thus the energy distribution was a function of the test material in the oven, as well as the oven itself.

A measure of the relative difference in energy distribution in the cavity was obtained using arrays of beakers containing water placed at a number of points in the cavity. Here again, as with the heating pattern, a different result was obtained for each array pattern investigated.

The results of experiments, using an array of beakers, showed that there was greater variability if twenty beakers of water were heated at the same time, than if beakers were heated individually at each position in the array. The first method is often used to demonstrate the energy distribution in the cavity, whereas the second technique is more closely resembled to the normal food heating situation, with a single item of food in the oven at any one time. From the results of the experiment it can be seen that the use of an array of beakers, heated simultaneously in the oven is not a good indicator of variability of the heating effect in the cavity at different

positions for a single item of food.

Although each method of measuring the energy distribution produced different results, a few characteristics of the heating pattern were common to several methods, for example the presence of a 'hot spot' at the centre point of the lower shelf position.

The results which were obtained refer to a single oven. It is to be expected that every oven would produce a different energy pattern so that it is not possible to generalise, from these results, about the energy pattern in all microwave ovens. The value of the present results lies in the comparison of a large number of methods which have been described by other workers. It would be interesting and useful to compare several ovens of the same type and ovens from different manufacturers, using the techniques described above.

5.1.2. Power absorption

The effect of the size of the load on the power absorption by water, corn oil and 30% sucrose solution was investigated; the results are given in Section 3.3. The relative power absorption by equal amounts of various simple foodstuffs was also measured and the results are summarised in Table 3.13. When calculating heating times for food in microwave ovens, it is usually assumed that the power supplied to the food is constant for all load sizes of the same material and this gives rise to the generally accepted rule that for a doubling of the weight of material to be heated, the heating time should also be doubled, if the food is to be heated to the same final temperature. It was found in practice that this was only true for large loads of material (see fig. 3.15). Thus in the case of water, for loads greater than 600 ml the power absorption was constant at 800 watts (33% efficient); below this volume

the efficiency of the oven decreases as the volume decreases. Similarly for corn oil volumes above 650 ml have a constant power absorption of 800 watts. At lower volumes the corn oil was much less efficient at absorbing energy than was water.

It was also found that absorption was a function of the sample geometry. Thus for 60 ml of water a single 60 ml sample absorbed less energy (492 watts) than six 10ml samples heated simultaneously (745 watts). This is obviously a very important factor in microwave heating and requires a more rigorous investigation, as it relates to the situation common when heating complete meals where separate items of different shapes and sizes, are heated at the same time.

The results shown in Table 3.13 are for 60g samples, each of the same geometry and at the same position in the oven. Although the results are for a restricted number of food materials they cover a wide range of dielectric properties from corn oil ($\tan \delta, 0.06$) to salt solutions ($\tan \delta$, for 3% salt, 0.6). Water has dielectric properties intermediate between these two materials ($\tan \delta, 0.16$). For high water content food materials the heating effect was found to be proportional to the mass of water in the sample and not to the dielectric properties. This is particularly exemplified in the case of salt solutions, which have a high loss tangent but absorb less energy than water. Thus it can be seen that the relative heating effect of a food material cannot be predicted from its dielectric properties. This is confirmed in the case of large volumes of corn oil and water. With these materials the oven has a similar efficiency even though there are marked differences in the dielectric properties of the two materials. The loss tangent is not, by itself, a determining factor in the relative power absorption, as is often stated (Van Zante, 1968).

5.1.3 Temperature profiles

The attenuation of microwave energy by a lossy material follows an exponential decay in the direction of propagation of the wave. The absorbed energy is converted into heat, so that the temperature profile should also follow an exponential decay. In Section 3.4 the change in temperature with depth in a semi-infinite solid was measured.

It was found that the measured temperature profile showed great variability and to overcome this it was necessary to measure several profiles, for any set of conditions, and to average the temperature at each depth, to give a mean temperature profile.

When this mean profile was plotted as a graph of $\log \Delta t$ against depth a straight line was not obtained, indicating that the attenuation of microwave energy was not following an exponential decay. Inside the body the graph was in the form of a straight line, indicating that at a depth of about 4 cm inside the solid the absorption was behaving as predicted by theory. The non-linearity of the graph near the surface was found to be caused by the absorption co-efficient being a function of temperature together with changes in temperature due to surface and internal heat transfer. At the lower depths of the solid, where a straight line logarithmic graph was obtained, it was found that the slope compared well with calculated values of the absorption co-efficient, obtained from literature values of K' and K'' for water. The straight line portion of the graph was because changes in the value of k were negligible owing to the small temperature rises.

Because of the deviation from pure exponential behaviour, the use of half power depth figures are of limited value in describing changes in temperature with depth. Half power and $D_{1/e}$, measured at room temperature, are often quoted for food

materials, as a measure of the relative heating power at a depth inside the material. Similarly, values of K' , K'' and $\tan \delta$ at a single temperature do not provide a full explanation of the behaviour of materials in microwave energy; the relationship between temperature and absorption co-efficient is different for all materials (see Section 2.3.5.).

Temperature profiles were measured for semi-infinite solids of agar gels containing water, salt, sugar and starch and for water/agar slabs of various thicknesses. The results are given in tables 3.18 to 3.27.

To test the validity of the assumption that the non-linearity was due to variations in the absorption co-efficient with temperature, coupled with other heat transfer modes, a finite difference computer simulation was developed for temperatures between 0 and 100 °C, as described in Section 4. A comparison of the simulated and measured profiles is given in Section 4.7.

For the simulation it was necessary to calculate a value for k , the absorption co-efficient, for any temperature between 0 and 100 °C. One method used was to extrapolate literature values of K' and K'' for a food and to use these figures to calculate k . The second technique was to calculate k from the relaxation time and static dielectric constant for water, modified to allow for the presence of non-polar solids and electrolytes. The first method gave good agreement with measured profiles both for water and for beef: the difficulty with using this method is that values of K' and K'' over a wide range of temperatures, are only available for a few foodstuffs. The second method worked well for water/agar gels, water/starch/agar gels and water/sugar/agar gels containing up to 10% solids. However it gave poor agreement for high solid content materials and for electrolytes.

The simulation requires a value for the surface microwave power density which was obtained by graphical integration of the experimentally measured temperature profiles. The surface power density was dependent on the nature of the material, as was found with the total power absorption. The experimental values for agar containing various food materials are summarised in Table 3.18. The maximum surface density was found for water (10 watts/cm^2) and the minimum value for 2% salt (4.5 watts/cm^2). Similarly the surface power density for slabs was a function of the thickness of the slab. For a 12 cm slab, the values of P_u and P_l were 12 and 10 watts/cm^2 whereas for a 6 cm slab values of 6 watts/cm^2 were obtained at both surfaces. These experimentally measured surface densities were then used as input data for the simulation.

Although the measurements of total power absorption and surface power density are unique for the particular oven used in the experiments, it is likely that the simulated temperature profile is valid for all types of resonant cavities. It can also be easily modified for other frequencies (Fig. 4.23) for combined heat transfer processes and for travelling wave applicators.

It is often stated, particularly in the trade literature that one of the characteristics of microwave heating is its evenness of heating. In the case of slabs of material with a high water content the heating was only even for thin slabs. For a 6 cm slab the surface temperature was 8°C higher than that at the centre of the slab, whereas for a 10 cm slab the difference was 26°C for a surface temperature rise of 40°C .

Of particular interest in the case of reheating foods is the effect of salt on the temperature profile. For water/solid mixtures k decreases as the temperature rises, which tends to even out any overheating at the surface of a solid. In the case of materials with a salt content of for instance 3% the

situation is reversed: the electrical conductivity increases with temperature, which has the effect of enhancing the surface heating effect and resulting in a 'runaway' heating effect at the surface. This is of importance in the case of the reheating of cooked foods, many of which have a significant salt content.

5.2. RECOMMENDATIONS FOR FURTHER WORK

5.2.1. Total power absorption

Although the results obtained for the measured total power absorption were only for a limited number of materials and for only one type of oven, it was found that there was a complex relationship between the chemical nature, size and shape of the load in the cavity. With this particular oven using small volumes of material it was found that, for water containing materials the governing factor in the power absorption was the amount of water in the load material. For large volumes, absorption was the same for oil and water. It would be useful to compare these results with those for other types of ovens. It would also be of value to extend the study to a wider range of food materials and also to determine the effect of the sample geometry on the total power absorption. No account was taken of the effect of heating several samples at the same time, which could involve samples of the same size, different sizes and materials of different dielectric properties. This information would be useful in a study of the effect of heating meals consisting of several components, of varying sizes and dielectric properties.

The power absorption was calculated by measuring the increase in enthalpy for a known heating time. This technique has the disadvantage that it is necessary to correct for heat losses due to cooling and evaporation losses. One possible way of measuring the power absorption would be fit power meters in the waveguide of the oven, which could be used to measure the transmitted and reflected power during a heating cycle. From these two measurements the power absorbed by the sample and oven could easily be calculated, with greater accuracy. This would probably require a specially built oven, as in a commercial oven there is insufficient room to make these modifications.

5.2.2. The computer simulation

The heat transfer section of the simulation uses only approximate methods and there are many ways in which its accuracy could be improved. Thus it would be possible to incorporate a temperature dependant value for the thermal conductivity. For the simulation used in this work, the heat transfer modes caused only secondary effects, and the approximate solution was satisfactory.

One source of error in the heat transfer simulation is in the values used for the surface heat transfer co-efficient. The values used in the simulation were only strictly valid over a temperature range from 20 to 40°C. It is likely that at higher temperatures the heat transfer co-efficient would increase rapidly, because of increased convection currents, radiation and surface evaporation. Before a variable value of 'h' can be used in the simulation, it would be necessary to develop a relationship between 'h' and the surface temperature.

The simulation could be adapted to cover the cases of two dimensional (rods, cylinders etc.) and three dimensional (cubes, bricks and spheres) solids. With these more complex geometries, the effect of standing waves and of varying surface power densities could lead to poor agreement between theoretical and experimental results.

The program, as given in Appendix IV (6) will provide a quick and accurate simulation for high moisture content foods. For foods with high solid contents and electrolytes it is necessary to know values of dielectric properties over temperatures from 0 to 100°C: other than the measurements of Bengtsson and Risman (1970), this material is not available for many foods. There is therefore a need for more information of this type.

SECTION 6 - CONCLUSIONS

6. CONCLUSIONS

6.1 ENERGY DISTRIBUTION IN THE CAVITY

Many methods have been described in the literature for the measurement of the energy distribution in the cavity of a microwave oven. Several of these methods were compared, in order to ascertain the best method for discovering optimum experimental conditions.

In general it was found that each method produced a unique pattern of the energy distribution and that there was very little similarity in the pattern obtained by different methods. It was concluded that it is not possible to talk about the energy distribution in the cavity per se, because the nature of the load in the cavity changes the nature of the energy coupling into the cavity and hence the distribution of energy in the cavity.

6.2 TOTAL POWER ABSORPTION

The effect of the size of load in the cavity and its chemical nature on the total amount of energy absorbed by the load was investigated. It was found that the total power absorption was a function of the volume of the load; since the power consumption of the oven is constant under all operating conditions, it also follows that the oven's efficiency is dependant upon the size of the load. Since resonant modes and tuning of microwave ovens differs between makes and even between two ovens of the same make, the actual relationship between load volume and power absorption will differ; it is however to be expected that for all resonant cavities, that the relationship will be of the same form. This relationship shows an increase in efficiency as the load volume increases up to a maximum value, above which the volume has no effect on the efficiency.

The total power absorption is also dependant upon the chemical nature of the material forming the load. It was found that the normal equations used for calculating the power absorption from an electromagnetic field which, under conditions of constant frequency and field strengths, gives a directly proportional relationship between power absorption and loss tangent, was not valid for the resonant cavity used in these experiments.

Maximum absorption was achieved into a load consisting of water, except at large volumes for which the same absorption was obtained for corn oil, and water. From the nature of the result it would appear that this oven was designed to give optimum operation into a water load.

6.3 TEMPERATURE PROFILE

Experimental measurements were made of the temperature distribution in various solid materials, after a period of microwave heating. These materials were in the form of a slab of materials and profiles were obtained with microwave radiation normal to one and both faces of the slab. The solid materials were prepared by adding simple food components to a 1% agar gel.

A finite difference method was developed for simulating the microwave heating process together with other heat transfer processes. The absorption co-efficient, used to calculate the energy absorption from the electromagnetic wave at every depth in the slab, was calculated by one of two possible methods. From the relaxation time and static dielectric constant, the real and imaginary relative permittivity at a particular frequency can be calculated and these can be used to calculate the absorption co-efficient. Alternatively the relative permittivities can be measured experimentally for any food material. Both of these methods were used in the simulation. The first method gave good agreement with experimental results for water and for solids with up to 10% solids, but not for higher solid contents and for solids containing electrolytes. The second technique gave good agreement for water and for beef: this technique is limited because of a lack of the necessary experimental data for many foods.

For investigations of processing techniques and for the investigation of combined heat processing methods, the first method discussed above is more flexible than the method based on measured values of the dielectric properties. Thus it can be easily modified to suit any frequency of radiation. For

situations where a simulated profile of an actual food material is required, the second method gives more accurate results, if the dielectric properties are known or can be measured.

REFERENCES

REFERENCES

Abadie, P Charbonniere, R Gidel, A Girard, P (1953): "L'eau dans la cristallisation du maltose et du glucose et états de l'eau sorbtion en radiofrequency", J. Chimie. Phys. 50(c), 46.

Bengtsson, N Melin, J Remi, K Soderlind, S (1963): "Measurement of the dielectric properties of frozen and defrosted meat and fish", J.Sci.Fd.Agric, 14, (8), 592-604.

Bengtsson, N Lyke, E. (1969): "Experiments with a heat camera for recording temperature distribution in foods during microwave heating", J. Microwave Power, 4 (2), 48-54.

Bengtsson, N Risman, P (1971): "Dielectric properties of foods at 3 GHz as determined by cavity perturbation techniques". J.Microwave Power, 6, (2), 107-23.

Bengtsson, N. (1972): Personal communication.

Brown, G Hoyler, C Bierworth, R (1947): "Theory and application of radio frequency heating", D.Van Nostrand, New York.

Buchanan, T (1954): "The dielectric properties of some long chain fatty acids and their methyl esters in the microwave region", J.Chem.Phys., 22, (4), 578-84.

Cole, K Cole, R. (1941): Dispersion and absorption in dielectrics", J.Chem.Phys., 9, (4), 341-51.

Cook, H (1951a): "Dielectric behaviour of human blood at microwave frequencies", Nature, 168, (4267), 247-8.

Cook, H (1951b): "The dielectric behaviour of some types of human tissue at microwave frequencies", Brit.J.Appl.Physics, 2, (10), 295-300.

Cook, H (1952): "A physical investigation of heat produced in human tissue when exposed to microwaves", Brit.J.Appl.Physics, 3, (1), 1-6.

Copson, D (1962): "Microwave heating", AVI Publishing Co.Ltd., Westport, Connecticut.

Gopson, D Decareau, R (1968) in "Microwave power engineering", Ed. Okress, E, Vol II, Academic Press, London, 6-28.

Cox, E (1971): "General review of HF dielectric heating in industry", IEE Colloquium on RF and microwave industrial heating, Univ. of Bradford, 27th and 28th Oct.

Crapuchettes, P (1966): "Microwaves on the production line", Electronics, 39, (5), 123-30.

D'Arsonoval, A (1893): "Influence de la fréquence sur les effets physiologiques des courants alternatifs", Compt. Rend. Acad. Sci (Paris), 116, 630-2.

Debye, P (1929): "Polar molecules", The Chemical Catalogue Co. Inc., New York.

Decareau, R (1965): "For microwave heating tune to 915 or 2450 MHz", Food Engineering, 37, (7), 54-6.

Decareau, R (1968a): "Microwave food applications", Microwave Energy Applications Newsletter, 1, (4), 3-8.

Decareau, R (1968b): in "Microwave power engineering", Ed. Okress, E, Vol II, Academic Press, London, 80-3.

Decareau, R (1969): "The microwave oven in hospital food service", Microwave Energy Applications Newsletter, 2, (1), 3-6.

De Loor, G Meejboom, F (1966): "The dielectric constants of foods and other materials with high water contents at microwave frequencies", J. Food Technology, 1, (4), 313-22.

Dunlap, W Makower, B (1945): "Radio frequency dielectric properties of dehydrated carrots", J, Phys. Chem. 49, (6), 601-22.

Dunn, D (1967): "Microwave power", Science Journal, 3, (6), 31-7.

Darle, R (1966): "Unit operations in food processing", Pergamon Press, Oxford.

Ede, J Haddow, R (1951): "The electrical properties of food at high frequencies", Food Manufacture, 26, (4), 156-60.

Elder, R Gundaker, W (1971): "Microwave ovens and their public health significance", J. Milk and Food Technology, 34, (9), 444-6.

Evans, K Taylor, H (1967): "Microwaves extend shelf life of cakes", Food Manufacture, 42, (10), 50-1.

Gebhart, B (1971): "Heat transfer", McGraw Hill, New York, 2nd Edition.

Goldblith, S (1966): "Basic principles of microwaves and recent developments", Recent Advances in Food Research, 15, 277-301.

Goodall, H (1970): "Microwave heating", BFMIRA Tech. Circular No. 459.

Guy, A (1971a): "Analyses of electromagnetic fields induced in biological tissue by thermographic studies on equivalent phantom models", IEE Tras, Microwave Theory and Techniques, MTT-19, (2), 205-14.

Guy, A (1971b): "Electromagnetic fields and relative heating patterns due to rectangular aperture source in direct contact with bilayered biological tissue", IEEE Trans. Microwave Theory and Techniques, MTT-19, (2), 214-23.

Hamid, M Boulanger, R Tong, S (1969): "Microwave pasteurisation of milk", J. Microwave Power, 4, (4), 272-275.

Hartshorn, L (1949): "Radio frequency heating", George Allen and Unwin, London.

Harvey, A (1963): "Microwave engineering", Academic Press, London.

Hasted, J Ritson, D Collie, C (1948): "Dielectric properties of aqueous ionic solutions", J. Chem. Phys., 16, (1), 1-21.

Hasted, J (1961): "The dielectric properties of water", Progress in Dielectrics, 3, 101-49.

Heenan, N (1968): in "Microwave power engineering", Ed. Okress, E, Vol II, Academic Press, London, 126-44.

Hull, J (1968): in "Microwave power engineering" Ed. Okress, E, Academic Press, London, 9-17.

Industrial Society (1972): "Canteen prices, costs, subsidies

and other information", Spring 1972.

James, C (1968): in "Microwave power engineering" Ed. Okress, E, Vol II, Academic Press, London, 28-38.

Jeppson, M (1964): "Techniques of continuous microwave food processing", Cornell Hotel and Restaurant Quart., 5, (1), 60-4.

Kenyon, E Rinaldi, P Gould, J (1969): "A microwave feeding system for extended space missions", J. Microwave Power, 4, (4), 258-72.

Kirk, D (1971): "Food research requirements of the catering industry", University of Surrey, Guildford.

Lane, J Saxton, J (1952a): "Dielectric dispersion in pure polar liquids at very high radio frequencies: I- measurements on water, ethyl alcohol and methyl alcohol", Proc. Royal Soc. A213, 400-8.

Lane, J Saxton, J (1952b): "Dielectric dispersion in polar liquids: II - effects of electrolytes in solution", Proc. Royal Soc., A214, 531-45.

McConnell, D (1972): "A durable choke seal design for microwave ovens", Microwave Energy Applications Newsletter, 5, (1), 11-4.

Mafrici, D (1970): "Nassau County microwave oven study",
Radiological Health Data Reports, 11, (12), 667-70

Manson, J Zahradnik, J Stumbo, C (1970): "Evaluation of
lethality and nutrient retention of conduction heating foods
in rectangular containers", Food Technology, 24, (11),
109-13.

Maurer, R (1972): "Microwave processing of pasta", Food
Technology, 25, 1244-9.

Maxwell, J (1865): "A dynamical theory of the electromag-
netic field", Phil.Trans.Royal Soc. 155.

May, K (1969): "Applications of microwave energy in preparing
poultry convenience foods", J. Microwave Power, 4, (2), 54-9.

Meredith, R (1971): "Industrial microwave equipment in the
900 MHz band", IEE colloquium on RF and Microwave industrial
heating, Univ. of Bradford, 27th and 28th Oct.

Moore, N (1968): "Microwave energy in the food field",
Microwave Energy Applications Newsletter, 1, (1), 5-7.

Moore, R Smith, S Cloke, R. Brown D (1971): "Comparison of
microwave power density meters", Non-ionising Radiation, 2, (1),
11-4.

Morse, P Revercomb, H (1947): "UHF heating of frozen food",
Electronics, 20, (10), 85-9.

Mudgett, R Smith, A Wang, D Goldblith, S (1971): "Prediction
on the relative dielectric loss factor in aqueous solutions
of non-fat dried milk through chemical simulations", J. Food
Science, 36, 915-8.

Mapleton, L (1967): "A guide to microwave catering", Northwood
Industrial Publications Ltd., London.

National Catering Enquiry (1970): "Food in pubs", Smethursts
Foods Ltd.

Nicholls, N (1971): "Thyratron invertors for induction heating",
IEEE colloquium on RF and microwave heating, Univ. of Bradford,
27th and 28th Oct.

Norrish, R (1967): "Selected tables of physical properties
of sugar solutions", BFMIRA Scientific and Technical Surveys
No 51.

Ohlsson, T Bengtsson, N (1971): "Microwave heating profiles in
Foods", Microwave Energy Applications Newsletter, 4, (6), 2-8.

O'Meara, J (1968): in "Microwave power engineering" Ed. Okress,
E, Vol II, Academic Press, London, 65,-73

Ono, S Kuge, T Koizumi, N (1958): "Dielectric properties of starch", Bull. Inst. Chem. Res. Kyoto University, 31, 40-5.

Pace, W Westphal, W Goldblith, S (1968a): "Dielectric properties of potatoes and potato chips", J. Food Science, 33, (1), 37-42.

Pace, W Westphal, W Goldblith, S (1968b): "Dielectric properties of commercial cooking oils", J. Food Science, 33, (1), 30-6.

Peterson, A Foerstner, R (1971): "Evaluation of microwave oven cooking performance", Microwave Energy Applications Newsletter, 4, (1), 3-8.

Püschner, H (1964): "Wärme durch Mikrowellen", Philips Tech. Bull., 231-75.

Püschner H (1966): "Heating with microwaves", Philips Technical Library, Eindhoven.

Roberts, J Cooke H (1952): "Microwaves in medical and biological research", Brit. J. Appl. Physics, 3, (2), 33-40.

Robson, B (1967): "Basic tables in physics", McGraw Hill, 287.

Roebuck, B Goldblith, S (1972): "Dielectric properties of carbohydrate-water mixtures", J. Food Science, 37, 199-204.

Saxton, J (1952): "Dielectric dispersion in pure polar liquids at very high radio frequencies", Proc. Royal Soc., A213, 473-91.

Schiffman, R Stein, E Kaufman, B (1971): "The microwave processing of yeast raised doughnuts", Bakers Digest, 45, (2), 55-61.

Schmidt, W (1960): "The heating of food in a microwave cooker", Philips Technical Review, 22, (3), 89-102.

Schwan, H Li, K (1953): "Capacity and conductivity of body tissue at ultra high frequencies", Proc. IRE, 41, 1735-40.

Schwan, H Li, K (1956): "The mechanism of absorption of ultra high frequency electromagnetic energy in tissue, as related to problems of tolerance dosage", IRE Trans. Medical Electronics, ME-4, 45-9.

Schwan H, (1965): "Electrical Properties of bound water", Annal of N.Y. Academy of Science, 125, 344-54.

Schwan, H (1969): "Effects of microwave radiation on tissue - a survey of basic mechanisms", Non-ionising Radiation, 1 (1), 23-31.

Schwan, H (1971): "Interaction of microwaves and radio frequency radiation with biological tissue", IEEE Trans. MTT-19, (2), 146-9.

Shelton, E (1969): "Devices for the generation of microwave power", J. Microwave Power, 4, (2) 75-79.

Sluce, P (1969): "Simple methods for determining energy distribution in a microwave oven", Non-ionising Radiation, 1, (3), 131-5.

Tape, N (1969): "Application of microwave energy in food manufacture", BFMIRA Golden Jubilee Conference, London, Oct.

Van Beek, L (1970): "Dielectric behaviour of heterogeneous systems", Progress in Dielectrics, 7, 69-114.

Van Dyke, D Goldblith, S Wang, D (1969): "Dielectric loss factor of reconstituted ground beef: the effect of chemical composition", Food Technology, 23, (7), 84-6.

Van Zante, J (1968): "Some effects of microwave cooking power upon certain basic food components", Microwave Energy Applications Newsletter, 1, (6), 3-9.

Von Hippel, A (1954): "Dielectric materials and applications", MIT, Cambridge, Massachusetts.

Weast, R (Editor) (1972): "Handbook of chemistry and physics",
53rd Edn., CRC Press, 1972-73, D-211.

Wilhelm, M Satterlee, L (1971): "A 3-D method for mapping
microwave ovens", Microwave Energy Applications Newsletter,
4, (5), 3-5.

APPENDICES

APPENDIX I Food research requirements of the catering industry

(Kirk, 1971)

A. Food Production

1. Data on heat transfer characteristics of foods.
2. Definition of cooking process in terms of chemical, biochemical and physical changes.
3. Investigation of food handling systems.

B. Holding

4. Changes in palatability and texture during hot holding.
5. Chilling - texture and flavour changes.
6. Freezing - texture and flavour changes.
7. Loss of flavour of 'boil in the bag' roast meats.
8. Reasons for short shelf life of frozen cooked liver and pork.
9. Freezing by liquid nitrogen and Freon.
10. Packaging of food during the holding stage.
11. Effect of storage conditions on the life and quality of cooked frozen and chilled foods.

C. Preparation and service

12. Microbiology of kitchen operations.
13. Tolerance of convenience foods to abuse and mishandling.
14. Microwave heating - effect of wavelength on thawing characteristics.
15. Effect of chemical and physical nature of food on heating effect of microwaves; efficiency and variability of ovens.

D. Assessment of quality and acceptability

16. Effect of environmental factors on acceptability.
17. Consumer testing in a catering situation.
18. Acceptability of processed foods/reasons for unacceptability.
19. Economics of convenience food and centralized production systems.
20. Comparison of nutritive value of fresh and processed foods.
21. Survey on importance of regional preferences on food acceptability.

APPENDIX II List of symbols used

cspeed of light (metres/sec)

$D_{\frac{i}{e}}$depth at which radiation is reduced to 37% of its power
at the surface.

Eelectric field strength

E_{zt}electric field strength at time t secs and a distance of
 z cm.

E_vrate of evaporation (grams/min)

ffrequency (Hertz), f_r - relaxation frequency.

FOFourrier number

Ggeometric factor for particles suspended in polar solvent

hsurface heat transfer co-efficient

H_{zt}magnetic field strength at time t and distance z .

Jmechanical equivalent of heat (joules/calorie)

kabsorption co-efficient

K_cthermal conductivity

Krelative permittivity

K^*complex relative permittivity

K'real part of K'

K''imaginary part of K''

K''_{dipole} contribution to K'' by dipole relaxation

K''_{ionic} contribution to K'' by ionic conductivity

K_ohigh frequency value of K

K_sstatic (low frequency) value of K

Llatent heat of evaporation

m, Mmass

P	Power (watts)
P_a	absorbed power
P_o	surface power density (watts/cm ²)
P_z	power density at a depth z cm.
S	specific heat
t	temperature (°C)
Tr	relaxation time
t_{np}	temperature rise at a depth p and after time p
v	volume concentration (ml/ml of solution)
V	volume
α	attenuation constant
β	phase constant
γ	propagation co-efficient
ϵ	permittivity
ϵ_o	permittivity of free space
η	viscosity
λ	wavelength
μ	permeability
μ_o	permeability of free space
μ_r	relative permeability
ρ	density
ρ	resistivity (ohm/m)
σ	conductivity (mho/m)
τ	time (secs)
ω	angular frequency
ω_r	relaxation frequency

APPENDIX III List of symbols used in the Computer Programs

ABSK [1:50].....store location for values of K from 0 to
100 °C.

CALPOWER (C).....Procedure for calculating the power absorbed
in a slab of C cm.

CALTEMP (D)Procedure for calculating the rise in
temperature in a slab of D cm.

CONDthermal conductivity -Kc

DENDensity - (g/ml)

DEPTHtotal slab thickness (cm.)

EIK"

EOKo

EQUIBtime interval between end of heating and
termination of the simulation (seconds)

ERK'

ESTKs

HBSAsurface heat transfer co-eff.(base) surface
hotter than air

HBASsurface heat transfer coeff.(base) air hotter
than surface

HTSAsurface heat transfer co-eff. (top) surface
hotter than air

HTASsurface heat transfer co-eff. (top) air hotter
than surface

HEATIMEmicrowave heating time (seconds)

INCTincremental time interval (seconds)


```

INCX .....incremental slab thickness (cm.)
K .....k
OUTDATA .....Procedure for printing out input data and
                the temperature simulation
PU .....surface power density (watts/cm2) at upper
                surface
PL .....surface power density (watts/cm2) at lower
                surface
REL .....Tr (secs.)
SELECT K .....Procedure for selecting or calculating a
                value of k at a given temperature
SH .....specific heat
TA .....air temperature (°C)
TEMP (0:N) .....array location for holding the temperature
                at each element of the slab
W ..... W
WAVE .....wavelength

```

APPENDIX IV(1)Procedure for selecting a value of k from an array of values

```

'PROCEDURE' SELECT K;

      'BEGIN'

      REAL E,A;

      E:= TEMP[X];

      A:= 0;

REPEAT:  A:= A +.2;

      'IF' E < A 'THEN' K:= ABSK[A/2]

      'ELSE' 'GOTO' REPEAT;

      'END' OF SELECT K;

```

Note: $ABSK[1:50]$ is an array of 50 store locations, each containing a value of k at 2°C intervals. Thus $ABSK[1]$ is equivalent to a value of k at 1°C and $ABSK[50]$ to a value of 99°C . E is set to the value of the temperature at location X in the slab. The value of A is increased from 1, two degrees at a time, until it is greater than E. The value of k equivalent to this value of temperature can be found in store location $ABSK[A/2]$.

The procedure is activated by the instruction 'SELECT' K; it will then select a value of k for the temperature at slab location X. The meaning of symbols used above is given in Appendix III.

APPENDIX IV(2)

Procedure for calculating k from values of Ks, Ko and Tr

```

'PROCEDURE 'SELECT K
      'BEGIN'
      'INTEGER'S;
      'REAL' EST,REL,ER,EI,EO,W,WAVE;
      WAVE:= 3& 10/2.49& 9;
      EO:= 5.5;
      W:= 3.1459 * 2 * 2.45& 9;
      REL:= 16.3 * EXP( -0.033 * TEMP[X])/ 1& 12;
      EST:= 88 - ( 0.4 * TEMP[X] );
      ER:= EO + ((EST - EO)/( 1 + W2 * REL2 ));
      EI:= W * REL *(EST - EO)/(1 + W2 * REL2);
      K:= 2*SQRT(ER * 6.2918)*SQRT(SQRT(1 + (EI/ER)2)-1)/W;
      'END' OF SELECT K;

```

APPENDIX IV(3) Temperature profile for semi-infinite solid

```

J:=DEPTH/INCX;
  'BEGIN'
  'ARRAY' TEMP [0:J]
  'FOR' I:=0 'STEP' 1 'UNTIL' J 'DO' TEMP I:=INIT;
  (Sets all locations in the temperature array to initial value)
  PROCEDURE 'SELECT' K; (Defined as in Appendix III(1) or III(2).)
  'PROCEDURE' CALTEMP(D);
  'REAL' D;
    'BEGIN'
    E2:=(E1*EXP(-K*D));
    TEMP [X]:=TEMP [X]+((E1-E2)/(4.2*SH*DEN*D));
    E1:=E2;
    'END' OF CALTEMP;
  'FOR' T:=1 'STEP' 1 'UNTIL' HEATIME/INCT 'DO'
    'BEGIN'
    E1:=P;
    X:=0;
    'SELECT' K;
    CALTEMP(INCX/2);
    'FOR' X:=1 'STEP' 1 'UNTIL' J 'DO'
      'BEGIN'
      'SELECT' K;
      CALTEMP(INCX);
      'END'
    'END';
  OUTDATA; (Procedure for printing out table of final temperatures)
  'END';

```

APPENDIX IV(4) Program for calculating temperature profile -microwave only

```

'BEGIN'
'REAL' INIT,DEN,SH,DEPTH,INCX,HEATIME,INCT,PU,PL,E1,E2,K,PA,CAL,TIME;
'INTEGER' M,I,X,T,J,A,Y;
READ(in data for INIT,DEN,SH,DEPTH,INCX,HEATIME,INCT,PU,PL)
J:=DEPTH/INCX;
M:=INCTIME/INCT;
  'BEGIN'
  'ARRAY' TEMP[0:J],POWER[0:J];
  'PROCEDURE' SELECT K ; (Defined as in Appendix : IV(1) or :IV(2).)
  'PROCEDURE' CALTEMP(D);(Calculates temperature rise due to power
  absoption - for declaration see Appendix IV(6).)
  'PROCEDURE' CALPOWER(C);(Calculates power absorption for incremental
  slab - for declaration see Appendix IV(6).)
  'PROCEDURE' OUTDATA(L);(Prints out heading,table of input data and
  together with the appropriate final temperatures.)
  'FOR' T:=0 'STEP' 1 'UNTIL' J 'DO'
    'BEGIN'
    POWER[T]:= 0;
    TEMP[T]:=INIT;
    'END';
  'FOR' T:=0 'STEP' 1 'UNTIL' M 'DO'
    'BEGIN'
    X:=0;
    SELECT K;
    E1:=PU;
    'FOR' Y:=0 'STEP' 1 'UNTIL' J 'DO' POWER Y :=0;
    CALPOWER(INCX/2);
    'FOR' X:=1 'STEP' 1 'UNTIL' J-1 'DO'
      'BEGIN'
      SELECT K;
      CALPOWER(INCX);
      'END';
    X:=J;
    SELECT K;
    CALPOWER(INCX/2);
    E1:=PL;
    CALPOWER(INCX/2);

```

```
'FOR'Y:=1'STEP'1'UNTIL'J-1'DO'  
    'BEGIN'  
    X:=X-1;  
    SELECT K;  
    CALPOWER(INCX);  
    'END';  
  
X:=0;  
SELECT K;  
CALPOWER(INCX/2);  
CALTEMP(INCX/2);  
'FOR'X:=1'STEP'1'UNTIL'J-1'DO' CALTEMP(INCX);  
X:=J;  
CALTEMP(INCX/2);  
'END';  
  
OUTDATA;  
'END';  
  
'END';
```

APPENDIX IV(5) Program for the calculation of heat transfer changes

```

INCX:=0.1;
INCT:= 3.4;
J:=DEPTH/INCX;
P:=HEATIME/INCT;
READ in values of HTSA,HTAS,HBSA,HBAS,TA,INIT,COND;
  'BEGIN'
  'ARRAY' TEMP1 [0:J],TEMP2 [0:J];
  'FOR' I:=1 'STEP' 1 'UNTIL' P 'DO'
    'BEGIN'
    X:=0;
    'IF' TA >= TEMP1 [X] 'THEN' H:=HTAS
    'ELSE' H:=HTSA;
    TEMP2 [X] := INCX * H * (TA - TEMP1 [X]) / COND + TEMP1 [X+1];
    'FOR' X:=1 'STEP' 1 'UNTIL' J-1 'DO'
      TEMP2 [X] := (TEMP [X-1] + TEMP1 [X+1]) / 2;
    X:=J;
    'IF' TA >= TEMP1 [X] 'THEN' H:=HBAS
    'ELSE' H:=HBSA;
    TEMP2 [X] := INCX * H * (TA - TEMP1 [X]) / COND + TEMP1 [X-1];
    'FOR' X:=0 'STEP' 1 'UNTIL' J 'DO' TEMP1 [X] := TEMP2 [X];
    'END';
  'FOR' X:=0 'STEP' 1 'UNTIL' J 'DO'
    PRINT (TEMP1 [X], 3, 3);
  'END';

```

APPENDIX IV(6)

```

'BEGIN'
'REAL'
EQUIB,
TA,
INIT,DEN,SH,DEPTH,INCX,HEATIME,INCT,PU,PL,E,E1,E2,K,PA,CAL,TIME;
'INTEGER'
M,
I,X,T,A,J,Y;
CYCLE:DEN:=READ;
IF'DEN#0'THEN'GOTO'FINISH;
INIT:=READ;
TA:=READ;
SH:=READ;
DEPTH:=READ;
INCX:=READ;
HEATIME:=READ;
INCT:=READ;
PU:=READ;
PL:=READ;

```

```

EQUIB:=READ;
J:=DEPTH/INCX;
'BEGIN'
'ARRAY' TEMP1[0:J],TEMP2[0:J],POWER[0:J];

```

```

'PROCEDURE'SELECTK;

```

```

'BEGIN'
'INTEGER'S;
'REAL'
EST,REL,ER,EI,E0,W,WAVE;
WAVE:=3810/2,4589;
E0:=5,5;
W:=3,1459*2*2,4589;
REL:=16,3*EXP(-0,033*TEMP1[X])+2,4;
REL:=REL/1&12;
EST:=88*(0,4*TEMP1[X]);
ER:=E0+((EST-E0)/(1+W*2*REL*2));
EI:=W*REL*(EST-E0)/(1+W*2*REL*2);
K:=2*3,1459*EI/(WAVE*SQR(ER));

```

```

'END'OFSELECTK;

```

```

'PROCEDURE'CALPOWER(C);

```

```

'REAL'C;
'BEGIN'
E2:=EXP(K*C);
E2:=E1/E2;
POWER[X]:=POWER[X]*E1=E2;
E1:=E2;

```

```

'END' OF CALPOWER;

```



```

      'PROCEDURE' CALTEMP(D);

      'REAL' D;
      'BEGIN'
TEMP1[X]:=TEMP1[X]+POWER[X]*INCT/(4.2*SH*DEN*D);
      'IF' TEMP1[X] GE '100' THEN
      'BEGIN'
        NEWLINE(1);
        WRITETEXT('('TEMPERATURE%EXCEEDED%'100%DEG%C.'))');
        PAPERTHROW;
        'GOTO' CYCLE;
      'END';
      'END' OF CALTEMP;
'PROCEDURE' OUTDATA(L);

      'REAL' L;
      'BEGIN'

        PAPERTHROW;
        WRITETEXT('('TEMPERATURE%DISTRIBUTION%FORX'))');
        'IF' PL=0 THEN
        WRITETEXT('('SEMI-INFINITE%SLAB'('10'))'))');
        'ELSE' 'BEGIN'
          PRINT(DEPTH,2,2);
          WRITETEXT('('CM%INFINITE%SLAB'('10'))'))';
        'END';
        WRITETEXT('('=====))');
        NEWLINE(2);
        WRITETEXT('('POWER%UPPER=WATTS%'))');
        PRINT(PU,3,2);
        NEWLINE(1);
        WRITETEXT('('POWER%LOWER=WATTS%'))');
        PRINT(PL,3,2);
        NEWLINE(3);
        WRITETEXT('('INITIAL%TEMP%='))');
        PRINT(INIT,3,2);
        WRITETEXT('('AIR%TEMP%DEG%C%='))');
        PRINT(TA,3,2);
        WRITETEXT('('DEG%C'('10'))'DENSITY%='))');
        PRINT(DEN,2,4);
        WRITETEXT('('GMS%PER%CC'('10'))'SPECIFIC%HEAT%='))');
        PRINT(SH,2,4);
        WRITETEXT('('DEPTH%INCREMENT%='))');
        PRINT(INCX,2,4);
        WRITETEXT('('CMS'('10'))'TIME%INCREMENT%='))');
        PRINT(INCY,2,4);
        NEWLINE(2);
        WRITETEXT('('EQUILIBRATION%TIME%='))');
        PRINT(EQUIB,3,2);
        WRITETEXT('('SECS'('10'))'TOTAL%HEATING%='))');
        PRINT(HEATIME,3,0);
        WRITETEXT('('SECS'('30'))'TEMPERATURE%DISTRIBUTION%AFTER%
TIME:=T-1;
TIME:=TIME*INCT;
PRINT(TIME,3,0);
WRITETEXT('('SECS'))');

```

```

NEWLINE(2);
WRITETEXT('('DEPTH=CMS')');
FOR I:=0 STEP 1 UNTIL DEPTH DO
BEGIN
SPACE(1);
PRINT(I,3,2);
END;
NEWLINE(1);
WRITETEXT('('TEMP=DEGXC')');

FOR I:=0 STEP 1/INCX UNTIL J DO
BEGIN
SPACE(1);
PRINT(TEMP1[I],3,2);
END;
END OF OUTDATA;
PROCEDURE TRANSFER;

BEGIN
REAL COND, HTSA, HTAS, HBAS, HBAS, H;
INTEGER L;
COND:=1.488-3;
HTSA:=78-4;
HTAS:=2.78-4;
HBAS:=18-3;
HBRA:=5.38-4;
X:=0;
IF TA<GE TEMP1[X] THEN
H:=HTAS
ELSE H:=HTSA;
TEMP2[X]:=INCX*H*(TA-TEMP1[X])/COND+TEMP1[X+1];
FOR X:=1 STEP 1 UNTIL J DO
BEGIN
TEMP2[X]:=(TEMP1[X-1]+TEMP1[X+1])/2;
END;
X:=J;
IF TA<GE TEMP1[X] THEN
H:=HBAS
ELSE
H:=HBRA;
TEMP2[X]:=INCX*H*(TA-TEMP1[X])/COND+TEMP1[X+1];
FOR X:=0 STEP 1 UNTIL J DO
TEMP1[X]:=TEMP2[X];
END OF TRANSFER;
FOR T:=0 STEP 1 UNTIL J DO
BEGIN
POWER[T]:=0;
TEMP1[T]:=INIT;
END;
A:=ENTIER(HEATIME/INCT);
FOR T:=1 STEP 1 UNTIL A DO
BEGIN
X:=0;
SELECTK;
E1:=PU;
FOR Y:=0 STEP 1 UNTIL J DO
POWER[Y]:=0;

```

```

      CALPOWER(INCX/2);
!FOR 'X:=1' STEP '1' UNTIL 'J=1' DO
  !BEGIN
    SELECTK;
    CALPOWER(INCX);
  !END;
  X:=J;
  SELECTK;
  CALPOWER(INCX/2);
  E1:=PL;
  CALPOWER(INCX/2);
!FOR 'Y:=1' STEP '1' UNTIL 'J=1' DO
  !BEGIN
    X:=X-1;
    SELECTK;
    CALPOWER(INCX);
  !END;
  X:=0;
  SELECTK;
  CALPOWER(INCX/2);
  CALTEMP(INCX/2);
!FOR 'X:=1' STEP '1' UNTIL 'J=1' DO
  CALTEMP(INCX);
  X:=J;
  CALTEMP(INCX/2);
TRANSFER;
!END;
  M:=ENTIER(=DEPTH/10);
  M:=ABS(M);
  A:=ENTIER(EQUIB/INCT);
  !FOR 'Y:=1' STEP '1' UNTIL 'A' DO
    TRANSFER;
    OUTDATA(M);
  !END;
  !GOTO CYCLE;
FINISH:PAPER THROW;
!END;
!END;

```

APPENDIX IV(7)

TEMPERATURE DISTRIBUTION FOR SEMI-INFINITE SOLID

POWER UPPER-WATTS 7.00
 POWER LOWER-WATTS 0.00

INITIAL TEMP = 5.00 AIR TEMP DEG C = 20.00 DEG C
 DENSITY = 1.0400 GMS PER CC
 SPECIFIC HEAT = 0.9400 DEPTH INCREMENT = 0.1000 CMS
 TIME INCREMENT = 3.4000

EQUILIBRATION TIME = 30.00 SECS
 TOTAL HEATING = 60 SECS

TEMPERATURE DISTRIBUTION AFTER 58 SECS	
DEPTH-CMS	TEMP-DEG C
0.00	40.02
1.00	26.70
2.00	16.30
3.00	9.99
4.00	6.97
5.00	5.73
6.00	5.27
7.00	5.10
8.00	5.11
9.00	8.41
10.00	

ACKNOWLEDGMENTS

ACKNOWLEDGMENTS

I should like to thank Professor A. W. Holmes of the British Food Manufacturing Industries Research Association for the interest he has shown in this project and for the wealth of useful advice he has given.

I am also grateful for the advice given by members of staff of the Department of Hotel and Catering Management, particularly J. O'Connor and F.R. Lawson.

Suggestions on the unsteady state heat transfer were given by Dr E.K. Clutterbuck of the Department of Chemical Engineering; advice on the theory of microwave absorption was provided by Dr. K.W.H. Foulds of the Department of Physics.

Financial support for this project, in the form of a Research Fellowship, was provided by Sir Charles Forte.