M00108305R

7305629

UNIVERSITY OF SURREY LIBRARY

ProQuest Number: 10130598

All rights reserved

INFORMATION TO ALL USERS

The quality of this reproduction is dependent upon the quality of the copy submitted.

In the unlikely event that the author did not send a complete manuscript and there are missing pages, these will be noted. Also, if material had to be removed, a note will indicate the deletion.

ProQuest 10130598

Published by ProQuest LLC (2017). Copyright of the Dissertation is held by the Author.

All rights reserved.

This work is protected against unauthorized copying under Title 17, United States Code
Microform Edition © ProQuest LLC.

ProQuest LLC.
789 East Eisenhower Parkway
P.O. Box 1346
Ann Arbor, MI 48106 – 1346

Decision Tree Simplification for Classifier Ensembles

G. Ardeshir

Submitted for the Degree of
Doctor of Philosophy
from the
University of Surrey

Centre for Vision, Speech and Signal Processing
School of Electronics and Physical Sciences
University of Surrey
Guildford, Surrey GU2 7XH, U.K.

December 2002

© G. Ardeshir 2002

Summary

Design of ensemble classifiers involves three factors: 1) a learning algorithm to produce a classifier (base classifier), 2) an ensemble method to generate diverse classifiers, and 3) a combining method to combine decisions made by base classifiers.

With regard to the first factor, a good choice for constructing a classifier is a decision tree learning algorithm. However, a possible problem with this learning algorithm is its complexity which has only been addressed previously in the context of pruning methods for individual trees. Furthermore, the ensemble method may require the learning algorithm to produce a complex classifier. Considering the fact that performance of simplification methods as well as ensemble methods changes from one domain to another, our main contribution is to address a simplification method (post-pruning) in the context of ensemble methods including Bagging, Boosting and Error-Correcting Output Code (ECOC). Using a statistical test, the performance of ensembles made by Bagging, Boosting and ECOC as well as five pruning methods in the context of ensembles is compared. In addition to the implementation a supporting theory called *Margin*, is discussed and the relationship of Pruning to bias and variance is explained. For ECOC, the effect of parameters such as code length and size of training set on performance of Pruning methods is also studied.

Decomposition methods such as ECOC are considered as a solution to reduce complexity of multi-class problems in many real problems such as face recognition. Focusing on the decomposition methods, AdaBoost.OC which is a combination of Boosting and ECOC is compared with the pseudo-loss based version of Boosting, AdaBoost.M2. In addition, the influence of pruning on the performance of ensembles is studied. Motivated by the result that both pruned and unpruned ensembles made by AdaBoost.OC have similar accuracy, pruned ensembles are compared with ensembles of single node decision trees. This results in the hypothesis that ensembles of simple classifiers may give better performance as shown for AdaBoost.OC on the identification problem in face recognition. The implication is that in some problems to achieve best accuracy of an ensemble, it is necessary to select base classifier complexity.

Key words: Decision Trees, C4.5, Pruning Methods, Bagging, Boosting, Error-Correcting Output (ECOC), Combining classifiers, Ensemble Methods, Face Verification and Identification

Acknowledgements

First of all, my deepest and sincere thanks goes to my supervisor **Dr. Terry Windeatt** who supervised me friendly for his advise, guidance, and patience.

I would like to thank all people in Centre for Vision , Speech, and Signal Processing (CVSSP) for providing such a friendly research environment.

I need to thank my wife. I appreciate her support and encouragement and especially for her patience during my PhD study.

Contents

1	Introduction	1
1.1	Learning algorithms and Ensemble Methods	1
1.1.1	Why Ensemble	2
1.2	The Problem, Objectives and approaches	3
1.3	Data Used in the Experiments	5
1.4	Structure of the Thesis	8
2	Ensemble of Decision Trees: A Literature Review	10
2.1	Introduction	10
2.2	Ensemble Methods	11
2.2.1	Methods of Ensemble Creation	11
2.2.1.1	Using Different Feature Sets	12
2.2.1.2	Incorporating Different Types of Base Classifier	12
2.2.1.3	Resampling Training Set	12
2.2.1.4	Injection Randomness into Base Classifier	13
2.2.1.5	Perturbing Class Labels	13
2.3	Diversity and Accuracy	14
2.4	Combining Methods	14
2.4.1	Information Level Categorising	15
2.4.2	Function Categorising	15
2.4.2.1	Voting Methods	15
2.4.2.2	Order Statistical Combining Methods	16
2.4.2.3	Stacking	16
2.4.2.4	Cascading	16

2.5	Decision Tree Learning Algorithms	16
2.5.1	Characteristics of Decision Trees	18
2.5.2	Two Phases of Decision Tree Construction	18
2.5.3	Best Attribute Selection Measures	19
2.5.3.1	Information Gain	19
2.5.3.2	Gain Ratio	19
2.5.3.3	Gini Diversity Index	19
2.6	Decision Tree Algorithms	20
2.6.1	ID3	20
2.6.2	C4.5	20
2.6.3	CART	21
2.6.4	The Linear Machine Decision Trees Induction Algorithm	22
2.6.5	Decision Tree Stumps	22
2.7	Decision Tree Simplification	23
2.7.1	Pruning	23
2.7.2	Modifying the Test Space	24
2.7.3	Modifying the Search for Tests	25
2.7.4	Database Restriction	25
2.7.5	Alternative Data Structures	25
2.7.6	Post-Pruning Methods	25
3	Comparing Pruning Methods for Ensemble Classifiers	27
3.1	Introduction	27
3.2	Two levels of Pruning	29
3.3	Pruning Methods for Ensembles	29
3.3.1	Early Stopping	29
3.3.2	KL-Divergence Pruning	29
3.3.3	Kappa Pruning	30
3.3.4	Kappa-Error Convex Hull Pruning	30
3.4	Pruning Base Classifiers	31
3.4.1	Error-based pruning (EBP)	31
3.4.2	Minimum Error Pruning (MEP)	32

3.4.3	Reduced Error Pruning (REP)	32
3.4.4	Critical Value Pruning (CVP)	33
3.4.5	Cost-complexity pruning (CCP)	33
3.4.6	Z-based Pruning	34
3.5	Bagging	35
3.6	Review of Boosting and its Supporting Theories	36
3.6.1	The Margin	38
3.6.2	Another Theory for Boosting	39
3.6.3	AdaBoost Algorithm	41
3.7	Bias, Variance and Pruning	41
3.7.1	Definition of Bias and Variance	41
3.7.2	Control Bias and Variance by Pruning	44
3.8	Statistical Test for Comparing Ensembles	44
3.9	Experimental Comparison Bagging and Boosting	45
3.9.1	Selecting the best tree in CCP and CVP	50
3.9.2	The Margin of Patterns in Boosting	53
3.10	Summary	55
4	Tree Pruning for Output Coded Ensembles	58
4.1	Introduction	58
4.2	Decomposition Methods	59
4.2.1	One-Per-Class (OPC)	60
4.2.2	Distributed output Code	60
4.2.3	Error Correcting Output Codes	60
4.3	Code Selection for ECOC	62
4.4	Code Generation for ECOC	63
4.4.1	Exhaustive Codes	63
4.4.2	Column Selection from Exhaustive Codes	63
4.4.3	Bose & Ray-Chaudhuri (BCH) Codes	64
4.5	Learning algorithm Selection for ECOC	64
4.6	Why ECOC Works	66
4.7	Experiment	67
4.8	Summary	72

5	Boosted Tree Ensembles for Solving Multi-class Problems	73
5.1	Introduction	73
5.2	Boosting Algorithm and Output Coding	75
5.2.1	AdaBoost.M2 Algorithm	75
5.2.2	Output Coding and diverse binary classifiers	76
5.2.3	AdaBoost.OC Algorithm	78
5.3	The Margin Based Analysis of Boosting	80
5.3.1	The Margin	80
5.3.2	The Edge	81
5.4	Solving Multi-class Problems with Boosting	82
5.4.1	Ensembles of Decision Stumps	86
5.4.2	The Margin Based Analysis of AdaBoost.OC	86
5.5	Summary	89
6	Face Identification and Verification	93
6.1	Introduction	93
6.2	Face Verification and Identification	94
6.2.1	Feature Based Face Recognition	95
6.3	AdaBoost.OC Algorithm	97
6.4	Face Identification and Verification Via Boosting	97
6.5	Summary	103
7	Conclusion	104
7.1	Summary of Chapters	105
7.2	Contributions	106
7.3	Future Works	108

List of Figures

1.1	Multiple classifier systems.	2
2.1	An example of decision tree. This tree is for playing golf [78].	17
2.2	C4.5 Decision tree Algorithm.	21
3.1	Bagging Algorithm. In the combination step, each classifier has the same weight and the output is the label with the largest amount of votes. . .	35
3.2	Algorithm of AdaBoost.M1[36].	40
3.3	Cumulative distribution of margins training examples after 1 (solid curve), 5(long dashed line curve) and 50(dotted curve) iterations.	53
4.1	Error-Correcting Output Code (ECOC) Algorithm	61
4.2	Test Error of Pruned ECOC as a function of Code Length on Soybean-large and Audiology, the number shown in brackets is the code length .	70
4.3	Test Error of Pruned ECOC as a function of Training set size for letter dataset, the figure at bottom is for ECOC pruned with MEP	71
5.1	AdaBoost.M2 algorithm.	77
5.2	The AdaBoost.OC algorithm.	79
5.3	Test Error of AdaBoost.M2 and AdaBoost.OC.	83
5.4	Test Error of AdaBoost.M2 and AdaBoost.OC.	84
5.5	Composite correct Classification of AdaBoost.M2 and AdaBoost.OC for pruned and unpruned decision trees.	85
5.6	Test Error AdaBoost.OC with C4.5 and Decision Stump.	87
5.7	Test Error AdaBoost.OC with C4.5 and Decision Stump.	88
5.8	Training Error AdaBoost.OC with Decision Stump on Anneal and Dermatology data sets.	89
5.9	Margin of training patterns in AdaBoost.OC for Anneal, Glass, Audiology, Soybean-Large.	90

5.10	Margin of training patterns in AdaBoost.OC for Anneal, Glass, Audiology, Soybean-Large, In this figure, Number of Decision Stump trees has been increased to 500 and compared with 100 trees created with C4.5. .	91
6.1	Identification performance of AdaBoost.OC.	98
6.2	Correct Classification of AdaBoost.OC on the training set of face database.	100
6.3	Verification performance of AdaBoost.OC on Evaluation Data Set. . . .	101
6.4	Verification performance of AdaBoost.OC on Test Data Set.	102

List of Tables

3.1	Specification of Datasets used for studying pruned and unpruned ensembles generated by Bagging and Boosting.	47
3.2	Test Error of C4.5, Bagging and Boosting on artificial data with EBP, T is number of rounds in Boosting and Bagging algorithms.	47
3.3	Average size of tree in Boosting using MEP.	49
3.4	Ratio of unpruned ($m = 0$) error rate to minimum pruned error rate using MEP, followed by the minimum error rate for single classifier (C4.5) or classifier ensembles (Boosted C4.5 or Bagged C4.5) over m . Dataset have been split into 70/30 (see text).	50
3.5	Mean test error for 10-fold Cross Validation with Boosting and Bagging, and ratio Boosting-Bagging using EBP.	51
3.6	Mean Test Error of Boosting and Bagging and Ratio Boosting-Bagging using EBP. The datasets have been split into 70% for training and 30% for test.	51
3.7	Test Error of Boosting with different Pruning Methods. The datasets have been split into 70% for training and 30% for test.	52
3.8	Test Error of Bagging with different Pruning Methods. The datasets have been split into 70% for training and 30% for test.	52
3.9	Test Error of Bagging with CCP method(1SE); to choose the best pruned tree, the whole training set has been used. The last column (PErr) shows the test errors for Bagging obtained by the method in which for selecting the best pruned tree the dataset is divided into growing set and pruning set, shown for CCP(1-SE) in table 3.8.	54
3.10	Test Error of Bagging with CCP method(0SE); to choose the best pruned tree, the whole training set has been used. The last column (PErr) shows the test errors for Bagging obtained by the method in which for selecting the best pruned tree the dataset is divided into growing set and pruning set, shown for CCP(0-SE) in table 3.8.	54
3.11	Test Error of Bagging with CVP method; to choose the best pruned tree, the whole training set has been used. The last column (PErr) shows the test errors for Bagging obtained by the method in which for selecting the best pruned tree the dataset is divided into growing set and pruning set, shown for CVP in table 3.8.	55

3.12	Number of datasets (out of eleven datasets) for each pruning method which has a test error equals to minimum error rate among them. . . .	56
4.1	The table of accepted code lengths and error correction capability for BCH codes	65
4.2	Specification of Datasets used for studying ensembles generated by Error-Correcting Output Code	67
4.3	Mean test error normalised with respect to minimum error (last column)	68
4.4	Number of significant differences of each pruning method from unpruned (UNP)	68
6.1	Verification with Euclidean Distance metric and Normalised Correlation.	100

Chapter 1

Introduction

1.1 Learning algorithms and Ensemble Methods

Supervised learning is one of the most popular and best methods in machine learning. In supervised learning, a set of labelled data in the format of a set of measurements called features or attributes is given to a learning algorithm. The goal is to find a function which maps the data to one of the labels. This function is called a classifier and is intended to explain the underlying knowledge of training data and is applied to a new dataset (named test data) to predict their labels. A learning algorithm such as a decision tree or neural network is able to produce different classifiers if different distributions of training dataset are provided to them. This can be used to build a group of classifiers called an ensemble (or committee in some contexts) as has been shown in figure 1.1. As we know, a team of experts may perform a given work better than one expert if each expert has its own knowledge about the problem and all work in a perfect harmony. With respect to an ensemble, this can be interpreted as diversity.

To build a good ensemble, we need methods which are able to provide approaches leading to diverse classifiers as well as learning algorithms which can produce such classifiers. For the former case, the following methods can be found in the literature[25]:

- Manipulating the training set (such as Boosting and Bagging)

Figure 1.1: Multiple classifier systems.

- Manipulating the Output Targets (or perturbing class labels such as Error-Correcting Output Code)
- Manipulating the input features
- Injecting Randomness in the learning algorithm such as C4.5
- Incorporating different learning algorithms

1.1.1 Why Ensemble

This problem can be considered from different viewpoints based on the fact that the training set used in supervised learning is a sample of its population [25]. Therefore, using this sample may not lead to finding the true function which describes the underlying knowledge of the population. From a statistical point of view, if the size of sample is small, generating different classifiers or hypotheses about the sample and combining them may result in more accurate prediction of new patterns. On the other hand, based on a computational view, if the sample is large enough, the nature of learning algorithm

could lead to getting stuck in local optima. Therefore, constructing an ensemble by running the local search from different points may lead to better approximation of the true function.

In addition to these two reasons which are based on the size of sample, finding a single classifier or hypothesis which represents the true function in the original hypothesis may be impossible[25]. Combining the classifiers is a way to expand the hypothesis space to represent the true function.

In chapter 2, we look at ensemble methods in more detail.

1.2 The Problem, Objectives and approaches

The performance of an ensemble of classifiers can be influenced by several factors including the learning algorithm (which is used to construct diverse classifiers), the ensemble design techniques and combining methods. Using a decision tree learning algorithm for building base classifiers in ensembles, which are known to be greedy in modelling the data [79], makes it necessary to address simplification methods such as post-pruning to avoid overfitting. On the other hand, the performance of pruning methods as well as ensemble methods changes from one domain to another. In a sentence, our research is about ensemble of simple classifiers. Since we have used a decision tree learning algorithm as base classifier in the ensemble, one of the main parts of the thesis is about influence of pruning methods on ensembles. Then the thesis goes on to address ensemble methods for solving multi-class problems by decomposition methods and the effect of pruning methods on this kind of ensemble. Finally, we will address ensemble of single node decision trees compared with ensemble of more complex classifiers.

To investigate the effect of pruning methods, we will start with two popular ensemble methods, Bagging and Boosting, and compare pruned and unpruned ensembles of decision trees (generated by using C4.5) over both artificial and real datasets. Meanwhile, in the last part of chapter 3 a comparison of performance of five decision tree pruning methods in different ensembles built by Bagging and Boosting will be performed to find out which one outperforms in different domains. To ascertain whether the differences

between them are statistically significant, a statistical test called McNemar test will be applied (section 3.8). To analyse how and why ensemble methods improve the accuracy of classification systems, the implementation of a supporting theory called *Margin* will be explained for both pruned and unpruned ensembles produced by Boosting (section 3.9.2). Another theory presented for ensemble methods is decomposition of error into bias and variance. We will explain this theory as well as its relationship to pruning of decision trees in section 3.7.

As addressed in [26], complexity of base classifiers is a problem in ensembles built by Error-Correcting Output Code (ECOC) which is in a second type of ensemble method and produces diverse classifiers by perturbing the class labels. To know which pruning methods may reduce complexity while preserving accuracy, we have applied five decision tree pruning methods to ensembles generated by ECOC (chapter 4). The performance of these five pruning methods will be compared with each other as well as unpruned ensembles. In ECOC, the Hamming distance between rows determines the error-correcting capability. To increase the Hamming distance, one way is to increase the code length. The effect of increasing code length on the performance of pruned and unpruned ensemble will be explained in section 4.7. Another factor which influences the performance of a classifier is the size of training set. The effect of training set size on the pruned ECOC will be shown in the last part of chapter 4.

Decomposition methods seem to outperform other methods such as Boosting and Bagging in solving multi-class problems. However, the complexity of decision trees in ECOC can not be removed by pruning methods if accuracy to be preserved. Therefore, we switch to another ensemble method which is a combination of Boosting and ECOC called AdaBoost.OC. To examine this method, we have chosen Error-Based Pruning (EBP) which was the best pruning method according to experiments performed with Bagging, Boosting and ECOC (sections 3.9 and 4.7). After finding that AdaBoost.OC produces pruned and unpruned ensembles with similar performance, we will add the ensemble of single node decision trees known as Decision Stumps and compare their performance to AdaBoost.OC ensembles (section 5.4.1). To verify that AdaBoost.OC as a decomposition method outperforms multi-class algorithms, we have compared it with AdaBoost.M2 which will be presented in section 5.4. The margin concept will be

used to describe the behaviour of AdaBoost.OC. It will be explained in section 5.4.2 that with a greater number of simple classifiers like Decision Stumps, we may achieve the same accuracy as ensemble of more complex decision trees.

With the conclusion from the aforementioned experiments that the accuracy of pruned ensemble generated by AdaBoost.OC is similar with unpruned ensembles built by AdaBoost.OC, we come to the final aim in our work which is to apply it to a face identification and verification problem. Both pruned ensemble and single node decision tree (Decision Stump) ensembles were applied to this problem (chapter 6). It will be shown that ensemble of Decision Stumps could give better results in identification while the error-correcting ability of AdaBoost.OC puts a limitation on the performance of ensembles.

1.3 Data Used in the Experiments

Most real data we have used in experiments are from UCI machine learning repository[9]. The summary of their descriptions is as follows:

Anneal It is a dataset with 9 continuous attributes and 29 nominal-valued features.

76.19% of the instances (798) belong to one of the six classes and the remaining to other classes. There are many missing attribute values.

Audiology This dataset is the standardised version of the original containing 200 instances with 69 discrete attributes and 24 classes. There are some missing attributes and the number of instances for some classes is low (there is just one instance for them). The largest class consists of 24% of instances.

Breast Wisconsin Breast Cancer database was obtained from the University of Wisconsin Hospitals, Madison from Dr. William H. Wolberg. It contains 699 instances in which 65.5% of instances is from one of two classes and 34.5% belong to other one. Each instance was represented by ten continuous attributes.

Breast Cancer This breast cancer domain was obtained from the University Medical Centre, Institute of Oncology, Ljubljana, Yugoslavia. This data set includes

201 instances of one class and 85 instances of another class. The instances are described by 9 nominal or discrete attributes.

Car A four-class database for evaluation of car which was derived from a simple hierarchical decision model. The classes of 1728 instances in this dataset are not equally distributed. The number of attributes has been reduced to six nominal features. The distribution of classes on the data is: 70.02%, 22.22%, 3.99%, and 3.76%.

Crx It contains a mix of continuous and nominal attributes. Continuous attributes have small values while nominal feature have large numbers. 690 instances of this two class dataset concern credit card application. 44% of instances belongs to one of two classes and 56% to another class.

Dermatology This database contains 34 attributes, 33 of which are linear valued and one of them is continuous. The aim is to determine the type of Eryhemato-Squamous Disease. The six classes are not equally distributed and are 30.60%, 16.67%, 19.67%, 13.39%, 14.21%, and 5.46%.

Glass This six class dataset with 9 continuous attributes was collected for criminological investigation. Number of patterns is 214. The distribution of classes is: 32.71%, 35.51%, 7.94%, 6.07%, 4.21%, and 13.55%.

Heart A two-class dataset which contains 270 instances. 120 instances are from class 1 which show presence of heart disease and the rest (150) show the absence of the disease. This database contains 13 continuous attributes which have been extracted from a larger set of 75.

Hypothyroid This dataset concerns thyroid disease and contains 3163 instances, two classes (4.77% and 95.23%) and several missing attribute values. Among 25 attributes, 18 of them are nominal and the rest are continuous.

Iris This data contains three classes. Each class refers to a type of iris plant. There are 50 instances for each class in the dataset with 4 continuous attributes. According to [9], one of the classes is linearly separable from the other two and the other two are not linearly separable from each other.

labor-neg Its complete title is "final settlements in labor negotiations in Canadian industry". It is a two-class dataset with 8 continuous and 8 nominal attributes. Number of Instances is 57 with 64.91% for one of the classes and 35.09% for another one.

Letter It is a 20000-instance dataset of the 26 capital letters in the English alphabet. Each instance contains 16 numerical attributes which were scaled to integer numbers between 0 and 15. 26 classes have approximately equal distributions.

Segmentation The instances of this dataset were drawn randomly from a database of 7 outdoor images. The images were hand segmented to create a classification for every pixel. Each instance is a 3×3 region. Each of 2310 instances has been represented by 19 continuous attributes. There are equal number of instances for 7 classes.

Soybean-Large It is a 307-instances dataset with 35 nominal features. Four of 19 classes of this dataset have a small number of patterns. The largest class consists of 13.47% of instances.

Vehicle This dataset originates from Turing Institute, Glasgow. The purpose of the dataset is to classify a given silhouette as one of four types of vehicles. The 18 continuous attributes for each silhouette were extracted to classify four vehicles. There are approximately equal number of instance for 4 classes in this dataset.

Vote This dataset includes votes for each of the USA House of Representatives Congressmen on the 16 key votes identified by the CQA. The values of 16 attributes were achieved by dividing different votes into three groups; yes, nay, or unknown disposition. 61.38% of the data are from class one (democrats) and the rest belong to class two (republicans). There are some missing attributes.

Waveform-21 It consists of 21 attributes with continuous values between 0 and 6. Noise has been added to values of each attribute. Each class of three classes in this dataset is a combination of 2 of 3 base waves. Distribution of each class is 33.33%.

Theses datasets have been summarised in tables 3.1 and 4.2.

1.4 Structure of the Thesis

The overall structure of the thesis is as follows:

We will first address in chapter 3 the complexity of decision trees generated for Bagging and Boosting and also we compare Bagging to Boosting for different pruning methods. Then, in chapter 4 we will explain how the pruning methods reduce complexity of decision trees in Error-Correcting Output Code. Using the result of these two chapters, in chapter 5 we will address the Output-Coding version of Boosting by applying Error-Based Pruning which is the best pruning method for two variants of Boosting algorithms. This chapter comes to the result that AdaBoost.OC produces pruned and unpruned ensembles with similar performance and in this respect it outperforms other ensemble methods in solving multi-class problems such as face recognition. The following chapters will be included:

- Chapter 2 we will start the thesis with a literature of ensemble methods, combining methods, decision tree learning algorithms and the decision tree simplification methods.
- Chapter 3 will be about two popular ensemble methods, Boosting and Bagging and about pruning of decision trees with five post pruning methods. Both Boosting and Bagging perform well with unstable learning algorithms such as neural networks or decision trees. Pruning decision tree classifiers is intended to make trees simpler and more comprehensible and avoid over-fitting. However it is known that pruning individual classifiers of an ensemble does not necessarily lead to improved generalisation. Examples of individual tree pruning methods which will be addressed in this chapter are Minimum Error Pruning (MEP), Error-Based Pruning (EBP), Reduced-Error Pruning (REP), Critical Value Pruning (CVP) and Cost-Complexity Pruning (CCP). At the end of the chapter we will present the results of applying Boosting and Bagging with these five pruning methods to eleven benchmark datasets.
- Chapter 4 is about Output Coding and the influence of tree pruning on it. Output Coding is a method of converting a multi-class problem into several binary

subproblems and gives an ensemble of binary classifiers. Like other ensemble methods, its performance depends on the accuracy and diversity of base classifiers. If a decision tree is chosen as base classifier, the issue of tree pruning needs to be addressed. In this chapter we investigate the effect of five methods of pruning on ensembles of trees generated by Error-Correcting Output Code (ECOC). The results with ECOC will be presented at the end of the chapter.

- In chapter 5 we consider AdaBoost.OC, an ensemble method which combines two ensemble techniques, Error-Correcting Output Code (ECOC) and Boosting. Both ECOC and Boosting are capable of producing diverse binary base classifiers. Decision trees have been chosen as the base classifiers, and the issue of tree pruning is addressed as well. In the last section experimental results have been explained.
- In Chapter 6 we will address applying AdaBoost.OC to a real face recognition problem. AdaBoost.OC combines the main features of Boosting algorithm and Error-Correcting Output Code (ECOC) to produce diverse classifiers by converting the multi-class problem such as face recognition into several binary subproblems and concentrating on hard examples. Recognising the advantage of decision trees which do not need any parameter tuning like neural network, C4.5 and Decision Stump have been used as base classifiers.
- Chapter 7 will be the last chapter which is about conclusion of the thesis.

Chapter 2

Ensemble of Decision Trees: A Literature Review

2.1 Introduction

As mentioned in chapter 1, our work is about ensembles of decision trees. Three main factors of an ensemble are: a method for generating diverse classifiers which we refer to as ensemble method, combining the decisions made by the classifiers (known as combining methods) and finally the base learning algorithms. The main purpose of this chapter is to review the literature of these three areas. For base learning algorithms, in addition to decision tree learning algorithms, we will address their simplification as well since we have used a kind of simplification method to reduce the complexity of decision trees.

An ensemble is a set of trained classifiers. The main idea behind the classifier ensemble is to improve the accuracy of the recognition system designed for the particular problem to be solved. Ensemble methods such as Boosting, Bagging, Output Coding work very well with decision trees learning algorithms such as C4.5 and CART. One problem with decision trees is their complexity which has been addressed with simplification techniques such as post-pruning methods. In designing ensembles of decision trees, pruning is an important research issue which has been addressed in our work.

In different parts of this chapter we will review methods concerned with generating ensembles.

First different ensemble methods will be explained in sections 2.2 and 2.2.1. Accuracy and diversity are discussed in section 2.3, and combining methods in section 2.4. In the second part of this chapter we will review existing decision tree algorithms and their simplification in sections 2.5, 2.6 and 2.7.

2.2 Ensemble Methods

For the classification task at hand, we could build many classifiers using different methods. Each classifier has specific information about the problem. So, choosing the best classifier and discarding others may lead to wasting useful information. Also, objects are represented by different types of feature sets and handling all of them by a particular classifier is difficult. These are the main reasons to consider constructing an ensemble of classifiers. We can identify five methods for constructing ensembles and two methods for combining the classifiers. Here, we first review the methods of construction in section 2.2.1, and then the methods of combination in section 2.4.

2.2.1 Methods of Ensemble Creation

To achieve a good performance for an ensemble, we need the base classifiers to satisfy three conditions: i) accuracy, ii) efficiency iii) diversity [82, 26]. An accurate classifier may mean just that its error rate is less than random guessing [44] (i.e., we do not necessarily need the base classifier to be highly accurate). An efficient classifier uses reasonable amounts of time and memory in training and when it is applied to new patterns. By diversity, we mean each individual classifier or expert has its own knowledge about the problem and different pattern of errors compared to other experts. In simple words, different classifiers do not make the same pattern mistakes. In terms of diversity, the methods for construction of ensembles can be divided into five categories [93],[25]:

- Using different feature sets

-
- Incorporating different types of base classifier
 - Resampling training set
 - Injection randomness into base classifier
 - Perturbing class labels.

2.2.1.1 Using Different Feature Sets

The first method needs a high number of features and suits a large data set. One approach is to use several feature sets. An example of this first method is [32]. The authors have used six different feature groups for 2000 handwritten numerals extracted from a set of Dutch utility maps. In [53], they applied this method to other domains; identity verification and handwritten digit recognition. As an example for identity verification frontal face, face profile and voice were used. Another approach in this method is to produce different feature sets by selecting subsets of features. The aim is to lessen the curse of dimensionality while classifiers with complementary information and lowest possible correlation [87] are produced. The curse of dimensionality occurs if the number of feature is too high compared to the number of training patterns. Training the classifiers on smaller features reduces overfitting in each classifier as well as training times [87].

2.2.1.2 Incorporating Different Types of Base Classifier

In the second method, different learning algorithms such as nearest neighbour, Bayes classifier, nearest mean, neural network, decision tree, and support vector machine are applied to the same training set to extract different information [32]. A combination of different learning algorithms may produce higher level diversity [91].

2.2.1.3 Resampling Training Set

This method works very well with unstable learning algorithms. An unstable learning algorithm is an algorithm in which a small perturbation in the training set may lead

to large changes in the resulting classifier. Examples of this type of learning algorithm are decision trees and neural networks. Stable learning algorithms include nearest neighbour, linear discriminant. By using different methods of sampling, in each round of generating classifiers the unstable learning algorithm is given a new replicate of the training set. Three main and important methods of resampling are: Bagging (abbreviation for bootstrap aggregating), Boosting, and the Random subspace method. We will explain Bagging and Boosting in chapter 3. Randomness can be introduced either through the randomisation of the training set or the randomisation of the base classifier itself. One well-known approach for the first method is cross validation in which the data set is randomly divided into several disjoint subsets and each time one of the subsets is left out [72]. Another way of using the random sampling method is to resample (with replacement) the training set reaching a node of a tree and use this sample to select the best attribute for the test. This method stops resampling when the number of patterns reaching the node is small to ensure that enough patterns exist at the node [51].

2.2.1.4 Injection Randomness into Base Classifier

An example of this method is to inject a random decision into decision tree algorithms such as ID3 and C4.5. C4.5 uses information ratio to select the best attribute for test at an internal node. One alternative way is to choose randomly one of 20 top-ranked attributes [27].

2.2.1.5 Perturbing Class Labels

These methods convert a multi-class problem into several binary subproblems. They actually make an ensemble of binary classifiers. One-per-class, Distributed Output Code and Error-Correcting Output Code (ECOC) are examples of this method. In all three methods a code matrix is used in which each row corresponds to a class. For example in One-per-class approach, the code matrix consists of k rows and k columns (k is the number of classes). In this matrix, all elements of each row or column are zero except one element which is one and corresponds to the related class [26]. In fact,

One-per-class finds the decision boundary between a class and the rest. Distributed Output Code method is based on the properties of the patterns. Therefore, distance between rows of code matrix depends on finding distinguishing features of patterns. In ECOC, code selection depends on number of classes and code generation is problem-independent. More details about this class of ensemble methods will be presented in chapter 4.

2.3 Diversity and Accuracy

Generalisation refers to the ability of a classifier to predict the label of a new pattern correctly. Although diversity means making different decisions by generated classifiers which leads to better generalisation, it does not mean the more diverse the better performance for the ensemble. As the experimental study in [59] shows there is no strong linear or non-linear relationship between diversity and accuracy. In this study, nine diversity measures introduced in the literature have been used and applied to Boosting and Bagging linear classifiers, i.e., nearest mean classifier and pseudo-Fisher linear classifier were used as base classifiers. According to their results, Boosting produces more diverse classifiers and there is a general trend in Boosting that greater diversity leads to higher accuracy. In [91] Coincident Failure Diversity has been used to measure the diversity and it has been shown that decision tree produces more diverse classifiers than neural network. However, the generalisation performance of combined decision trees is not better than combined neural networks. In [71], a genetic algorithm was used to search for accurate and diverse classifiers and a neural network ensemble was built by linear combination of them.

2.4 Combining Methods

In addition to diversity, the method of combining affects the performance of an ensemble. After generating different classifiers; at decision level, a question that needs to be addressed is how to combine the decisions or the outputs of the classifiers to

obtain better results. Based on different aspects, the combining methods developed by researchers can be divided into different categories.

2.4.1 Information Level Categorising

Based on the type of the outputs of the base classifiers or the level of information provided by them, one may divide the methods into three categories: abstract level, rank level and measurement level [103]. In abstract level, the output of each base classifier is only a class label. In rank level the outputs of classifiers are in class ranking as in a queue in which the top one is the first choice. In third level, a measurement such as class probability is assigned to each class label. The measurement level has the most information and the abstract level has the least.

2.4.2 Function Categorising

Based on the methodology used for combining the decisions made by the base classifiers, one may classify the combining methods into different types. Here, we explain them: Voting methods, order statistics, stacking and cascading.

2.4.2.1 Voting Methods

Simplicity is the main advantage of voting methods. In these methods the test pattern is assigned to the label which receives more votes than others. It is called *majority voting* if the class label of the test pattern is chosen based on receiving more than half votes (50 %) and it is a *plurality voting* if it is based on less than 50 %. In Bagging a simple or uniform scheme of voting is used and in Boosting a weighted vote. In both of them, to decide the final class label, the abstract level of the outputs of base classifiers is used. In [53], to define majority vote rule the authors have used the measurement levels. In the simple or uniform voting all the base classifiers have the same weight and in the weighted vote a procedure is used to compute the weights. For example in AdaBoost weights are computed according to the performance of base classifiers on the training set or in [46] a linear discriminant is used for this purpose.

2.4.2.2 Order Statistical Combining Methods

For these type of methods, we need the outputs of the base classifiers to be in the measurement level such as posterior probability of the classes. Examples of these methods are Max, Min, median and sum (or average). In [53] and [86] a theoretical framework has been presented for these kinds of methods.

2.4.2.3 Stacking

In this method, first the original training set is used to train different classifiers and the output of generated classifiers is used to form another training set called meta-level data set. A learning algorithm is applied to meta-level data set to build the classifier for combining [102][22].

2.4.2.4 Cascading

As with stacking, learning is performed in several steps but the high level or meta-level classifier uses original training set plus the probability class distributions provided by the base classifiers. That is, at each step a new attribute is added to the data set without changing the number of training patterns. The new attribute is the class probability distribution obtained at the previous step. Therefore, at each step the learning algorithm uses a new data set to produce a classifier and in a sequential way the classifiers are combined [22].

2.5 Decision Tree Learning Algorithms

A decision tree is a tree which represents the classification rules. It assigns a class label to a test pattern by filtering the pattern down through the tests in the tree. It contains a root as the starting node and the leaves as the terminal nodes. The leaves represent the class labels or categories of patterns and the other nodes represent the attributes associated with the objects being classified. The branches of the tree represent each possible value of the attribute node which they originate. The non-leaf nodes are called

Figure 2.1: An example of decision tree. This tree is for playing golf [78].

internal nodes. Decision tree can be divided into different types. For example, based on type of test, the decision tree can be a univariate or a multivariate tree. In multivariate decision tree, a combination of several attributes is used for test while in univariate tree only one attribute is used.

Figure 2.1 shows an example of decision tree. This decision tree is to ascertain whether to play golf or not. In this tree the leaves take *yes* or *no* values. At the root, the *outlook* attribute is tested. Depending on the value of the input pattern for this attribute one of the branches is selected. The same process is repeated for internal nodes (here shown as *humidity* and *wind*) until a leaf in which a label (yes or no) is given to the input pattern[78].

In this section, we review the methods of constructing decision trees and the methods of pruning them.

2.5.1 Characteristics of Decision Trees

Depending on different situations, decision tree classifiers have the following advantages and disadvantages:

1. **Nonparametric Method**

This is an advantage for constructing a classifier using a set of patterns a decision tree does not need to know the distribution of the data nor does it need any parameter to be set.

2. **Understandability**

Understanding the structure of decision trees is simple and the classification rules in terms of values of attributes can be extracted easily. This advantage makes decision trees popular in machine learning.

3. **Instability**

This feature of decision trees makes them popular for ensemble methods. With small changes in the dataset, decision tree learning algorithms produce large changes in the resulting classifier [15]. On the other hand, it is a disadvantage in the context of single decision tree.

4. **Missing Values**

If the value of an attribute for a test pattern at a node is not given, it is impossible to decide which branch should be followed. Decision learning algorithms (e.g. C4.5) solve this problem in constructing stage [78].

2.5.2 Two Phases of Decision Tree Construction

In our work, since we have used post-pruning methods as simplification methods, there are two main phases in creating a decision tree classifier from a noisy dataset. First, a decision tree is created from the whole set of patterns and then it is pruned to remove those parts of the tree which model the noise. In creating the decision tree, a divide and conquer method is used to split the dataset. Partitioning the dataset is performed based on the values of an attribute which is the best choice according to a selection measure. The second phase is discussed in section 2.7.

2.5.3 Best Attribute Selection Measures

Here we review a number of methods to choose the best attribute for test at a node.

2.5.3.1 Information Gain

Information Gain (or entropy) is a statistical property which was introduced by Quinlan in the ID3 algorithm. It is an idea from information theory and can be defined as[77]:

$$Entropy(S) = - \sum_C (P(C) \times \log_2(P(C))) \quad (2.1)$$

where S is pattern set, $P(C)$ is proportion of S belonging to class C .

$Gain(S, At)$ which is the information of S on attribute At is defined as:

$$Gain(S, At) = Entropy(S) - \sum_v \left(\frac{|S_v|}{|S|} \right) \times Entropy(S_v) \quad (2.2)$$

where S_v is the set of patterns which belong to one of the values of the attribute At .

2.5.3.2 Gain Ratio

The drawback of Gain Information is that it has a strong bias in favour of attributes which have many values. To solve this problem Quinlan introduced Gain Ratio as measure of test selection. The definition of Gain Ratio is as follows [78]:

$$SplitInfo(S, At) = - \sum_{v=1}^n \frac{|S_v|}{|S|} \times \log_2\left(\frac{|S_v|}{|S|}\right) \quad (2.3)$$

and the Gain Ratio

$$GainRatio(S, At) = Gain(S, At) / SplitInfo(S, At) \quad (2.4)$$

2.5.3.3 Gini Diversity Index

Gini diversity index is similar to Gain Information, but measures the impurity of an attribute with respect to the classes. Since each node of the tree contains a subset of

patterns, we can compute the class probability function $P(C|t_n)$ in node t_n and the Gini diversity for this node is[13]:

$$GI(t_n) = \sum_{i \neq j} P(C_j|t_n)P(C_i|t_n) = 1 - \sum_i P^2(C_i|t_n) \quad (2.5)$$

$\sum_i P^2(C_i|t_n)$ is defined as impurity function. This function becomes maximum when all classes have equal probability and it is minimum when all instances in the sample belong to only one class.

2.6 Decision Tree Algorithms

Decision tree algorithms can be divided into different kinds like univariate and multivariate decision trees. A multivariate decision tree uses a linear combination of attributes in each decision, while a univariate decision tree uses one feature. ID3, C4.5 and CART are examples of univariate decision trees. Bredensteiner and Bennett used a robust linear program(RLP) to construct a multivariate decision tree [6]. In this section we briefly review a number of decision tree algorithms.

2.6.1 ID3

ID3, developed by Quinlan, constructs a decision tree by recursively selecting the best attribute to use at current node in the tree. To choose the best attribute, information gain, equation 2.2 is used. If the chosen best attribute perfectly classifies the training set then ID3 stops; otherwise it recursively operates on the n (n is the number of values of the selected attribute) partitioned subsets to get their best attribute [77].

2.6.2 C4.5

Figure 2.2 briefly shows the main part of C4.5 algorithm which has been developed by Quinlan. ID3 uses information gain to determine which attribute is suitable for test at a node while C4.5, the newer version of ID3, uses gain ratio [78]. Both of them divide the set of examples at each node according to value of the selected attribute. Construction

-
1. Compute frequency of each Class.
 2. Return if all examples have the same class or there are fewer than specified number of examples.
 3. Calculate information gain and gain ratio for each attribute.
 4. Identify which attribute has maximum gain ratio for use as the test at this node.
 5. Divide the training set according to values of that attribute.
 6. For each subset if the subset is not empty repeat from step 1 otherwise return a leaf.
 7. Return the tree.

Figure 2.2: C4.5 Decision tree Algorithm.

of the tree starts with the root and if all examples have the same class or there are few patterns at a node, the node will be a leaf. Since C4.5 uses the information in the initial training set to split, the node is a leaf if the resulting subset after division is empty. C4.5 keeps weights for each example and changes the weight of an example for which the selected attribute at a node has unknown value according to proportion of examples[78]. C4.5 can deal with continuous attributes by using Information Gain to discretise them. The Information Gain equation is used to find a threshold. Then this threshold is used to convert the values of the continuous attribute into two values. When a continuous attribute has maximum gain ration, its values are discretised.

2.6.3 CART

CART (Classification and Regression Trees) methodology is technically known as binary recursive partitioning. The process is binary because parent nodes are always

split into exactly two child nodes and recursive because the process can be repeated by training each child node as a parent. To split a node into two child nodes, CART always asks questions that have yes or no answer. To split the data in a node, Gini diversity index is one of the criteria used to choose the attribute which has maximum entropy reduction. CART stops growing the tree when there are not enough patterns in the subset reaching a node, or the entropy reduction has reached a pre-defined threshold, or all patterns reaching the node belong to the same class [13].

2.6.4 The Linear Machine Decision Trees Induction Algorithm

The LMDT algorithm uses a top-down approach and trains a linear machine for each node of the tree. This algorithm constructs each test in a decision tree by training a linear machine based on a subset of the input variables, which then serves as a multi-variate test for the decision node. A linear machine is a multi-class linear discriminant, which itself classifies an instance. The result of the linear machine test is the class name. There is a branch for each possible class at a node. For classification of an instance, it is encoded according to the local encoding information retained in the decision node. For example, for a two-valued variable, one of the values is encoded as 1 and the other as -1. At the end of repeating this process, a leaf node shows the class of the instance[89].

2.6.5 Decision Tree Stumps

This kind of decision tree contains only one node and is the simplest tree. If the attribute chosen for the test in the node is discrete or nominal, a multi-branch split is created (according to values of the attribute) and a branch for unknown values. If the attribute is continuous or real valued, it is discretised and two-branch split is created with a branch for unknown values. To discretise the continuous attribute, a method similar to that in C4.5 is used.

2.7 Decision Tree Simplification

Sometimes, the generated decision tree has large size and is very complex and so it is not comprehensible. Our interest is a tree as small as possible with the same accuracy as a complex tree. According to Occam's razor principle when we have two competing classifiers which make the same predictions, the one that is simpler is the better. That is, by Occam's razor the simpler classifier should be chosen and the other one should be eliminated.

The methods for simplification of a large decision tree can be divided into five categories to control tree size. These methods are: pruning, modify test space, modified test search, database restrictions, and alternative data structures [16]. These methods improve the comprehensibility of decision trees while maintaining or improving accuracy.

The complexity of a univariate decision tree is measured as the number of nodes. The reasons for complexity are mismatch of representational biases and noise. In the first, the learning algorithm is unable to model some target concepts. Also, in some algorithms, (e.g. C4.5), obtaining perfect accuracy results in subtree replication which makes the tree large and suggests a mismatch of representational biases [78]. In the second, the values of features or classes are unknown. Overfitting may occur due to this noise. Simplification is performed to reduce complexity and remove the small disjuncts which are leaves with a few cases.

2.7.1 Pruning

Pre-pruning and post-pruning are examples of this method [16]. In the simplest pre-pruning methods, a threshold stopping criterion is imposed on the algorithm. The stopping criterion estimates the performance gain expected from further tree expansion. It stops the expansion of the tree when the expected gain is not accessible. In fact, after selecting the best test, the resulting partitioning is assessed. If the quality is lower than the threshold, tree expansion is terminated. A disadvantage of this method is the setting of the threshold. Too low a value causes a little simplification and too high a

value results in losing useful information that can be obtained from data [78]. Quinlan first used this method in ID3 [77].

Post-pruning methods remove one or more subtrees and replace them by a leaf or one branch of that subtree. One class of these algorithms divides the training set into growing set and pruning set. The growing set is used to generate the tree as well as prune. The pruning set is used to select the best tree [13]. In the case of shortage of training set, cross-validation method is used. In this method, the training set first is divided into several equal-sized blocks and then on each iteration one of the blocks is used as a pruning set and rest as a growing set. Another class of post-pruning algorithms like pessimistic pruning use all the training set for both growing and pruning [79]. We review a number of post-pruning methods used in our work in section 3.4.

2.7.2 Modifying the Test Space

At each node in the decision tree, a test is carried out. Some approaches modify the set of tests via attribute construction and use multivariate tests which consist of combinations of attributes. In these methods, complexity is defined as the sum of the number of attributes included in all nodes and the number of leaves. Using combination of attributes at each node results in a smaller tree. However, the space of hypotheses becomes larger and searching this space increases the computational complexity. Two methods of attribute construction are Data-Driven Test Construction and Hypothesis-driven Test Construction [16]. The first method uses numeric and logical operators for attribute construction. Oblique Classifier 1 (OC1), which was developed by Murthy et. al. [68], uses Numeric Construction Operators method and can be applied to examples that have continuous attributes. Algorithms for Hypothesis-driven Test Construction iteratively create a tree and induce new attributes via combining primitive attributes by simple logical operators. To construct the new attributes previous induced tree is used to constrain the selection of attributes to combine.

2.7.3 Modifying the Search for Tests

These algorithms modify the ways of selecting the best test. Some of them propose alternative test selection measures like Minimum Description Length (MDL) based algorithms [65]. MDL-based algorithms select a tree that minimises the Description Length [74]. Description Length is defined as the number of bits needed to encode both the theory (the decision tree) and the data from which the tree was built. Dietterich et. al. introduced an improved information gain test selection measure which is based on weak learning or boosting model [24]. In some algorithms, continuous attributes have been discretised to change their representation. Discretisation of continuous attributes results in more chance to be selected for test at nodes of the tree. In C4.5, continuous attributes have two values after Discretisation [78].

2.7.4 Database Restriction

These methods perform case selection or attribute selection and eliminate them to have smaller trees. Examples of case selection algorithm are Windowing [78] and ROBUST-C4.5 [50]. Attribute selection algorithms remove irrelevant attributes prior to decision tree induction [3].

2.7.5 Alternative Data Structures

These methods reduce the tree size by translating it into a *decision graph* or *rules*. Oliver introduced an algorithm for translating a tree to graph by using the Minimum Message Length [70]. C4.5 has an option for generating rules from an induced tree. According to this option, first a decision tree is built and then it is translated to a set of rules.

2.7.6 Post-Pruning Methods

In these methods which are the more usual ones, first the tree is grown and then starting from the leaves, by applying the pruning criteria one or more subtrees are replaced by

a leaf or a branch. Hereafter anytime we refer to pruning, we mean post-pruning methods. Examples of decision tree post-pruning methods are Error-based Pruning (EBP), Minimum Error Pruning (MEP), Reduced-Error Pruning (REP), Critical Value Pruning (CVP) and Cost-Complexity Pruning (CCP). These methods will be explained in chapter 3.

Chapter 3

Comparing Pruning Methods for Ensemble Classifiers

3.1 Introduction

Research on ensemble methods or ensemble design tasks involves finding answers to questions such as:

- Which ensemble methods are suitable for a specific data set?
- How do base classifiers need to be configured to improve the performance of the ensemble? (e.g. for decision trees is pruning necessary or not?)
- How many base classifiers need to be used in the ensemble?

This chapter will address the answers to the first two questions. Decision trees have been used as base classifiers and as we know, one of their characteristics is that they do not need any parameter to be set except switching pruning off or on (also a pruning parameter in some methods) which is used to reduce the complexity and to answer the second question about decision trees.

Diversity of classifiers in an ensemble is a necessary condition for improvement of its performance. Diversity means that each individual classifier like an expert has its

own knowledge about the problem and different pattern of errors compared to others. In simple words, different classifiers do not make the same pattern mistakes. Various techniques for reducing correlation between classifiers before combining are: (i) reducing dimension of training set to give different feature sets, (ii) incorporating different types of base classifier, (iii) designing base classifiers with different parameters for same type of classifier, (iv) resampling training set so each classifier is specialised on a different subset, (v) injection of randomness into base classifiers, and (vi) coding multi-class binary outputs to create complementary two-class problems[93],[25]. In this chapter, we consider two popular examples belonging to category (iv), that rely on perturbing training sets.

Bagging and Boosting work very well with Decision trees. On the other hand, pruning methods are used to reduce their complexity and make them more comprehensible. This may influence their accuracy. The performance of an ensemble also depends on the base classifiers. Therefore, our goal is to find the effect of pruning methods on the performance of ensembles which are generated by two popular ensemble methods; i.e., Bagging and Boosting. As a related work, in [30], Drucker has used decision trees for two-class problems and Error-Based Pruning and Z-Based Pruning to prune them. Separating training into growing set and pruning set has been considered for the pruning methods. Drucker reported that the best results have been obtained without pruning. In contrast to the work here, Boosting has been used as ensemble method and two-class datasets have been employed for the experiments. To explain our experiments and results, we will review the following materials in next sections:

In sections 3.2, 3.3, and 3.4 we will explain the existing pruning methods for base classifiers and ensembles. Sections 3.5 and 3.6 include a review of Bagging and Boosting. Different definitions of bias, variance and their relation to pruning will be presented in section 3.7. To compare Bagging and Boosting, we have used a statistical test called McNemar which will be described in section 3.8. In the last part of this chapter we will explain the experiments and the results we have obtained.

3.2 Two levels of Pruning

In designing an ensemble, Pruning can be performed at two levels: ensemble level and base classifier level. At the ensemble level the goals are:

- To reduce the amount of memory required for storing the base classifiers by discarding a subset of them while preserving the performance [21];
- To reduce the run-time system resources[73]

At the base classifier level, which is addressed in our work, in addition to the above goals, reducing the complexity to make the decision trees more comprehensible and avoid overfitting are the aims. These methods are explained in section 3.4.

3.3 Pruning Methods for Ensembles

At the ensemble level, according to [21] the pruning method is the process to find the best subset of generated base classifiers according to the given conditions (such as memory size) while the performance and accuracy are maintained. Among the methods used and developed in literature, a few have been extracted from decision tree pruning methods. Reduced-Error Pruning (REP) [21] and Cost Complexity Pruning (CCP) [73] are examples of these kinds. Here, we review other methods and the decision tree pruning methods will be explained in section 3.4.

3.3.1 Early Stopping

According to the given condition, when the required number of classifiers are generated, the algorithm stops[21]. As we know, the drawback of this method is the potential loss of other useful classifiers which may be produced later.

3.3.2 KL-Divergence Pruning

Training unstable learning algorithms (e.g. decision tree) on datasets with different probability distributions results in diverse classifiers. Therefore, measuring the distance

between different probability distributions may enable us to have an ensemble with diverse classifiers. To measure the distance, a method known as the Kullback-Leibler Divergence may be used. K-L Divergence is defined as [19]:

$$D(p, q) = \sum_{x \in X} p(x) \log \frac{p(x)}{q(x)} \quad (3.1)$$

where p (or q) is the probability of training set used in the ensemble algorithm (e.g. Boosting). A subset of base classifiers is chosen according to the given condition (3.1) which is maximum summed KL-distance. To reduce the computation cost for choosing this subset, a greedy algorithm is used. The greedy algorithm starts from the first generated classifier and then iteratively adds to the subset a classifier which increases sum of $D(p, q)$. This is repeated until the required number of classifiers is reached.

3.3.3 Kappa Pruning

In this method, an agreement measurement, called *kappa statistics* (κ), is computed for each pair of generated classifiers and then it is sorted in ascending order to choose the required number of classifiers [21]. It is defined as follows:

$$\frac{\Theta_1 - \Theta_2}{1 - \Theta_2} \quad (3.2)$$

where Θ_1 and Θ_2 are the probability that two classifiers agree. Θ_2 is the modified variant of Θ_1 to prevent random agreement between classifiers (for more details, see [21]). To choose a subset of generated classifiers in Kappa pruning algorithm, κ is calculated for each pair of classifiers and then the values of κ is sorted in ascending order. It is started from the lowest value of κ to choose the classifiers until the subset is completed. A disadvantage of this method is that it does not consider the weights or the accuracy of the base classifiers on the training set and it is possible to prune a classifier which has higher weight than others.

3.3.4 Kappa-Error Convex Hull Pruning

This method considers both diversity and accuracy. A Kappa-Error diagram is used in which the x coordinate is the κ statistics of each pair of classifiers and the y coordinate is

their average errors on the training set. Using this diagram a convex hull is constructed in which the most accurate and the most diverse pairs of classifiers are included [21].

3.4 Pruning Base Classifiers

Pruning which is a concept developed for decision trees has been applied to neural networks as well. *Weight decay*, *optimal brain surgeon* are examples of pruning methods for neural networks[45][8]. However, the pruning methods used in neural networks are different to those for decision trees, because the methods of constructing neural networks and decision trees are very different. The main difference is that the decision tree architecture is implicitly data-dependent.

All the pruning methods considered here use post-pruning, and therefore construct the full tree before applying the pruning criteria. Also, we will explain Z-based Pruning which has been used in a work similar to ours.

3.4.1 Error-based pruning (EBP)

EBP was developed by Quinlan for use in C4.5. It does not need a separate pruning set, but uses an estimate of the expected error rate. A set of examples covered by the leaf of a tree is considered to be a statistical sample from which it is possible to calculate the confidence for the posterior probability of mis-classification. The assumption is made that the error in this sample follows a binomial distribution, from which the upper limit of confidence [75] is the solution for p of

$$CF = \sum_{x=0}^E \binom{N}{x} p^x (1-p)^{N-x} \quad (3.3)$$

where CF is confidence level, N is number of cases covered by a node and E is number of cases which are covered by that node erroneously (As in C4.5 we have used an approximate solution for equation (3.3)).

A default confidence level of 25% is suggested, and the upper limit of confidence is multiplied by the number of cases which are covered by a leaf to determine the number of predicted errors for that leaf. Further the number of predicted errors of a subtree

is the sum of the predicted errors of its branches. If the number of predicted errors for a leaf is less than the number of predicted errors for the subtree in which that leaf is, then the subtree is replaced with the leaf. We tried changing the confidence level to vary the degree of pruning but found that this is not a reliable way of varying tree complexity [94],[29].

3.4.2 Minimum Error Pruning (MEP)

MEP was introduced by Niblett and Bratko, and uses Laplace probability estimates to improve the performance of ID3 in noisy domains [69]. Cestnik and Bratko have changed this algorithm by using more general Bayesian approach to estimating probabilities which they called *m-probability estimation* [18]. In this algorithm, the parameter m is changed to vary degree of tree pruning. Their suggestion is that perhaps the parameter can be adjusted to match properties of learning domain such as noise. To prune a tree at a node, the first step is to calculate the expected error rates of its children. The expected error rate of a node is the minimum on i of $1 - p_i(t_n)$ where $p_i(t_n)$ is the probability of i th class of examples reaching that node and is determined by

$$p_i(t_n) = \frac{n_i(t_n) + p_{ai} \cdot m}{n(t_n) + m} \quad (3.4)$$

where t_n is the test node, $n_i(t_n)$ is the number of examples reaching the node and belong to the i th class, $n(t_n)$ is the total number of examples reaching the node t_n and p_{ai} is the a priori probability of the i th class.

Cestnik and Bratko called the expected error rate the *static error*. In the second step, *dynamic error* of the node is calculated, where *dynamic error* is defined as the weighted sum of the static errors of its children [18]. The node will be pruned if its static error is smaller than its dynamic error and will be replaced by a leaf.

3.4.3 Reduced Error Pruning (REP)

REP requires a separate pruning set, and was proposed by Quinlan [79]. It simply replaces each internal node (non-leaf node) by the best possible leaf with respect to the error rate over the pruning set. Branch pruning is repeated until there is an increase

in the pruning set error rate. The procedure is guaranteed to find the smallest, most accurate subtree with respect to the pruning set.

3.4.4 Critical Value Pruning (CVP)

CVP was proposed in [67], and operates with a variety of node selection measures. The idea is to set a threshold, the *critical value* which defines the level at which pruning takes place. An internal node is only pruned if the associated selection measures for the node and all its children do not exceed the *critical value*. The full tree is pruned for increasing critical values giving a sequence of trees, and then the best tree is selected on the basis of predictive ability. A number of suggestions were made for finding the best tree in the sequence, the obvious one being to use a separate pruning set as in REP.

3.4.5 Cost-complexity pruning (CCP)

CCP was developed for the CART system, and produces a sequence of trees by pruning those branches that give lowest increase in error rate per leaf over the training set [13]. Breiman defines cost-complexity for tree T used as :

$$\frac{E}{N} + \alpha \times L(Tr) \quad (3.5)$$

where N is the number of patterns in the training set used for generating the tree and E is the misclassified patterns, $L(Tr)$ is the number of leaves, and α is a parameter which can be used for trade-off between cost and complexity. Let the sequence of subtrees be denoted by $Tr_1 > Tr_2 > \dots > tr$ in which Tr_1 is the original tree and Tr_2 has been generated by pruning Tr_1 and finally tr is the root. To produce Tr_{i+1} from Tr_i , all non-leaf node are examined. If a subtree is replaced by a leaf, then new tree (Tr_{i+1}) has the same cost-complexity as the previous tree (Tr_i) when

$$\alpha = \frac{M}{N(L(ts) - 1)} \quad (3.6)$$

where N is the number of training examples, M is the additional number of misclassified examples when a subtree is replaced with the best possible leaf, $L(ts)$ is number of leaves

in the subtree ts [79]. To produce Tr_{i+1} from Tr_i , all nodes in Tr_i with the lowest α are pruned.

In order to select the best tree in the sequence, either cross-validation on the training set or a separate pruning set is employed. The selected tree is either

1. the smallest tree with error rate (on pruning set) less than minimum observed error (on training set) rate (OSE rule)
2. the smallest tree with error rate less (on pruning set) than minimum observed error rate (on training set) plus one standard error (1SE rule).

However in Breiman's Bagging [14], since each tree is built on a bootstrap replicate he uses the full training set to prune.

3.4.6 Z-based Pruning

In [30] the effect of pruning on the performance of ensembles has been studied. Two pruning methods have been used: Error-Based Pruning and Z-based pruning. In constructing binary decision trees, Z criterion can be defined as follows: In building the tree, for each internal node a hypothesis, a test (a selected attribute to split on) and a critical value of the chosen attribute are assigned. Since values of patterns are less than a critical value or greater than that, each node has two branches. Let W_+^L be the sum of weights of patterns belong to the left branch of a node (their feature values at the node are less than the critical value) and their class is +1, and W_-^L with the definition for the patterns belong to class -1. Suppose c_L is the hypothesis (suggested class label) of the left branch. With similar definitions for the right branch of the node, we can define:

$$Z = W_+^L e^{-c_L} + W_-^L e^{c_L} + W_+^R e^{-c_R} + W_-^R e^{c_R} \quad (3.7)$$

In Z-based Pruning, the dataset is divided into two sets; 80% for building the tree and 20% for pruning. A parent node (denoted by A in the following formula) is converted to a terminal node if

$$W_+^A e^{-c_A} + W_-^A e^{c_A} = W_+^L e^{-c_L} + W_-^L e^{c_L} + W_+^R e^{-c_R} + W_-^R e^{c_R} \quad (3.8)$$

Input: Training set S , Learning Algorithm A , Number of Rounds T

1. For $I = 1$ to T
2. $S' = \text{Bootstrap Sample from } S$
3. Call A
4. Get the Hypothesis h_t trained on S'
5. Next I

Output : The final hypothesis

$$h_{fin}(x) = \arg \max_{y \in Y} \sum_{t: h_t(x)=y} 1$$

where $Y = 1, 2, \dots, K$ is the class labels of patterns

Figure 3.1: Bagging Algorithm. In the combination step, each classifier has the same weight and the output is the label with the largest amount of votes.

In this formula, W refers to the patterns in the pruning set and c , the hypothesis, comes from the training set.

3.5 Bagging

Bagging (abbreviation for bootstrap aggregating) forms replicate training sets with replacement[14]. That is, on each round a subset is randomly drawn which is of the same size as the original training set and on the average contains $1 - 1/e = 63.2\%$ of the large training set (some patterns may appear more than once). Figure 3.1 shows the Bagging algorithm.

Breiman believes that the 37% left-out patterns can be used for estimation of impor-

tant quantities such as node probabilities and node error rates in decision trees[10]. In [42], Grossman and Williams have proposed to use these out-of-bag patterns for giving weights to each classifier (decision trees in their work) based on its performance on these out-of-bag data and use the weights in decision stage via weighted voting method. One of mentioned advantages of Bagging is that with an unstable base classifier, it performs at least as well as the single classifier [14]. Empirical evaluation shows that Bagging is relatively impervious to overfitting [61]. In terms of processing, Bagging is a parallel process and its performance is affected by the sample size and the base classifier [84].

3.6 Review of Boosting and its Supporting Theories

The first Boosting Algorithm was designed by Schapire in the context of the PAC (Probably Approximately Correct) learning Algorithm in 1990 [81]. This algorithm was called Boosting by Filtering and contained a proof of equality of weak and strong learning algorithms. Three hypotheses (or classifiers) are generated in this algorithm by filtering of patterns and an ensemble (or committee machine) is constructed by a simple voting. The first hypothesis is generated over the training set of patterns. Then, the generated hypothesis is used to filter another set of patterns and provide training patterns for the second hypothesis. After constructing the second hypothesis, these two hypotheses are used to provide training set for a third hypothesis. If two hypotheses disagree in their decision on a pattern, that pattern is added to the new training set. To evaluate the performance of these three hypotheses, a test sample is presented to them. If the first and second hypothesis agree in a class label, that class label is given to the pattern. Otherwise, the output of the third hypothesis will be the class label of the test sample.

According to Schapire [81] if each of the three hypotheses has an error rate less than or equal to ϵ ($\epsilon < 1/2$), then the error rate on the combined classifier is bounded by $g(\epsilon) = 3\epsilon^2 - 2\epsilon^3$, This bound is smaller than the original error rate ϵ .

The algorithm of Boosting by filtering needs a large number of training patterns which is a practical limitation. Freund introduced Boosting by majority algorithm to

solve this problem in 1995. Two variants of this algorithm are: Boosting using sub-sampling and Boosting using filtering [35]. In the first variant, a large training set is sampled to make a training sample with size m and a weight for each pattern in the sample is considered. To achieve the goal of Boosting which is an error smaller than $1/m$ with respect to the uniform distribution on the sample, different distributions on the training sample are generated by updating the weights and each time, for generating a weak hypothesis, the weak learning algorithm is applied to a set of patterns which are sampled randomly from the training sample. Weak hypothesis is a hypothesis which has an accuracy a little better than $1/2$. Boosting performs a majority vote over all generated weak hypotheses to make accuracy larger than 0.5. This algorithm needs a large memory to store training patterns in application like on-line learning (this is called space complexity) while the weak learning algorithm does not use all the patterns. Freund presented the second variant of boosting-by-majority algorithm which uses a subset of training patterns and reduces the space complexity. Because of direct selection of patterns from the original sample, this algorithm was called Boosting using filtering. This algorithm like the boosting using sub-sampling calls weak learning algorithm several times and makes several different hypotheses. At each iteration, the weak learning algorithm is given a training set with a new distribution. At the beginning of each iteration, new patterns are drawn for the original training set and its weight is calculated to decide whether it is acceptable or not. A possible problem with this algorithm is that if a large number of patterns are rejected by the filtering operation, we need a very large number of patterns to provide the necessary training patterns for weak learning algorithm [35].

The boosting-by-majority needs to know ahead of time the bias of weak learning algorithm. This is not only impossible, but also the bias changes as the distribution varies.

In 1996, Freund and Schapire introduced a new algorithm of Boosting, called AdaBoost which is an acronym for Adaptive Boosting. AdaBoost, the most popular version of Boosting, adaptively changes the distribution of the training set based upon the performance of sequentially constructed classifiers. Each new classifier is used to adaptively filter and re-weight the training set, so that the next classifier in the sequence

has increased probability of selecting patterns that have been previously misclassified [36]. In AdaBoost, hard patterns which are often misclassified, get higher weight and the weak learning algorithm is forced to focus on them.

Breiman believes that the success of Boosting is in the sampling method it uses. To explain this he developed an algorithm called Arcing (Aaptively resample and combine) in which the final classifier is not built by weighting scheme as in Boosting [15]. That is, Arcing retains weights for each instance and uses the same resampling method as Boosting, however, combines the generated classifiers using simple voting method.

According to Schapire and Freund [39], the AdaBoost algorithm exponentially reduces training error of the final hypothesis which is at most

$$\prod_t 2\sqrt{\epsilon_t(1 - \epsilon_t)} = \prod_t \sqrt{1 - 4\gamma_t^2} \leq \exp(-2 \sum_t \gamma_t^2) \quad (3.9)$$

where ϵ_t is the error of h_t (base classifier) and equals to $\frac{1}{2} - \gamma_t$. They showed that the generalisation error is at most

$$\hat{Pr}[H(x) \neq y] + \tilde{O} \left(\sqrt{\frac{Td}{N}} \right) \quad (3.10)$$

where $\hat{Pr}[\cdot]$ denotes empirical probability on the training pattern. T is number of rounds of boosting, d is the VC-dimension of the weak hypothesis space, and N is the number of training patterns. According to this relation, Boosting will overfit as T , the number of Boosting round, becomes large. However, some experiments showed that on many datasets Boosting does not overfit even if T is very large, and also test error continues to drop even after training error is zero [82].

3.6.1 The Margin

Schapire and Freund presented a new theory for explanation of the effectiveness of Boosting and stated in their paper that this theory can be applied to other ensemble methods. According to this theory, Boosting reduces the test error by increasing the margins of training patterns even if the training error becomes zero. Margin for a

training pattern can be defined as the difference between the vote given to the correct class and the largest vote given to any other class or mathematically for the classifier f at point x with label y :

$$\text{Margin}(x) = f(x, y) - \max_{y' \neq y} f(x, y') \quad (3.11)$$

where x belongs to the training set, y is the class labels of patterns. According to this definition, a pattern is classified correctly if its corresponding margin is positive ($\text{Margin}(x) > 0$). We always have $-1 < \text{Margin}(x) < 1$. The value of margin can be interpreted as the level of confidence in classification of the patterns. In [82], it is reported that Bagging and Boosting increase the margin of training examples as the number of classifiers is increased and this leads to improvement and reduction in the test error. Theoretically, it is expected that test error increases while the number of classifiers in the ensemble is increased[37]. Schapire uses the margin definition and gives a relation between test error and training error[82]. Although this relation shows that as training error reduces, test error will reduce at the same rate, there is another term which is a function of the number of patterns (the larger training set the smaller test error) and number of base classifiers. Therefore, there is no guarantee that reduction in training error leads to reduction in test error [49]. The other problem with Schapire's theorems mentioned in [49] is that the training errors of base classifiers should be better than $1/2$, while the AdaBoost tendency to focus on hard patterns does not make it possible in practice. In [80], Rätsch used the soft margin concept by introducing slack variables to AdaBoost to avoid overfitting. To explain the behaviour of Arcing methods, Breiman introduced *edge* which is similar to margin[12] (see section 5.3.2).

3.6.2 Another Theory for Boosting

Schapire and Freund also explained Boosting behaviour by using game theory. In their explanation, Boosting algorithm is a row player and the weak learning algorithm is a column player in the game matrix. Boosting algorithm chooses a distribution over the training patterns and if the weak learning algorithm presents a hypothesis with error at most $1/2 - \gamma$, then the weak hypotheses chosen by the weak learning algorithm have a convex combination with the margin at least 2γ for all patterns [38].

Algorithm AdaBoost.M1

Input: N examples $\langle (x_1, y_1), \dots, (x_N, y_N) \rangle$ x_i is an instance drawn from some space X ,
with labels $y_i \in Y = \{1, \dots, K\}$

Weak learning Algorithm: WeakLearn

Number of iteration: L

Initialise: $D_i(i) = 1/N$ for all i

Do for $l = 1, 2, \dots, T$:

1. Call WeakLearn, providing it with the distribution D_t .
2. Get back a hypothesis: $h_t : X \rightarrow Y$.
3. Calculate the error of h_t : $\varepsilon_t = \sum_{i: h_t(x_i) \neq y_i} D_t(i)$
if $\varepsilon_t > 1/2$, then set $T = t - 1$ and abort loop.
4. Set $\beta_t = \varepsilon_t / (1 - \varepsilon_t)$.
5. Update distribution D_t :

$$D_{t+1}(i) = \frac{D_t(i)}{Z_t} \times \begin{cases} \beta_t & \text{if } h_t(i) = y_i \\ 1 & \text{otherwise} \end{cases}$$

where Z_t is a normalisation constant

Output : the final hypothesis:

$$h_{fin}(x) = \arg \max_{y \in Y} \sum_{t: h_t(x)=y} \log \frac{1}{\beta_t}$$

Figure 3.2: Algorithm of AdaBoost.M1[36].

3.6.3 AdaBoost Algorithm

In our work, we have used AdaBoost which has been shown in figure 3.2. According to this algorithm, in each round, a training set with a new distribution(D_t) is provided for the weak learning algorithm and a hypothesis is built by using this training set. The error of each base hypothesis is measured with respect to distribution over the training set. The training error, ϵ_t , is used to calculate a factor, called β_t , ($\beta_t = \frac{\epsilon_t}{1-\epsilon_t}$). In round t , if the example is correctly classified by the base classifier (or hypothesis), its weight is multiplied by β_t , otherwise, its weight will not be changed. According to this scheme, hard examples which are often misclassified, get higher weight and the weak learning algorithm is forced to concentrate on the hard examples. Every base classifier is assigned a weight which is equal to $\log 1/\beta_t$ that represents its accuracy on the training set. The final classifier is constructed by combining generated hypotheses using $\log \frac{1}{\beta_t}$.

In the implementation of AdaBoost, one may use either Boosting by resampling or Boosting by reweighting. If the base classifier is unable to handle weights for patterns, the first is used. The second implementation method is useful if the base classifier keeps weight for patterns (e.g. C4.5). For the experiments explained we have used the second method (reweighting).

3.7 Bias, Variance and Pruning

One of the theories for explaining why ensemble classifiers improve performance and outperform a single classifier relies on decomposition of the misclassification error into bias and variance used in regression.

3.7.1 Definition of Bias and Variance

In regression, the expected predictive error of using a predictor contains three terms:

1. a bias term, which measures the distance between the produced predictor and the target function

2. variance of the produced predictors
3. the intrinsic variance of the target function.

Among these three terms, we can not control the third one and the prediction error can be reduced by reducing the first and second terms. The third term does not depend on the learning algorithm. Considering bias as the loss incurred by the main prediction relative to the optimal prediction, the bias term is independent from training set and is zero for the learning algorithm which makes the optimal prediction. The variance term is zero for the learning algorithm which makes the same prediction regardless of the training set [29]. The variance increases as the sensitivity of the learning algorithm increases with the changes in the training set[55]. That is, unstable learning algorithms have high variance [11].

This decomposition in regression relies on these assumptions that the loss function is the squared error and the random variable is a real value. This is not valid in classification. In classification the function is a 0 – 1 loss function and the random variable is a categorical one. Therefore, to use the bias and variance concept in classification, we need to redefine the bias and variance. Here, we review some definitions presented in the literature.

Given a training set $(x_1, y_1), \dots, (x_n, y_n)$, a learning algorithm produces a predictor (or hypothesis) h which classifies pattern x as $\hat{Y} = h(x)$. If $f(x)$ be the value of the target function for the pattern x , the three common loss functions are defined as:

- the squared loss function: $L(f(x), \hat{Y}) = (f(x) - \hat{Y})^2$
- the absolute loss function: $L(f(x), \hat{Y}) = |f(x) - \hat{Y}|$
- the zero-one loss function: $L(f(x), \hat{Y}) = 0$ if $f(x) = \hat{Y}$ and $L(f(x), \hat{Y}) = 1$, otherwise.

The loss function measures the cost of predicting $\hat{Y}$ while the true value is Y .

In [57], it has been stated that the reason for Error-Correcting Output Code (ECOC, see chapter 4) in improving the performance is the uncorrelated errors (diversity of

base classifiers) produced by the learned binary functions built according to ECOC algorithm. Variance and bias are two causes of uncorrelated errors. Learning algorithms such as decision trees (e.g. CART and C4.5) have high variance. This arises from their instability nature. Also, the bias errors produced by learning algorithms like C4.5 on each generated binary classifiers are different and this is made by the non-local-behaviour of C4.5.

Usually, but not always, reducing bias leads to increasing variance and vice versa. This makes a trade-off between bias and variance necessary. Kong and Dietterich claim that Error-Correcting Output Code (ECOC) reduces the bias and variance of a learning algorithm (in their work C4.5). Their definition of bias and variance is as follows: let $h^*(x)$ be the voted hypothesis made by the final classifier and $f(x)$ the classification function, the bias learning algorithm A applied to a training set with size n at point x is defined as [57]:

$$Bias(A, n, x) = \begin{cases} 0 & \text{if } h^*(x) = f(x) \\ 1 & \text{if } h^*(x) \neq f(x) \end{cases} \quad (3.12)$$

and the variance:

$$Var(A, n, x) = Error(A, n, x) - Bias(A, n, x) \quad (3.13)$$

If $C_0, \dots, C_k$ are the classes of patterns in the training set, then $Error(A, n, x) = 1 - p_j$ and p_j is the probability that $h(x) = C_j$. According to these definitions, bias takes zero and one values and variance can be negative. Their definition has the disadvantage that it takes no account of Bayes classifier.

Other definitions of bias and variance have been presented by Breiman. Let $h_B(x)$ be the output of the Bayes classifier for point x , the voting final classifier (called aggregated classifier) is unbiased if $h^*(x) = h_B(x)$ and the bias of a classifier is defined as [11]:

$$Bias = h_B(x) - h(x). \quad (3.14)$$

The same definition applies to variance but for the patterns for which the classifier is biased (i.e. $h^*(x) \neq h_B(x)$). Using these definitions, he states that bias and variance are always non-negative and the bias of the aggregated classifier ($h^*(x)$) is zero. Bayes classifier has zero bias.

Kohavi and Wolpert presented definitions in which bias and variance are non-negative [55]. For the bias, the authors used $bias^2$ and defined as:

$$Bias^2 = \frac{1}{2} \sum [f(x) - h(x)]^2 \quad (3.15)$$

and variance:

$$Var = \frac{1}{2} (1 - \sum [h(x)]^2) \quad (3.16)$$

Using these definitions, Kohavi and Wolpert concluded that error reduction by Bagging is due to variance reduction [4]. However, for Boosting, the error reduction is due to both bias and variance reduction when decision tree is used as the base classifier. Comparing Bagging and Boosting, Kohavi and Wolpert stated that Boosting has higher variance and lower bias [4]. Different definitions of bias and variance have been addressed and compared in [49].

3.7.2 Control Bias and Variance by Pruning

Pruning is one of the methods for controlling bias and variance[4]. Actually there is a tendency in Pruning to produce the smallest tree. This tendency leads to reduction in variance and increase in bias. On the other hand, the structure of the ensemble method may inhibit the pruning method[4]. Therefore, non pruned trees produced in an ensemble such as Bagging and Boosting have smaller bias than pruned trees. Quite the opposite, variance is increased for non-pruned trees.

3.8 Statistical Test for Comparing Ensembles

There are several tests for comparing two learning algorithms (here Boosting and Bagging) and determining whether their difference is significant or not. Among five tests introduced in[23], we have applied McNemar's test. The reason is that in addition to comparing two learning algorithms when the data has been divided into training set and test set it can be applied to cross validation as well. Also, according to [23], this test worked very well in all experiments performed by the author.

In this test, first the two learning algorithms A_1 and A_2 are applied to the training set to construct two classifiers f_A and f_B and then these classifiers are applied to a test set. To find out whether two learning algorithms are significantly different, a contingency table as shown in the following table is built.

$n00$	$n01$
$n10$	$n11$

where:

- $n00$ =number of patterns misclassified by both f_A and f_B
- $n01$ =number of patterns misclassified by f_A but not by f_B
- $n10$ =number of patterns misclassified by f_B but not by f_A
- $n11$ =number of patterns misclassified by neither f_A nor f_B , and
- $n = n00 + n01 + n10 + n11$ is the number of patterns in the test set.

Two learning algorithms are the same if $n01 = n10$ and based on χ^2 test the following quantity is calculated to find whether the difference is significant or not:

$$\frac{(|n01 - n10|)^2 - 1}{n01 + n10}$$

Considering a 5% confidence level, if this quantity is less than or equal to 3.841459, the two algorithms are the same, otherwise they are significantly different.

3.9 Experimental Comparison Bagging and Boosting

In this section we explain the experiments with Bagging and Boosting. The purpose is to compare pruning methods in the context of ensemble methods. Furthermore, the performance of Bagging and Boosting in generating pruned and unpruned ensembles will be compared.

To generate the decision tree that to be used as base classifier in the ensemble we have used C4.5 algorithm. After building the tree, we have used five different pruning algorithms MEP, EBP, REP, CVP, CCP (described in section 3.4) where EBP is the pruning method used in the C4.5 system.

First the experiment has been performed on two sets of artificial data. The first one was an implementation of Breiman's ringnorm example and the second artificial data set was Breiman's twonorm example [11]. Both of them are 20 dimensional, 2 class classification examples. In the first dataset, each class is drawn from a multivariate normal distribution and class 1 has mean zero and covariance 4 times the identity. Class 2 has mean $(a, a, \dots, a)$ and unit covariance ($a = 2/\sqrt{20}$). The theoretically expected misclassification rate reported by Breiman is 1.3%. For the second dataset, each class is drawn from a multivariate normal distribution with unit variance and class 1 has mean $(a, a, \dots, a)$ while Class 2 has mean $(-a, -a, \dots, -a)$. Breiman reports the theoretically expected misclassification rate as 2.3%. Number of training patterns was 300 and 5000 patterns have been used for test.

The other datasets which have been used in the experiments can be found on UCI web site [9]. However, we have used the datasets which have been downloaded from Quinlan's web site at the University of New South Wales [85], which have already been split into training and test sets. Table 3.1 gives the description of the datasets, showing that they have been divided into approximately 70/30 training/testing split according to class distribution. All experiments have been carried out with number of base classifiers set to ten as in [76]. Each experiment is repeated ten times, and where a separate pruning set is employed this includes a random 70/30 growing/pruning split of the training set.

Table 3.2 shows the results on the artificial datasets. The experiment has been repeated ten times. As can be seen from this table, When the number of classifiers is 10, Bagging outperforms on RingNorm and Boosting has better accuracy on TwoNorm and the difference between them was significant (Mc Nemar's test with 5% confidence level [23]). However, as the number of classifiers is increased, Boosting produces better classifiers by forcing the learning algorithm to focus on the hard patterns so that Boosting

Table 3.1: Specification of Datasets used for studying pruned and unpruned ensembles generated by Bagging and Boosting.

Name	Training set	Test set	Class	Attributes		% largest class
				Cont.	Disc.	
Breast	466	233	2	10	–	65.5
BreastCancer	191	95	2	–	9	70.28
Crx	490	200	2	6	9	56
Glass	142	72	6	9	–	35.51
Heart	180	90	2	13	–	55.56
Hypothyroid	2108	1055	2	7	18	95.23
Iris	100	50	3	4	–	33.33
Labor-neg	40	17	2	8	8	64.91
Soybean-large	455	228	19	–	35	13.47
Vote	300	135	2	–	16	61.38
waveform-21	300	4700	3	21	–	33.33

significantly outperforms Bagging when the number of classifiers is 50. For comparison, Breiman's error rate (for Bagging) on these problems was 11.00% for RingNorm and 7.4% for TwoNorm. For CART, Breiman's results show 21.4% test error for RingNorm and 22.1% test error for TwoNorm[15].

In order to test whether degree of pruning could be varied to optimise generalisation performance we selected the MEP method, and varied parameter m as follows (see equation (3.4)): $m = 0, .01, .5, 1, 2, 3, 4, 8, 12, 16, 32, 64, 128, 999, 9999$. For each value of m , resampling is started from the same random state. As shown in table 3.3, for values

Table 3.2: Test Error of C4.5, Bagging and Boosting on artificial data with EBP, T is number of rounds in Boosting and Bagging algorithms.

Data	C4.5	Bagged C4.5		Boosted C4.5	
		T=10	T=50	T=10	T=50
RingNorm	25.26	12.97	11.88	14.47	10.85
TwoNorm	23.40	11.96	8.04	11.32	6.53

of $m > 4$ size of tree indicated that varying m was not a reliable way of varying the degree of pruning, which agrees with the assessment in [33].

Table 3.4 shows for C4.5, Bagged C4.5 and Boosted C4.5 the ratio of unpruned ($m = 0$) test error rate to minimum (over m , see equation (3.4)) pruned test error rate. There are two numbers in each cell of the table separated by /. The first is the ratio and the second one is the minimum test error rate obtained for MEP applied to C4.5, Bagging or Boosting. That is, it is not the minimum error among C4.5, Bagged C4.5 and Boosted C4.5.

To have a comparison with cross-validation, we have applied 10-fold cross validation to the datasets, with results shown in table 3.5. We also applied McNemar's test with 5% confidence level to determine whether the difference between Boosting and Bagging was significant, and table 3.5 shows the number of folds out of 10 that showed a significant difference. Only two datasets appeared significantly different, Waveform21 and Soybean.

The results shown in table 3.6 are the average test errors of C4.5, Boosting and Bagging with EBP when the datasets have been split into 70% for training and 30% for test. The ratio of Boosting/Bagging error rates is shown for each dataset and averaged over all datasets.

Comparisons of different pruning methods shown in tables 3.7 and 3.8, for Boosting and Bagging respectively, present the relative performance of the five pruning methods (for MEP $m = 2$). In tables 3.7 and 3.8 the pruning method with the minimum error rate is set to 1.00. The minimum error rate for each dataset is shown in the column representing the appropriate pruning method.

Table 3.4 shows that, on average over these datasets, Boosting and Bagging can both benefit from varying parameter m in the MEP method. However, as noted previously as m increases for some datasets there was not a monotonic decrease with tree complexity. It should also be noted from table 3.5 that the average ratio for Boosting/Bagging for these datasets is 1.02, compared with a value of 0.93 over twenty-two datasets in [76].

The comparison of pruning methods in tables 3.7 and 3.8 shows that EBP performs best on average for Bagging and Boosting, and MEP worst. However the individual

Table 3.3: Average size of tree in Boosting using MEP.

m	0	.01	.5	1	2	3	4	8	12	16	32	64	128	999	9999
Breast	8.40	4.80	4.80	4.80	4.80	4.80	5.40	3.60	3.60	3.60	3.40	4.80	4.80	6.20	6.20
Breast-Cancer	46.50	38.90	38.90	35.70	34.40	30.60	15.00	4.60	1.20	1.20	1.50	1.00	1.00	1.00	1.00
Crx	22.90	10.90	9.60	11.90	10.70	10.90	6.00	3.20	3.20	3.20	3.20	4.00	3.40	4.40	4.50
Glass	26.20	18.80	18.80	18.80	19.40	15.20	14.80	16.40	18.20	19.60	20.40	22.60	20.60	18.14	16.00
Heart	19.20	10.40	10.40	10.40	10.40	10.40	10.40	7.20	6.80	8.20	5.40	3.40	4.20	7.20	7.60
Hypothyroid	3.20	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Iris	6.40	5.40	5.40	5.40	5.40	5.40	5.40	5.40	5.40	5.40	5.20	5.60	5.67	5.67	5.67
Labor-neg	5.00	3.20	3.20	3.20	3.20	3.20	3.20	3.00	3.00	2.40	2.40	1.67	1.67	1.67	1.67
Soybean-large	34.00	24.50	24.50	24.50	24.00	24.00	24.00	28.50	34.50	34.50	40.00	98.30	102.80	126.80	126.80
Vote	8.60	5.40	5.40	5.40	5.00	5.30	5.30	5.30	5.30	4.30	4.30	4.00	4.40	1.00	1.00
Waveform-21	28.80	21.20	21.20	21.20	21.20	23.40	21.00	21.80	15.60	16.40	19.20	20.80	30.20	30.20	30.20

Table 3.4: Ratio of unpruned ($m = 0$) error rate to minimum pruned error rate using MEP, followed by the minimum error rate for single classifier (C4.5) or classifier ensembles (Boosted C4.5 or Bagged C4.5) over m . Dataset have been split into 70/30 (see text).

Name	C4.5	Boosted C4.5	Bagged C4.5
Breast	1.00/4.29	1.00/2.58	1.00/3.86
Breast-Cancer	1.72/45.26	1.07/33.68	1.23/31.58
Crx	1.18/20.00	1.00/17.00	1.00/17.00
Glass	1.04/37.50	1.09/31.94	1.00/30.56
Heart	1.00/21.11	1.15/16.67	1.06/20.00
Hypothyroid	1.00/5.21	1.00/5.21	1.00/5.21
Iris	1.00/4.00	1.00/6.00	1.00/4.00
Labor-neg	1.00/29.41	1.00/23.53	1.00/23.53
Soybean-large	1.01/49.12	1.01/49.12	1.00/68.86
Vote	1.75/5.19	1.25/3.70	1.25/3.70
Waveform-21	1.00/30.74	1.10/23.15	1.00/23.70
Average	1.15	1.06	1.05

results indicate that there is no pattern corresponding to which pruning method performs best. For example, MEP performs best on three datasets. This suggests that if the type or level of pruning could be suitably chosen, performance would improve.

The fact that decision trees have a growing phase and pruning phase that are both data-dependent makes it difficult to match level or type of pruning to an ensemble of tree classifiers. Our results indicate that if a single pruning method needs to be selected then overall the popular EBP makes a good choice.

3.9.1 Selecting the best tree in CCP and CVP

CCP and CVP methods need a separate dataset to choose the best pruned tree. However, in the experiment which is explained here, we have used the whole training set to choose the best tree. It means that we have not split training sets into growing set and pruning set. At first we apply the training set to C4.5 in which CCP and CVP have

Table 3.5: Mean test error for 10-fold Cross Validation with Boosting and Bagging, and ratio Boosting-Bagging using EBP.

Name	C4.5	Boosted C4.5	Bagged C4.5	Ratio	McNemar's Test
Breast	5.29	4.43	4.29	1.03	0
Breast Cancer	31.60	28.50	29.53	0.97	0
Crx	16.23	14.49	14.78	0.98	0
Glass	37.43	27.69	28.41	0.97	0
Heart	22.22	19.26	20.00	0.96	0
Hypothyroid	1.30	1.36	1.23	1.11	0
Iris	3.33	4.67	4.67	1.00	0
Labor-neg	41.67	28.33	31.67	0.89	0
Soybean-Large	42.42	35.27	24.71	1.43	2
Vote	5.06	4.60	4.83	0.95	0
Waveform-21	25.14	17.32	18.40	0.94	1
Average				1.02	

Table 3.6: Mean Test Error of Boosting and Bagging and Ratio Boosting-Bagging using EBP. The datasets have been split into 70% for training and 30% for test.

Name	C4.5	Boosted C4.5	Bagged C4.5	Ratio
Breast	5.58	3.86	3.86	1.00
Breast-Cancer	40.00	33.68	29.47	1.14
Crx	21.00	17.00	18.00	0.94
Glass	37.50	29.17	30.56	0.95
Heart	21.11	20.00	18.89	1.06
Hypothyroid	1.70	1.23	0.95	1.29
Iris	4.00	6.00	4.00	1.50
Labor-neg	29.41	23.53	23.53	1.00
Soybean-large	34.64	26.75	32.89	0.81
Vote	7.41	2.96	2.96	1.00
Waveform-21	30.74	20.09	22.09	0.91
Average				1.05

Table 3.7: Test Error of Boosting with different Pruning Methods. The datasets have been split into 70% for training and 30% for test.

Name	MEP	EBP	REP	CCP (0-SE)	CCP (1-SE)	CVP
Breast	1.00/2.58	1.50	1.73	1.63	1.57	1.58
breast Cancer	1.02	1.25	1.00/26.96	1.01	1.28	1.20
Crx	1.02	1.02	1.02	1.00/16.70	1.07	1.06
Glass	1.19	1.00/29.17	1.45	1.24	1.40	1.24
Heart	1.00/14.44	1.38	1.35	1.37	1.45	1.26
Hypothyroid	4.33	1.02	1.16	1.13	1.08	1.00/1.20
Iris	1.07	1.07	1.00/5.60	1.04	1.04	1.00
Labor-neg	1.00/23.53	1.00	1.02	1.12	1.18	1.18
Soybean-large	2.11	1.16	1.02	1.00	1.05	1.00/23.11
Vote	1.00/2.96	1.00	1.05	1.15	1.20	1.20
Waveform-21	1.04	1.00/20.09	1.22	1.14	1.18	1.17
Average	1.50	1.13	1.18	1.17	1.23	1.17

Table 3.8: Test Error of Bagging with different Pruning Methods. The datasets have been split into 70% for training and 30% for test.

Name	MEP	EBP	REP	CCP(0-SE)	CCP(1-SE)	CVP
Breast	1.22	1.00/3.86	1.18	1.01	1.07	1.02
BreastCancer	1.12	1.12	1.00/26.21	1.00	1.17	1.14
Crx	1.00/17.00	1.06	1.07	1.00	1.03	1.03
Glass	1.14	1.00/30.56	1.49	1.23	1.20	1.23
Heart	1.00/18.89	1.00	1.09	1.09	1.08	1.11
Hypothyroid	5.50	1.00/0.95	1.06	1.03	1.03	1.08
Iris	1.00/4.00	1.00	1.50	1.40	1.60	1.50
Labor-neg	1.00/23.53	1.00	1.20	1.25	1.43	1.02
Soybean-large	2.73	1.30	1.15	1.00/25.26	1.02	1.04
Vote	1.00/2.96	1.00	1.05	1.07	1.05	1.10
Waveform-21	1.29	1.00/22.09	1.09	1.07	1.09	1.07
Average	1.64	1.04	1.17	1.11	1.16	1.12

Figure 3.3: Cumulative distribution of margins training examples after 1 (solid curve), 5(long dashed line curve) and 50(dotted curve) iterations.

been used to prune the initial generated tree. Then, the chosen tree has been applied to the test set. Tables 3.9, 3.10 and 3.11 show test error of C4.5 on 11 datasets. At the next stage, we have performed 50 times (randomly) bootstrap resampling to make an ensemble using Bagging. This has been repeated 10 times and the results shown in the tables 3.9, 3.10, and 3.11 are the average test errors. Standard deviation of 10 test errors for each data set has been shown in the last column of these tables.

Comparing the results shown in table 3.8 with tables 3.9, 3.10 shows that the method explained in this section, applying the whole training set to choose the best pruned tree instead of splitting it into growing set and pruning set, gives better results on all datasets except Breast Cancer for CCP. Also, according to tables 3.8 and 3.11, better performance has been obtained by this method for CVP. This method of CCP and CVP outperforms on Breast, Breast Cancer, Crx, Heart, Labor-neg, Soybean-large and Waveform-21 comparing with EBP. EBP outperforms on three datasets.

3.9.2 The Margin of Patterns in Boosting

Figure 3.3 shows the result over Soybean-large dataset. This figure shows the cumulative distribution of the margins of the training examples after 1, 5, 50 iterations.

Table 3.9: Test Error of Bagging with CCP method(1SE); to choose the best pruned tree, the whole training set has been used. The last column (PErr) shows the test errors for Bagging obtained by the method in which for selecting the best pruned tree the dataset is divided into growing set and pruning set, shown for CCP(1-SE) in table 3.8.

Name	C4.5	Bagged C4.5	Std	PErr
Breast	5.58	3.30	0.20	4.13
Breast Cancer	35.79	27.79	1.84	30.67
Crx	18.50	16.05	0.79	17.51
Glass	38.89	33.19	2.10	36.67
Heart	20.00	15.22	1.80	20.40
Hypothyroid	0.95	0.95	0.00	0.98
Iris	6.00	6.00	0.00	6.40
Labor-neg	17.65	21.76	2.70	33.65
Soybean-Large	17.54	17.15	0.72	25.77
Vote	5.19	2.96	0.00	3.11
Waveform-21	29.74	18.86	0.50	24.08

Table 3.10: Test Error of Bagging with CCP method(0SE); to choose the best pruned tree, the whole training set has been used. The last column (PErr) shows the test errors for Bagging obtained by the method in which for selecting the best pruned tree the dataset is divided into growing set and pruning set, shown for CCP(0-SE) in table 3.8.

Name	C4.5	Bagged C4.5	Std	PErr
Breast	5.58	3.52	0.26	3.90
Breast Cancer	35.79	28.95	2.22	26.21
Crx	18.50	16.05	0.79	17.00
Glass	38.89	32.92	2.06	37.59
Heart	20.00	15.67	1.53	20.59
Hypothyroid	0.95	0.95	0.00	0.98
Iris	6.00	6.00	0.00	5.60
Labor-neg	17.65	21.76	2.70	29.41
Soybean-Large	17.54	17.11	0.65	25.26
Vote	5.19	3.04	0.22	3.17
Waveform-21	29.74	18.66	0.44	23.64

Table 3.11: Test Error of Bagging with CVP method; to choose the best pruned tree, the whole training set has been used. The last column (PErr) shows the test errors for Bagging obtained by the method in which for selecting the best pruned tree the dataset is divided into growing set and pruning set, shown for CVP in table 3.8.

Name	C4.5	Bagged C4.5	Std	PErr
Breast	5.58	3.13	0.27	3.94
Breast Cancer	34.74	28.42	2.11	29.88
Crx	19.00	15.80	0.68	17.51
Glass	38.89	33.61	2.13	37.59
Heart	18.89	15.78	1.09	20.97
Hypothyroid	0.95	0.95	0.00	1.03
Iris	6.00	6.00	0.00	6.00
Labor-neg	17.65	21.76	2.70	24.00
Soybean-Large	17.54	17.15	0.66	26.27
Vote	5.19	2.96	0.00	3.26
Waveform-21	36.17	18.94	0.50	23.64

By comparing the curves when $T > 1$ and $T = 1$, it can be found that AdaBoost increases the margin of examples and also decreases the number of patterns which have margin less than zero. This means that it decreases the error. The result for pruned trees for this dataset shows the same characteristic. Comparing pruned and unpruned ensembles shows that margin concept is not helpful to ascertain which one has better performance. It is because there is insufficient resolution to differentiate between them.

3.10 Summary

In this chapter, we have first explained methods for ensemble and base classifier pruning in sections 3.3 and 3.4, followed by a review of Bagging and Boosting. An explanation using "Margin concept", has been used to describe the behaviour of pruned and unpruned ensemble generated by Boosting. Then, different definitions of bias and vari-

Table 3.12: Number of datasets (out of eleven datasets) for each pruning method which has a test error equals to minimum error rate among them.

	MEP	EBP	REP	CCP(0-SE)	CCP(1-SE)	CVP
Boosting	4	4	2	2	0	3
Bagging	5	8	1	3	0	0

ance as a supporting theory of ensemble was presented and the the relationship of pruning with them was expressed (section 3.7). Finally, we presented the experiments performed with five pruning methods applied to Bagging and Boosting.

Since the construction methods of decision trees and pruning methods are data dependent, as the results expressed in section 3.9 show, the performance of pruning methods as well as ensemble methods changes from one domain to another. Table 3.12 shows a summary of the performance of pruning methods used with Boosting and Bagging. In this table, for each pruning method the number of datasets (out of eleven datasets) that the error rate Bagging or Boosting equals to the minimum error rate has been shown. As can be seen from this table, we can put the pruning methods in order: EBP is the best, MEP is in the second position and then CCP(0-SE), CVP, REP and CCP(1-SE).

Comparing Boosting and Bagging (EBP used as pruning method), we have obtained that difference between Boosting and Bagging on two datasets (Soybean-Large and Waveform-21) is significant in terms of McNemar's test with 5% confidence level. Boosting outperforms Bagging on both of them. Comparison between Boosting and Bagging has been done using 10-fold cross validation technique and nearly the same results have been achieved. On two artificial datasets, Boosting (AdaBoost) and Bagging were significantly different; when the number of rounds was set to 10, Boosting outperforms on TwoNorm while Bagging results in lower test error on RingNorm. However increasing the number of classifiers results in Boosting giving better performance on both of them.

Furthermore, we applied the whole training set to choose the best pruned tree in CCP and CVP in the context of Bagging. The results show that this approach gives better accuracy for the ensembles.

In summary, our goal was to investigate the role of simplification methods (here, post-pruning) on performance of ensemble methods by comparing them to each other. We did not compare with the unpruned ensemble. If we need a pruning method to be used for reducing the complexity of decision tree employed as base classifier in an ensemble (without considering the type of domain or data), it will be Error-Based Pruning. On the other hand, pruned ensembles generated by Boosting (AdaBoost) outperform those generated by Bagging.

Chapter 4

Tree Pruning for Output Coded Ensembles

4.1 Introduction

In chapter 3 we compared five pruning methods in the context of Bagging and Boosting (AdaBoost.M1). In this chapter the same will be performed with Error-Correcting Output Code (ECOC).

In classification tasks, one possible source of complexity is the large number of classes. Examples of this kind of classification tasks are medical diagnosis, digit and letter recognition, phoneme recognition and face recognition. There are multi-class algorithms like decision trees available to handle these tasks. However, when the number of classes increases and the dimension of the feature space is high, learning all decision boundaries becomes difficult for a multi-class learning algorithm. Therefore, decomposition of the task into binary subproblems allows learning algorithm to learn simple decision boundaries. On the other hand, converting a multi-class problem into several binary subproblems gives diverse binary classifiers which results in an accurate ensemble.

In spite of diverse binary classifiers, complexity of generated classifiers is still a problem in decomposition methods such as Error-Correcting Output Code (ECOC) [26]. To reduce the complexity, if a decision tree is chosen as base classifier, the issue of

tree pruning needs to be addressed. On the other hand, the merit of pruning methods changes from one data set to another and changes performance of both base classifier and ensemble. Previously, there has not been study comparing different methods in the context of ECOC. In this chapter, we will be investigating the effect of five pruning methods on the performance of ensembles generated by ECOC and compare these pruning methods to each other. Also, the effect of code length will be investigated. In a related work [26], it has been stated that pruning does not change the performance of ECOC significantly except for one dataset on which it decreases the accuracy. For one-per-class, pruning makes significant improvement in accuracy on two datasets. In this work, only one pruning (EBP) has been used.

The structure of this chapter is as follows:

In section 4.2, we review the decomposition methods and explain what their features are. Two main features of ECOC are code design and learning algorithm selection. We will discuss them in sections 4.3, 4.4 and 4.5. A brief review of why ECOC works very well will be presented in section 4.6. Then, we will discuss the results we have obtained with applying these methods to ECOC to find out which configuration can make significant changes in performance of ECOC and which outperforms the others in different domains.

4.2 Decomposition Methods

Decomposition of a multi-class problem into binary subproblems makes possible the use of simple learning algorithms and reduction in computational costs. In the new space defined by the decomposition, it may be possible to increase the separability of classes. One-Per-Class (OPC), Distributed output Code and Error-Correcting Output Code (ECOC), are examples of such methods in which each class is represented by a binary string of length B . We refer to this string as a codeword. In fact a code matrix C is a $k \times B$ matrix of 0's and 1's and each row corresponds to a codeword for a class and the columns are used to relabel the patterns. The diversity of base classifiers is determined by the distance between columns and the error correcting ability or classes separability is defined by row distances. A pattern is presented to the B trained binary

classifiers and thereby mapped into vector $\mathbf{y} = [y_1, y_2, \dots, y_B]$, in which y_j is the output of j th base classifier and the pattern is assigned to the class corresponding to the closest row (code word) in C .

4.2.1 One-Per-Class (OPC)

One-per-class approach is widely used in neural networks [58] and has been applied to decision trees as well [26]. In this method, for a k class problem, each class is relabelled to a k dimensional binary vector $C_i = [c_{i1}, c_{i2}, \dots, c_{ik}] = [c_{ij}]$, $j = 1, 2, \dots, k$, where:

$$c_{ij} = \begin{cases} 1 & \text{if } i = j \\ 0 & \text{otherwise} \end{cases}$$

and then by using this codeword, an individual binary function is learned for each class. A new example is assigned to a class for which the corresponding column in hypothesis vector produced by the learned functions is one [26].

4.2.2 Distributed output Code

In the Distributed Output Code method, properties of the objects are used to produce a matrix of codewords. It means each bit of the codeword is meaningful. More meaningful properties imply more unique codewords [58] [26]. If we suppose the codeword is a $k \times B$ matrix, B binary functions are trained. To classify a new example, each of B binary functions are evaluated and the outputs form a B length string which is compared with the codewords of each class. The class which has closest distance with the generated string will be the class of the new example.

4.2.3 Error Correcting Output Codes

Error Correcting Output Codes (ECOC) was developed by Dietterich and Bakiri for solving a k class problem by using binary classifiers. In ECOC, it is assumed that the classification task can be modelled as a communication problem and the class information is transmitted over a channel. The channel consists of training patterns

- Produce a k by B binary coding matrix (i.e. a matrix of zeroes and ones). We call this matrix C and each row is identified with exactly one class

Training

- For $i = 1 : B$
 - Assign all classes to zero or one according to column i of coding matrix.
 - Train base classifiers on the new relabelled two class training set

Testing

- To classify a new example, apply it to the B classifiers giving output vector $y = [y_1, y_2, \dots, y_B]^T$
- Use $L_i^1 = \sum_{j=1}^B |C_{ij} - y_j|$ to find the distance of the output vector to each row of the coding matrix.
- The class of new example will be the class for which its corresponding row in coding matrix has minimum distance $ArgMin_i(L_i^1)$.

Figure 4.1: Error-Correcting Output Code (ECOC) Algorithm

and a learning algorithm and the aim is to recover any errors due to finite training patterns, unsuitable feature selection or limitation in the learning algorithm.

Figure 4.1 shows ECOC Algorithm. In this algorithm, to convert a multi-class problem into two-class subproblems, a binary coding matrix is produced which is the key point in the performance of ECOC. The columns of the $k \times B$ matrix are used to assign training set into two set of classes and the new assigned training set is used to train base classifier such as decision tree, neural network or support vector machine. An ensemble is built by B trained base classifiers, their outputs forming a hypothesis vector for a new pattern. To assign the new example to a class, Hamming Distance was originally chosen to measure closeness, since the code was based on error-correcting principles. However when it was shown [56] that the method produced good probability estimates

the decision strategy was modified to the L_1^1 norm or Minkowski distance given by $L_i^1 = \sum_{j=1}^b |C_{ij} - y_j|$. The decision strategy assigns class w_i according to $ArgMin_i(L_i^1)$.

Several researchers have shown that ECOC improves the performance of several learning machines including decision tree [26], neural network [40, 101], multi-layer perceptron, support vector machine [64, 90] and k-nearest-neighbours classifiers [1].

4.3 Code Selection for ECOC

The first step in an ECOC algorithm is to produce or select a code matrix which is a key and critical point and affects the performance of the ensemble. According to [40], a good code for achieving the best possible performance should provide the following conditions:

- Maximum Hamming Distance; distance between codewords affects the capability of error correcting and can increase the separability in the new space created by the code matrix. If d is the minimum Hamming distance, then the code can correct $(d - 1)/2$ bit errors. We will explain a few methods of code generation in section 4.4
- Equal number of ones for the codewords; this prevents biased distance measurement.
- Equal distance between codewords; This makes the distance measurement to be just a function of the posterior probabilities of the classes and not the distance between codewords.

In addition to the row separation mentioned above, the column separation should be guaranteed by the method of code generation since it determines the diversity of the classifiers and error reduction. Combining diverse base classifiers in an ensemble reduces the bias errors of the learning algorithms since the bias errors are not correlated. Having complementary columns in the code matrix results in the same classifiers for learning algorithm like decision trees. In other words, complementary columns create the same decision boundaries for the data.

4.4 Code Generation for ECOC

A review of current approaches to code design is given in section 5.2.2. There are three basic code generation approaches for ECOC[41]:

1. Standard coding theory methods
2. Random codes
3. Meaningful Codes that represent some feature of the training set.

In the first method, the row separation has been guaranteed with a large Hamming distance, however, the column separation is not guaranteed [40]. In the second approach of code generation, it is difficult to guarantee code separation, especially when the code length approaches infinity [7]. To use this approach, we need to check the row and column separation. Both of these two approaches are problem independent and are generated without looking into the data. The third approach is based on data features and the classes are grouped together based on their relationship [41]. Here, we will review the methods of the first approach which we have used in our work. These methods depend on the number of classes.

4.4.1 Exhaustive Codes

This method is suitable for the dataset with the number of classes (k) between 3 and 7. It produces a code with $2^{k-1} - 1$ length. Starting with all ones in first row, the second row consists of 2^{k-2} zeroes followed by $2^{k-2} - 1$ ones. In row 3, 2^{k-3} zeroes are followed by 2^{k-3} ones then followed by $2^{k-3} - 1$ zeroes. In row i , there are alternating runs of 2^{k-i} zeroes and ones. The rows will be separated from each other by $2^{k-1}/2$ and there are no identical or complementary columns.

4.4.2 Column Selection from Exhaustive Codes

This method is applied to the problems for which the number of classes is between $8 \leq k \leq 11$. After generating the Exhaustive Codes, a good subset of its columns is

chosen. To preserve the columns separation while reducing the code length by column selection, we have to select the rows which leads to more separated columns. For more details, see [26].

4.4.3 Bose & Ray-Chaudhuri (BCH) Codes

This method is used for $k > 11$. It uses algebraic methods to generate the error-correcting code based on adding a number of bits to BCD (Binary Coded Decimal) numbers [62] (BCD numbers are binary equivalent of the decimal numbers). The number of codewords is a power of 2, so we have to reduce the number of rows to k and this causes problems in column separation. For a given number of classes, k , we can choose the code length (N) and error correction capability (T) according to table 4.1. For example with a code with 7 bits length we can cover $2^7 - 1$ classes while error correction capability is 1 ($2^K - 1$ classes where K is the number of added bits) or with 15 bits code length, depending on the number of classes, we can choose 1, 2 or 3 for T as error correction capability. We may need to remove some columns. For example columns with all ones or zeros are not useful and the same or complementary columns result in generating the same classifiers.

4.5 Learning algorithm Selection for ECOC

One open problem in ECOC is selection of the optimal learning algorithm. Ensemble methods like Bagging need unstable learning algorithm and as stated in [26], ECOC would fail if the errors made in different positions are correlated. In addition to row separation and column selection in code matrix, the variance of ECOC depends on base classifier accuracy[40]. To have diverse classifiers in an ensemble, one may use different learning algorithms or apply the same learning algorithm to different distributions of the training set. In ECOC, the same algorithm and the same training set are used. However, the problem represented by the given training set is changed via relabelling.

ECOC works very well with neural networks and decision trees. It seems that the learning algorithm should be able to produce diverse classifiers. Instability of these

Table 4.1: The table of accepted code lengths and error correction capability for BCH codes

N	K	T	N	K	T	N	K	T
7	4	1	255	199	7	511	358	18
15	11	1		191	8		349	19
	7	2		187	9		340	20
	5	3		179	10		331	21
31	26	1		171	11		322	22
	21	2		163	12		313	23
	16	3		155	13		304	24
	11	5		147	14		295	25
	6	7		139	15		286	26
63	57	1		131	16		277	27
	51	2		123	17		268	28
	45	3		115	18		259	29
	39	4		107	19		250	30
	36	5		99	21		241	31
	30	6		91	22		238	32
	24	7		87	23		229	33
	18	10		79	24		220	34
	16	11		71	25		211	35
	10	13		63	26		202	36
	7	15		55	27		193	37
127	120	1		47	28		184	38
	113	2		45	29		175	39
	106	3		37	30		166	40
	99	4		29	31		157	41
	92	5		21	32		148	42
	85	6		13	33		139	43
	78	7		9	34		130	44
	71	9	511	502	35		121	45
	64	10		493	36		112	46
	57	11		484	37		103	47
	50	13		475	38		94	48
	43	14		466	39		85	49
	36	15		457	40		76	50
	29	21		448	41		67	51
	22	23		439	42		58	52
	15	27		430	43		49	53
	8	31		421	44		40	54
255	247	1		412	45		31	55
	239	2		403	46		28	56
	231	3		394	47		19	57
	223	4		385	48		10	58
	215	5		376	49			59
	207	6		367	50			60

N: code word length; K: message length; T: error-correction capability

learning algorithms guarantees the diversity. In [1], nearest neighbour which is a stable classifier has been used in ECOC. However, to make possible using nearest neighbour in ECOC, Aha and Bankert have used different subsets of features for each bit in an ECOC code. Another learning algorithm used in ECOC is support vector machine (SVM)[90]. SVM solves different problems defined by ECOC (via relabelling the training patterns) and the authors stated that error correction capability of ECOC enables SVM to solve the multi-class problem. In sum, what we can conclude from previous works is that a combination of instability of the learning algorithm, defining different binary problems via relabelling in the training stage and the error correcting capability of ECOC in the composing or reconstruction stage results in improved accuracy for the ensembles generated by ECOC. Still an open problem is that ECOC can work very well with a simple learning algorithm like decision tree stumps which are only one node trees?

4.6 Why ECOC Works

To increase the accuracy of a problem, an ensemble method should be able to reduce the variance of the base classifier. Variance errors result from noise in the training set and any randomness in the training set or in the behaviour of the learning algorithm. Error correction capability of ECOC can correct these errors. In addition, according to [57], ECOC corrects the errors caused by the bias of learning algorithms. To reduce the bias errors in an ensemble, the errors made by different classifiers should be uncorrelated. This is one of main features of ECOC and in [57] the authors used variance and bias to explain why the errors of base classifiers in ECOC are uncorrelated. Unstable learning algorithms such as decision trees and neural networks have high variance and this can result in uncorrelated errors. Relabelling the training patterns in ECOC defines a new learning task for the learning algorithm and this makes algorithms such as C4.5 produce different decision boundaries and then different bias errors. In summary, uncorrelated errors result from combination of variance and variation in bias. The above explanation for ECOC is based on a definition proposed in [57]. For more details about different definitions of Bias and Variance, see section 3.7.

4.7 Experiment

Table 4.2: Specification of Datasets used for studying ensembles generated by Error-Correcting Output Code

Name	# patterns	# Class	# Features		% largest class
			Cont.	Disc.	
Anneal	898	6	9	29	76.19
Audiology	200	24		69	24
Car	1728	4		6	70.02
Dermatology	366	6	1	33	30.60
Glass	214	6	9		35.51
Iris	150	3	4		33.33
Letter	20000	26	16		3.85
Segmentation	2310	7	19		14.28
Soybean-Large	683	19		35	13.47
Vehicle	846	4	18		24.94

Datasets used in these experiments have been randomly split into training set (70%) and test set (30%). The numbers of patterns, classes and features are shown in table 4.2[9]. We have used C4.5 as base classifier with five methods of pruning given in Section 3.4, plus the unpruned (UNP) case. For REP, CVP and CCP, the datasets have been divided into growing set and pruning set and pruning set has been used for selection the best pruned tree. To generate the ECOC code matrix, we have used exhaustive and BCH codes (with 31 columns, $B = 31$) as explained in section 4.4. For the datasets described in table 4.2, table 4.3 shows the mean test error over ten independent runs normalised with respect to the minimum test error over all pruning methods for the specified dataset. Also, shown in table 4.4, is the number of times that the pruning method is significantly different (McNemar's test 5%) from UNP. Table 4.3 can be used to find that these significant differences in favour of which method are.

In table 4.3, the mean normalised error (last row) over the ten datasets shows that MEP on average has higher error and UNP has lower error compared with all other

Table 4.3: Mean test error normalised with respect to minimum error (last column)

Dataset	EBP	MEP	CVP	REP	CCP0	CCP1	UNP	MinErr
Anneal	2.55	3.19	1.00	1.19	1.09	1.26	1.04	7.46
Audiology	1.31	1.31	1.02	1.10	1.00	1.01	1.17	31.30
Car	1.19	2.32	1.34	1.26	1.25	1.28	1.00	12.96
Dermatology	1.00	1.68	1.52	1.33	1.23	1.24	1.17	11.23
Glass	1.00	1.34	1.16	1.19	1.17	1.19	1.02	26.84
Iris	1.00	1.13	1.52	1.52	1.48	1.48	1.22	5.11
Letter	1.01	5.78	1.11	1.09	1.09	1.10	1.00	9.89
Segmentation	1.01	6.88	1.70	1.59	1.62	1.58	1.00	2.05
Soybean-large	1.40	3.22	1.23	1.31	1.19	1.22	1.00	11.32
Vehicle	1.02	1.22	1.07	1.05	1.06	1.04	1.00	28.36
(Mean)	1.25	2.80	1.27	1.26	1.23	1.24	1.06	

Table 4.4: Number of significant differences of each pruning method from unpruned (UNP)

Dataset	EBP	MEP	CVP	REP	CCP0	CCP1
Anneal	10	10	2	1	1	1
Audiology	1	1	2	3	0	0
Car	5	10	10	6	7	7
Dermatology	0	1	2	0	0	2
Glass	0	2	3	3	4	2
Iris	0	0	0	0	0	0
Letter	1	10	8	7	7	8
Segmentation	0	10	3	3	1	2
Soybean-large	8	10	0	2	2	2
Vehicle	0	5	1	0	1	0
(Mean)	2.5	5.9	3.1	2.5	2.3	2.4

pruning methods. However for MEP we used the default value of $m = 2$ and it is likely that the error would improve if m was allowed to vary. There is little difference in the mean normalised error and mean number of significant differences for EBP, CVP, REP, CCP0, CCP1. We can see that UNP performs best for five datasets, EBP for 3 datasets and CVP and CCP0 for one dataset. Ignoring UNP, EBP outperforms other pruning methods for seven data sets (Glass, Iris, Vehicle, Car, Letter, Dermatology, Segmentation), CCP0 is the best for two data sets (Soybean-large, audiology) and CVP for one (audiology).

Overall it appears that if a single problem-independent strategy is to be selected then UNP is likely to give lowest error rate. If pruning is required to simplify the ensemble, any one of EBP, CVP, REP, CCP0, CCP1 should give similar error rate. However, since EBP performs better on seven out of ten datasets it may be that problem-dependent pruning should be considered. From table 4.3 and from specification of datasets table 4.2 we can see that EBP performs well with those datasets that have only continuous features. For example, if EBP was selected for datasets with no discrete features (glass, iris, letter, segmentation, vehicle) and UNP was selected for the other datasets the mean normalised error over ten datasets would be 1.025. This suggests that a larger study should be carried out to test the hypothesis that problem-dependent pruning is worthwhile.

To investigate more about effect of pruning methods on ECOC as a combining method and the effect of code length, we have changed length of codewords, and applied ECOC to two data sets; Soyben-large and Audiology. As figure 4.2 shows, pruning methods result in different performance as the length of codewords change. For example, on audiology when the number of combined classifiers (length of codeword) is 67, CCP(1SE) method has the minimum test error while with 127 bit codeword CVP method, with 255 and 511 bit codeword CCP(1SE) has minimum test error. For Soybean-large, when 31 and 63 binary classifiers are combined CCP(0SE) and CCP(1SE) are the best while with 127 and 255 bit codewords CVP is the best pruning method.

When we change the size of training set, all pruning methods behave the same except MEP. As shown in figure 4.3 for letter dataset, test error for CCP0SE, CCP1SE, CVP,

Figure 4.2: Test Error of Pruned ECOC as a function of Code Length on Soybean-large and Audiology, the number shown in brackets is the code length

Figure 4.3: Test Error of Pruned ECOC as a function of Training set size for letter dataset, the figure at bottom is for ECOC pruned with MEP

EBP, REP is reduced as the size of training set increased. However, for MEP we have contrary result. The reason seems to be that MEP overprunes the trees in comparison with other pruning methods.

4.8 Summary

The main aim of this chapter was to explain the performance of five pruning methods in reducing the complexity of base classifiers generated in ECOC. The main features of ECOC, code design (sections 4.3 and 4.4) and learning algorithm selection (section 4.5) have been explained. Code selected for ECOC should guarantee the row separation for reducing variance and bias in reconstruction stage and column separation should be considered as the main factor in generating diverse classifiers and their uncorrelated errors to reduce the bias errors. To have uncorrelated errors in ECOC, we need unstable learning algorithm such as decision trees or neural networks or a high accuracy classifier like Support Vector Machine (SVM) to produce different decision boundaries which resulted from solving different binary problems defined via relabelling the training patterns in ECOC.

The goal of this chapter was to address the complexity of base classifiers in ECOC. Our results show that unpruned tree ensembles outperform pruned tree ensembles and among five pruning methods EBP gives ensembles with higher accuracy (section 4.7). Therefore, if one needs to choose a single pruning method for ECOC to reduce the complexity of decision trees (with considering that performance of pruning methods is subject to domain), EBP should be the choice. There was more evidence to suggest that data-dependent pruning could be worthwhile (section 4.7). In summary, comparing EBP with others, it outperforms them on seven datasets (out of ten), while CVP on one dataset, CCP0 on two datasets give better results.

Code length can change the performance of pruning methods (figure 4.2). While a pruning method outperforms others for a given code length, choosing another code length may lead to this result that another method is better. As we expected, increasing the training set size causes improvement in performance of pruning methods. However, MEP degrades with increasing training set size, but this was a special case (figure 4.3).

Chapter 5

Boosted Tree Ensembles for Solving Multi-class Problems

5.1 Introduction

As emphasised in chapter 2, the theory of ensemble classifiers has been developed to address the problem of designing a system with improved accuracy. Recognising that each classifier may make different and perhaps complementary errors, the aim is to pool together the results from all classifiers in such a way that the ensemble outperforms any constituent (also called base) classifier. There are several categories of techniques capable of producing diversity among base classifiers, which is a necessary condition for improvement by combining. In the first category are methods that reduce the dimension of the training set to give different feature sets. The second category includes methods that incorporate different types of base classifier or different base classifier parameters. In the third category, which includes Boosting, are techniques that resample the training set and thereby specialise each classifier on a different subset. The fourth category consists of methods which inject randomness into the base classifiers. Finally in the fifth category are Output Coding methods that create complementary two-class problems from multi-class problems.

Ensemble methods from these five categories have been developed and tuned over the past decade. In principle, the problem of creating a good ensemble is solved by

jointly optimising the design and fusion of base classifiers. However this is a difficult optimisation, and frequently a relatively simple fusion strategy is applied, such as majority or weighted vote. Base classifiers are then designed to match the fusion rule. In this chapter, two ensemble design strategies are combined. AdaBoost which is from category three is combined with Output Coding from category five. This combined algorithm is called AdaBoost.OC. The idea is to convert a multi-class problem into complementary binary sub-problems and at the same time concentrate on difficult-to-classify patterns by reweighting; the idea was first reported in [83]. In this study, decision trees are chosen as base classifier and the effect of tree pruning on the ensemble performance is investigated. An advantage of using decision trees over other base classifiers is that the decision to prune is the only parameter to be set. Pruning reduces the complexity of base classifiers, but does not necessarily lead to improved accuracy. Another subject which has been studied here is how AdaBoost works with a simple base classifier such as decision stump. The concept of margin has been used to show why and how AdaBoost.OC improves performance.

There are several motivations for decomposing a multi-class problem into separate and complementary two-class problems. Firstly some accurate and efficient two-class classifiers do not naturally scale up to multi-class. Attention can then be focused on developing an effective technique for the two-class case, without having to consider explicitly the design and automation of the multi-class classifier. Secondly, it is hoped that the parameters of a simple parallel machine run several times are easier to set and may facilitate more efficient solutions than a complex machine run once. Finally, solving different 2-class sub-problems, perhaps repeatedly with random perturbation, may help to reduce error evident in the original problem.

The structure of this chapter is as follows:

In section 5.2 we will review the idea of output coding and two Boosting algorithms; AdaBoost.M2 which is a multi-class algorithm and AdaBoost.OC which is the main topic of this chapter. Then, the margin concept will be reviewed in section 5.3. Finally we will explain the experiments and the results of applying AdaBoost.M2 and AdaBoost.OC to a number of datasets.

5.2 Boosting Algorithm and Output Coding

As explained in section 3.6, Boosting adaptively changes the distribution of the training set based upon the performance of sequentially constructed classifiers. Each new classifier is used to adaptively filter and re-weight the training set, so that the next classifier in the sequence has increased probability of selecting patterns that have been previously mis-classified. Boosting is a general method for converting a weak learner into one with high accuracy, but it requires that the weak learning algorithm produce hypotheses with accuracy better than random guessing. For a k -class problem, $k \gg 2$, it may be difficult to achieve the required accuracy. One solution proposed by Schapire, referred to as AdaBoost.M2, is based on a pseudo-loss measure in which the weak learner chooses from a set of plausible labels [83]. AdaBoost.M2 divides the training set into hard and easy patterns and forces the learning algorithm to concentrate on patterns whose labels are hard to distinguish from each other. Another solution is to combine Boosting with Output Coding (AdaBoost.OC), in which the weak learner is rerun on the training patterns while reweighting and relabelling on each round [83]. As explained in section 4.2, Output Coding is an ensemble method in which a binary code matrix defines the decomposition of the multi-class into binary sub-problems. Each classifier operates on the same training set but the patterns are relabelled according to the columns of the Output Coding matrix. This process of relabelling was referred to as colouring of the patterns in the context of AdaBoost.OC. By introducing Boosting into colouring, the weak learner no longer uses the same training set on each round. The main advantage is that AdaBoost is only required to solve a two-class problem.

5.2.1 AdaBoost.M2 Algorithm

The main idea in AdaBoost.M2 algorithm (shown in figure 5.1) is to make the base classifier (or weak learner) to compute a soft hypothesis in which a set of plausible labels are included rather than choosing a single label for a new pattern. AdaBoost.M2 forces the learning algorithm to focus on hard patterns which are misclassified in previous rounds and their labels are indistinguishable. This is performed by updating $\tilde{D}_t$, the weight matrix of patterns ($i = 1, \dots, k$), in each round according to performance of the

previous generated classifier. $\tilde{\epsilon}_t$ is the training error of the base classifier and as can be seen from figure 5.1, it consists of errors resulting from including incorrect labels and excluding the correct label. The final classifier chooses the label which has the largest number in plausible label sets. According to [83], if $\tilde{\epsilon}_t = 1 - \tilde{\gamma}_t$, then the training error of final classifier is bounded by:

$$(k-1) \prod_{t=1}^T \sqrt{1 - 4\tilde{\gamma}_t^2} \leq (k-1) \exp \left(-2 \sum_{t=1}^T \tilde{\gamma}_t^2 \right) \quad (5.1)$$

where k is the number of classes.

5.2.2 Output Coding and diverse binary classifiers

Output Coding is a two-stage method, the first being the relabelling stage which can be defined as follows. Let C be the $k \times B$ code matrix with binary elements, where K is the number of classes and B is the number of binary classifiers. Each column provides a map to convert the multi-class problem to binary sub-problems. Specifically, for the j th sub-problem, a training pattern with target class w_i ($i = 1 \dots k$) is re-labelled either as class Ω_1 or as class Ω_2 depending on the value of C_{ij} (zero or one). Therefore for each column, the K classes can be considered to be arranged into two *super-groups* of classes Ω_1 and Ω_2 . (The second stage of Output Coding is the decision rule which is based on finding distance to each row of C that acts as a B -dimensional code word to represent a class).

The Output Coding method was introduced in [28, 26] and named Error-Correcting Output Coding (ECOC). As explained in section 4.2.3, the idea was to base the code on error-correcting principles to facilitate a robust fusion strategy. Actually, the original idea was that there may be some advantage to employing error-correcting codes to represent different signals which should be distinguished from each other when they are corrupted after passing through a transmission channel. The assumption is that the prediction task can be modelled as a communication problem, in which the *channel* consists of input features, finite training samples and learning algorithm. The class label is encoded as a row of the binary code matrix and if the signals from base classifiers are transmitted independently the ECOC framework provides the possibility of detecting

Given $(x_1, y_1), \dots, (x_m, y_m)$ where $x_i \in X, y_i \in Y$.

Initialise $\tilde{D}_1(i, \ell) = \llbracket \ell \neq y_i \rrbracket / (m(k-1))$, where $\llbracket x \rrbracket$ is 1 when x is true otherwise 0

For $t = 1, \dots, T$

1. Train a weak learner using pseudo-loss defined by $\tilde{D}_t$

2. Get weak hypothesis $\tilde{h}_t : X \rightarrow 2^Y$

3. Let

$$\tilde{\epsilon}_t = \frac{1}{2} \sum_{i=1}^m \sum \tilde{D}_t(i, \ell) \cdot (\llbracket y_i \notin \tilde{h}_t(x_i) \rrbracket + \llbracket \ell \in \tilde{h}_t(x_i) \rrbracket)$$

4. Let $\alpha_t = \frac{1}{2} \ln(\frac{1-\tilde{\epsilon}_t}{\tilde{\epsilon}_t})$

5. Update

$$\tilde{D}_{t+1}(i, \ell) = \frac{\tilde{D}_t(i, \ell) \cdot \exp(\alpha_t (\llbracket y_i \notin \tilde{h}_t(x_i) \rrbracket + \llbracket \ell \in \tilde{h}_t(x_i) \rrbracket))}{Z_t}$$

where Z_t is a normalisation factor chosen so that $\tilde{D}_{t+1}$ will sum to 1

Output the final hypothesis:

$$H_{final}(x) = \arg \max_{\ell \in Y} \sum_{t=1}^T \alpha_t \llbracket \ell \in \tilde{h}_t(x) \rrbracket.$$

Figure 5.1: AdaBoost.M2 algorithm.

and correcting some of the errors transmitted. While in practice it is known that there will be some correlation between base classifiers, the evidence is that the ECOC method is capable of improving performance. Various coding strategies have since been proposed, but most code matrices that have been investigated previously are binary and problem-independent, that is pre-designed. Optimal properties of the code matrix for producing diverse classifiers are believed to be maximum Hamming Distance between pairs of columns [26, 99]. Random codes have received much attention, and were first mentioned in [28] as performing well in comparison with error-correcting codes. In [26] random, exhaustive, hill-climbing search and BCH coding methods were used to produce ECOC code matrices for different column lengths. Random codes were also shown in [48] to give Bayesian performance if pairs of code words were equidistant, and it was claimed that a long enough random code would not be outperformed by a pre-defined code. In [100] a random assignment of class to codeword was suggested in order to reduce sensitivity to code word selection and it is shown that an optimal code performs better than random code as code word length is reduced. Although various heuristics have been employed to produce better binary problem-independent codes, there appears to be little evidence to suggest that performance significantly improves by a clever choice of code, except that One-Per-Class is usually inferior [2, 28, 26]. Recent developments include investigation of three-valued codes [2], and problem-dependent continuous and discrete codes [20].

5.2.3 AdaBoost.OC Algorithm

AdaBoost.OC reruns the weak learning algorithm many times and trains it over a new distribution of examples, relabelled as in Output Coding. As can be seen in figure 5.2, given a training set of size m , the weights of patterns are initialised as in AdaBoost.M2, that is

$$\tilde{D}_1(i, \ell) = \llbracket \ell \neq y_i \rrbracket / (m(k-1)) \quad (5.2)$$

where k is the number of classes and $\llbracket x \rrbracket$ is 1 when x is true otherwise 0. On each round, patterns are relabelled according to the colouring (μ_t). To minimise the training errors, a colouring scheme should be chosen to maximise U_t , which is defined in step two of

Given $(x_1, y_1), \dots, (x_m, y_m)$ where $x_i \in X, y_i \in Y$.

Initialise $\tilde{D}_1(i, \ell) = \llbracket \ell \neq y_i \rrbracket / (m(k-1))$

For $t = 1, \dots, T$

1. Compute random colouring $\mu_t : Y \rightarrow \{0, 1\}$.
2. Let $U_t = \sum_{i=1}^m \sum_{\ell \in Y} \tilde{D}_t(i, \ell) \llbracket \mu_t(y_i) \neq \mu_t(\ell) \rrbracket$
3. Let $D_t(i) = \frac{\sum_{\ell \in Y} \tilde{D}_t(i, \ell) \llbracket \mu_t(y_i) \neq \mu_t(\ell) \rrbracket}{U_t}$
4. Train a weak learner on $(x_1, \mu_t(y_1)), \dots, (x_m, \mu_t(y_m))$ weighted according to D_t
5. Get weak hypothesis $h_t : X \rightarrow \{0, 1\}$.
6. Let $\tilde{h}_t = \{\ell \in Y : h_t(x) = \mu_t(\ell)\}$.
7. Let $\tilde{\epsilon}_t = \frac{1}{2} \sum_{i=1}^m \sum \tilde{D}_t(i, \ell) \cdot (\llbracket y_i \notin \tilde{h}_t(x_i) \rrbracket + \llbracket \ell \in \tilde{h}_t(x_i) \rrbracket)$
8. Let $\alpha_t = \frac{1}{2} \ln(\frac{1-\tilde{\epsilon}_t}{\tilde{\epsilon}_t})$
9. $\tilde{D}_{t+1}(i, \ell) = \frac{\tilde{D}_t(i, \ell) \cdot \exp(\alpha_t (\llbracket y_i \notin \tilde{h}_t(x_i) \rrbracket + \llbracket \ell \in \tilde{h}_t(x_i) \rrbracket))}{Z_t}$

where Z_t is a normalisation factor chosen so that $\tilde{D}_{t+1}$ will sum to 1

Output the final hypothesis:

$$H_{final}(x) = \arg \max_{\ell \in Y} \sum_{t=1}^T \alpha_t \llbracket h_t(x) = \mu_t(\ell) \rrbracket.$$

Figure 5.2: The AdaBoost.OC algorithm.

figure 5.2. We have used the scheme from [83] which uses a random assignment of $k/2$ labels to 0 and $k/2$ labels to 1 on each round. The weak learner is trained according to D_t and then by calculating the weak hypothesis h_t , all of the labels satisfying $h_t(x) = \mu_t(\ell)$ receive a vote. The weight of this weak hypothesis (α_t), is found from the weighted training error, $\tilde{\epsilon}_t$, which includes penalty terms for failing to include the correct label in the plausible label set and for including any incorrect labels. The weights of patterns ($D_t(i)$) are updated so that the learning algorithm is forced to concentrate on hardest patterns. Finally the generated hypotheses are combined according to weighted voting so that a test pattern is assigned to the class whose label has received the most votes.

5.3 The Margin Based Analysis of Boosting

Decomposition of classification error into bias and variance and margin based analysis are two theoretical explanations for the experimental results of combining methods. The first one, bias and variance, has been generalised from regression theories to classification and the second theory has been presented by Schapire et. al. as explanation for voting methods such as Boosting [82]. Breiman has presented a theory similar to margin as well.

5.3.1 The Margin

The general definition of margin has been given in section 3.6.1. For a k class problem, the definition of margin can be expressed as the difference between the vote obtained by the correct label and the maximum vote achieved by any incorrect label. In a two class problem, the margin of a learning algorithm at training pattern x is defined as:

$$yf(x) \tag{5.3}$$

where $f(x)$ is the output of the binary learning algorithm and y is the class label. The pattern is classified correctly by the learning algorithm if the margin is positive, otherwise it has been misclassified. The magnitude of the margin can be considered as the level of confidence in the prediction [82]. The training error of the learning

algorithm will be

$$\frac{1}{m} \sum_{i=1}^m \mathbb{I}[y_i f(x_i) \leq 0] \quad (5.4)$$

where $\mathbb{I}[\pi]$ is 1 when π is true otherwise 0. In other words the probability of the misclassification errors made by combined classifier f is $P(\text{margin}(f) < 0)$.

The effect of Boosting is that it increases the margin of patterns which have initially small margins and this causes an improvement in the generalisation error. There is a relation between the training error and the generalisation error and according to [82] for a k class problem with probability at least $1 - \delta$ ($\delta > 0$), this relation can be expressed for all $\theta > 0$ as:

$$P_D[\text{margin}(f, x, y) \leq 0] \leq P_S[\text{margin}(f, x, y) \leq \theta] + O\left(\frac{1}{\sqrt{m}} \left(\frac{\log(mk)\log|\mathcal{H}|}{\theta^2} + \log(1/\delta)\right)^{1/2}\right) \quad (5.5)$$

As it can be seen, the difference between the test error, $P_D[\text{margin}(f, x, y)]$, and training error, $P_S[\text{margin}(f, x, y)]$, is a constant factor which is a function of m , number of training patterns, k , number of classes, and $\log|\mathcal{H}|$, complexity of the base classifier. Therefore, by maximising the margins of training, one can reduce the training error and then obtain better performance on the test dataset. However, it has been reported in [12] and [49] that their results do not support such bound on generalisation error.

5.3.2 The Edge

Breiman has introduced a concept called *edge* which is similar to margin and differs from the margin when the number of classes is more than two. It is defined as follows[12]: Suppose α_i are the weights of classifiers ($h_i(x)$) such that $\sum \alpha_i = 1$. The *edge*(f) (f is the combined classifier) on the training pattern x is:

$$\text{edge}(f) = \sum_{i=1}^T \alpha_i \mathbb{I}[h_i(x) \neq y(x)] \quad (5.6)$$

where $y(x)$ is the label of pattern x and T is the number of classifiers combined in a voting method such as Boosting, Bagging or Arcing. For two-class case $\text{margin}(f) = 1 - 2\text{edge}(f)$ and the misclassification on training set is $P(\text{edge}(f) > 1/2)$. The goal of building an ensemble of classifiers is to find a set of α_i such that $P(\text{edge}(f) > \delta)$ to be minimised (for small values of δ).

5.4 Solving Multi-class Problems with Boosting

In this section we will explain the experiments and the corresponding results that we have obtained by applying two Boosting algorithms to a number of real multi-class datasets. Data sets used in these experiments have been shown in table 4.2 with the number of patterns, classes and features. These data sets can be found on UCI web site [9]. The data have been randomly split into training set (70%) and test set (30%) and we rerun the process 10 times. In the first set of experiments only C4.5 has been used as base classifier for generating the decision trees and also the effect of pruning has been investigated (for Pruning methods, see section 3.4). To prune the decision trees, we used Error-Based Pruning which has been known from the previous chapters to outperform other post-pruning methods for ensemble methods [95, 98]. In these experiments we compare ensemble of unpruned and pruned decision trees built by AdaBoost.M2 and AdaBoost.OC. In the second set of experiments, we focused on AdaBoost.OC and used C4.5 and Decision Stumps to find out how it works with simple base classifier. In fact it is an attempt to find an answer to the question of how ensemble methods such as Boosting work with a simple learning algorithm as they do with a complex learning algorithm.

As figures 5.3 and 5.4 show, the test error of AdaBoost.OC over all data for both Pruned and Unpruned reduces as the number of classifier increases. However, the test error of AdaBoost.M2 appears somewhat insensitive to number of rounds although error increases slightly for Car, Glass and Soybean-Large. This appears to show that the pseudo-loss based algorithm AdaBoost.M2 with C4.5, in contrast to the error-based AdaBoost.M1 with C4.5, only takes a few rounds to learn the training set and in some cases overfits as number of rounds increases.

For AdaBoost.OC the performance of pruned ensembles is similar to the performance of unpruned ensembles, although appears slightly better for Anneal, Audiology, Glass, and Iris. However the difference did not show up as significant (McNemar 5%). For AdaBoost.M2, the unpruned ensemble outperforms the pruned ensemble except for Dermatology.

In an attempt to see overall performance, the composite curve over all datasets is

Figure 5.3: Test Error of AdaBoost.M2 and AdaBoost.OC.

Figure 5.4: Test Error of AdaBoost.M2 and AdaBoost.OC.

Figure 5.5: Composite correct Classification of AdaBoost.M2 and AdaBoost.OC for pruned and unpruned decision trees.

plotted in figure 5.5. The plot is normalised with respect to the best classification rate for each particular dataset as follows. The best classification rate is the mean over the last x rounds, where x is judged to be the number of classifiers above which there is no further improvement. From the composite performance we see that the mean classification rate over the nine datasets for AdaBoost.OC is higher for unpruned than pruned. For AdaBoost.M2, ensemble of unpruned decision trees outperforms pruned ensemble.

As explained in Section 5.2.2 the choice of a code matrix may affect the performance of Output Coding. In AdaBoost.OC, we have used a random approach to dividing the labels on each round. This may mean that diversity is not as great as it could be, since the Hamming Distance between columns has not been maximised. Providing that the code matrix has enough columns random code may perform as well as an optimal code. However, since each round of Boosting depends on the previous round it may be important for efficiency reasons to minimise the total number of rounds. Pursuing optimal codes is a possible way forward in this regard and would likely modify the

curves shown in figure 5.5 at the low end. AdaBoost.M2 is a time-consuming algorithm because on each round it constructs classifiers according to the same number of classes and in comparison AdaBoost.OC has removed this complexity.

5.4.1 Ensembles of Decision Stumps

In the second set of experiments we have used C4.5 with Error-Based Pruning [78] and Decision Stump[47] in AdaBoost.OC. C4.5 is a multi-node decision tree while Decision Stump is a single node tree. In a Decision Stump Tree, if the attribute tested in root is a discrete attribute, a multi-branch split according to the values of the attribute is created and if the attribute is a continuous one a threshold is calculated and the node will have three branches: less than or equal to threshold, greater than threshold and unknown value. In our work, to find the threshold for a decision stump, we have used gain ratio (as in C4.5). The outputs of classifiers generated sequentially by AdaBoost.OC are binary and define the new space for each pattern. In these the ensemble of unpruned and pruned and decision stump trees have been compared.

As can be seen in figures 5.6 and 5.7, like the results we have obtained in the first experiment, test error of AdaBoost.OC decreases for both C4.5 and decision stump as the number of classifiers is increased. For Decision Stump, test error on most of data set decreases very fast so that for Anneal and Dermatology ensemble with Decision Stump outperforms ensemble with pruned and unpruned C4.5 when the number of classifiers is 100. As an example, for Anneal, test error of AdaBoost.OC with Decision Stump has been shown in figure 5.7 (bottom row) and according to figure 5.8 while training error of AdaBoost.OC becomes zero, its test error may still decrease. These results suggest that with a simple base classifier we may get the same performance as a more complex base classifier.

5.4.2 The Margin Based Analysis of AdaBoost.OC

This behaviour of Boosting can be explained by using the margin concept [2]. As can be seen in figures 5.9 and 5.10, AdaBoost with C4.5 produces larger margin for the training patterns and the margin of the patterns is increased as the number of classifiers

Figure 5.6: Test Error AdaBoost.OC with C4.5 and Decision Stump.

Figure 5.7: Test Error AdaBoost.OC with C4.5 and Decision Stump.

Figure 5.8: Training Error AdaBoost.OC with Decision Stump on Anneal and Dermatology data sets.

in the ensemble increases. The same happens to Boosting with Decision Stumps, but smaller margin for the patterns (dash curves in figure 5.9 and dash-dot curves in figure 5.10). That is, for both C4.5 and Decision Stump, the number of patterns which have larger margins increases as the number of classifiers combined in the ensemble increases. In figure 5.10, margins of the training patterns achieved with C4.5 and decision stumps while the number of classifiers is 100 have been compared with decision stump while the number of classifiers is 500. For Anneal, margins of patterns for decision stump with 500 classifiers are larger than those with C4.5 with 100 classifiers (dash curve in figure 5.10 for Anneal) and this can explain why the accuracy of AdaBoost.OC with Decision Stumps with 500 classifiers is better than C4.5.

5.5 Summary

In this chapter we focused on AdaBoost.OC which combines two methods of construction of ensembles of classifiers. First, we reviewed the main features of two Boosting algorithms used in this study and Error Coding as well in section 5.2. In the second part

Figure 5.9: Margin of training patterns in AdaBoost.OC for Anneal, Glass, Audiology, Soybean-Large.

of this chapter we explained two sets of experiments in which we studied the Boosting algorithms for solving multi-class problems (sections 5.4). In the first set of experiments, we have applied two multi-class versions of Boosting to nine datasets by using pruned and unpruned decision trees as base classifiers. In conclusion, AdaBoost.OC outperforms AdaBoost.M2. For AdaBoost.OC, the performance of the ensemble of pruned decision trees is similar to the performance of unpruned ones. However, for AdaBoost.M2, the ensemble of pruned decision trees gives higher test error.

In the second set of experiments, we have studied AdaBoost.OC using two different decision tree learning algorithms which were C4.5 and Decision Stump. The latter is a single node tree and the results obtained with it were comparable with the ones achieved by ensembles of C4.5. Likewise we have studied AdaBoost.OC using the margin concept. The results show that there is a corresponding relation between the margins of the training patterns and the generalisation error: larger margins lead to better accuracy. Another consideration that was addressed was the complexity of ensembles generated by Boosting which can be reduced by using simple classifiers. On the other hand, to get the same accuracy with a simple classifier like decision stump we need more classifiers to combine which increases time complexity. Further work should address this trade off between space and time complexity.

Chapter 6

Face Identification and Verification

6.1 Introduction

One conclusion from the experiments in chapter 5 is that pruned and unpruned ensembles made by AdaBoost.OC have similar performance on different datasets[96, 97]. On the other hand, AdaBoost.OC as a decomposition method can reduce the class complexity for multi-class problems. In this chapter, we address applying AdaBoost.OC to face recognition as a multi-class problem.

Face recognition technology can be used in different applications such as identity authentication, access control to restricted areas, information security, and surveillance. Feature extraction methods and recognition methods of new faces are two main subjects in face recognition research. Principal Component Analysis (PCA) and Linear Discriminant Analysis (LDA) are examples of face feature extraction methods. Examples of methods for the second area (face recognition) are Distance Metrics such as Euclidean distance, normalised correlation measure [60], and Support Vector Machine (SVM) [54]. In [43], a modified version of AdaBoost has been applied to face recognition problem and as the final example, Error-Correcting Output Code has been used for face identification and verification in [52].

Briefly speaking, AdaBoost.OC combines the main features of Boosting algorithm and Error-Correcting Output Code (ECOC) to produce diverse classifiers by converting the multi-class problem such as face recognition to several binary sub-problems and concentrating on hard examples. It reruns the weak learning algorithm many times and trains it over a new distribution of examples, relabelled as in Output Coding. On each round, patterns are relabelled according to a random scheme called colouring which has an important role in minimising the training errors (for more details see 5.2). To build more accurate ensemble of classifiers, the base classifier used in the ensemble method has an important role. The advantage of decision trees is that they do not need to set any parameters like neural networks. We have used C4.5 and Decision Stump as base classifiers. The results show that, for identification, ensemble methods may result in higher accuracy and reduce the complexity with simpler decision trees.

The structure of this chapter is as follows:

In section 6.2 we will present definition of verification and identification in face recognition and then in sub-section 6.2.1 we will briefly explain Principal Component Analysis (PCA) and Linear Discriminant Analysis (LDA) as two methods of feature extraction. Finally, in section 6.4 we will present the results we have obtained with applying AdaBoost.OC to a face database called XM2VTS.

6.2 Face Verification and Identification

A typical face recognition system consists of three functional stages. In the first stage the image of a face has to be registered and normalised geometrically and photometrically. The second stage is feature extraction in which discriminant features need to be extracted from the face region. Finally, there is the matching stage in which a decision making scheme or classifier needs to be designed. In matching, a face recognition system may involve two problems: verification and identification. In verification, the system should confirm or reject a claimed identity and in identification, the system reports an identity from a database of known individuals. In these systems to match an input face image to a face in a database, two methods are used: geometric feature-based matching and template matching [17]. In the former, relative positions and other pa-

rameters of distinctive features such as eyes, mouth, nose, and chin are extracted. Also characteristic points such as the notch between the brow and the nose or the tip of the nose are used [92]. In the second method, instead of considering different parts of the face, the whole image of the face is considered. Principal Component Analysis (PCA) and Linear Discriminant Analysis (LDA) play a fundamental role in this method. The aim of using these two methods is to reduce the dimensionality. After projecting the original face image into a subspace, a classifier or a matching scheme is needed for face identification or verification[92] [60]. Matching schemes such as Euclidean distance, normalised correlation, Mahalanobis distance have been used for LDA or PCA based systems [60]. It is believed that LDA-based systems are superior to the systems based on PCA [5]. However, according to [63], PCA can outperform LDA when the training set is small. In [54], it has been reported that support vector machine (SVM) achieved better performance than Euclidean distance and in [52] Error correcting output code (ECOC) has been used to transform LDA subspace into another space defined by the outputs of binary classifiers. The binary classifiers are trained by relabelling the training set into two super-classes according to a code matrix (see section 4.2.3). The aim in this work was to provide a space in which patterns are more separable.

6.2.1 Feature Based Face Recognition

Performance of a face recognition system depends on the feature extraction methods and the matching scheme used. The features which are chosen should be the most effective and discriminating ones. The role of the matching scheme such as Euclidean distance measure, normalised correlation, and gradient direction, is crucial in making decisions[60]. These matching schemes are feature-based schemes. The matching used in our work is the same as in [52], i.e. first order Minkowski metric. For the i -th client, first order Minkowski metric is defined as:

$$d_i(\hat{y}) = \frac{1}{N} \sum_{l=1}^N \sum_{j=1}^T |y_j^l - y_j| \quad (6.1)$$

where N is the number of i -th client patterns used for training, y_j^l is the j -th classifier output for l -th member of client i and y_j is the j -th binary classifier output. T is the number of binary classifiers.

Since the grey-level matrix of an image has high dimensionality which is difficult to use directly in face recognition, one should use a low dimension feature representation for images. PCA, known as eigenface in the context of face recognition and proposed in [88], is used to find a subspace whose basis vectors correspond to the maximum-variance directions in the original space. This new subspace's dimensionality is less than the dimensionality of the original one and the new feature vectors are the eigenvectors of total scatter matrix. Linear transformation provided by PCA maximises the scatter of all patterns. This means not only it maximises between-class scatter, but also results in within-class scatter which is useless for face recognition.

LDA, known as Fisherfaces, provides a linear transformation to make patterns belonging to the same class closer together and patterns to different classes farther apart from each other. Given a set of N sample images $x_1, x_2, \dots, x_N$, each one belongs to one of k classes $C_1, C_2, \dots, C_k$, the between-class scatter matrix, S_B , and within-class scatter matrix, S_W are defined as follows:

$$S_B = \sum_{i=1}^k (\mu_i - \mu)(\mu_i - \mu)^T \quad (6.2)$$

$$S_W = \sum_{i=1}^k \sum_{x_j \in C_i} (x_j - \mu_i)(x_j - \mu_i)^T \quad (6.3)$$

where μ represents the mean of all classes and is defined as:

$$\mu = \frac{1}{N} \sum_{i=1}^N x_i$$

and μ_i is the mean of Class C_i . If M is considered as to be the number of sample patterns belonging to class C_i , μ_i can be defined as:

$$\mu_i = \frac{1}{M} \sum_{j=1}^M x_j$$

To maximise the between-class scatter while minimising the within-class scatter, we need to find the transformation matrix, W , which maximises the ratio $\frac{|W^T S_B W|}{|W^T S_W W|}$. According to [34], this ratio is maximised if S_w is a nonsingular matrix and column vectors of W are the eigenvectors of $S_W^{-1} S_B$. Since the dimension of the original problem is high and the number of training patterns is too small compared to the dimension of

the original space, S_W is almost always singular. if D is the dimension of the original space, to avoid S_W to be a singular matrix we need $D + k$ number of patterns which is almost impossible in real problems. One solution proposed to this problem is to use PCA to reduce the dimension to a lower-dimension space and then apply LDA to reduce the dimension to $(k - 1)$ [5][31].

6.3 AdaBoost.OC Algorithm

The main feature of Boosting algorithm for producing base classifiers is based on updating weights of training patterns in order to force the learning algorithm to concentrate on hard patterns and learn more from data. In AdaBoost.OC, this feature has been combined with the main feature of ECOC which is decomposition of the multi-class problem into several binary subproblems by perturbing the class labels (this is called colouring in the context of AdaBoost.OC). The colouring or relabelling is performed based on a random scheme. Relabelled patterns are used to train a classifier. The performance of the generated classifier is used to update the weights of the training patterns. Section 5.2 gives more details about AdaBoost.OC.

6.4 Face Identification and Verification Via Boosting

In this section we will explain the experiments in which AdaBoost.OC has been applied to a face database. The data used in the experiments was XM2VTS¹ face database which is a multi-modal database and contains 295 (200 as clients and 95 as impostors according to Lausanne evaluation protocol, the first configuration has been used) subjects and were recorded in four separate session over a period of 5 months.

To simulate real situation, the subjects were asked to read a predefined sentence in 30 seconds in a frontal view and rotate their heads until finally a head side profile is obtained. The database is constituted by eight shots. On each session, a speech shot and a rotation shot were recorded. The database has been divided into training,

¹this data can be found at:<http://www.ee.surrey.ac.uk/Research/VSSP/xm2vtsdb/>

Figure 6.1: Identification performance of AdaBoost.OC.

evaluation, and test set. In our work we have used the training set for building the classifiers and evaluation set to produce access scores of client and imposter and to find a threshold to accept or reject a claimed identity. The test set is used to find the performance of the designed face recognition system. For details of the database, see [66].

As base classifier or learning algorithm, we have used C4.5 [78] and Decision Stump[47] (see section 2.6) in AdaBoost.OC. C4.5, developed by Quinlan, is a multi-node decision tree while Decision Stump is a single node tree.

Data used in the experiments were projected to a lower dimension feature space by the techniques described in section 6.2.1. So each image is represented by a vector with 199 elements ($k-1 = 199$). To find the required threshold for verification, we have used two methods with first order Minkowski metric (see section 6.2.1). In the first method, starting from zero, the point where the difference between False Rejection (FA) and False Acceptance (FR) was minimum ($\min(|FA - FR|)$) is chosen as the threshold. In the second method the point where the sum of False Acceptance and False Rejection is minimum ($\min(|FA + FR|)$), is chosen as the threshold.

An input pattern is accepted as a client if the distance to the claimed identity is less than or equal to the threshold, otherwise it will be rejected. For identification, first the distances of the probe image to all clients in the training are found and then a label is assigned to the probe image which has minimum distance with the input pattern.

Figure 6.1 shows the results of using AdaBoost.OC to identify the evaluation data set and the test set. As can be seen in this figure, correct classification rate of AdaBoost.OC with Decision Stump when the number of classifiers is less than 200 increases faster and on the whole error rate is less than AdaBoost with C4.5. It means that in any application in which we need fewer classifiers, Decision Stump is the better option. In addition, this can be viewed as reduction of computational complexity. Furthermore, the correct classification of C4.5 and Decision Stump on training set have been shown in figure 6.2. According to this figure, both C4.5 and Decision Stump reach 100% accuracy when the number of classifiers is less than 40. However, C4.5 achieves 100% for 20 classifiers. Number of classifiers was increased to 1300 as in figure 6.1, however, there was no change in accuracy. From this figure, it can be said that C4.5 appears to be overtrained and this is why it gives worse result than Decision Stump. According to AdaBoost.OC algorithm, the only ensemble parameter we can change to prevent C4.5 from overtraining is the number of classifiers in the ensemble. As can be seen from figure 6.1, this will not work for this problem. It seems that we need the learning algorithm to have appropriate complexity for the problem.

For the verification problem, as can be seen in figures 6.3 and 6.4, on the whole, the error rates decrease as the number of classifiers are increased. However, AdaBoost.OC with C4.5 can provide a more separable space for clients and impostors. Another result is about the role of the method for finding the threshold. When we use $\min(|FA+FR|)$, False Acceptance reduces to about 2 % and in this case, the minimum FA is 1.625% which has been achieved with Decision Stump on evaluation data set (1.83% with C4.5). To achieve lower error rate one may choose either of these methods (depending on the application) and increase the number of classifiers to get the required performance.

To compare with feature-based methods such as Euclidean Distance metric and Normalised Correlation, we have shown the results of these methods in table 6.1. Our

Figure 6.2: Correct Classification of AdaBoost.OC on the training set of face database.

Table 6.1: Verification with Euclidean Distance metric and Normalised Correlation.

	Evaluation		Test	
	FA	FR	FA	FR
Euclidean Distance	11.34	11.33	13.40	9.00
Normalised Correlation	4.00	4.00	2.90	2.75

method outperforms Euclidean Distance, however, to achieve better performance, we need to increase the number of classifiers. Another reason for not obtaining better performance by AdaBoost is the code generation method used in AdaBoost.OC which prevents it from providing more separable space for clients and impostors. Since code generation method in AdaBoost.OC is based on a random scheme, it does not guarantee optimal diversity of base classifiers. Therefore, it is a good idea to consider applying different code generation methods explained in section 4.4 in future work.

Figure 6.3: Verification performance of AdaBoost.OC on Evaluation Data Set.

Figure 6.4: Verification performance of AdaBoost.OC on Test Data Set.

6.5 Summary

In this chapter we have presented the results of applying AdaBoost.OC to XM2VTS face database. In the approach used in this work, first features are extracted and then AdaBoost.OC has been applied to the data to build binary classifiers. The feature extraction methods have been explained in section 6.2. Then AdaBoost.OC was used to generate the base classifiers and finally a method based on distance measure was employed to combine the decisions made by base classifiers for identification and verification. In the identification problem, the label which has minimum distance is assigned to the new pattern, while in verification, to reject or accept a claim a threshold is used. For identification, AdaBoost.OC with a single decision tree (Decision Stump) outperforms AdaBoost.OC with C4.5 which is a more complex tree. In the verification case, the results show the reverse, AdaBoost.OC with C4.5 gives better results. The results show that the relabelling scheme used in AdaBoost.OC puts a limit in its ability to create a good separable space.

In summary, we were looking for ensemble of simplified classifiers while preserving the accuracy. Among different ensemble methods examined in our work, pruned and unpruned ensemble produced by AdaBoost.OC have similar performance. Therefore, choosing AdaBoost.OC, we came to our final object in this project, that of applying the selected method to a real problem (face recognition).

Chapter 7

Conclusion

In designing an ensemble, three factors need to be considered:

1. The method of constructing diverse base classifier (ensemble method)
2. The method of combining the base classifiers (combining method)
3. The learning algorithm used to produce the base classifier

For the first factor, we know that different ensemble methods such as Bagging, Boosting, Error-Correcting Output Code (ECOC) have different performance in different domains. The ability of the ensemble to produce diverse classifiers is one necessary condition that should be considered. So, one may need to select one of these ensemble methods for a particular dataset. With respect to the second factor in designing ensembles, obviously the method of combining decisions made by the generated base classifiers plays an important role in the performance of the ensemble. For example, Bagging and Boosting use voting schemes. Boosting uses weighted voting and Bagging employs a simple vote. On the other hand ECOC uses a distance measuring approach. The third factor is the main subject of this thesis. We have used decision tree learning algorithms (C4.5 and Decision Stump) as base classifiers in the ensembles. One of the parameters in decision tree algorithm such as C4.5 that needs to be set is Pruning. In fact, Pruning can be on or off or a different type of pruning can be used.

In this thesis, we started with Boosting and Bagging and examined five pruning methods (chapter 3). Then, we performed similar comparison with ECOC (chapter 4). Choosing the best pruning method which was Error-Based Pruning (EBP) according to results of Boosting, Bagging and ECOC, we applied EBP to AdaBoost.OC which is a combination of Boosting and ECOC. The result was that if one needs to choose whether to prune (with regard to performance not the complexity of base classifiers or the ensemble itself), ensembles with unpruned trees are the better choice. Likewise, it appears that ensembles of single nodes (such as Decision Stump) are superior on a number of datasets as we have shown in chapters 5 and 6.

7.1 Summary of Chapters

- A review of ensemble and combining methods was presented in the first part of chapter 2. The second part of this chapter consists of a review of decision tree learning algorithms and their simplification.
- In Chapter 3, we compared experimentally Bagging and Boosting by applying five pruning methods to them. The Mc Nemar test (with 5% confidence level) was used to find out whether their differences were significant or not. Both growing phase and pruning phase of a decision tree are data-dependent and this makes it difficult to match the level or type of pruning to an ensemble of tree classifiers. The results indicate that if a single pruning method needs to be selected then overall the popular EBP makes a good choice for Boosting and Bagging.
- Chapter 4 has addressed the complexity of base classifiers in ECOC. Like other ensemble methods the performance of ECOC depends on the performance of the base classifiers. Among five pruning methods used to reduce the complexity of decision trees, our results show that Error-Based Pruning outperforms the others on most datasets. On the other hand, if ECOC is used for building ensemble, it is better not to prune than to select a single pruning strategy for all datasets. However, there was some evidence that problem-dependent pruning might be beneficial.

- In chapter 5 we have the results of previous chapters and addressed the complexity of base classifiers and analysed the behaviour of AdaBoost.OC using the Margin concept. In the first part, EBP has been used to reduce the complexity of base classifiers generated in two versions of Boosting algorithm. In fact, in this chapter we compared two methods for solving multi-class problems and the effect of reducing complexity of decision trees. The results support the hypothesis that decomposition methods such as AdaBoost.OC are more efficient in solving multi-class problems, since pruned and unpruned ensemble made by AdaBoost.OC have similar performance. The complexity of generated base classifiers in AdaBoost.OC can be removed while preserving the performance. This is not true for AdaBoost.M2. On the other hand the results obtained with the ensemble of Decision Stumps show that a simple base classifier can be a good choice in reducing the size of ensemble. Also, the results show a relationship between the margins of the training patterns and the generalisation error and also the number of classifiers combined in the ensemble. That is, in general, with higher number of classifiers, the higher margin has resulted in improvement in accuracy.
- Comparison of the results of the ensemble methods discussed in previous chapters brings us to this conclusion that AdaBoost.OC is a good ensemble method for solving multi-class problems such as face recognition and it has been addressed in Chapter 6. In this chapter, we have presented the results of applying AdaBoost.OC to XM2VTS face database. In the approach used in this work, first features are extracted and then AdaBoost.OC has been applied to the data to build binary classifiers. A comparison of the ensemble of decision trees made by C4.5 and the ensemble made by Decision stumps shows that Decision Stump outperforms C4.5 in the Identification problem. However, in verification, the ensemble of decision trees made by C4.5 gives better results.

7.2 Contributions

In this thesis, we have contributed the following:

-
1. Applied five pruning methods to base classifiers generated by ensemble methods and compared them to each other in the context of ensembles made by Bagging, Boosting and Error-Correcting Output Code (chapters 3 and 4).
 2. In Critical Value Pruning (CVP) and Cost-complexity pruning (CCP), applied the whole training set to choose the best pruned tree rather than dividing into two sets for growing and selecting the best pruned tree (section 3.9.1).
 3. Compared the performance of unpruned and pruned ensembles to find whether differences are significant or not (chapters 3 and 4 and 5).
 4. Showed that in the context of ECOC, Error-Based Pruning works very well with datasets which have only continuous attributes (section 4.7).
 5. Characterised the effect of code length as well as training set size on the performance of pruning methods for ECOC (section 4.7). Code length can change the performance order of pruning methods. Increasing the size of the training set improves the performance of all pruning methods except Minimum Error Pruning (MEP) method.
 6. Analysed pruned and unpruned ensembles generated by AdaBoost.M1 using margin (section 3.9.2). However, there is not enough evidence to say that Margin can explain the differences between pruned and unpruned ensembles.
 7. Analysed the behaviour of AdaBoost.OC by using the margin concept (section 5.4.2). The results show a relationship between the margins of the training patterns and the generalisation performance.
 8. Compared two variants of Boosting algorithm for solving multi-class problems (chapter 5). This comparison gives good evidence that AdaBoost.OC as a decomposition method is insensitive to complexity of base classifiers, since it produces similar results for pruned and unpruned ensembles. In contrast, for AdaBoost.M2, unpruned outperforms pruned ensembles and increasing number of classifiers does not result in improvement.

-
9. Applied AdaBoost.OC to face identification and verification (chapter 6). AdaBoost.OC was used to produce ensembles of decision trees and a method based on distance measure was used to combine decisions made by base classifiers (see section 6.2.1, we did not use the combining method of Boosting algorithm which is a voting scheme).
 10. Showed that ensembles of Decision Stumps outperform ensembles of C4.5 for identification, but are inferior for the verification task.

7.3 Future Works

1. In this work we used the Margin concept to analyse the behaviour of AdaBoost.OC. As a recommended work, one may apply this concept to analyse ECOC.
2. In section 3.7 various definitions of bias and variance were explained. It was noted that Bayes classification is required to compute bias and variance. It would be interesting to investigate methods of estimating Bayes classification to determine if bias and variance can be used to determine when problem-dependent pruning is worthwhile.
3. In AdaBoost.OC, the code which is used to relabel patterns or decompose the problem is based on a random scheme. This limits the diversity of the base classifiers. For example in a three class problem, there are a few combinations for 0 and 1. Therefore, one possible way to improve the performance of AdaBoost.OC is to use another method for code generation.
4. For ECOC, we introduced the hypothesis that EBP gives better results with all-continuous attribute dataset. Verifying this hypothesis needs a study on large number of different datasets.
5. In chapter 5, the hypothesis was introduced that an ensemble of simple classifiers may reduce the space complexity. However, since we need more base classifiers to achieve the same accuracy, it may cause time complexity. Further work is needed to address tradeoff between time and space complexity.

-
6. This study on ensemble methods assumes that the decisions of the base classifiers are combined. As an alternative strategy, the trees themselves could be combined, but it is an open issue whether it would lead to improved performance.

Bibliography

- [1] D. Aha and R. Bankert. Cloud classification using error-correcting output codes. *Artificial Intelligence Applications: Natural Resources, Agriculture, and Environmental Science*, 11(1):13–28, 1997.
- [2] E.L. Allwein, R.E. Schapire, and Y. Singer. Reducing multi-class to binary: A unifying approach for margin classifiers. *Machine learning research*, 1:113–141, 2000.
- [3] H. Almulim and T. Dietterich. Learning with many irrelevant features. In *Proceeding of the ninth International Conference on Artificial Intelligence*, pages 547–552, 1991.
- [4] E. Bauer and R. Kohavi. An empirical comparison of voting classification algorithms: Bagging, boosting, and variants. *Maching Learning*, 36(1):105–142, 1999.
- [5] P. N. Belhumeur, Joao Hespanha, and David J. Kriegman. Eigenfaces vs. fisherfaces: Recognition using class specific linear projection. In *European Conference on Computer Vision ECCV (1)*, pages 45–58, 1996.
- [6] K. P. Bennett and E. Bredensteiner. Feature minimization within decision trees. *Computational Optimization & Applications*, 10(2):111–126, 1998.
- [7] A. Berger. Error-correcting output coding for text classification. In *IJCAI'99: Workshop on machine learning for information filtering*, 1999.
- [8] C. Bishop. *Neural Network for Pattern Recognition*. Oxford University Press, 1995.

-
- [9] C.L. Blake and C.J. Merz. UCI repository of machine learning databases, 1998.
<http://www.ics.uci.edu/~mlearn/MLRepository.html>.
 - [10] L. Breiman. Out-of-bag estimation. Breiman, L. (1996e), Out-of-bag Estimation, (<ftp.stat.berkeley.edu/users/pub/breiman/OOBestimation>).
 - [11] L. Breiman. Bias, variance, and arcing classifiers. Technical Report 460, Statistics Department, University of California, 1996.
 - [12] L. Breiman. Arcing the edge. Technical Report 486, Department of Statistics, University of California, Berkeley, CA., 1997.
 - [13] L. Breiman, J. H. Freidman, R. A. Olshen, and C.J. Stone. *Classification and regression Trees*. Wadsworth International Group, 1984.
 - [14] Leo Breiman. Bagging predictors. *Machine Learning*, 26(2):123–140, 1996.
 - [15] Leo Breiman. Arcing classifiers. *The Annals of Statistics*, 26(3):801–849, 1998.
 - [16] L. A. Breslow and D. W. Aha. Simplifying decision trees: A survey. *Knowledge Engineering Review*, pages 1–40, 1997.
 - [17] R. Brunelli and T. Poggio. Face recognition: Features versus templates. In *IEEE Transactions on Pattern Analysis and Machine Intelligence*, volume 15, pages 1042–1052, 1993.
 - [18] B. Cestnik and I. Bratko. On estimating probabilities in tree pruning. In Kordratoff Y., editor, *Machine Learning - EWSL-91. European Working Session on Learning*, pages 151–163. Springer-Verlag, 1991.
 - [19] T. Cover and J. Thomas. *Elements of Information Theory*. J. Wiley and Sons, Inc., 1991.
 - [20] Koby Crammer and Yoram Singer. On the learnability and design of output codes for multiclass problems. In *Computational Learning Theory*, pages 35–46, 2000.
 - [21] T. G. Dietterich D. Margineantu. Pruning adaptive boosting. In *International Conference on Machine Learning*, pages 211–218. Morgan Kaufmann, 1997.

-
- [22] Joao Manuel Portela da Gama. *Combining Classification Algorithms*. PhD thesis, University of Porto, Portugal, 1999.
 - [23] Thomas G. Dietterich. Approximate statistical tests for comparing supervised classification learning algorithms. *Neural Computation*, 10:1895–1923, 1998.
 - [24] T. Dietterich, M. Kearns, and Y. Mansour. Applying the weak learning framework to understand and improve c4.5. In *Proceedings of the Thirteen International conference on Machine Learning*, pages 96–104. Morgan Kaufmann, 1996.
 - [25] T. G. Dietterich. Ensemble methods in machine learning. In J. Kittler and F. Roli, editors, *First International Workshop on Multiple Classifier Systems*, pages 1–15, 2000.
 - [26] T. G. Dietterich and G. Bakiri. Solving multiclass learning problems via error-correcting output codes. *Journal of Artificial Intelligence*, 2:263–286, 1995.
 - [27] T. G. Dietterich and E. B. Kong. Machine learning bias, statistical bias, and statistical variance of decision tree algorithms. Technical report, Department of Computer Science, Oregon State University, 1995.
 - [28] T.G Dietterich and G. Bakiri. Error-correcting output codes: A general method for improving multiclass inductive learning programs. In *Proceedings of the Ninth National Conference on Artificial Intelligence (AAAI-91)*, pages 572–577. AAAI Press, 1991.
 - [29] P. Domingos. A unified bias-variance decomposition for zero-one and squared loss. In *the Seventeenth National Conference on Artificial Intelligence*, pages 564–569, 2000.
 - [30] H. Drucker. Effect of pruning and early stopping on performance of a boosting ensemble. *Computational Statistics & Data Analysis*, 38:393–406, 2002.
 - [31] Richard O. Duda, Peter E. Hart, and David G. Stork. *Pattern classification and scene analysis*. Wiley, 2nd edition, 2000.

-
- [32] R.P.W. Duin and D.M.J. Tax. Experiments with classifier combining rules. In J. Kittler and F. Roli, editors, *First International Workshop on Multiple Classifier Systems*, pages 1–15, 2000.
 - [33] F. Esposito, D. Malerba, and G. Semeraro. A comparative analysis of methods for pruning decision trees. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 19(5):476–491, May 1997.
 - [34] R.A. Fisher. The statistical utilization of multiple measurements. *Annals of Eugenics*, 8:376–386, 1938.
 - [35] Y. Freund. Boosting a weak learning algorithm by majority. *Information and Computation*, 121(2):256–285, 1995.
 - [36] Y. Freund and R. Schapire. Experiments with a new boosting algorithm. *Machine Learning: Proceedings of the Thirteenth International Conference*, pages 148–156, 1996.
 - [37] Yoav Freund and Robert E. Schapire. A decision-theoretic generalization of on-line learning and an application to boosting. In *Proceedings of the European Conference on Computational Learning Theory*, pages 23–37, 1995.
 - [38] Yoav Freund and Robert E. Schapire. Game theory, on-line prediction and boosting. In *Proceedings of the Ninth Annual Conference on Computational Learning Theory*, pages 325–332, 1996.
 - [39] Yoav Freund and Robert E. Schapire. A short introduction to boosting. *Journal of Japanese Society for Artificial Intelligence*, 14(5):771–780, 1999.
 - [40] Reza Ghaderi. *Arranging simple neural networks to solve complex classification problems*. PhD thesis, School of Electronics, Computing and Mathematics, University of Surrey, 2000.
 - [41] Rayid Ghani. Using error-correcting codes for text classification. In Pat Langley, editor, *Proceedings of ICML-00, 17th International Conference on Machine Learning*, pages 303–310. Morgan Kaufmann Publishers, San Francisco, US, 2000.

-
- [42] D. Grossman and T. Williams. Machine learning ensembles: An empirical study and novel approach, 1999. <http://citeseer.nj.nec.com/391913.html> or <http://www.cs.washington.edu/homes/grossman/projects/573projects/learning/>.
 - [43] Guo-Dong Guo and Hong-Jiang Zhang. Boosting for fast face recognition. In *IEEE ICCV Workshop on Recognition, Analysis, and Tracking of Faces and Gestures in Real-Time Systems*, pages 96–100, 2001.
 - [44] L. K. Hansen and P. Salamon. Neural network ensembles. *IEEE Trans. Pattern Analysis and Machine Intelligence*, 12(10):993–1001, 1990.
 - [45] S. Haykin. *Neural Networks, a Comprehensive Foundation*. Prentice Hall, 1999.
 - [46] T. K. Ho and J.J. Hull. Decision combination in multiple classier systems. *IEEE Transactions on pattern Analysis and Machine Intelligence*, 16(1), 1994.
 - [47] Wayne Iba and P. Langley. Induction of one-level decision trees. In *Proceedins of ninth international conference on machine learning*, pages 233–240, 1992.
 - [48] G. M. James and T. Hastie. The error coding method and PICT's. *Computational and Graphical Statistics*, 7:377–387, 1998.
 - [49] Gareth James. *Majority Vote Classifiers: Theory and Applications*. PhD thesis, Stanford University, 1998.
 - [50] G. John. Robust decision tree. In *Proceeding of the first International Conference on Knowledge Discovery and Data Mining*, pages 174–179, 1995.
 - [51] C. Kamath and E. Cantu-Paz. Creating ensembles of decision trees through sampling. In *Interface: Computer Science and Statistics*, volume 34, 2001.
 - [52] J. Kittler, R Ghaderi, T Windeatt, and J Matas. Face verification via ECOC. In *Proceedings of British Machine Vision Conference 2001*, pages 593–602, 2001.
 - [53] J. Kittler, M Hatef, R P W Duin, and J Matas. On combining classifiers. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 20:226–239, 1998.

-
- [54] J. Kittler and Y.P. Li. Support vector machines for face authentication. In *Brit. Machine Vision Conf*, pages 543–553, 1999.
- [55] Ron Kohavi and David H. Wolpert. Bias plus variance decomposition for zero-one loss functions. In Lorenza Saitta, editor, *Machine Learning: Proceedings of the Thirteenth International Conference*, pages 275–283. Morgan Kaufmann, 1996.
- [56] E. G. Kong and T. G. Dietterich. Probability estimation using error-correcting. In *IASTED International Conference: Artificial Intelligence and Soft Computing*, 1997.
- [57] E.B. Kong and T.G. Dietterich. Error-correcting output coding corrects bias and variance. In *Proceedings of the 12th International Conference on Machine Learning*, pages 313–321. Morgan Kaufmann, 1995.
- [58] Eun Bae Kong. *Understanding and Improving Error-Correcting Output Coding*. PhD thesis, Oregon State University, 1995.
- [59] L.I. Kuncheva, M. Skurichina, and R.P.W. Duin. An experimental study on diversity for bagging and boosting with linear classifiers. *Information Fusion*, 2002.
- [60] Y.P. Li, J. Kittler, and J. Matas. On matching scores of LDA-based face verification. In Tony Pridmore and Dave Elliman, editors, *Proc British Machine Vision Conference BMVC2000*. British Machine Vision Association, 2000.
- [61] R. Maclin and D. Opitz. An empirical evaluation of bagging and boosting. In *AAAI/IAAI*, pages 546–551, 1997.
- [62] F.J. Macwilliams and J.J.A Sloane. *The theory of Error-Correcting Codes*. North Holland Company, Amsterdam, 1977.
- [63] Aleix M. Martinez and Avinash C. Kak. PCA versus LDA. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 23(2):228–233, 2001.
- [64] F. Masulli and G. Valentini. Comparing decomposition methods for classification. In R.J. Howlett and L.C. Jain, editors, *Fourth International Conference on*

-
- Knowledge-Based Intelligent Engineering Systems and Allied Technologies*, pages 788–791, 2000.
- [65] M. Mehta, J. Rissanen, and R. Agrawal. MDL-based decision tree pruning. In *Proceeding of the 1st Int'l Conference on Knowledge Discovery in Databases and Data Mining*, 1995.
- [66] K Messer, J Matas, J Kittler, J Luetttin, and G Maitre. XM2VTSDB: The extended M2VTS database. In *Second International Conference on Audio and Video-based Biometric Person Authentication*, pages 72–77, March 1999.
- [67] J. Mingers. Expert systems-rule induction with statistical data. *Operational Research Society*, 38:39–47, 1987.
- [68] S. Murthy, S. Kasif, and S. Salzberg. A system for induction of oblique decision trees. *Journal of Artificial Intelligence Research*, 2:1–32, 1994.
- [69] T. Niblett and I. Bratko. Learning decision rules in noisy domains. In *Expert System 86, Cambridge*, pages 25–34. Cambridge University Press, 1986.
- [70] J. J. Oliver. Decision graphs-an extension of decision trees. In *the Fourth International Workshop on Artificial Intelligence and Statistics*, pages 343–350, 1993.
- [71] D. W. Opitz and J. W. Shavlik. Generating accurate and diverse members of a neural-network ensemble. In D. S. Touretzky, M. C. Mozer, and M. E. Hasselmo, editors, *Advances in Neural Information Processing Systems*, volume 8, pages 535–541. The MIT Press, 1996.
- [72] B. Paramanto, P. W. Munro, and H. R. Doyle. Improving committee diagnosis with resampling techniques. In D. S. Touretzky, M. C. Mozer, and M. Hesselmo, editors, *Advances in Neural Information Processing Systems*, volume 8, pages 882–888. MIT Press, 1996.
- [73] Andreas L. Prodromidis and Salvatore J. Stolfo. Cost complexity-based pruning of ensemble classifiers. *Knowledge and Information Systems*, 3(4):449–469, 2001.
- [74] J. R. Quinlan and R. L. Rivest. Inferring decision trees using the minimum description length principle. *Information and Computation*, pages 227–248, 1989.

-
- [75] J. Ross Quinlan. Personal communication from Quinlan.
 - [76] J. Ross Quinlan. Bagging, boosting, and C4.5. In *Fourteenth National Conference on Artificial Intelligence*, pages 725–730, 1996.
 - [77] R. Quinlan. Induction of decision tree. *Machine Learning*, 1:81–106, 1986.
 - [78] R. Quinlan. *C4.5: Programs for Machine Learning*. Morgan Kaufmann, San Mateo, California, 1993.
 - [79] R.J. Quinlan. Simplyfying decision trees. *International Journal of Man-Machine Studies*, 27:221–234, 1987.
 - [80] G. Rätsch, T. Onoda, and K.-R. Müller. Soft margins for AdaBoost. *Machine Learning*, 42(3):287–320, March 2001.
 - [81] R. E. Schapire. The strength of weak learning. *Machine Learning*, 5(2):197–227, 1990.
 - [82] R. E. Schapire, Y. Freund, and P. Bartlett. Boosting the margin: A new explanation for the effectiveness of voting methods. *The Annals of Statistics*, 26(5):1651–1686, 1998.
 - [83] Robert E. Schapire. Using output codes to boost multiclass learning problems. In *the Fourteenth International Conference of Machine Learning*, pages 313–321. Morgan Kaufman, 1997.
 - [84] M. Skurichina and R.P.W. Duin. Bagging, Boosting and the random subspace method for linear classifiers. *Pattern Analysis and Applications*, 5:121–135, 2002.
 - [85] <http://www.cse.unsw.edu.au/~quinlan/>.
 - [86] K. Tumer and J. Ghosh. Classifier combining: analytical results and implications. In *AAAI 96 - Workshop in Induction of Multiple Learning Models*, 1996.
 - [87] K. Tumer and N.C. Oza. Decimated input ensembles for improved generalization. In *International Joint Conference on Neural Networks, IJCNN '99*, volume 5, pages 3069 –3074, 1999.

-
- [88] M. Turk and A. Pentland. Eigenfaces for recognition. *Journal of Cognitive Neuroscience*, 3(1):71–86, 1991.
- [89] P. E. Utgoff and C. E. Brodley. Linear machine decision trees. Technical report, Department of Computer Science, University of Massachusetts, 1991.
- [90] G. Valentini. Upper bounds on the training error of ECOC-SVM ensembles. Technical report, Dipartimento di Informatica e Scienze dell' Informazione, Università di Genova, 2000. Report TR-00-17, DISI.
- [91] W. Wang, O. Jones, and D. Partridge. Diversity between neural networks and decision trees for building multiple classifier systems. In J. Kittler and F. Roli, editors, *First International Workshop on Multiple Classifier Systems*, pages 1–15. Springer-Verlag, Lecture Notes in Computer Science, 2000.
- [92] J. Weng and D. Swets. Face recognition. In A. Jain, R. Bolle, and S. Pankanti, editors, *in Biometrics: Personal Identification in Networked Society*, pages 67–86. MA: Kluwer Academic, 1999.
- [93] T. Windeatt. Classifier instability and partitioning. In J. Kittler and F. Roli, editors, *First International Workshop on Multiple Classifier Systems*, pages 260–269. Springer-Verlag, Lecture Notes in Computer Science, 2000.
- [94] T. Windeatt and G. Ardeshir. Boosting unpruned and pruned decision trees. In *Applied Informatics. Preceedings of the IASTED International Symposia*, pages 66–71, 2001.
- [95] T. Windeatt and G. Ardeshir. An empirical comprison of pruning methods for ensembles classifiers. In *Int. Conf Intelligent Data Analysis (IDA)*, pages 208–217. Springer-Verlag, Lecture Notes in Computer Science, 2001.
- [96] T. Windeatt and G. Ardeshir. Boosted tree ensembles for solving multiclass problems. In F. Roli and J. Kittler, editors, *3rd Int. Workshop Multiple Classifier Systems*, pages 42–51. Springer-Verlag, Lecture Notes in Computer Science, 2002.
- [97] T. Windeatt and G. Ardeshir. Decision tree simplification for classifier ensembles.

-
- IJPRAI: International Journal of Pattern Recognition and Artificial Intelligence*, 2002. submitted.
- [98] T. Windeatt and G. Ardeshir. Tree pruning for output coded ensembles. In *Int. Conf. Pattern Recognition, ICPR02, Quebec, Canada*, pages 92–95, 2002.
- [99] T. Windeatt and R. Ghaderi. Multi-class learning and error-correcting code sensitivity. *Electronics Letters*, 36(19):1630–1632, 2000.
- [100] T. Windeatt and R. Ghaderi. Binary labelling and decision level fusion. *Information Fusion*, 2(2):103–112, 2001.
- [101] T. Windeatt, R. Ghaderi, and G. Ardeshir. Error correcting output codes and multiple classifier systems. In *Int. Conf. on Optical Communications and Multimedia*, 2002. To appear.
- [102] D. H. Wolpert. Stacked generalization. *Neural Networks*, 5:241–259, 1992.
- [103] L. Xu, A. Krzyzak, and C.Y. Suen. Methods of combining multiple classifiers and their applications to handwriting recognition. *IEEE Transactions on Systems, Man, and Cybernetics*, 22(3):418–435, 1992.