Disinfection byproduct formation during drinking water treatment and distribution: A review of unintended effects of engineering agents and materials.

Shunke Ding ^{a, b, c}, Yang Deng ^d, Tom Bond ^e, Chao Fang ^{a, b, c}, Zhongqi Cao ^{a, b, c},
Wenhai Chu ^{a, b, c, *}

^a State Key Laboratory of Pollution Control and Resources Reuse, College of Environmental Science and Engineering, Tongji University, Shanghai, 200092, China

^b Key Laboratory of Yangtze River Water Environment, Ministry of Education, Tongji University, Shanghai, 200092, China

^c Shanghai Institute of Pollution Control and Ecological Security, Shanghai, 200092, China

^d Department of Earth and Environmental Studies, Montclair State University, Montclair, New Jersey, 07043, USA

^e Department of Civil and Environmental Engineering, University of Surrey, Guildford GU2 7XH, UK

*Corresponding author:

Tel.: +8618721871983; fax: +86 21 65986839

E-mail address: feedwater@126.com (W. Chu)

Address: Room 308, Mingjing Building, 1239 Siping Road, Shanghai, 200092, China

Abstract

Unintended effects of engineering agents and materials on the formation of undesirable disinfection byproducts (DBPs) during drinking water treatment and distribution were comprehensively reviewed. Specially, coagulants, biologically active filtration biofilms, activated carbons, nanomaterials, ion-exchange resins, membrane materials in drinking water treatment and piping materials, deposits and biofilms within drinking water distribution systems were discussed, which may serve as DBP precursors, transform DBPs into more toxic species, and/or catalyze the formation of DBPs. Speciation and quantity of DBPs generated rely heavily on the material characteristics, solution chemistry conditions, and operating factors. For example, quaternary ammonium polymer coagulants can increase concentrations of *N*-nitrosodimethylamine (NDMA) to above the California notification level (10 ng/L). Meanwhile, the application of strong base ion-exchange resins has been associated with the formation of *N*-nitrosamines and trichloronitromethane up to concentrations of 400 ng/L and 9.0 µg/L, respectively. Organic compounds leaching from membranes and plastic and rubber pipes can generate high NDMA (180–450 ng/L) and chloral hydrate (~12.4 µg/L) upon downstream disinfection. Activated carbon and membranes preferentially remove organic precursors over bromide, resulting in a higher proportion of brominated DBPs. Copper corrosion products (CCPs) accelerate the decay of disinfectants and increase the formation of halogenated DBPs. Chlorination of high bromide waters containing CCPs can form bromate at concentrations exceeding regulatory limits. Owing to the aforementioned concern for the drinking water quality, the application of these materials and reagents during drinking water treatment and distribution should be based on the removal of pollutants with consideration for balancing DBP formation during disinfection scenarios. Overall, this review highlights situations in which the use of engineering agents and materials in drinking water treatment and distribution needs balance against deleterious impacts on DBP formation.

Keywords

Disinfection byproducts; drinking water treatment; drinking water distribution; agents and materials; unintended effect.

49 **Abbreviations of DBPs:**

50 Chloroform, CF; Bromodichloromethane, BDCM; Dibromochloromethane, DBCAM; Bromoform,
51 BF; Dichloriodomethane, DCIM; Bromochloriodomethane, BCIM; Dibromiodomethane,
52 DBIM; Chlorodiiodomethane, CDIM; Bromodiiodomethane, BDIM; Iodoform, IF;
53 Monochloroacetic acid, MCAA; Monobromoacetic acid, MBAA; Dichloroacetic acid, DCAA;
54 Bromochloroacetic acid, BCAA; Dibromoacetic acid, DBAA; Trichloroacetic acid, TCAA;
55 Bromodichloroacetic acid BDCAA; Dibromochloroacetic acid DBCAA; Tribromoacetic acid,
56 TBAA; Chloral hydrate, CH; 1,1,1-trichloropropanone, 1,1,1-TCP; 1,1-dichloropropanone, 1,1,1-
57 DCP; Monochloronitromethane, MCNM; Dichloronitromethane, DCNM; Dichloroacetonitrile,
58 DCAN; Trichloroacetonitrile, TCAN; Chloroacetamide, MCAM; Dichloroacetamide, DCAM;
59 Trichloroacetamide, TCAM; Bromodichloroacetamide, BDCAM; Dibromochloroacetamide,
60 DBCAM; Tribromoacetamide, TBAM; Diiodoacetamide, DIAM; N-nitrosodimethylamine, NDMA;
61 N-nitrosodipropylamine, NDPA.

1. Introduction

Reliable access to safe and affordable water, as one of the most essential humanitarian goals, has remained a global challenge in the 21st century. As a consequence of unavailability of clean water, at a minimum, 1.8 million people, of whom 90% are under the age of 5, die due to water-related or waterborne diseases (e.g. diarrhea) every year (WHO, 2004). In order to combat pathogens in drinking water, efforts need to be made in two aspects. Firstly, effective disinfection is required for inactivation of pathogenic microorganisms during water treatment. Presently, chlorination is the most common disinfection option. Secondly, a sufficient disinfectant (e.g. chlorine) residual needs to be maintained within a water distribution system for prevention of the regrowth of unwanted microbes in finished water (Richardson et al., 2007; Richardson and Postigo, 2012; Sharma et al., 2017). However, many disinfectants, such as free chlorine, ozone, chlorine dioxide and chloramines, can potentially react with different water matrix constituents (e.g. natural organic matter (NOM), anthropogenic contaminants, bromide (Br^-), and iodide (I^-)) to generate undesirable disinfection byproducts (DBPs), which are cytotoxic, genotoxic and/or carcinogenic (Krasner et al., 2006; Richardson et al., 2007; Plewa et al., 2008; Richardson et al., 2008; Yang and Zhang, 2014; Chu et al., 2016b; Ding et al., 2018c).

Since trihalomethanes (THMs) were first identified during chlorination of drinking water in 1974, significant efforts have been made to investigate occurrence, toxicity, formation mechanisms and mitigation technologies of various DBPs in water (Rook, 1974; Deborde and von Gunten, 2008; Bond et al., 2011; Shah and Mitch, 2012; Krasner et al., 2013). THMs, haloacetic acids (HAAs), and haloacetaldehydes (HALs) are three principal DBP classes typically ranging from several to a few hundreds of $\mu\text{g/L}$ in finished water. In contrast, other DBPs such as haloacetonitriles (HANs), haloacetamides (HAMs) and halonitromethanes (HNMs) are formed at a much lower range from several ng/L to a few $\mu\text{g/L}$ (Richardson et al., 2007; Bond et al., 2011; Wang et al., 2015). Besides the aforementioned halogenated DBPs, *N*-nitrosamines (NAs) represent a type of non-halogenated DBPs. The most well-known NA is *N*-nitrosodimethylamine (NDMA) with a typical concentration within several to a few tens of ng/L in finished water (Krasner et al., 2013; Bei et al., 2016). The US Environmental Protection Agency (USEPA) Integrated Risk Information System database indicates that the occurrence of 6 NAs in drinking water at several ng/L is associated with a 10^{-6}

lifetime excess cancer risk. The notification level, which was set by California's Department of Public Health, for NDMA is 10 ng/L, several order lower than the regulated levels for THMs (80 µg/L) and HAAs (60 µg/L) (USEPA, 2006; CDPH, 2009). In general, the concentration levels of carbonaceous DBPs (C-DBPs), are higher than that of nitrogenous DBPs (N-DBPs). However, systematic quantitative toxicological analyses of ~ 80 DBPs by Plewa and colleagues indicated that the N-DBPs are more toxic than C-DBPs (Muellner et al., 2007; Jeong et al., 2015). Moreover, some halogenated aromatic DBPs with higher toxicity than halogenated haloaliphatic DBPs were identified and quantified in various drinking water samples, ranged from several ng/L to a few µg/L (Pan and Zhang, 2013; Pan et al., 2014; Wang et al., 2018). Therefore, the toxic effect of N-DBPs and halogenated aromatic DBPs cannot be ignored because toxicity relies upon their concentration and toxic potency. Furthermore, the cytotoxicity and genotoxicity of DBPs are also highly influenced by the species of halogen substituted in the DBP compounds with the following order : iodo- > bromo- >> chloro- (Plewa et al., 2008).

Previous studies on the precursors of DBPs in drinking water treatment have primarily focused on NOM and anthropogenic contaminants originally present in raw water (Korshin et al., 2007; Deborde and von Gunten, 2008; Bond et al., 2012; Shah and Mitch, 2012). Among these precursors, phenolic structures identified in humic acids (HAs) and fulvic acids have been recognized as the principal precursors of THMs and HAAs, while amino acids, oligopeptides, and nitrogen-containing contaminants serve as the major N-DBP precursors (Gallard and von Gunten, 2002; Lee and Westerhoff, 2006; Chu et al., 2010; Yang et al., 2010; Bond et al., 2012; Chu et al., 2015b; Ding et al., 2018b). However, in many cases, concentrations of the known precursors in raw water cannot be sufficiently transformed to experimentally measured DBPs in finished waters (Bond et al., 2012). Therefore, the recent interest has been directed to other DBP precursors. These alternative chemical constituents in water may be those originally existing in raw water or may be treatment agents externally added and chemicals released from treatment and piping materials (Bolto and Gregory, 2007; Krasner et al., 2013; Sharma et al., 2017). Recent studies have highlighted the role of different chemical agents and treatment/piping materials on the DBP formation (Mitch and Sedlak, 2004; Padhye et al., 2011; Verdugo et al., 2014; Du et al., 2016). Besides the additional DBP precursors, another emerging concern is that certain treatment steps have the potential to transform existing

DBPs into more toxic compounds. For example, activated carbon (AC), ion-exchange resins or membrane treatments can increase the ratios of brominated DBPs (Br-DBPs) to chlorinated DBPs (Cl-DBPs), resulting in greater mammalian cell cytotoxicity and genotoxicity, although the overall DBP concentrations decrease (Chellam and Krasner, 2001; Kemper et al., 2009; Krasner et al., 2016b; Zhang et al., 2017).

This article provides a critical review on the unintended effects of drinking water treatment reagents and treatment/piping materials on the DBP formations. The unwanted effects include: 1) alternative DBP precursors of DBPs; 2) transformation of DBPs into more toxic species; and 3) catalysis of DBP formation.

2. Unintended effects of engineering agents and materials in drinking water treatment on DBP formation

2.1. Coagulants

Coagulation is a process where the addition of an inorganic or organic coagulant for destabilizing particular matter, for promoting their aggregation or for forming precipitates that can sweep particulates in water (Matilainen et al., 2010). Organic polyelectrolytes (Fig. 1) have been widely applied as coagulants or coagulant aids for promoting the coagulation performance in water treatment, such as polyacrylamide (PAM), anion PAM (APAM), cation PAM (CPAM), poly(diallyldimethylammonium chloride) (PDADMAC), and epichlorohydrin/dimethylamine (ECH/DMA) (Bolto and Gregory, 2007). Benefits of these organic treatment agents include an excellent coagulation efficiency achieved at a low coagulant dose, the production of less sludge, no reduction in alkalinity, and a low cost (ca. 70-75% of the costs associated with inorganic coagulants) (Bolto and Gregory, 2007). However, the amide, quaternary amine and primary amine groups on these compounds and their monomers can react with several disinfectants to produce toxic N-DBPs (Bolto and Gregory, 2007; Krasner et al., 2013).

【Figure 1】

148 **【 Table 1 】**

149
150 2.1.1. PAM

151 Formation of THMs from the reactions of chlorine with PAM, APAM, CPAM or their monomers,
152 e.g. acrylamide (AM), has been reviewed (Bolto, 2005). These reactions can produce THMs at
153 several µg/mg in ultrapure water (**Table 1**) (Klaus and Lawrence, 1977; Feige et al., 1980;
154 Soponkanaporn and Gehr, 1988). The presence of AM, as an impurity of PAM, can greatly enhance
155 the formation of THMs, because 1 mg/L of AM can produce 800 µg/L CF in ultrapure water
156 (Mallevialle et al., 1984). Thus, it is of importance to increase the purity of PAM products during
157 manufacture or adopt high-purity PAM coagulants for water treatment. Under the treatment
158 conditions related to water treatment, the dose of AM based coagulant is typically less than 1 mg/L
159 and the residual polymer coagulant after filtration is quite low (Bolto and Gregory, 2007).
160 Consequently, the formation of THM due to the presence of residual PAM compounds is minor.
161 Therefore, the use of AM based coagulant does not greatly contribute to the production of THMs in
162 comparison with NOM in water during chlor(am)ination (Richardson et al., 2007; Ding et al.,
163 2018a).

164 Recent studies validate that PAM and AM can also serve as the precursors of N-DBPs which
165 are much more toxic than THMs (Plewa et al., 2008). Li et al. (2017) compared the formation of
166 NAs during coagulation with different coagulants, including $Al_2(SO_4)_3$ alone and in combination of
167 $Al_2(SO_4)_3$ and PAM, followed by chloramination. Results showed that the addition of 2 mg/L PAM
168 as the coagulant aid only increased the formation of total NAs (TONO) from 75 ng/L to 80 ng/L and
169 NDMA from 26 ng/L to 29 ng/L, separately. The subsequent DBP formation potential (FP)
170 experiments revealed that 1mg/L of PAM could produce 8 ng/L NDMA and 20 ng/L TONO. The
171 enhanced removal of NA precursors and the sedimentation of partial PAM inhibits the rate of TONO
172 and NDMA increase. Because the typical AM dose and residual AM concentration are typically low
173 in realistic water coagulation, PAM cannot significantly increase the formation of TONO and
174 NDMA in practice. Moreover, PAM and APAM exhibit much less FP of NDMA than that of
175 PDADMAC due to less abundant dimethylamine (DMA) groups (Krasner et al., 2013). However,
176 the NDMA yield of DMA-based CPAM is approximately greater than that of DMA by two orders

of magnitude after 4 h chloramination (12.1 ± 4.3 $\mu\text{g NDMA/mg DMA based CPAM}$), indicating a high potential of the DMA-based CPAM in the enhanced formation of NDMA (Mitch and Sedlak, 2004). Therefore, the application of DMA based CPAM in drinking water treatment should be carefully evaluated before adoption.

Contribution of PAM to the formation of HAMs, HANs, and THMs was recently investigated (Ding et al., 2018a). Coagulation with PAM did not greatly promote the formation of THMs and HANs in the downstream post-chlorination, suggesting that the role of PAM residuals for the overall THM and HAN formation is insignificant. However, coagulation with combined $\text{Al}_2(\text{SO}_4)_3$ (10 mg/L as alum) and PAM (2 mg/L) increased total HAM concentrations by 40 ~ 96%, corresponding to 4.9-7.7 $\mu\text{g/L HAMs}$, in comparison with those produced from coagulation with alum alone (2.5-5.5 $\mu\text{g/L HAMs}$). Moreover, the DBP FP experiments revealed that chlorination following coagulation with 1 mg/L PAM produced 5.2 $\mu\text{g/L DCAM}$. Therefore, the potential of the PAM residual in the formation of HAMs is close to that of NOM. It should be noted that the DBP associated toxicity in water is a function of both its concentration and its toxic potency. Even though the concentration of HAMs is less than that of THMs nearly by one order of magnitude, the CHO cell cytotoxicity of HAMs is greater than that of THMs by several orders of magnitude (Wagner and Plewa, 2017). After considering the two factors, it is concluded that the health risk associated with HAMs formed from residual PAM is close to or even greater than that of THMs transformed from NOM in water.

2.1.2. PDADMAC and ECH/DMA

A review on the formation of THMs from the chlorination of PDADMAC and ECH/DMA indicates that the THM yield of PDADMAC or ECH/DMA is substantially lower than that of CPAM under identical water treatment conditions ([Table 1](#)) (Bolto, 2005). However, a concern has been raised since NDMA was identified in the water treated with PDADMAC and chlorine (Child et al., 1996; Kohut and Andrews, 2003; Bolto, 2005; Park et al., 2009; Krasner et al., 2013). As shown in [Table 1](#), the NDMA yields from chlorination of PDADMAC range from 0.2 to 1.2 ng NDMA/mg polymer (Child et al., 1996). Later, studies showed that the NDMA yields from reactions of PDADMAC or ECH/DMA with chlorine or ozone were substantially below those produced from chloramines

(Najm and Trussell, 2001; Wilczak et al., 2003). NDMA after chloramination of PDADMAC or ECH/DMA was reported to reach several μg NDMA/mg coagulant (Table 1). Hanigan et al. (2015) reported that coagulation with 1.5 mg/L PDADMAC in 7 water samples across the U.S. led to the formation of 47 ± 3 ng NDMA/mg active polymer during the downstream chloramination. Although the NDMA yields were approximately one-third of the NDMA FP (129 ng NDMA/mg PDADMAC) measured in ultrapure water (Hanigan et al., 2015), the NDMA concentrations far exceeded the California notification Level (10 ng/L) (CDPH, 2009). The US Environmental Protection Agency (USEPA) Integrated Risk Information System database indicates that the occurrence of 6 NAs in drinking water at several ng/L is associated with a 10^{-6} lifetime excess cancer risk. Moreover, application of PDADMAC during coagulation frequently increased the NDMA FP during ensuing chloramination water, regardless of the disinfectant dose, suggesting that an optimal coagulant dose should be selected based on the trade-off between turbidity removal and NDMA formation (Hanigan et al., 2015). Furthermore, NDMA concentrations formed from the chloramination of coagulated waters with PDADMAC or ECH/DMA can be similar to those formed from the chloramination of wastewater effluent or reclaimed water, which are known to be important sources of NDMA precursors (Le Roux et al., 2011; Parker et al., 2014; Sgroi et al., 2015; Chuang and Mitch, 2017; Chuang et al., 2019).

Park et al. (2009) reported that ECH/DMA had a greater NDMA yield than PDADMAC and the formation of NDMA from the both polymers was strongly correlated to the polymer degradation and DMA release during chloramination. Two chloramine dosing modes, i.e. direct addition of preformed chloramines and simultaneous addition of chlorine and ammonia, favor the formation of NDMA, compared with addition of free chlorine before ammonia. And the concentration of NDMA decreases with the increase of pre-chlorination time (Wilczak et al., 2003). Therefore, pre-chlorination appears to be effective for the reduction of NDMA FP of PDADMAC or ECH/DMA. During *in situ* chloramination, dichloramine (NHCl_2) formation plays a critical role in the formation of NDMA from the aforementioned polymers (Park et al., 2015). Moreover, pre-oxidation with ClO_2 also reduces the formation of NDMA from PDADMAC and ECH/DMA, whereas pre-ozonation favors its production (Selbes et al., 2014; Park et al., 2015). The different findings are due to the fact that hydroxyl radicals ($\bullet\text{OH}$) generated from ozonation can break down the quaternary

ammonium ring on PDADMAC following by the release of DMA, which can later form NDMA during downstream chloramination (Padhye et al., 2011). Furthermore, the reaction of hydroxylamine, another ozonation product of DMA, with DMA can also directly generate NDMA during ozonation (Padhye et al., 2011). Therefore, the application of PDADMAC before disinfection with ozone and NHCl_2 should be avoided for the minimization of the NDMA formation. Additionally, the stock age of coagulants is a factor likely affecting the DBP formation in subsequent disinfection. Kohut and Andrews (2003) found that the stock age of PDADMAC did not significantly alter the NDMA production, whereas the NDMA concentration was appreciably increased when the stock age of ECH/DMA increased from 0 to 5 h.

In order to inhibit the formation of NAs, Zeng et al. (2016) attempted to modify PDADMAC and ECH/DMA. In the first modification pathway, methyl iodide (MeI) was used to convert polymer-bound tertiary amine groups to less chloramine-reactive quaternary ammonium groups on the polymer. The modification could reduce the NDMA formation approximately by 75%. In the other modification method, the chloramine-reactive DMA group was converted to longer alkyl substituents (i.e. dipropylamine (DPA) substituents), completely eliminating the NDMA formation in the following disinfection. The yields of *N*-nitrosodipropylamine (NDPA) from DPA based polymers were 5% of the NDMA yields from DMA based polymers. Zeng et al. (2016) reported that chloramination of water coagulated with the combination of untreated PDADMAC or ECH/DMA (2.0 mg/L) with alum or ferric salts increased the yields of NDMA by 6 ~ 17 times (38-101 ng/L) and TONO by 2 ~ 3 times (76-135 ng/L) in comparison with their respective yields when chloramination of water coagulated with alum or ferric salt alone. NDMA was the dominant NA species produced from these polymers. Coagulation with DPA-based analogues of PDADMAC or ECH/DMA produced less NDMA and TONO than coagulation with MeI-treated polymers. However, coagulation with the aforementioned modified polymers also produced more NDMA and TONO. Zeng et al. (2014) synthesized a novel quaternary phosphonium cationic polymer, i.e. poly (diallyldiethylphosphonium chloride) (PDADEPC), which could achieve comparable turbidity and NOM removals with commercial PDADMAC. Moreover, chloramination of PDADEPC primarily produced oxygenated products rather than nitrosated products even under strong nitrosation conditions. This could be achieved by converting the chloramine-reactive DMA group to longer

alkyl substituents (i.e. DEP) substituents. One study found that powdered and granular activated carbon (PAC and GAC) could effectively remove ECH/DMA (up to 75%) compared to PDADMAC (Hanigan et al., 2015). Therefore, AC adsorption, when ECH/DMA is applied before polymer addition and/or after sedimentation, is a potential method to inhibit the NDMA formation.

In summary, the NDMA FP or HAM FP of the waters coagulated with the quaternary ammonium polymer coagulants or AM based coagulants is potentially high. Therefore, adoption of these coagulants has a risk to produce NAs and HAMs at undesirable levels.

2.2. Biological filtration

Biological active filtration (BAF) is designed to remove not only particles but also dissolved organic matters by microbial, growing in the form of biofilm attached to a support media (Bablon et al., 1988; Hu et al., 2018). Recently, Liu et al. (2017) reviewed the impact of BAF on the control of DBP precursors and DBPs and demonstrated that biofiltration generally can enhance the removal of the precursors of DBPs. However, some studies also indicated that BAF process can also increase the formation of NAs and halogenated N-DBPs under certain conditions (Chu et al., 2011; Chu et al., 2015a). Chu et al. (2011) reported that, compared to conventional drinking water treatment, BAF pretreatment resulted in the increases of DCAN, DCAM and TCNM by 43.3%, 115.4% and 33.3% to 8.6 µg/L, 5.6 µg/L and 1.6 µg/L, respectively. Chu et al. (2015a) investigated the impact of pre-ozonation on the ability of the coupling pre-ozonation with biological activated carbon (O₃-BAC) to remove the N-DBP precursors. Results showed that, when the pre-ozonation was terminated after the first backwash cycle, DCAN, TCAN, DCAM and TCAM concentrations were 21.3%, 19.6%, 33.5% and 53.7% higher than that in the chlorinated effluent of the O₃-BAC. Moreover, other studies also observed an increase of NA precursors after biofiltration. Krasner and colleagues found that the removal of NDMA precursors by biofiltration ranged from -344% to 50% of 37 full-scale water treatment BAF effluents compared to BAF influents (Krasner et al., 2015; Krasner et al., 2016a). The negative removal of NDMA precursors were observed in 22 samples, indicating the increase in NDMA FP after BAF treatment. The increases of N-DBPs may be ascribed to the biomass sloughing off from the biofilter and/or the release of soluble microbial products (Chu et al., 2011; Chu et al., 2015a; Liu et al., 2017). On the one hand, bacterial cells in the BAF biofilms, bacterial extracellular

polymeric substances, intracellular organic matter in cyanobacteria, and soluble microbial products can all provide reactive DBP precursors (Chu et al., 2011; Chu et al., 2015a; Liu et al., 2017). In addition to generating organic nitrogen compounds, microbial mediated processes (nitrification) can also enhance the formation of NDMA in the presence of inorganic nitrogen species (Zeng and Mitch, 2016). Moreover, the desorption of cationic polymers and other positively-charged amine based precursors from BAF can release existing DBP precursors and in this way also contribute to DBP FP (Liao et al., 2015). Overall, during biological filtration, there are a number of processes which it may enhance DBP formation. However, the increase of N-DBP precursors after biofiltration appeared to be site-specific and need to be comprehensively investigated in future studies. It is necessary to investigate the dominant factors which determine increases or decreases in N-DBP precursors, in future research.

2.3. AC

Adsorption in drinking water treatment is a surface process in which atoms, ions, or molecules (i.e. adsorbates) are accumulated on the surface of a solid (i.e. adsorbent). AC is the most popular adsorbent applied for environmental purification purposes, particularly capturing traceable micro-pollutants in drinking water treatment. The AC serving as adsorbent can be categorized into cylindrical AC, granular AC (GAC), powder AC (PAC) and AC fiber in terms of their shape and appearance (Padhye et al., 2010; Bond et al., 2012; Krasner et al., 2016b). The excellent adsorption ability of AC is ascribed to its large specific surface area, well-developed pore structures, and abundant surface functional groups (Li, 2012).

AC adsorption has served as an effective barrier for the abatement of DBP precursors such as NOM. Chiu et al. (2012) reported the simultaneous and effective removals of dissolved organic carbon (DOC), ultraviolet absorbance at 254 nm (UV_{254}), total dissolved nitrogen (TDN), dissolved inorganic nitrogen (DIN), dissolved organic nitrogen (DON), and Br^- using rapid small-scale column tests (RSSCTs) loaded with GAC for water treatment. As shown in [Fig. 2](#), the capability of GAC in the alleviation of different water quality indicators follows the order: UV_{254} absorbance > DOC > DON > TDN > Br^- . The better removal efficiency of UV_{254} absorbance than the removal of DOC suggests that GAC preferentially captures aromatic NOM molecules with typically higher

UV₂₅₄ absorbance. A primary approach for controlling for formation of regulated DBPs, i.e. THMs and HAAs, is effective removal of NOM before disinfection, because aromatic fractions in NOM serve as the major precursors of THMs and HAAs (Gallard and von Gunten, 2002). However, AC moderately and even poorly removes DON and TDN in water, thereby leading to a high ratio of DON to DOC in the AC-treated water (Chiu et al., 2012), which may increase the ratios of N-DBPs to C-DBPs during the subsequent chlorination and chloramination (Chiu et al., 2012).

【Figure 2】

Br⁻ is an almost inert constituent during AC adsorption. Consequently, the ratios of Br⁻ to DOC (Br⁻/DOC) and Br⁻ to DON (Br⁻/DON) in the GAC effluent significantly increase (Summers et al., 1993; Chiu et al., 2012). Moreover, the AC-treated water has a lower chlorine demand than the water without AC adsorption, thereby decreasing the ratio of free available chlorine (FAC) to Br⁻ (FAC/Br⁻) after AC adsorption (Summers et al., 1993; Symons et al., 1993). Consequently, the increased Br⁻/DOC and decreased FAC/Br⁻ favor the bromine incorporation into DBPs, increasing the ratio of Br-DBPs to Cl-DBPs (Symons et al., 1993; Krasner et al., 2016b; Zhang et al., 2017). To our knowledge, there are no relevant reference reported the ratio of bromine in Br-DBPs to TOX until now. This is a research gap and warrants to be investigated in future study. Krasner et al. (2016b) reported that GAC treatment resulted in the greater genotoxicity in the presence of Br⁻ than an expected level, due to the formation of more Br-DBPs with stronger geno- and cytotoxicity. Therefore, though AC adsorption is an effective treatment option for controlling the formation of regulated C-DBPs through the abatement of NOM, it poorly prevents the formation of N-DBPs and Br-DBPs. Since N-DBPs are generally more cyto- and genotoxic than the regulated C-DBPs and Br-DBPs are generally more cyto- and genotoxic than their chlorinated analogs, additional treatments for the enhanced removal of Br⁻ and DON are needed before GAC treatment of influents with appreciable levels of Br⁻ (> ~ 50 µg/L) and DON (> ~ 0.3 mg-N/L) (Plewa et al., 2008; Plewa and Wagner, 2015). It should also be remembered that DBP FP is not equivalent to authentic DBP concentrations and increases in the relative proportions of particular groups of DBPs may still be accompanied by overall decreases in DBP concentrations.

When chlorine, chloramines or chlorine dioxide is used for pre-oxidation, their reactions with AC and adsorbed compounds onto AC inevitably occur (Table 2). The pre-treatment has been demonstrated to produce toxic by-products and/or increase total organic halogen (TOX) concentrations, as shown in Table 2 (McCreary and Snoeyink, 1981; Chen et al., 1982; Voudrias et al., 1985b; Stüber et al., 2005). Several chlorinated organic compounds and chlorate were found to be generated from the reactions of chlorine-containing disinfectant (i.e. free chlorine, monochloramine and chlorine dioxide) and AC (Snoeyink et al., 1981; Chen et al., 1982). However, it should be noted that the disinfectant doses used in the previous studies were much greater than those during realistic drinking water treatment. Recently, Zhang and colleagues also found similar phenomenon (Jiang et al., 2017; Jiang et al., 2018). Therefore, the formation of sufficient undesirable DBPs from the reactions between these chlorine-containing disinfectants and AC in a treatment train is an unlikely concern (Snoeyink et al., 1981; Chen et al., 1982).

【Table 2】

Previous efforts were made to explore the differences of final products between the reactions of disinfectants with NOM and with organic compound absorbed onto AC, as shown in Table 2 (McCreary and Snoeyink, 1981; Chen et al., 1982; McCreary et al., 1982; Chen et al., 1984; Voudrias et al., 1985b; a; Jackson et al., 1987; Hwang et al., 1990; Gonce and Voudrias, 1994; Vel Leitner et al., 1994). Many unwanted oxidation products are identified from the latter reaction pathway, including hydroxylation products, quinones, chlorine substitution products, carboxylation and oxidative coupling products (Chen et al., 1984). Of note, these compounds are typically more toxic than regulated DBPs (Du et al., 2013; Yang and Zhang, 2013; Liu and Zhang, 2014). However, the typical doses of chlorine-containing pre-oxidants (e.g. chlorine, chloramines or chlorine dioxide) applied during realistic disinfection are lower than 1 mg/L, much less than the oxidant doses selected in the laboratory studies (up to a few g/L). Moreover, because part of the oxidants has been scavenged by NOM in raw water during pre-oxidation, the real concentration of the oxidant can be further reduced before AC adsorption. Therefore, the reactions of residual chlorine-containing pre-oxidants with NOM absorbed onto AC cannot pose a serious threat in terms of the DBP formation.

2.4. Nanomaterials

Applications of various nanomaterials such as adsorbents, filter media, disinfectants, and reactive agents, have a potential to revolutionize the traditional treatment processes for the water treatment industry. For example, fullerene (C_{60}) has potential uses as an adsorbent in drinking water treatment and C_{60} is likely to be oxidized during chemical disinfection (Alpatova et al., 2013). A series of studies demonstrated that functionalized carbon nanotubes (CNTs) can be used as sorbents for organic pollutants, complexation agents for metals, and sensitizers for hydroxyl radical formation (Pan and Xing, 2008; Chen and Jafvert, 2010). However, the most studies on nanomaterial-based water treatment were carried out at a laboratory or pilot scale (Li et al., 2008; Tofighy and Mohammadi, 2011; Adeleye et al., 2016). Concerns about adoption of nanomaterials at full-scale water treatment facilities have been raised, including the regulatory challenges, technical hurdles, public perception, and uncertainties about fate of nanomaterials in the environment (Adeleye et al., 2016).

C_{60} can undergo surface reactions with ozone and chlorine in water and then be transformed into C_{60} derivatives containing hydroxyl, hemiketal and epoxy functional groups (Fortner et al., 2007; Wang et al., 2012). The transformation rate of C_{60} by photochlorination under the fluorescent light was much faster than that in the dark. Moreover, the presence of Cl atoms covalently bonded to C atoms has been confirmed by X-ray photoelectron spectroscopy peaks corresponding to a binding energy of 200.1-202.4 eV, indicating that C_{60} may be a precursor of DBPs (Wang et al., 2012; Alpatova et al., 2013). The specific DBP yields from C_{60} deserves a further investigation.

CNTs were reported to serve as the precursor of NAs and halogenated DBPs, including THMs, HAAs and HNMs (Verdugo et al., 2014; Verdugo et al., 2016). Concentrations of NDMA produced from the reactions of CNTs with free chlorine, monochloramine, and ozone were lower than those reported for those from the reactions with polymer coagulants. The NDMA yield reaches 50 ± 15 ng NDMA/mg CNTs (Verdugo et al., 2014). However, CNTs cannot make a significant contribution to the formation of NDMA, because the majority of NDMA from the chloramination, chlorination and ozonation of CNTs was lower than 10 ng NDMA/mg CNTs. Du et al. (2016) investigated the formation mechanisms and kinetics of THMs during the chlorination of five CNTs, graphene oxide

(GO) and reduced GO. GO exhibited the greatest yield of THM derived from these nanomaterials, but the THM yield was only up to 1.0 µg TCM/mg GO after 120 h chlorination with 140 µM free chlorine. Therefore, CNTs seem not to be a major precursor of THMs in drinking water due to their low THM yields in comparison to that of NOM (Du et al., 2016).

In order to minimize the formation of regulated DBPs, alternative disinfection methods, including titanium dioxide photocatalysis (TiO₂/PC) and TiO₂ photoelectrocatalysis (TiO₂/PEC), are explored. Richardson et al. (1996) identified 3-methyl-2, 4-hexanedione as a DBP in an ultrafiltration membrane treated filtrate after the TiO₂/PC treatment. A number of DBPs, including Cl-DBPs, Br-DBPs and bromate, were also observed after the PEC treatment of HA in the presence of Cl⁻ or Br⁻ (Selcuk et al., 2006; Selcuk, 2010). Similar to other AOPs, HO• and other ROS generated in a TiO₂/PC system are capable of inactivating various microorganisms and destructing numerous organic and inorganic water contaminants, while generating certain DBPs (Richardson et al., 1996; Sokolowski et al., 2014). When chlorine is used after TiO₂/PC, both the increase and decrease of DBPFP in the treated water were reported, depending on the specific water characteristics (Li et al., 1996; Liu et al., 2008; Sokolowski et al., 2014). Metch et al. (2015) investigated the catalytic properties of silver nanoparticles (AgNPs), TiO₂, ceria and nano zero-valent iron (nZVI) on the formation of DBPs under disinfections with three different disinfection options, i.e. free chlorine, UV alone and UV/chlorine. Results showed that only AgNPs significantly promoted the formation of THMs during UV/chlorine (Metch et al., 2015). However, the same results were not found by Tugulea et al. (2014) under similar experimental conditions.

In summary, though the aforementioned nanomaterials may potentially contribute to the formation of regulated DBPs (i.e. THMs, HAAs and NAs) in drinking water, the role of these nanomaterials appears to be insignificant due to their typically low DBP yields in comparison to those of NOM. The potential environmental and health effects of these nanomaterials may be of real concern (Qu et al., 2013; Adeleye et al., 2016).

2.5. Ion-exchange resins

In drinking water treatment, ion exchange is the exchange of ions with the same charges between water and an insoluble solid (i.e. resins). Strong base ion-exchange resins are commonly used in the

anion-exchange processes for the removal of negatively charged pollutants, such as nitrate, arsenate and perchlorate in raw water, because ion exchange technologies are simple, effective, selective, and relatively low-cost due to the repeated use after the resin regeneration (Gough et al., 1977; Samatya et al., 2006; Kemper et al., 2009). However, NDMA at a concentration of up to 2000 ng/L is found after ion exchange treatment of tap water or chlorinated water (Fiddler et al., 1977; Gough et al., 1977; Kimoto et al., 1980). NDMA is also observed in two samples of deionized water after ion exchange treatment (Fiddler et al., 1977), indicating that ion-exchange resins may release organic compounds serving as the precursor of NDMA. Of interest, the presence of nitrite can double the formation of NDMA in a deionized water system placing these resins (Najm and Trussell, 2001). However, the aforementioned studies may have overestimated the NA formation, because the empty bed contact time used in these laboratory studies was much longer than that typically applied in the realistic full scale treatment plants.

Kemper et al. (2009) comprehensively evaluated the formation of NAs in anion-exchange column experiments with and without disinfection using free chlorine or chloramine before or after the resin columns. Results showed that the use of three commercially available strong base ion-exchange resins, including Rohm and Haas Amberlite IRA400, Sybron Ionac SR6 and Sybron Ionac ASB2, did not produce NAs at a concentration above the notification levels in the absence of disinfectants. When chlorination or chloramination followed ion exchange, the formation of NAs was not enhanced. However, upstream disinfection with chlor(am)ine significantly increased the TONO concentrations to 20-100 ng/L for the IRA400 and SR6 resins and to ~ 400 ng/L for the ASB2 resin, all above the California notification level (10 ng/L). These findings highlight that application of anion-exchange resins may be problematic due to the formation of certain DBPs. Moreover, when feed water with 2 mg/L chlorine passed through different ion exchange resins, the SR6 resin was the one with the greatest formation of TCNM (up to 9 µg/L). But the highest TCNM concentration (up to 10 µg/L) was observed in the sample of IRA400 during the treatment of water containing 2 mg/L NH_2Cl as Cl_2 (Kemper et al., 2009). When feed water without oxidation passed through the fresh ASB2 and IRA400 resins, traceable TCNM was observed in only one sample of the fresh IRA400 resin followed by chloramination (Kemper et al., 2009). Although the formation of TCNM is negligible without oxidation, concerns on the formation of unwanted DBPs remain.

To sum up, application of ion-exchange resins for direct treatment of tap water or chlorinated water needs to be cautious due to the potential formation of DBPs. Owing to recent efforts to produce new resin materials, research is required to investigate the contribution of new ion exchange resins to the formation of DBPs.

2.6. Membranes

Membrane filtration is a separation process that can separate two phases via a membrane material (Takht Ravanchi et al., 2009). In water treatment, the technology can remove particulate or dissolved pollutants such as NOM from water. The most common membrane separation processes in drinking water treatment are the pressure-driven membrane filtration, including microfiltration, ultrafiltration, nanofiltration (NF), and reverse osmosis (RO). Ersan et al. (2015) noticed that NDMA precursors could leach from five NF membranes and the NDMA FP of the permeate ranged within ~180-450 ng/L. Xie et al. (2015) also found that chlorination of polyvinyl pyrrolidone–polysulfone membranes led to the leaching of organic compounds from the membrane material and the formation of TCM, CH, TCNM, 1,1,1-trichloropropanone (1,1,1-TCP), and 1,1-dichloropropanone (1,1-DCP). Concentrations of these compounds reached a few µg/L. CH was the dominant by-product, followed by TCM, 1,1,1-TCP, 1,1-DCP and TCNM, in terms of their abundance. When chlorine dose was increased from 0 mg/L to 14.2 mg/L, the concentrations of TCM, CH and TCNM were increased to 5.2 µg/L, 12.4 µg/L and 0.8 µg/L. However, such high doses and long contact time (72 h) were rarely used in realistic drinking water treatment. Moreover, membrane separation units were typically applied in the upstream of disinfection. Furthermore, the aforementioned studies may have overestimated the DBP formation, because the long-time soaking used in these laboratory studies was not representative of membrane operation that typically applied in the realistic full scale treatment plants. Besides, the realistic leaching of organic compounds may be vary from lab studies because static pipe experiment used in these laboratory studies are different from that typically used in full-scale water supply. Static experiments may limit the continuous leaching of organic compounds when the chemical equilibrium of organic compounds is reached. Therefore, the leaching of membrane materials is not a major concern in the formation of halogenated DBPs when chlor(am)ination is applied after the membrane filtration. It should be noted that membrane cleaning

with higher doses of chlorine may produce more halogenated DBPs, which may be a concern (Cai et al., 2017; Sun et al., 2018).

Furthermore, Chellam (2000) reported that NF could influence the speciation of DBPs in the downstream disinfection. Similar to GAC treatment, NF treatment can increase the molar ratio of Br-DBPs to Cl-DBPs in its permeate, even if chlorination of nanofiltered waters produced lower DBPs. They noticed that BCAA and TBAA accounted for 50% of the total HAAs on a molar basis as Br-/DOC increased to 25 $\mu\text{M}/\text{mM}$ or greater. It should be noted that the majority of HAAs produced are not regulated in existing five HAAs (HAA₅) regulations and guidelines. Bromine incorporation into THMs and HAAs was a function of $[\text{Br}^-]/[\text{DOC}]$ that influences the speciation of DBPs produced. A model was further developed to correlate the bromine incorporation factors (BIFs) of THMs and HAAs with chlorination conditions as well as Br⁻ and DOC concentrations (Chellam, 2000). BIF is defined as the molar ratio of bromine incorporated into a given class of DBP to the total halogens in that class. It should be noted that BIF was typically increased after NF treatment, suggesting that chlorination following NF treatment potentially increased the mammalian cell cytotoxicity and genotoxicity, though the overall DBP concentrations may decrease. Particularly, HAA₉ concentrations were greater than the 4 regulated THMs (THM₄) level in the NF permeate (Chellam and Krasner, 2001; Chellam et al., 2008). According to CHO cell experiments, the toxicity of HAAs as a class is higher than THMs (Wagner and Plewa, 2017). Thus, a more equitable regulation of THMs and HAAs may be worthy of consideration.

Similar to AC treatment, treatment of high bromide-containing water using a membrane separation also promotes the ratio of brominated DBPs to chlorinated DBPs in effluents. Organic compounds leaching from membrane can bring about potential risks associated with the formation of DBPs during a downstream disinfection.

3. Unintended effects of engineering agents and materials in drinking water distribution on DBP formation

Drinking water distribution systems (DWDSs) are an essential component in municipal water supply. Iron, copper and zinc are widely incorporated into the materials in DWDSs and water storage facilities (Seidel, 1985). A 2004 survey of American Water Works Association (AWWA) indicates

that iron based (i.e. ductile iron, cast iron and steel), PVC, and asbestos cement pipes account for 56.6%, 16.6% and 15.2% of total pipe miles, respectively (USEPA, 2007). Moreover, copper, polymer, lead, iron, and galvanized pipes are 56.3%, 19.6%, 3.3%, 2.7% and 8.0% of the total customer service lines, respectively (USEPA, 2007). Over the service time, the interior surface of metallic pipes exposed to an oxic environment is gradually corroded. Biofilms attached to the pipe walls are ubiquitous in DWDSs, contributing to more than 90% of the overall biomass (Flemming et al., 2002; Liu et al., 2016). However, only up to 5% of the biomass suspended in the bulk water can be monitored using the sampling procedure of drinking water. Therefore, microbial contamination in the pipes is underestimated (Flemming et al., 2002). Previous studies have revealed that the occurrence of biofilms within the pipes can accelerate depletion of disinfectant residual, favor excessive accumulation of microorganisms, increase the release of pipe corrosion products, decrease water pH, and lower dissolved oxygen (DO) (Emde et al., 1992; Lehtola et al., 2004; Zeng and Mitch, 2016). Kinetics and mechanism of these reactions of disinfectant residuals with NOM, pipe deposits and pipe biofilms may play an essential role in the fate and transportation of DBPs within DWDSs. Moreover, hydraulics patterns, seasonal variables and the finished water quality all impact the fate and transportation of DBPs within DWDSs.

3.1. Distribution system pipes

Based on the AWWA's WaterStats database in 2002, 22.5% of 202158-mile U.S. DWDSs are made of unlined cast/ductile iron or steel (USEPA, 2007). It is well known that elemental transition metals, such as iron, zinc and copper, are commonly used as reductants to detoxify halogenated organic compounds in site remediation (Matheson and Tratnyek, 1994; Arnold and Roberts, 1998). To understand the fate of DBPs in DWDSs and to develop possible treatment processes for removal of DBPs from drinking water, numerous studies have focused on degradation of representative DBPs (i.e. THMs, HAAs, HALs, HKs, HANs, HNMs, HAMs and NAs) in the presence of zero-valent metals (Gui et al., 2000; Hozalski et al., 2001; Zhang et al., 2004; Pearson et al., 2005; Lee et al., 2007; Arnold et al., 2010; Wang and Zhu, 2010; Han et al., 2013; Tang et al., 2015; Chu et al., 2016c; Han et al., 2017). **Table 3** presents the experimental conditions and results for the reactions of DBPs with different elemental metals. The metals, regardless of their shape and size, are capable

of degrading halogenated DBPs and non-halogenated NAs via reductive mechanisms. Tendency of dehalogenation from the alkyl carbon decreases in the following order: $I > Br \gg Cl$, due to an increasing bond length and a decreasing dissociation energy. Therefore, a faster dehalogenation rate occurs for I-DBPs than those of Br- and Cl-DBPs (Chu et al., 2016c). Moreover, the removal of Cl-DBPs initially increases and then decreases with the increase of DO (Lee et al., 2007; Tang et al., 2015). This finding can be explained by the theory that the degradation of Cl-DBPs is limited by the reduction or migration rate within metal particles rather than mass transfer (Zhang et al., 2004). In the iron-based pipes, low oxidic condition favors the formation of a thin lepidocrocite layer, which can enhance the degradation of Cl-DBPs. In contrast, at a high oxidic condition, oxygen competing for reductive agents and significant growth of lepidocrocite can inhibit reductive dehalogenation (Tang et al., 2015). Although the base-catalyzed hydrolysis of HAN, HAMs, HNMs, or HALs simultaneously occurred during the reduction process, the hydrolysis rates under typical drinking water conditions (pHs 7-8) were several orders of magnitude slower than that reduction reaction (Joo and Mitch, 2007; Yu and Reckhow, 2015; Ma et al., 2016; Ding et al., 2018c). Therefore, the effect of hydrolysis on the degradation of N-DBPs was not discussed in this study.

【 Table 3 】

Although ZVI can theoretically remove many halogenated DBPs and NAs, the treatment efficiency of ZVI is discounted at realistic treatment condition. As shown in Table 3, the highest observed order degradation rate constant of halogenated DBPs and NAs under neutral condition reaches 19.65 h^{-1} , whereas the most observed rate constants are lower than 0.1 h^{-1} . Half-lives of the halogenated DBPs and NAs are more than several hours. In general, the dehalogenation tendency of halogenated DBPs decreases in the following order: $I > Br \gg Cl$. Moreover, dehalogenation rates increase with the number of halogens substituted on the methyl group and monohalogenated DBPs are difficult to form non-halogenated compounds by dehalogenation. Furthermore, the corrosion products and biofilm also inhibit the dehalogenation reactions. Besides, DWDSs are composed of metal pipe rather than metal powder, and the surface area of metal pipe were several order lower than that of metal powder. Therefore, ZVI rarely completely degrades halogenated DBPs into non-

halogenated compounds during the drinking water distribution. Although the observed rate constants for the reaction of zero-valent zinc with halogenated DBPs or NAs are usually higher than 1 h^{-1} (Table 3), zinc pipes are much less popularly used than iron based pipes.

While zero-valent metals (i.e. iron, zinc and copper) can serve as potential reductants capable of reducing a wide variety of halogenated DBPs and NAs, they were reported to enhance the formation DBPs or generate more toxic DBPs during water treatment. Chu et al. (2016a) demonstrated that the reduction of three chloramphenicol antibiotics by ZVI can produce DCAM firstly and then MCAM in the absence of disinfectants. Given that unlined cast iron pipes are widely used in many drinking water distribution systems, reactions between chloramphenicol antibiotics and ZVI may contribute to the formation of DCAM. I^- is considered as the main iodine source accounting for the formation of toxic I-DBPs during disinfection, while iodinated X-ray contrast media and iodate can also serve as the iodine sources of I-DBPs in the presence of ZVI (Xia et al., 2017; Dong et al., 2018). Iopamidol or iodate is subjected to the deiodination or reduction by ZVI to yield I^- , which enhances the formation of I-DBPs during subsequent chlor(am)ination (Xia et al., 2017; Dong et al., 2018). However, these reactions will also be inhibited by the aforementioned inhibiting factors for the zero-valent metal facilitated dehalogenation.

Polyvinyl chloride (PVC) and chlorinated PVC pipes may leach vinyl chloride, a confirmed human carcinogen, in several tens of ng/L over a couple of days and a few hundreds of ng/L after two-year exposure (Ando and Sayato, 1984; Benfenati et al., 1991; Walter et al., 2011). Results also demonstrated that aging had no significant effect on the accumulation of vinyl chloride (Walter et al., 2011). Although these levels exceed the maximum contaminant level goal of vinyl chloride at $0 \text{ } \mu\text{g/L}$ in water, they are still much lower than that the EPA's maximum contaminant level of $2 \text{ } \mu\text{g/L}$ (Walter et al., 2011). Nevertheless, similar to the leaching of membrane, the accumulation of vinyl chloride may be limited in static pipe experiment used in these laboratory studies. Morran et al. (2011) noticed that NDMA could not be generated from the reactions of PVC pipe with chloramine. However, a 24 h immersion of new rubber pipeline sealing rings, gate valve inserts and gaskets, which are used to connect pipes and construct temporary storage tanks in ultrapure water, can cause the formation of NDMA ranging from $< 3 \text{ ng/L}$ to 930 ng/L (Morran et al., 2011; Teefy et al., 2014). Furthermore, the presence of chlorine or chloramines produces 2-fold NDMA or greater under the

identical conditions. Therefore, pre-treatments of these new rubber materials are of importance for alleviation of the NDMA formation.

In summary, the use of plastic and rubber, rather than metal, pipelines can become the major concern for serving as the source of NDMA.

3.2. Distribution system deposits

Corrosion products of iron pipes are comprised of various iron (hydr)oxides. Lin et al. (2001) identified goethite (75.6%), magnetite (21.5%) and lepidocrocite (2.9%) in complex iron corrosion products. Table 3 presents the degradation of DBPs in the presence of various synthetic and realistic pipe deposits. The dehalogenation rates of TCNM, TCAN, 1,1,1-TCP, CH, TCAA and CF, which share the same chemical structure $\text{CCl}_3\text{-R}$, increase with the increasing electron-withdrawal of substituents ($-\text{NO}_2 > -\text{CN} > -\text{C}(=\text{O})\text{CH}_3 > -\text{CHO} > -\text{COO}^- > -\text{H}$) (Chun et al., 2005). This observation can be explained by the fact that electron-withdrawal groups can move electron density away from the $-\text{CCl}_3$ moiety, thereby becoming more electrophilic (Croue and Reckhow, 1989).

Although pipe deposits are capable of removing DBPs, half-lives of the DBPs are typically as long as several hours or greater (Table 3). Generally, dihalogenated and monohalogenated DBPs are more difficultly degraded than trihalogenated DBPs (Chun et al., 2005; Chu et al., 2016c). One previous study also reported that lead oxide (PbO_2) can oxidize iodide to reactive iodine, which lead to IF formation in the presence of NOM (Lin et al., 2008). However, the high oxidant and iodide doses and reaction time in that study hardly occurs in realistic DWDSs. Apart from reductive capability of the pipe deposits, they can serve as a catalyst for altering the decay rate of disinfectant and/or influencing the formation of DBPs (Blatchley et al., 2003; Chu et al., 2016c; Sharma et al., 2017). Catalytic effects of iron corrosion products on disinfectant decomposition are insignificant (Liu et al., 2013a; b; Zhao et al., 2016). However, copper corrosion products (CCPs), including Cu(II) , Cu_2O , CuO and $\text{Cu}_2(\text{OH})_2\text{CO}_3$, can accelerate the decay of oxidants, including HOCl , ClO_2 , HOBr and HOI (Fig. 3) (Liu et al., 2012; 2013b; Liu et al., 2014). Along with the rapid decay of disinfectants in the presence of CCPs, the formation of THMs, HAAs, bromate, chlorate, chlorite and NAs in simulated DWDSs is enhanced (Li et al., 2007; Fu et al., 2009; Zhang and Andrews, 2012; Liu et al., 2013c; Zhang and Andrews, 2013; Zhao et al., 2016). Moreover, more TOX is

produced during chlorination of drinking water in the presence of CCPs (Liu et al., 2013c). Fu et al. (2009) proposed two plausible pathways to explain the reaction mechanisms for the CCPs-catalyzed formation of THM and HAA. In the first mechanism, the enhancement is attributed to the increased yield of $\bullet\text{OH}$ validated from the electron spin resonance analysis (Fu et al., 2009). A previous study also found that metal-loaded HA could produce $\bullet\text{OH}$ through the metal-driven Fenton chemistry (Paciolla et al., 1999). $\bullet\text{OH}$ is capable of oxidizing large molecular weight (MW) NOM compounds (e.g. HA) into small MW molecules that are more reactive DBP precursors than the initial material (Hua and Reckhow, 2007). In the other pathway, CCPs complexes with HA can accelerate the decarboxylation steps for THM and HAA formation (Fu et al., 2009).

【Figure 3】

As shown in Fig. 3, CCPs also catalyze the disproportionation of HOBr to enhance the formation of bromate during chlorination of bromide-containing waters (Liu et al., 2012; 2013a). Subsequent studies indicated that the formation of bromate from the disproportionation of HOBr competed with the formation of Br-DBPs (Liu and Croué, 2016). Fractions of the product species rely on how reactively bromine reacts with NOM and how rapid HOBr disproportionation is. Results indicated that the reactivity of HOBr with phenols was much stronger than that of the HOBr disproportionation in the presence of CuO, whereas the disproportionation of HOBr prevails in comparison with the reactions of HOBr with certain less reactive compounds, such as acetone, butanol, propionic and butyric acids (Liu and Croué, 2016). Hu et al. (2016) reported that three CCPs (i.e. Cu(II), Cu₂O and CuO) simultaneously enhanced the formation of bromate and Br-DBPs during chlorination of bromide-containing waters. As shown in Fig. 4, 0.04% and 24.6% of Br⁻ (on a molar basis) are converted to bromate and Br-DBPs, respectively, in the absence of CCPs. However, the conversion ratios of Br⁻ to bromate rise to 22.1%, 8.6% and 9.1% in the presence of CuO, Cu₂O and Cu(II), respectively. Meanwhile, the conversion ratios of Br⁻ to the studied Br-DBPs reach 24.7%, 36.0% and 30.6%, respectively. It should be noted that there is a substantial discrepancy between Br⁻ with and without the addition of CCPs. The concentration of unutilized Br⁻ accounts for 23.9% of initial Br⁻ concentration in the absence of CCPs, while the unutilized Br⁻

decreases to 14.3%, 8.4% and 9.6% in the presence of CuO, Cu₂O and Cu(II), respectively. Furthermore, CuO, Cu₂O and Cu(II) catalyze the transformations of Cl-DBPs to brominated analogues in the presence of Br⁻ (Li et al., 2007; Liu et al., 2013a). It was reported that the concentrations of bromate and Br-DBPs (i.e. THMs, HAAs and HAMs) under CuO, Cu₂O or Cu(II) catalysis were generally lower than the maximum contaminant level at the Br⁻ concentration of 0.2 mg/L (Hu et al., 2016). However, when the Br⁻ concentration increased to 0.5 mg/L, the concentration of bromate after the CuO, Cu₂O or Cu(II) catalysis significantly increased, ranging from 15.1 - 54.6 µg/L, and the enhancement ratios of Br-DBPs (i.e. THMs, HAAs and HAMs) formation under Cu₂O catalysis were 47.4%, 44.0% and 42.9%, respectively, corresponding to 117.1, 82.3 and 68.6 µg/L, all above or equivalent to their respective EPA's maximum contaminant levels (10 µg/L, 80 µg/L and 60 µg/L for bromate, THM₄ and HAA₅) (USEPA, 2006). Because Br-DBPs are generally more toxic than Cl-DBPs, the health risks associated with Br-DBPs should be paid special attention to when copper is used as the inlet pipe materials and the filter waters have higher Br⁻ level (> 200 µg/L).

Accordingly, CCPs accelerate the decay of disinfectants, promote the formation of DBPs and total organic halogen, and lead to additional byproduct formation. A partial loss of disinfectants is problematic to drinking water quality and enhances formation of DBPs.

【Figure 4】

3.3. Distribution system biofilms

Numerous models have been developed to predict the formation of DBPs during water treatment, but the role of biofilms (up to 10⁴ - 10⁷ CFU/ cm²) in these models has been generally underestimated (Ged et al., 2015; Abokifa et al., 2016). Similarly, the formation of DBPs in the DWDS environment is generally underemphasized (Rossman et al., 2001). Moreover, the concentration of THMs at DWDSs and the points of use are higher than those in finished water, while chlorine is rapidly consumed within the pipe system (Toroz and Uyak, 2005; Pieri et al., 2014). These findings show that DWDS pipe biofilms may have been an important DBP precursor.

Rossman et al. (2001) compared the formation of THMs and HAAs in a simulated DWDS pipe

to that in a bottle. They found that the decline of chlorine was faster while the concentration of THMs increased by an average of 15% in simulated DWDS pipe. Moreover, the hydrolysis and chlorination of intermediate DBPs into THMs may also contribute to increases in the latter group and will be affected by pH values of the particular system. Many DBPs, including THMs, HALs, HKs, HNMs and HANs, are detectable at several tens $\mu\text{g/L}$ regulated DBPs/mg-C/L or several $\mu\text{g/L}$ N-DBPs/mg-C/L during chlor(am)ination of pure bacterial cells and EPS isolated from biofilms (Wang et al., 2013; Lemus Pérez and Rodríguez Susa, 2017). DBP FP is also correlated with the log reduction of bacterial cells (i.e. bacterial cells) and EPS (Wang et al., 2013; Lemus Pérez and Rodríguez Susa, 2017). Abokifa et al. (2016) developed a multiple species reactive transport model to predict chlorine decay and microbial regrowth dynamics in a realistic DWDS, along with THMs formation in a pilot-scale distribution system simulator by accounting for the simultaneous transport and interactions of disinfectants, organic compounds and biomass. Results indicate that the contribution of biofilm to the formation of THMs relies heavily on hydraulics patterns, seasonal variables and the finished water quality in the system (Abokifa et al., 2016). Besides, nitrification in storage facilities enhances the formation of NDMA and other halogenated DBPs in the downstream chloramine application in the DWDSs (Zeng and Mitch, 2016). The enhanced DBP formation in the presence of nitrifying biofilm indicates that the release of organic compounds from nitrifying biofilm can serve as the precursors of DBPs (Zeng and Mitch, 2016). An integrated approach, starting from the treatment of drinking water prior to entering the DWDSs to the potential implementation of “biofilm-limiting” operational conditions and, finally, ending with the careful selection of flushing of DWDS, nutrient removal, and emerging available technologies for biofilm monitoring and control, is needed.

Pipe biofilms accelerate coliform growth and pipe corrosion, lead to water taste and odour issues, and promote the decay of disinfectant and formation of DBPs. Therefore, appropriate management of biofilm growth in a water distribution system is of importance to the additional formation of DBPs within the pipes (Liu et al., 2016).

4. Conclusions and implications for drinking water treatment and distribution

Drinking water disinfection requires tradeoffs between the inactivation of pathogens and the

formation of hazardous DBPs. This article reviews and analyses the unintended effects of engineering materials and reagents during drinking water treatment and distribution on the formation of DBPs. Quaternary ammonium polymer coagulants may lead to violation of the NDMA notification levels, which may be a major concern for the drinking water quality. Organic compounds leached from strong base ion-exchange resins, membranes and pipes can also cause noncompliance with regulatory limits. Biofilm formation in BAF and DWDSs can accelerate disinfectant decomposition and DBP formation. In order to minimize the biofilm facilitated formation of DBPs, it is essential to implement 'biofilm-limiting' operation, flush distribution systems and remove nutrients within the distribution system. Furthermore, the treatment of high Br⁻ (> ~100 µg/L) source waters with AC or membranes can elevate toxicity in effluents, despite an overall decrease in the overall DBP concentrations. CCPs can accelerate the decay of disinfectants and oxidants, promote the formation of DBPs (particularly bromate), increase the concentration of TOX and lead to the formation of additional byproducts. A partial loss of disinfectants is problematic to drinking water quality and enhanced formation of DBPs makes this even worse. These impacts can be mitigated by replacement of copper pipes, application of lined cast copper pipes, flushing of distribution systems and improved monitoring of CCPs. This study highlights the role of engineering agents and materials in the formation of DBPs in water treatment and distribution.

Acknowledgements

The authors gratefully acknowledge the National Natural Science Foundation of China (No. 51822808; 51578389; 51778445), the National Major Science and Technology Project of China (No. 2017ZX07201-005), the Shanghai City Youth Science and Technology Star Project (No. 17QA1404400), Shanghai City Youth Top Talent Project and Fundamental Research Funds for the Central Universities (1380219169). S. Ding was partially supported by Shanghai Tongji Gao Tingyao Environmental Science & Technology Development Foundation (STGEF).

References

Abokifa, A.A., Yang, Y.J., Lo, C.S., Biswas, P., 2016. Investigating the role of biofilms in trihalomethane formation in water distribution systems with a multicomponent model.

757 Water Res. 104, 208-219.

758 Adeleye, A.S., Conway, J.R., Garner, K., Huang, Y., Su, Y., Keller, A.A., 2016. Engineered
 759 nanomaterials for water treatment and remediation: Costs, benefits, and applicability. Chem.
 760 Eng. J. 286, 640-662.

761 Alpatova, A.L., Baumann, M.J., Davies, S.H., Masten, S.J., 2013. Evidence for covalently bonded
 762 chlorine–fullerene formed by ozonation and chlorination at room temperature. Environ.
 763 Chem. Lett. 11(3), 309-313.

764 Ando, M., Sayato, Y., 1984. Studies on vinyl chloride migrating into drinking water from polyvinyl
 765 chloride pipe and reaction between vinyl chloride and chlorine. Water Res. 18(3), 315-318.

766 Arnold, W.A., Roberts, A.L., 1998. Pathways of Chlorinated Ethylene and Chlorinated Acetylene
 767 Reaction with Zn(0). Environ. Sci. Technol. 32(19), 3017-3025.

768 Arnold, W.A., Hozalski, R.M., Pearson, C.R., Morre, K., 2010. TBAA reduction in reactors
 769 simulating distribution system pipes. J. Am. Water. Works. Ass. 102(3), 99-106.

770 Bablon, G.P., Ventresque, C., Aïm, R.B., 1988. Developing a Sand-GAC Filter to Achieve High-
 771 Rate Biological Filtration. J. Am. Water. Works. Ass. 80(12), 47-53.

772 Bei, E., Shu, Y., Li, S., Liao, X., Wang, J., Zhang, X., Chen, C., Krasner, S., 2016. Occurrence of
 773 nitrosamines and their precursors in drinking water systems around mainland China. Water
 774 Res. 98, 168-175.

775 Benfenati, E., Natangelo, M., Davoli, E., Fanelli, R., 1991. Migration of vinyl chloride into PVC-
 776 bottled drinking-water assessed by gas chromatography-mass spectrometry. Food
 777 Chem.Toxicol. 29(2), 131-134.

778 Blatchley, E.R., Margetas, D., Duggirala, R., 2003. Copper catalysis in chloroform formation during
 779 water chlorination. Water Res. 37(18), 4385-4394.

780 Bolto, B., 2005. Reaction of chlorine with organic polyelectrolytes in water treatment: A review. J.
 781 Water Supply: Res. T. 54(8), 531-544.

782 Bolto, B., Gregory, J., 2007. Organic polyelectrolytes in water treatment. Water Res. 41(11), 2301-
 783 2324.

784 Bond, T., Huang, J., Templeton, M.R., Graham, N., 2011. Occurrence and control of nitrogenous
 785 disinfection by-products in drinking water – A review. Water Res. 45(15), 4341-4354.

786 Bond, T., Templeton, M.R., Graham, N., 2012. Precursors of nitrogenous disinfection by-products
 787 in drinking water—A critical review and analysis. *J. Hazard. Mater.* 235-236, 1-16.

788 Cai, W., Liu, J., Zhu, X., Zhang, X., Liu, Y., 2017. Fate of dissolved organic matter and byproducts
 789 generated from on-line chemical cleaning with sodium hypochlorite in MBR. *Chem. Eng.*
 790 *J.* 323, 233-242.

791 CDPH (2009) NDMA and Other Nitrosamines e Drinking Water Issues,
 792 <http://www.cdph.ca.gov/certlic/drinkingwater/Pages/NDMA.aspx>.

793 Chellam, S., 2000. Effects of Nanofiltration on Trihalomethane and Haloacetic Acid Precursor
 794 Removal and Speciation in Waters Containing Low Concentrations of Bromide Ion.
 795 *Environ. Sci. Technol.* 34(9), 1813-1820.

796 Chellam, S., Krasner, S.W., 2001. Disinfection byproduct relationships and speciation in chlorinated
 797 nanofiltered waters. *Environ. Sci. Technol.* 35(19), 3988-3999.

798 Chellam, S., Sharma, R.R., Shetty, G.R., Wei, Y., 2008. Nanofiltration of pretreated Lake Houston
 799 water: Disinfection by-product speciation, relationships, and control. *Sep. Purif. Technol.*
 800 64(2), 160-169.

801 Chen, A.S.C., Larson, R.A., Snoeyink, V.L., 1982. Reactions of chlorine dioxide with hydrocarbons:
 802 effects of activated carbon. *Environ. Sci. Technol.* 16(5), 268-273.

803 Chen, A.S.C., Larson, R.A., Snoeyink, V.L., 1984. Importance of surface free radicals in an aqueous
 804 chlorination reaction (Indan-ClO₂) promoted by granular activated carbon. *Carbon* 22(1),
 805 63-75.

806 Chen, C.-Y., Jafvert, C.T., 2010. Photoreactivity of Carboxylated Single-Walled Carbon Nanotubes
 807 in Sunlight: Reactive Oxygen Species Production in Water. *Environ. Sci. Technol.* 44(17),
 808 6674-6679.

809 Child, P., Kaa, G., Benitz, D., Fowlie, P., Hong, R., 1996. Reaction between chlorine and a
 810 dimethylamine containing polyelectrolyte leading to the formation of N-
 811 nitrosodimethylamine.

812 Chiu, C.A., Westerhoff, P., Ghosh, A., 2012. GAC removal of organic nitrogen and other DBP
 813 precursors. *J. Am. Water. Works. Ass.* 104(7), 406-415.

814 Chu, W.H., Gao, N.Y., Deng, Y., Krasner, S.W., 2010. Precursors of Dichloroacetamide, an

815 Emerging Nitrogenous DBP Formed during Chlorination or Chloramination. *Environ. Sci.*
816 *Technol.* 44(10), 3908-3912.

817 Chu, W.H., Gao, N.Y., Deng, Y., Templeton, M.R., Yin, D.Q., 2011. Impacts of drinking water
818 pretreatments on the formation of nitrogenous disinfection by-products. *Bioresource*
819 *Technol.* 102(24), 11161-11166.

820 Chu, W.H., Li, C.J., Gao, N.Y., Templeton, M.R., Zhang, Y.S., 2015a. Terminating pre-ozonation
821 prior to biological activated carbon filtration results in increased formation of nitrogenous
822 disinfection by-products upon subsequent chlorination. *Chemosphere* 121, 33-38.

823 Chu, W.H., Li, D.M., Gao, N.Y., Yin, D.Q., Zhang, Y.S., Zhu, Y.P., 2015b. Comparison of free amino
824 acids and short oligopeptides for the formation of trihalomethanes and haloacetonitriles
825 during chlorination: Effect of peptide bond and pre-oxidation. *Chem. Eng. J.* 281, 623-631.

826 Chu, W.H., Ding, S.K., Bond, T., Gao, N.Y., Yin, D.Q., Xu, B., Cao, Z.Q., 2016a. Zero valent iron
827 produces dichloroacetamide from chloramphenicol antibiotics in the absence of chlorine
828 and chloramines. *Water Res.* 104, 254-261.

829 Chu, W.H., Krasner, S.W., Gao, N.Y., Templeton, M.R., Yin, D.Q., 2016b. Contribution of the
830 Antibiotic Chloramphenicol and Its Analogues as Precursors of Dichloroacetamide and
831 Other Disinfection Byproducts in Drinking Water. *Environ. Sci. Technol.* 50(1), 388-396.

832 Chu, W.H., Li, X., Bond, T., Gao, N.Y., Bin, X., Wang, Q.F., Ding, S.K., 2016c. Copper increases
833 reductive dehalogenation of haloacetamides by zero-valent iron in drinking water:
834 Reduction efficiency and integrated toxicity risk. *Water Res.* 107, 141-150.

835 Chuang, Y.-H., Mitch, W.A., 2017. Effect of ozonation and biological activated carbon treatment of
836 wastewater effluents on formation of N-nitrosamines and halogenated disinfection
837 byproducts. *Environ. Sci. Technol.* 51(4), 2329-2338.

838 Chuang, Y.-H., Szczuka, A., Shabani, F., Munoz, J., Aflaki, R., Hammond, S.D., Mitch, W.A., 2019.
839 Pilot-scale comparison of microfiltration/reverse osmosis and ozone/biological activated
840 carbon with UV/hydrogen peroxide or UV/free chlorine AOP treatment for controlling
841 disinfection byproducts during wastewater reuse. *Water Res.* 152, 215-225.

842 Chun, C.L., Hozalski, R.M., Arnold, W.A., 2005. Degradation of Drinking Water Disinfection
843 Byproducts by Synthetic Goethite and Magnetite. *Environ. Sci. Technol.* 39(21), 8525-

844 8532.

845 Croue, J.P., Reckhow, D.A., 1989. Destruction of chlorination byproducts with sulfite. *Environ. Sci.*

846 *Technol.* 23(11), 1412-1419.

847 Deborde, M., von Gunten, U., 2008. Reactions of chlorine with inorganic and organic compounds

848 during water treatment—Kinetics and mechanisms: A critical review. *Water Res.* 42(1–2),

849 13-51.

850 Ding, S.K., Chu, W.H., Bond, T., Cao, Z.Q., Xu, B., Gao, N.Y., 2018a. Contribution of amide-based

851 coagulant polyacrylamide as precursors of haloacetamides and other disinfection by-

852 products. *Chem. Eng. J.* 350, 356-363.

853 Ding, S.K., Chu, W.H., Bond, T., Wang, Q., Gao, N.Y., Xu, B., Du, E.D., 2018b. Formation and

854 estimated toxicity of trihalomethanes, haloacetonitriles, and haloacetamides from the

855 chlor(am)ination of acetaminophen. *J. Hazard. Mater.* 341, 112-119.

856 Ding, S.K., Chu, W.H., Krasner, S.W., Yu, Y., Fang, C., Xu, B., Gao, N.Y., 2018c. The stability of

857 chlorinated, brominated, and iodinated haloacetamides in drinking water. *Water Res.* 142,

858 490-500.

859 Dong, H., Qiang, Z., Lian, J., Li, J., Yu, J., Qu, J., 2018. Deiodination of iopamidol by zero valent

860 iron (ZVI) enhances formation of iodinated disinfection by-products during chloramination.

861 *Water Res.* 129, 319-326.

862 Du, H., Li, J., Moe, B., McGuigan, C.F., Shen, S., Li, X.-F., 2013. Cytotoxicity and Oxidative

863 Damage Induced by Halobenzoquinones to T24 Bladder Cancer Cells. *Environ. Sci.*

864 *Technol.* 47(6), 2823-2830.

865 Du, T., Wang, Y., Yang, X., Wang, W., Guo, H., Xiong, X., Gao, R., Wuli, X., Adeleye, A.S., Li, Y.,

866 2016. Mechanisms and kinetics study on the trihalomethanes formation with carbon

867 nanoparticle precursors. *Chemosphere* 154, 391-397.

868 Emde, K.M.E., Smith, D.W., Facey, R., 1992. Initial investigation of microbially influenced

869 corrosion (MIC) in a low temperature water distribution system. *Water Res.* 26(2), 169-175.

870 Ersan, M.S., Ladner, D.A., Karanfil, T., 2015. N-Nitrosodimethylamine (NDMA) Precursors Leach

871 from Nanofiltration Membranes. *Environ. Sci. Technol. Lett.* 2(3), 66-69.

872 Feige, M.A., Glick, E.M., Munch, J.W., Munch, D.J., Noschang, R.L., Brass, H.J. (1980) *Water*

873 Chlorination: Environmental Impact and Health Effects. Jolley, R.L., Brungs, W. A.,
874 Cumming, R. B. & Jacobs, V. A. (ed), pp. 789-799, Ann Arbor Science Publishers, Ann
875 Arbor, Michigan.

876 Fiddler, W., Pensabene, J.W., Doerr, R.C., Dooley, C.J., 1977. The presence of dimethyl- and
877 diethyl-nitrosamines in deionized water. Food Cosmet. Toxicol. 15(5), 441-443.

878 Flemming, H.C., Percival, S.L., Walker, J.T., 2002. Contamination potential of biofilms in water
879 distribution systems. Wa. Sci. Technol. 2(1), 271.

880 Fortner, J.D., Kim, D.-I., Boyd, A.M., Falkner, J.C., Moran, S., Colvin, V.L., Hughes, J.B., Kim, J.-
881 H., 2007. Reaction of Water-Stable C60 Aggregates with Ozone. Environ. Sci. Technol.
882 41(21), 7497-7502.

883 Fu, J., Qu, J., Liu, R., Qiang, Z., Liu, H., Zhao, X., 2009. Cu(II)-catalyzed THM formation during
884 water chlorination and monochloramination: A comparison study. J. Hazard. Mater. 170(1),
885 58-65.

886 Gallard, H., von Gunten, U., 2002. Chlorination of natural organic matter: kinetics of chlorination
887 and of THM formation. Water Res. 36(1), 65-74.

888 Ged, E.C., Chadik, P.A., Boyer, T.H., 2015. Predictive capability of chlorination disinfection
889 byproducts models. J. Environ. Manage. 149, 253-262.

890 Gonce, N., Voudrias, E.A., 1994. Removal of chlorite and chlorate ions from water using granular
891 activated carbon. Water Res. 28(5), 1059-1069.

892 Gough, T.A., Webb, K.S., McPhail, M.F., 1977. Volatile nitrosamines from ion-exchange resins.
893 Food Cosmet. Toxicol. 15(5), 437-440.

894 Gui, L., Gillham, R.W., Odziemkowski, M.S., 2000. Reduction of N-Nitrosodimethylamine with
895 Granular Iron and Nickel-Enhanced Iron. 1. Pathways and Kinetics. Environ. Sci. Technol.
896 34(16), 3489-3494.

897 Han, Y., Chen, Z.-l., Tong, L.-n., Yang, L., Shen, J.-m., Wang, B.-y., Liu, Y., Liu, Y., Chen, Q., 2013.
898 Reduction of N-Nitrosodimethylamine with zero-valent zinc. Water Res. 47(1), 216-224.

899 Han, Y., Chen, Z.-l., Shen, J.-m., Wang, J.-h., Li, W.-w., Li, J., Wang, B.-y., Tong, L.-n., 2017. The
900 role of Cu(II) in the reduction of N-nitrosodimethylamine with iron and zinc. Chemosphere
901 167, 171-177.

902 Hanigan, D., Zhang, J., Herckes, P., Zhu, E., Krasner, S., Westerhoff, P., 2015. Contribution and
 903 Removal of Watershed and Cationic Polymer N-Nitrosodimethylamine Precursors. *J. Am.*
 904 *Water. Works. Ass.* 107(3), 152-163.

905 Hozalski, R.M., Zhang, L., Arnold, W.A., 2001. Reduction of Haloacetic Acids by Fe⁰:
 906 Implications for Treatment and Fate. *Environ. Sci. Technol.* 35(11), 2258-2263.

907 Hu, J., Qiang, Z., Dong, H., Qu, J., 2016. Enhanced formation of bromate and brominated
 908 disinfection byproducts during chlorination of bromide-containing waters under catalysis
 909 of copper corrosion products. *Water Res.* 98, 302-308.

910 Hu, J.L., Chu, W.H., Sui, M.H., Xu, B., Gao, N.Y., Ding, S.k., 2018. Comparison of drinking water
 911 treatment processes combinations for the minimization of subsequent disinfection by-
 912 products formation during chlorination and chloramination. *Chem. Eng. J.* 335, 352-361.

913 Hua, G., Reckhow, D.A., 2007. Comparison of disinfection byproduct formation from chlorine and
 914 alternative disinfectants. *Water Res.* 41(8), 1667-1678.

915 Hwang, S.C., Larson, R.A., Snoeyink, V.L., 1990. Reactions of free chlorine with substituted
 916 anilines in aqueous solution and on granular activated carbon. *Water Res.* 24(4), 427-432.

917 Jackson, D.E., Larson, R.A., Snoeyink, V.L., 1987. Reactions of chlorine and chlorine dioxide with
 918 resorcinol in aqueous solution and adsorbed on granular activated carbon. *Water Res.* 21(7),
 919 849-857.

920 Jeong, C.H., Postigo, C., Richardson, S.D., Simmons, J.E., Kimura, S.Y., Mariñas, B.J., Barcelo, D.,
 921 Liang, P., Wagner, E.D., Plewa, M.J., 2015. Occurrence and Comparative Toxicity of
 922 Haloacetaldehyde Disinfection Byproducts in Drinking Water. *Environ. Sci. Technol.*
 923 49(23), 13749-13759.

924 Jiang, J., Zhang, X., Zhu, X., Li, Y., 2017. Removal of Intermediate Aromatic Halogenated DBPs
 925 by Activated Carbon Adsorption: A New Approach to Controlling Halogenated DBPs in
 926 Chlorinated Drinking Water. *Environ. Sci. Technol.* 51(6), 3435-3444.

927 Jiang, J., Li, W., Zhang, X., Liu, J., Zhu, X., 2018. A new approach to controlling halogenated DBPs
 928 by GAC adsorption of aromatic intermediates from chlorine disinfection: Effects of
 929 bromide and contact time. *Sep. Purif. Technol.* 203, 260-267.

930 Joo, S.H., Mitch, W.A., 2007. Nitrile, Aldehyde, and Halonitroalkane Formation during

931 Chlorination/Chloramination of Primary Amines. *Environ. Sci. Technol.* 41(4), 1288-1296.

932 Kemper, J.M., Westerhoff, P., Dotson, A., Mitch, W.A., 2009. Nitrosamine, Dimethylnitramine, and

933 Chloropicrin Formation during Strong Base Anion-Exchange Treatment. *Environ. Sci.*

934 *Technol.* 43(2), 466-472.

935 Kimoto, W.I., Dooley, C.J., Carré, J., Fiddler, W., 1980. Role of strong ion exchange resins in

936 nitrosamine formation in water. *Water Res.* 14(7), 869-876.

937 Klaus, L.E.K., Lawrence, J., 1977. Polyelectrolytes: Potential Chloroform Precursors. *Science*

938 196(4295), 1205-1206.

939 Kohut, K.D., Andrews, S.A., 2003. Polyelectrolyte age and N-nitrosodimethylamine formation in

940 drinking water treatment. *Water Qual. Res. J. Can.* 38(4), 719-735.

941 Korshin, G.V., Benjamin, M.M., Chang, H.-S., Gallard, H., 2007. Examination of NOM

942 Chlorination Reactions by Conventional and Stop-Flow Differential Absorbance

943 Spectroscopy. *Environ. Sci. Technol.* 41(8), 2776-2781.

944 Krasner, S.W., Weinberg, H.S., Richardson, S.D., Pastor, S.J., Chinn, R., Scilimenti, M.J., Onstad,

945 G.D., Thruston, A.D., 2006. Occurrence of a New Generation of Disinfection Byproducts.

946 *Environ. Sci. Technol.* 40(23), 7175-7185.

947 Krasner, S.W., Mitch, W.A., McCurry, D.L., Hanigan, D., Westerhoff, P., 2013. Formation,

948 precursors, control, and occurrence of nitrosamines in drinking water: A review. *Water Res.*

949 47(13), 4433-4450.

950 Krasner, S.W., Shirkhani, R., Westerhoff, P., Hanigan, D., Mitch, W.A., McCurry, D.L., Chen, C.,

951 Skadsen, J., Gunten, U.V. (2015) Controlling the Formation of Nitrosamines during Water

952 Treatment, Denver, Colorado.

953 Krasner, S.W., Leavey, S., Qian, Y., Li, X.F., Marfil-Vega, R., Bukhari, Z. (2016a) Nitrosamine

954 Occurrence Survey, Denver, Colorado.

955 Krasner, S.W., Lee, T.C.F., Westerhoff, P., Fischer, N., Hanigan, D., Karanfil, T., Beitasandí, W.,

956 Tayloredmonds, L., Andrews, R.C., 2016b. Granular Activated Carbon Treatment May

957 Result in Higher Predicted Genotoxicity in the Presence of Bromide. *Environ. Sci. Technol.*

958 50(17), 9583-9591.

959 Le Roux, J., Gallard, H., Croué, J.-P., 2011. Chloramination of nitrogenous contaminants

960 (pharmaceuticals and pesticides): NDMA and halogenated DBPs formation. *Water Res.*
 961 45(10), 3164-3174.

962 Lee, J.-Y., Hozalski, R.M., Arnold, W.A., 2007. Effects of dissolved oxygen and iron aging on the
 963 reduction of trichloronitromethane, trichloroacetonitrile, and trichloropropanone.
 964 *Chemosphere* 66(11), 2127-2135.

965 Lee, W., Westerhoff, P., 2006. Dissolved organic nitrogen removal during water treatment by
 966 aluminum sulfate and cationic polymer coagulation. *Water Res.* 40(20), 3767-3774.

967 Lehtola, M.J., Nissinen, T.K., Miettinen, I.T., Martikainen, P.J., Vartiainen, T., 2004. Removal of
 968 soft deposits from the distribution system improves the drinking water quality. *Water Res.*
 969 38(3), 601-610.

970 Lemus Pérez, M.F., Rodríguez Susa, M., 2017. Exopolymeric substances from drinking water
 971 biofilms: Dynamics of production and relation with disinfection by products. *Water Res.*
 972 116, 304-315.

973 Li, B., Qu, J., Liu, H., Hu, C., 2007. Effects of copper(II) and copper oxides on THMs formation in
 974 copper pipe. *Chemosphere* 68(11), 2153-2160.

975 Li, B. (2012) Characterization of Pore Structure and Surface Chemistry of Activated Carbons - A
 976 Review.

977 Li, J.W., Yu, Z., Gao, M., Zhang, L., Cai, X., Chao, F., 1996. Effect of ultraviolet irradiation on the
 978 characteristics and trihalomethanes formation potential of humic acid. *Water Res.* 30(2),
 979 347-350.

980 Li, Q., Mahendra, S., Lyon, D.Y., Brunet, L., Liga, M.V., Li, D., Alvarez, P.J.J., 2008. Antimicrobial
 981 nanomaterials for water disinfection and microbial control: Potential applications and
 982 implications. *Water Res.* 42(18), 4591-4602.

983 Li, Z., Chen, T., Cui, F., Xie, Y., Xu, W., 2017. Impact of chitosan and polyacrylamide on formation
 984 of carbonaceous and nitrogenous disinfection by-products. *Chemosphere* 178, 26-33.

985 Liao, X., Chen, C., Xie, S., Hanigan, D., Wang, J., Zhang, X., Westerhoff, P., Krasner, S.W., 2015.
 986 Nitrosamine Precursor Removal by BAC: A Case Study of Adsorption Versus Biotreatment.
 987 *J. Am. Water. Works. Ass.* 107(9), E454-E463.

988 Lin, J., Ellaway, M., Adrien, R., 2001. Study of corrosion material accumulated on the inner wall of

989 steel water pipe. *Corro. Sci.* 43(11), 2065-2081.

990 Lin, Y.-P., Washburn, M.P., Valentine, R.L., 2008. Reduction of Lead Oxide (PbO₂) by Iodide and
 991 Formation of Iodoform in the PbO₂/I⁻/NOM System. *Environ. Sci. Technol.* 42(8), 2919-
 992 2924.

993 Liu, C., von Gunten, U., Croué, J.-P., 2012. Enhanced Bromate Formation during Chlorination of
 994 Bromide-Containing Waters in the Presence of CuO: Catalytic Disproportionation of
 995 Hypobromous Acid. *Environ. Sci. Technol.* 46(20), 11054-11061.

996 Liu, C., von Gunten, U., Croué, J.-P., 2013a. Chlorination of bromide-containing waters: Enhanced
 997 bromate formation in the presence of synthetic metal oxides and deposits formed
 998 in drinking water distribution systems. *Water Res.* 47(14), 5307-5315.

999 Liu, C., von Gunten, U., Croué, J.-P., 2013b. Enhanced Chlorine Dioxide Decay in the Presence of
 1000 Metal Oxides: Relevance to Drinking Water Distribution Systems. *Environ. Sci. Technol.*
 1001 47(15), 8365-8372.

1002 Liu, C., Salhi, E., Croué, J.P., Von, G.U., 2014. Chlorination of Iodide-Containing Waters in the
 1003 Presence of CuO: Formation of Periodate. *Environ. Sci. Technol.* 48(22), 13173-13180.

1004 Liu, C., Croué, J.-P., 2016. Formation of Bromate and Halogenated Disinfection Byproducts during
 1005 Chlorination of Bromide-Containing Waters in the Presence of Dissolved Organic Matter
 1006 and CuO. *Environ. Sci. Technol.* 50(1), 135-144.

1007 Liu, C., Olivares, C.I., Pinto, A.J., Lauderdale, C.V., Brown, J., Selbes, M., Karanfil, T., 2017. The
 1008 control of disinfection byproducts and their precursors in biologically active filtration
 1009 processes. *Water Res.* 124, 630-653.

1010 Liu, J., Zhang, X., 2014. Comparative toxicity of new halophenolic DBPs in chlorinated saline
 1011 wastewater effluents against a marine alga: Halophenolic DBPs are generally more toxic
 1012 than haloaliphatic ones. *Water Res.* 65, 64-72.

1013 Liu, S.-g., Zhu, Z.-l., Tan, X.-c., Feng, X.-h., Huang, Z.-y., Qiu, Y.-l., Zhao, J.-f., 2013c. The
 1014 Influence of Cu(II) on the Formation and Distribution of Disinfection By-Products during
 1015 the Chlorination of Drinking Water. *Water, Air, Soil Pollut.* 224(4), 1493.

1016 Liu, S., Lim, M., Fabris, R., Chow, C., Drikas, M., Amal, R., 2008. TiO₂ Photocatalysis of Natural
 1017 Organic Matter in Surface Water: Impact on Trihalomethane and Haloacetic Acid

1018 Formation Potential. Environ. Sci. Technol. 42(16), 6218-6223.

1019 Liu, S., Gunawan, C., Barraud, N., Rice, S.A., Harry, E.J., Amal, R., 2016. Understanding,
 1020 Monitoring, and Controlling Biofilm Growth in Drinking Water Distribution Systems.
 1021 Environ. Sci. Technol. 50(17), 8954-8976.

1022 Ma, S., Guo, X., Chen, B., 2016. Toward better understanding of chloral hydrate stability in water:
 1023 Kinetics, pathways, and influencing factors. Chemosphere 157, 18-24.

1024 Mallevalle, J., Bruchet, A., Fiessinger, F., et al., 1984. How Safe Are Organic Polymers in Water
 1025 Treatment? J. Am. Water. Works. Ass. 76(6), 87-93.

1026 Matheson, L.J., Tratnyek, P.G., 1994. Reductive Dehalogenation of Chlorinated Methanes by Iron
 1027 Metal. Environ. Sci. Technol. 28(12), 2045-2053.

1028 Matilainen, A., Vepsäläinen, M., Sillanpää, M., 2010. Natural organic matter removal by
 1029 coagulation during drinking water treatment: A review. Adv. Colloid Interfac. 159(2), 189-
 1030 197.

1031 McCreary, J.J., Snoeyink, V.L., 1981. Reaction of free chlorine with humic substances before and
 1032 after adsorption on activated carbon. Environ. Sci. Technol. 15(2), 193-197.

1033 McCreary, J.J., Snoeyink, V.L., Larson, R.A., 1982. Comparison of the reaction of aqueous free
 1034 chlorine with phenolic acids in solution and adsorbed on granular activated carbon. Environ.
 1035 Sci. Technol. 16(6), 339-344.

1036 Metch, J.W., Ma, Y., Pruden, A., Vikesland, P.J., 2015. Enhanced disinfection by-product formation
 1037 due to nanoparticles in wastewater treatment plant effluents. Environ. Sci.: Water Res.
 1038 Technol. 1(6), 823-831.

1039 Mitch, W.A., Sedlak, D.L., 2004. Characterization and Fate of N-Nitrosodimethylamine Precursors
 1040 in Municipal Wastewater Treatment Plants. Environ. Sci. Technol. 38(5), 1445-1454.

1041 Morran, J.I.M., Whittle, M., Fabris, R.B., Harris, M., Leach, J.S., Newcombe, G., Drikas, M., 2011.
 1042 Nitrosamines from pipeline materials in drinking water distribution systems. J. Am. Water.
 1043 Works. Ass. 103(10), 76-83.

1044 Muellner, M.G., Wagner, E.D., McCalla, K., Richardson, S.D., Woo, Y.T., Plewa, M.J., 2007.
 1045 Haloacetonitriles vs. regulated haloacetic acids: are nitrogen-containing DBPs more toxic?
 1046 Environ. Sci. Technol. 41(2), 645-651.

1047 Najm, I., Trussell, R.R., 2001. NDMA Formation in Water and Wastewater. J. Am. Water. Works.
 1048 Ass. 93(2), 92-99.

1049 Paciolla, M.D., Davies, G., Jansen, S.A., 1999. Generation of Hydroxyl Radicals from Metal-
 1050 Loaded Humic Acids. Environ. Sci. Technol. 33(11), 1814-1818.

1051 Padhye, L., Wang, P., Karanfil, T., Huang, C.-H., 2010. Unexpected Role of Activated Carbon in
 1052 Promoting Transformation of Secondary Amines to N-Nitrosamines. Environ. Sci. Technol.
 1053 44(11), 4161-4168.

1054 Padhye, L., Luzinova, Y., Cho, M., Mizaikoff, B., Kim, J.-H., Huang, C.-H., 2011. PolyDADMAC
 1055 and Dimethylamine as Precursors of N-Nitrosodimethylamine during Ozonation: Reaction
 1056 Kinetics and Mechanisms. Environ. Sci. Technol. 45(10), 4353-4359.

1057 Pan, B., Xing, B., 2008. Adsorption Mechanisms of Organic Chemicals on Carbon Nanotubes.
 1058 Environ. Sci. Technol. 42(24), 9005-9013.

1059 Pan, Y., Zhang, X., 2013. Four Groups of New Aromatic Halogenated Disinfection Byproducts:
 1060 Effect of Bromide Concentration on Their Formation and Speciation in Chlorinated
 1061 Drinking Water. Environ. Sci. Technol. 47(3), 1265-1273.

1062 Pan, Y., Zhang, X., Wagner, E.D., Osiol, J., Plewa, M.J., 2014. Boiling of Simulated Tap Water:
 1063 Effect on Polar Brominated Disinfection Byproducts, Halogen Speciation, and Cytotoxicity.
 1064 Environ. Sci. Technol. 48(1), 149-156.

1065 Park, S.-H., Wei, S., Mizaikoff, B., Taylor, A.E., Favero, C., Huang, C.-H., 2009. Degradation of
 1066 Amine-Based Water Treatment Polymers during Chloramination as N-
 1067 Nitrosodimethylamine (NDMA) Precursors. Environ. Sci. Technol. 43(5), 1360-1366.

1068 Park, S.H., Padhye, L.P., Wang, P., Cho, M., Kim, J.-H., Huang, C.-H., 2015. N-
 1069 nitrosodimethylamine (NDMA) formation potential of amine-based water treatment
 1070 polymers: Effects of in situ chloramination, breakpoint chlorination, and pre-oxidation. J.
 1071 Hazard. Mater. 282, 133-140.

1072 Parker, K.M., Zeng, T., Harkness, J., Vengosh, A., Mitch, W.A., 2014. Enhanced Formation of
 1073 Disinfection Byproducts in Shale Gas Wastewater-Impacted Drinking Water Supplies.
 1074 Environ. Sci. Technol. 48(19), 11161-11169.

1075 Pearson, C.R., Hozalski, R.M., Arnold, W.A., 2005. Degradation of chloropicrin in the presence of

1076 zero-valent iron. *Environ. Toxicol. Chem.* 24(12), 3037-3042.

1077 Pieri, P., Andra, S.S., Charisiadis, P., Demetriou, G., Zambakides, N., Makris, K.C., 2014.

1078 Variability of Tap Water Residual Chlorine and Microbial Counts at Spatially Resolved

1079 Points of Use. *Environ. Eng. Sci.* 31(4), 193-201.

1080 Plewa, M.J., Wagner, E.D., Muellner, M.G., Hsu, K.-M., Richardson, S.D. (2008) Disinfection By-

1081 Products in Drinking Water, pp. 36-50, American Chemical Society.

1082 Plewa, M.J., Wagner, E.D. (2015) Recent Advances in Disinfection By-Products, pp. 3-23,

1083 American Chemical Society.

1084 Qu, X., Alvarez, P.J.J., Li, Q., 2013. Applications of nanotechnology in water and wastewater

1085 treatment. *Water Res.* 47(12), 3931-3946.

1086 Richardson, S.D., Thruston, A.D., Collette, T.W., Patterson, K.S., Lykins, B.W., Ireland, J.C., 1996.

1087 Identification of TiO₂/UV Disinfection Byproducts in Drinking Water. *Environ. Sci.*

1088 *Technol.* 30(11), 3327-3334.

1089 Richardson, S.D., Plewa, M.J., Wagner, E.D., Schoeny, R., DeMarini, D.M., 2007. Occurrence,

1090 genotoxicity, and carcinogenicity of regulated and emerging disinfection by-products in

1091 drinking water: A review and roadmap for research. *Mutat. Res/Rev. Mutat.* 636(1-3), 178-

1092 242.

1093 Richardson, S.D., Fasano, F., Ellington, J.J., Crumley, F.G., Buettner, K.M., Evans, J.J., Blount,

1094 B.C., Silva, L.K., Waite, T.J., Luther, G.W., McKague, A.B., Miltner, R.J., Wagner, E.D.,

1095 Plewa, M.J., 2008. Occurrence and Mammalian Cell Toxicity of Iodinated Disinfection

1096 Byproducts in Drinking Water. *Environ. Sci. Technol.* 42(22), 8330-8338.

1097 Richardson, S.D., Postigo, C. (2012) Emerging Organic Contaminants and Human Health. Barceló,

1098 D. (ed), pp. 93-137, Springer Berlin Heidelberg, Berlin, Heidelberg.

1099 Rook, J.J., 1974. Formation of haloforms during chlorination of natural water. *Water Treat. Exam.*

1100 23, 234-243.

1101 Rossman, L.A., Brown, R.A., Singer, P.C., Nuckols, J.R., 2001. DBP formation kinetics in a

1102 simulated distribution system. *Water Res.* 35(14), 3483-3489.

1103 Samatya, S., Kabay, N., Yüksel, Ü., Arda, M., Yüksel, M., 2006. Removal of nitrate from aqueous

1104 solution by nitrate selective ion exchange resins. *React. Funct. Polym.* 66(11), 1206-1214.

1105 Seidel, H.F., 1985. Water Utility Operating Data: An Analysis. J. Am. Water. Works. Ass. 77(5), 34-
 1106 41.

1107 Selbes, M., Kim, D., Karanfil, T., 2014. The effect of pre-oxidation on NDMA formation and the
 1108 influence of pH. Water Res. 66, 169-179.

1109 Selcuk, H., Sarikaya, H.Z., Bekbolet, M., Anderson, M.A., 2006. Bromate formation on the non-
 1110 porous TiO₂ photoanode in the photoelectrocatalytic system. Chemosphere 62(5), 715-721.

1111 Selcuk, H., 2010. Disinfection and formation of disinfection by-products in a photoelectrocatalytic
 1112 system. Water Res. 44(13), 3966-3972.

1113 Sgroi, M., Roccaro, P., Oelker, G.L., Snyder, S.A., 2015. N-nitrosodimethylamine (NDMA)
 1114 formation at an indirect potable reuse facility. Water Res. 70, 174-183.

1115 Shah, A.D., Mitch, W.A., 2012. Halonitroalkanes, Halonitriles, Haloamides, and N-Nitrosamines:
 1116 A Critical Review of Nitrogenous Disinfection Byproduct Formation Pathways. Environ.
 1117 Sci. Technol. 46(1), 119-131.

1118 Sharma, V.K., Yang, X., Cizmas, L., McDonald, T.J., Luque, R., Sayes, C.M., Yuan, B., Dionysiou,
 1119 D.D., 2017. Impact of metal ions, metal oxides, and nanoparticles on the formation of
 1120 disinfection byproducts during chlorination. Chem. Eng. J. 317, 777-792.

1121 Snoeyink, V.L., Clark, R.R., McCreary, J.J., McHie, W.F., 1981. Organic compounds produced by
 1122 the aqueous free-chlorine-activated carbon reaction. Environ. Sci. Technol. 15(2), 188-192.

1123 Sokolowski, A., Gora, S., Andrews, S. (2014) Nanotechnology for Water Treatment and Purification.
 1124 Hu, A., Apblett, A. (eds), pp. 275-306, Springer International Publishing, Cham.

1125 Soponkanaporn, T., Gehr, R. (1988) Water Pollution Research and Control Brighton. Lijklema, L.,
 1126 Imhoff, K.R., Ives, K.J., Jenkins, D., Ludwig, R.G., Suzuki, M., Toerien, D.F., Wheatland,
 1127 A.B., Milburn, A., Izod, E.J. (eds), pp. 857-868, Pergamon.

1128 Stüber, F., Font, J., Fortuny, A., Bengoa, C., Eftaxias, A., Fabregat, A., 2005. Carbon materials and
 1129 catalytic wet air oxidation of organic pollutants in wastewater. Top. Catal. 33(1), 3-50.

1130 Summers, R.S., Benz, M.A., Shukairy, H.M., Cummings, L., 1993. Effect of Separation Processes
 1131 on the Formation of Brominated THMs. J. Am. Water. Works. Ass. 85(1), 88-95.

1132 Sun, H., Liu, H., Han, J., Zhang, X., Cheng, F., Liu, Y., 2018. Chemical cleaning-associated
 1133 generation of dissolved organic matter and halogenated byproducts in ceramic MBR:

1134 Ozone versus hypochlorite. *Water Res.* 140, 243-250.

1135 Symons, J.M., Krasner, S.W., Simms, L.A., Scilimenti, M., 1993. Measurement of THM and
 1136 Precursor Concentrations Revisited: The Effect of Bromide Ion. *J. Am. Water. Works. Ass.*
 1137 85(1), 51-62.

1138 Takht Ravanchi, M., Kaghazchi, T., Kargari, A., 2009. Application of membrane separation
 1139 processes in petrochemical industry: a review. *Desalination* 235(1), 199-244.

1140 Tang, S., Wang, X.-m., Mao, Y.-q., Zhao, Y., Yang, H.-w., Xie, Y.F., 2015. Effect of dissolved oxygen
 1141 concentration on iron efficiency: Removal of three chloroacetic acids. *Water Res.* 73, 342-
 1142 352.

1143 Teefy, S., Chan Clifford, C., Wong, W., Work, L., 2014. NDMA formation from gaskets used in
 1144 water storage tanks. *J. Am. Water. Works. Ass.* 106(9), 408-417.

1145 Tofighy, M.A., Mohammadi, T., 2011. Adsorption of divalent heavy metal ions from water using
 1146 carbon nanotube sheets. *J. Hazard. Mater.* 185(1), 140-147.

1147 Toroz, I., Uyak, V., 2005. Seasonal variations of trihalomethanes (THMs) in water distribution
 1148 networks of Istanbul City. *Desalination* 176(1), 127-141.

1149 Tugulea, A.M., Bérubé, D., Giddings, M., Lemieux, F., Hnatiw, J., Priem, J., Avramescu, M.L., 2014.
 1150 Nano-silver in drinking water and drinking water sources: stability and influences on
 1151 disinfection by-product formation. *Environ. Sci. Pollut. R.* 21(20), 11823-11831.

1152 USEPA, 2006. Stage 2 disinfectants and disinfection byproducts rule: National primary and
 1153 secondary drinking water regulations: Final rule. *Federal Register* 71(2).

1154 USEPA (2007) Distribution System Inventory, Integrity and Water Quality,
 1155 <http://www.epa.gov/safewater/disinfection/lt2/compliance.html>.

1156 Vel Leitner, N.K., De Laat, J., Dore, M., Suty, H., Pouillot, M., 1994. Inorganic and organic
 1157 byproducts of the reactions between chlorite, activated carbon, and phenolic compounds.
 1158 *Environ. Sci. Technol.* 28(2), 222-230.

1159 Verdugo, E.M., Krause, C., Genskow, K., Han, Y., Baltrusaitis, J., Mattes, T.E., Valentine, R.L.,
 1160 Cwiertny, D.M., 2014. N-Functionalized Carbon Nanotubes As a Source and Precursor of
 1161 N-Nitrosodimethylamine: Implications for Environmental Fate, Transport, and Toxicity.
 1162 *Environ. Sci. Technol.* 48(16), 9279-9287.

1163 Verdugo, E.M., Nelson, K.J., Bako, C.M., Valentine, R.L., Cwiertny, D.M., 2016. Formation of
 1164 trihalomethanes and haloacetic acids during chlorination of functionalized carbon
 1165 nanotubes. *Environ. Sci.: Nano* 3(6), 1327-1339.

1166 Voudrias, E.A., Larson, R.A., Snoeyink, V.L., 1985a. Effects of activated carbon on the reactions of
 1167 free chlorine with phenols. *Environ. Sci. Technol.* 19(5), 441-449.

1168 Voudrias, E.A., Larson, R.A., Snoeyink, V.L., 1985b. Effects of activated carbon on the reactions of
 1169 combined chlorine with phenols. *Water Res.* 19(7), 909-915.

1170 Wagner, E.D., Plewa, M.J., 2017. CHO cell cytotoxicity and genotoxicity analyses of disinfection
 1171 by-products: An updated review. *J. Environ. Sci.* 58, 64-76.

1172 Walter, R.K., Lin, P.-H., Edwards, M., Richardson, R.E., 2011. Investigation of factors affecting the
 1173 accumulation of vinyl chloride in polyvinyl chloride piping used in drinking water
 1174 distribution systems. *Water Res.* 45(8), 2607-2615.

1175 Wang, C., Shang, C., Ni, M., Dai, J., Jiang, F., 2012. (Photo)chlorination-Induced Physicochemical
 1176 Transformation of Aqueous Fullerene nC60. *Environ. Sci. Technol.* 46(17), 9398-9405.

1177 Wang, C., Yang, X., Zheng, Q., Moe, B., Li, X.-F., 2018. Halobenzoquinone-Induced
 1178 Developmental Toxicity, Oxidative Stress, and Apoptosis in Zebrafish Embryos. *Environ.*
 1179 *Sci. Technol.* 52(18), 10590-10598.

1180 Wang, J.-J., Liu, X., Ng, T.W., Xiao, J.-W., Chow, A.T., Wong, P.K., 2013. Disinfection byproduct
 1181 formation from chlorination of pure bacterial cells and pipeline biofilms. *Water Res.* 47(8),
 1182 2701-2709.

1183 Wang, W., Zhu, L., 2010. Effect of zinc on the transformation of haloacetic acids (HAAs) in drinking
 1184 water. *J. Hazard. Mater.* 174(1), 40-46.

1185 Wang, X., Mao, Y., Tang, S., Yang, H., Xie, Y.F., 2015. Disinfection byproducts in drinking water
 1186 and regulatory compliance: A critical review. *Frontiers of Environmental Science &*
 1187 *Engineering* 9(1), 3-15.

1188 WHO, 2004. Water, Sanitation and hygiene links to health : facts and figures.
 1189 http://www.who.int/water_sanitation_health/factsfigures2005.pdf.

1190 Wilczak, A., Assadi-Rad, A., Lai, H.H., Hoover, L.L., Smith, J.F., Berger, R., Rodigari, F., Beland,
 1191 J.W., Lazzelle, L.J., Kincannon, E.G., Baker, H., Heaney, C.T., 2003. Formation of NDMA

1192 in Chloraminated Water Coagulated with DADMAC Cationic Polymer. J. Am. Water.
 1193 Works. Ass. 95(9), 94-106.

1194 Xia, Y., Lin, Y.-L., Xu, B., Hu, C.-Y., Gao, Z.-C., Chu, W.-H., Gao, N.-Y., 2017. Iodinated
 1195 trihalomethane formation during chloramination of iodate-containing waters in the
 1196 presence of zero valent iron. Water Res. 124, 219-226.

1197 Xie, P., de Lannoy, C.-F., Ma, J., Wiesner, M.R., 2015. Chlorination of polyvinyl pyrrolidone–
 1198 polysulfone membranes: Organic compound release, byproduct formation, and changes in
 1199 membrane properties. J. Membr. Sci. 489, 28-35.

1200 Yang, M.T., Zhang, X.R., 2013. Comparative Developmental Toxicity of New Aromatic
 1201 Halogenated DBPs in a Chlorinated Saline Sewage Effluent to the Marine Polychaete
 1202 *Platynereis dumerilii*. Environ. Sci. Technol. 47(19), 10868-10876.

1203 Yang, M.T., Zhang, X.R., 2014. Halopyrroles: A New Group of Highly Toxic Disinfection
 1204 Byproducts Formed in Chlorinated Saline Wastewater. Environ. Sci. Technol. 48(20),
 1205 11846-11852.

1206 Yang, X., Fan, C., Shang, C., Zhao, Q., 2010. Nitrogenous disinfection byproducts formation and
 1207 nitrogen origin exploration during chloramination of nitrogenous organic compounds.
 1208 Water Res. 44(9), 2691-2702.

1209 Yu, Y., Reckhow, D.A., 2015. Kinetic Analysis of Haloacetonitrile Stability in Drinking Waters.
 1210 Environ. Sci. Technol. 49(18), 11028-11036.

1211 Zeng, T., Pignatello, J.J., Li, R.J., Mitch, W.A., 2014. Synthesis and Application of a Quaternary
 1212 Phosphonium Polymer Coagulant To Avoid N-Nitrosamine Formation. Environ. Sci.
 1213 Technol. 48(22), 13392-13401.

1214 Zeng, T., Li, R.J., Mitch, W.A., 2016. Structural Modifications to Quaternary Ammonium Polymer
 1215 Coagulants to Inhibit N-Nitrosamine Formation. Environ. Sci. Technol. 50(9), 4778-4787.

1216 Zeng, T., Mitch, W.A., 2016. Impact of Nitrification on the Formation of N-Nitrosamines and
 1217 Halogenated Disinfection Byproducts within Distribution System Storage Facilities.
 1218 Environ. Sci. Technol. 50(6), 2964-2973.

1219 Zhang, H., Andrews, S.A., 2012. Catalysis of copper corrosion products on chlorine decay and HAA
 1220 formation in simulated distribution systems. Water Res. 46(8), 2665-2673.

1221 Zhang, H., Andrews, S.A., 2013. Factors affecting catalysis of copper corrosion products in NDMA
1222 formation from DMA in simulated premise plumbing. *Chemosphere* 93(11), 2683-2689.
1223 Zhang, L., Arnold, W.A., Hozalski, R.M., 2004. Kinetics of Haloacetic Acid Reactions with Fe(0).
1224 *Environ. Sci. Technol.* 38(24), 6881-6889.
1225 Zhang, Y.M., Chu, W.H., Yao, D.C., Yin, D.Q., 2017. Control of aliphatic halogenated DBP
1226 precursors with multiple drinking water treatment processes: Formation potential and
1227 integrated toxicity. *J. Environ. Sci.* 58, 322-330.
1228 Zhao, Y., Yang, H.-w., Liu, S.-t., Tang, S., Wang, X.-m., Xie, Y.F., 2016. Effects of metal ions on
1229 disinfection byproduct formation during chlorination of natural organic matter and
1230 surrogates. *Chemosphere* 144, 1074-1082.
1231

Fig. 1. Structures of PAM, APAM, CPAM, PDADMAC, ECH/DMA and Chitosan.

C—concentration, C_0 —initial concentration, DIN—dissolved inorganic nitrogen, DOC—dissolved organic carbon, DON—dissolved organic nitrogen, RSSCT—rapid small-scale column test, SUVA—specific ultraviolet absorbance, TDN—total dissolved nitrogen, UV₂₅₄—ultraviolet absorbance at 254 nm

Fig. 2. Normalized DOC, UV₂₅₄, TDN, DIN, DON and Br⁻ breakthrough curves from RSSCTs conducted with sedimentation basin effluents. Adapted from Chiu et al. (2012).

Fig. 3. Proposed reactions for CuO-enhanced HOCl, HOBr, HOI and ClO₂ decay. Adapted from Liu et al. (2012), Liu et al. (2013b) and Liu et al. (2014). The compounds labeled with red represented the enhanced products in the presence of CuO.

Fig. 4. Bromine mass balance in the presence of CCPs and HA during chlorination of synthetic water (SW). Experimental conditions: $\text{Cl}_2 = 14.2 \text{ mg/L}$, $[\text{Br}]_0 = 2.0 \text{ mg/L}$, $[\text{HA}]_0 = 5.0 \text{ mg/L}$, $[\text{CuO}]_0 = 2.0 \text{ g/L}$, $[\text{Cu}_2\text{O}]_0 = 0.5 \text{ g/L}$, $[\text{Cu}^{2+}]_0 = 2.0 \text{ mg/L}$, $\text{pH} = 7.6$, reaction time = 72 h. Adapted from the Hu et al. (2016).